

# OXYTOTE "ALL-IN-ONE" PORTABLE OXYGEN SYSTEM

**PL**  
PRIVATE LABEL



## OXYTOTE OXYGEN REGULATOR WITH SURECLICK™ FEATURE

The OxyTOTE™ "All-In-One" regulator is perfect for transporting and dispensing oxygen in one easy-to-use package. With Western's innovative concept and design, the OxyTOTE regulator provides optimal performance in a click-style regulator by delivering the liter flow needed without the time and frustration of matching regulators and cylinders. This unique "All-In-One" design is a safe, easy-to-use and cost-effective method of distributing oxygen. The OxyTOTE, like all Western products, meets exacting standards for performance and reliability.

Sold separately or attached to cylinder

### FEATURES:

- Regulator and cylinder valve combined into one unit
- User can initiate flow in one easy step
- Compact design with all brass body
- Maximum rated inlet pressure 3000 psi
- 1-1/2" diameter gauge
- Transfill through CGA-540 port (CGA-346 for AirTOTE)
- Filtration throughout for maximum safety
- Integral reseating relief valve protects against over-pressurization
- Protective shroud ensures safety and lasting performance
- Hose barb outlet is standard
- Unit can be ordered with or without DISS (demand valve)

### OXYTOTE REGULATOR SPECIFICATIONS

(OxyTOTE Regulator Only)

Size	7-3/4" x 4-1/2"
Weight	2 lbs. 10 oz
OxyTOTE Flow (LPM)	1/2, 1, 1-1/2, 2, 3, 4, 5, 6, 8, 10, 15, 25, AUX
AirTOTE Flow (LPM)	1, 2, 3, 4, 6, 8, 10, 12, 15, 20, 25, AUX

Durable cover protects regulator & valve assembly.

SureClick™ feature reduces the risk of dialing the flow selector between click settings, making it easier for clinicians to dial in and secure oxygen flow.

All-In-One Brass regulator assembly incorporates post valve and flow control device into a single unit. Units are quickly refilled through a CGA-540 fill port on reverse side. (CGA-346 for AirTOTE)

**OxyTOTE**  
without DISS 1240  
Auxiliary port

Easy-to-read 1-1/2" cylinder contents gauge.

Permanent assembly onto a lightweight aluminum or steel cylinder.



Built in handle for portability.

On/Off flow control knob with adjustable flow rates of .5 - 25 liters per minute.

Tapered hose barb for attaching cannula. Barb outlet is recessed for protection against damage.

**5 Year Warranty**

On/Off valve maximizes regulator life by minimizing its exposure to cylinder pressure.



DESCRIPTION	OXYTOTE HOSE BARB ONLY PART #	OXYTOTE HOSE BARB & DISS* OUTLETS PART #
OxyTOTE Head only for aluminum cylinder	MTR-500	MTR-600
OxyTOTE Head only for steel cylinder	MTR-510	MTR-610
OxyTOTE on C aluminum cylinder	MTS-501	MTS-601
OxyTOTE on D aluminum cylinder	MTS-502	MTS-602
OxyTOTE on E aluminum cylinder	MTS-503	MTS-603
OxyTOTE on M6A aluminum cylinder	MTS-505	MTS-605
OxyTOTE on E steel cylinder	MTS-513	MTS-613

\*DISS outlet is Auxiliary port (demand valve). Outlet pressure 50 psi. Hose barb for use in controlled flow applications (cannot be used simultaneously with DISS).

**AIRTOTE PORTABLE MEDICAL AIR SYSTEM**

Western's new AirTOTE™ portable medical air system brings a new level of simplicity and cost effectiveness to distributing air. The AirTOTE system is based on Western's OxyTOTE design, proven in years of use in thousands of locations. Call us for more information.



**AIRTOTE** with DISS 1160 Auxiliary Port Use Part # MTR-300 (Head only) or MTS-303 (System)



**MTS-503**



**MTS-513**



**MTS-502**



**MTS-501**



**MTS-505**

**OXYTOTE SYSTEM SPECIFICATIONS**

	MTS-503	MTS-513	MTS-502	MTS-501	MTS-505
Cylinder Size	679 liter "E" Aluminum	665 liter "E" Steel	425 liter "D" Aluminum	246 liter "C" Aluminum	170 liter "M6A" Aluminum
System Size	32-1/2" H x 4-1/2" W	32-1/2" H x 4-1/4" W	23-1/2" H x 4-1/2" W	18" H x 4-1/2" W	15-1/4" H x 4-1/2" W
System Weight	10.3 lbs.	12.6 lbs.	7.9 lbs.	6.5 lbs.	5.8 lbs.
Regulator Flow (SLPM)	1/2 - 25	1/2 - 25	1/2 - 25	1/2 - 25	1/2 - 25