



CONDUCTILE®

The Premier Static Control Flooring Solution



The longer that static electricity is “allowed to stay in the environment” the more likely the chance of damage. VPI Conductile® Conductive ESD tiles carry static electricity away from the environment **up to twenty times faster than static dissipative tiles**. In fact, more and more ESD flooring experts believe that conductive flooring should be used everywhere static protection is required.

- **The default choice for controlling static electricity**
- For use with highly sensitive equipment and critical applications
- Protects the most sensitive equipment by keeping static away
- Retains its conductive properties indefinitely
- Suited for printed circuit and chip manufacturing
- Resists acids, alkalis, and other harsh solvents and chemicals
- Comes with a lifetime warranty for electrical performance and a 25-year warranty for wear and tear
- Emits zero VOC's so is ideal choice for clean rooms where VOC elimination is critical

Conductile Specifications

- Gauge: 1/8" (3 mm)
- Tiles available in 12" x 12", 24" x 24" and 36" x 36" (24's and 36's can be welded to be seamless)
- 11 Colors Available
- **Electrical resistance: 25,000–1,000,000 Ohms**

Adhesives

VPI 150

A two part epoxy adhesive specially engineered for use below grade (porous or non-porous) and /or with heavy load traffic or heavy static loads such as hospital beds. Depending on conditions and application, spread rate is nominally 135 square feet. RH requirements are a maximum of 85% and a PH of 6 - 9. See adhesive section for more details including substrate requirements and open times. Zero detectable VOC's.

VPI 165

A simple to use **one part adhesive for use on or above grade.** Can be used on porous or non-porous substrates in applications with light to medium traffic. Depending on conditions and application, spread rate is nominally 135 square feet. RH requirements are a maximum of 85% and a PH of 7 - 11. See adhesive section for more details including substrate requirements and open times. Zero detectable VOC's.

Conductile Color Options



[View color swatches.](#)

Additional Information

[Adhesive Details](#)
[Installation & Maintenance](#)
[Specification Details](#)
[Performance Properties](#)
[LEED Credits & VOCs](#)
[MSDS](#)
[Warranty](#)
[Catalogs & Sales Info](#)

VPI Flooring

Proudly Made in the USA

Customer Service

800.8744240

or

9204584664

Mailing Address

VPI Corporation

3123 South 9th Street,

P.O. Box 451

Sheboygan, Wisconsin 53082-0451

Need a Sample?

[Click here.](#)