

Belinea

[Belinea 10 17 15]

The new generation of the low cost 17-inch-entry model.

Belinea 10 17 15 – 17-inch entry model

The new generation of the Belinea 10 17 15 continues to offer a very cost-efficient entry to the 17-inch LCD area. High contrast and brightness values allow a very good picture performance. The integrated speaker and the short response time of 20 ms are very interesting for users who work with multimedia applications. The high quality of the new generation of Belinea 10 17 15 is proved by numerous certifications, e.g. TCO99 and ISO 13406-2.



D-Sub connection
for analogue
graphics cards



Integrated
speaker



Belinea 10 17 15 – The 17-inch entry model

- 17 inch (43.18 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 150° / 125°
- Response time rise / fall: 4 / 16 ms

Target Groups

- Small and Medium Business
- Price sensitive users
- Video applications

Belinea 10 17 15 – Technical Data

Panel characteristics

Image size	17"
Viewable image size in inch / cm	17" / 43.18
Max. picture size (w x h) in mm	337.9 x 270.3
Physical resolution	1280 x 1024
Pixel pitch in mm	0.264 x 0.264
Active Matrix, TFT	•
Displayable colours (max.)	16.7 Mio
Brightness in cd / qm	300
Contrast ratio	450:1
Viewing angle horizontal	150°
Viewing angle vertical	125°
Coating	Anti Glare
Response time: rise / fall in ms	4 / 16
Panel technology / manufacturer	TN / QDI
Back Light	4 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 81
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	135
Input voltage 110-230V, 50-60Hz	•
Power consumption in Watt (On / Sleep)	50 / 1
Input signal (VGA-card) analog / digital	• / -
Output audio amplifier	2 x 1 Watt

Features

Factory / user defined modes	16 / 9
OSD	•
Integrated microphone	-
Integrated speaker	•
Power supply in the panel/in the stand / external	• / - / -
Tilt back / forth	25° / 5°
Swivel right / left	- / -

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	external / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	- / •
Zoom / frequency	- / •
Recall / video signal selection	• / -
OSD position / OSD language(s)	• / 5
Mute	external
Volume	external

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	75
1280 x 1024	75

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO 99	•
TÜV GS / TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	•
MAC compliant	•

Connections

15 pin. Mini-D-Sub	•
24-pin DVI-D	-
USB upstream / downstream	-
Headphone plug	-
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect. 15 pin. Mini-D-Sub	• (non detachable)
Video connect. 24 pin. DVI-D	-
Audio cable	•
USB cable	•
Optional accessories	-
Microphone cable	-

Physical specification

Size (w x h x d) in mm	375 x 393 x 182
Net / gross weight in kg	4.6 / 6.8

Warranty

3 years incl. panel and backlight	•
-----------------------------------	---

Austria

MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux

MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal

MAXDATA Iberia
c/ Collado mediano, s/n • Edificio Prisma
Portal 1-Pta. 1ª B • E-28230-Las ROZAS, Madrid

France

MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY Cedex

Germany

MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45786 Marl

Italy

MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland

MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Pulawska 303
02-785 Warszawa

Switzerland

MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom

MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: