

# Facility Inspection Report

---

## 60 kmta Caprolactam Facility



*Prepared by:*  
**International Process Plants**  
Hamilton Business Center  
17A Marlen Drive  
Hamilton, NJ 08691

# 60 kmta Caprolactam Facility

## Executive Summary

This Caprolactam Facility includes all intermediate and byproduct plants. The facility starts with benzene and finishes with caprolactam and ammonium sulfate byproduct:

- Cyclohexane Plant – 80 kmta
- Cyclohexanone Plant – 55 kmta
- Oximation Plant – 62 kmta
- Caprolactam Plant – 60 kmta
- Ammonium Sulfate – 108 kmta
- Incinerator – 5 m<sup>3</sup>/hr liquid waste

The facility had some upgrades over the years. The majority of the site shut down in 2009, but the cyclohexane unit ran until August 2013.

Documentation is complete and well-organized. Much of it is electronic and has already been shared with IPP. The facility received ISO-9001 certification in 1997 and ISO-14001 certification in 2004.


DCS is by Yokogawa (Centum CS-3000) and is used in the Oximation, Caprolactam, Ammonia Sulfate, and Incinerator units.

The plant has been well-maintained and is still being kept up with a staff of four employees. There is a nitrogen pad on the process and they are turning the rotating equipment monthly.

There are abundant spare parts available with the facility.

Transportation to and from the facility by road is excellent and it is 24 km to the nearest major port.

## Detailed Process Description – Caprolactam Facility



Overall Caprolactam Facility Process Flow Diagram

This Caprolactam Facility includes all intermediate and byproduct plants. The facility starts with benzene and finishes with caprolactam and ammonium sulfate byproduct:

- Cyclohexane Plant – 80 kmta
- Cyclohexanone Plant – 55 kmta
- Oximation Plant – 62 kmta
- Caprolactam Plant – 60 kmta
- Ammonium Sulfate – 108 kmta
- Incinerator – 5 m<sup>3</sup>/hr liquid waste

The facility can be turned-down to about 40 kmta of caprolactam, or 67% of capacity.

The total facility uses the following raw material and utility quantities:

Benzene = 79 kmta	Electricity = 52 GWhr/yr	Nitrogen = 6.0 MMNm <sup>3</sup> /yr
Hydrogen = 10 kmta	Steam = 720 kmta	Fuel Oil = 1.0 kmta
Ammonia = 50 kmta	Air = 33 MMNm <sup>3</sup> /yr	
Sulfuric Acid = 78 kmta	Water = 1.3 MMNm <sup>3</sup> /yr	

The following chart shows more details about the sub-processes within each of the individual units.

**Cyclohexane Plant**

Hydrogenation of Benzene to Cyclohexane

U-5200 Plant Designation

No sub-series - unit operations listed below:

- Benzene Evaporation
- Hydrogenation
- Separation
- Ammonia Refrigeration Unit

**Cyclohexanone Plant**

Oxidation of Cyclohexane to Cyclohexanone

U-5000 Plant Designation

Series:

- 5000 Utilities (includes incinerator)
- 5400 Oxidation
- 5500 Absorption
- 5600 Neutralization/Hydrolysis
- 5700 Distillation
- 5800 Purification
- 5900 Conversion of Cyclohexanol to Cyclohexanone

**Cyclohexanone-Oxime Plant**

Oximation of Cyclohexanone to Oxime

U-6000 Plant Designation

Series

- 6000 Utilities
  - 6100 Hydrogen Purification
  - 6200 Hydroxylamine Preparation
  - 6300 Oximation/Neutralization/Washing
  - 6400 Toluene/Oxime Distillation
  - 6500 Toluene Extraction/Separation
  - 6600 Ammonia Burner
  - 6700 Nitric Adsorption
  - 6800 NOx Removal
- > **Nitric Acid Plant**

**Caprolactam Plant**

Rearrangement of Oxime to Caprolactam & Ammonium Sulfate

U-7000 Plant Designation

Series:

- 7000 Utilities (Includes Effluent Evaporator, Incinerator)
- 7200 Rearrangement
- 7300 Extraction
- 7400 Ion Exchange
- 7500 Hydrogenation
- 7600 Evaporation
- 7700 Distillation
- 7800 Flocculation

**Ammonium Sulfate Plant**

Recovery of Ammonium Sulfate byproduct

U-8500 Plant Designation

No sub-series - unit operations listed below:


- Evaporation
- Crystallization
- Centrifugation
- Drying
- Solids Transport

## Detailed Process Description – Cyclohexane Facility



Cyclohexane Plant

The Cyclohexane Plant uses 73 kmta of benzene to produce 80 kmta of pure cyclohexane. It can also produce a small heptane byproduct and has a small effluent stream that is mostly water from the benzene drying column overheads. The plant was the last plant running when it shut down in August, 2013.



Cyclohexane Plant Process Flow Diagram

The incoming benzene is heated to 60°C by cross-exchanging with the benzene drying columns bottoms stream. The benzene is then dried in the drying column to less than 100 ppm water and pumped from the bottom of the column.

The drying column has 20 sieve trays, a reboiler, and an overhead condenser system. The carbon steel column is 0.7 meters diameter by 12.5 meters tall and is rated for 2.6 bar at 115°C. There is an azeotropic mixture going overhead in the column at 15,000 ppm water. This stream is used for reflux in the drying column.

The dry benzene is now pumped up to high-pressure using two Sundyne pumps and is then heated with hot oil and evaporated at 130°C. The benzene is mixed with hydrogen which is compressed with a Demag compressor rated for 41.6 bar. The compressor is driven with a steam turbine.



Hydrogen Compressor

The benzene/hydrogen mixture is then sent to the hydrogenation reactor which operates at 30 bar and 340°C with 0.3% platinum catalyst on aluminum oxide substrate. Hydrogen with purity as low as 74% can be used in this process. The carbon steel reactor is 1.8 meters diameter by 6.1 meters tall. It is rated for 34 bar at 315°C.



Hydrogenation Reactor



After-Reactor

The hydrogenation reactor products then flow to the after-reactor which is filled with zinc oxide catalyst in the first bed and platinum catalyst on aluminum oxide substrate in the second bed. The after-reactor is 2.2 meters diameter by 5.2 meters tall. It is rated for 34 bar at 315°C. All catalysts have been removed from the reactors.

The cyclohexane product is then cooled with a steam-generating boiler and some other cross-exchangers for energy efficiency. The carbon steel boiler is 2.4 meters diameter by 5.8 meters long and is rated for 21 bar at 226°C. The condensed product is sent to the heptane column where n-heptane and other high-boiling compounds are removed. Pure cyclohexane exits the top of the heptane column. The pure cyclohexane product is then condensed and pumped to storage. The heptane column has been removed because it was not necessary.





The oxidation reaction takes place in four agitated oxidation reactors in series. Air is blown into the bottom of the oxidation reactors while the agitator spins at 190 rpm. Each reactor is 35 cubic meters in volume providing 37 minutes of residence time. The oxidation of cyclohexane takes place at 9.0 bar and 160°C with a cobalt naphthenate catalyst. The four carbon steel reactors are 3.4 meters diameter by 6.0 meters tall and are rated for 12.8 bar at 190°C.



Oxidation Reactors (4)

The Demag model 06-MH-7C air compressor is rated for 8,173 Nm<sup>3</sup>/hr of air at a discharge pressure of 12 bar and 220°C. The KKK steam turbine spins the compressor at 14,235 rpm.



Process Air Compressor

The reaction products from the oxidation reactors flow to a series of separators. The overhead vapors from the separators proceed to the series of three distillation columns. The liquid in the separators flows to the stripper column. The bottoms or heavies flow from the stripper column are sent to the incinerator. The overheads from the stripper column proceed to the drying column. The drying column also receives feed from the salt extraction column and from the dehydrogenation reactor.

The bottoms from the drying column go to the forerun column. The overheads from the forerun column are sent to the incinerator. The bottoms from the forerun column are pumped to the large anone distillation column. The overheads from the anone distillation column are the final cyclohexanone product which is condensed and sent to storage. The bottoms from the column are pumped to the anol distillation column. The bottoms or heavies from the anol distillation column are pumped to the incinerator.

The overheads from the anol distillation column flow to the dehydrogenation reactor which converts the anol back to anone. The products leaving the dehydrogenation reactor are sent back to the drying column as previously mentioned.

The dehydrogenation reactor uses a copper-magnesium catalyst to convert the cyclohexanol to cyclohexanone. The charge is 8.8 metric tons and the catalyst life is about one year. The reaction takes place at atmospheric pressure and 250°C. Heat is provided for the dehydrogenation reactor with a dedicated hot oil furnace. The carbon steel reactor is a shell and tube design with catalyst in the tubes and hot oil on the shell side. The reactor is 2.6 meters diameter by 7.2 meters tall with 1,483 tubes.



Dehydrogenation Reactor

The overheads from the oxidation reactor separators mentioned earlier flow to the series of three distillation columns. The overhead from these columns go back to the oxidation reactor feed lines. The bottoms from the distillation columns are pumped to a caustic mix vessel for neutralization. The bottoms from the mix vessel are then pumped to a salt extraction column. The bottoms from this column are pumped to the waste water line, and the overheads are sent back to the drying column as previously mentioned.

The specifications for all of the columns in the Cyclohexanone Plant are shown in the table below. Sulzer reciprocating vacuum pumps are used to supply vacuum on some of the columns.

Cyclohexanone Plant Columns	Diameter (m)	Height (m)	Pressure (bar)	Temp (°C)	Comments	Material of Construction
C5401 Cooling Scrubber	2.0	22.6	12.8	215	3-packed	304SS
C5402 Direct Heat Exchange Col	2.8	13.0	12.8	215	2-packed	CS
C5501 Cyclohexane Absorber	0.9	14.3	12.8	90	2-packed	304SS
C5601 Stripper	1.2	13.6	2.3	175	1-packed	304SS
C5602 Salt Extraction Col	1.8	11.4	5.2	115	1-packed	CS
C5701 1st Distillation Col	2.3	20.4	7.3	175	18-Sieve	CS
C5702 2nd Distillation Col	2.2	21.5	7.3	175	18-Sieve	CS
C5703 3rd Distillation Col	3.2	25.9	7.3	190	21-Sieve	CS
C5801 Drying Col	1.2	16.3	2.3	190	14-Sieve	CS
C5802 Fore Run Col	1.6	38.3	1.8/FV	190	60-Sieve	CS
C5803 Anone Distillation Col	3.0	49.7	1.8/FV	190	80-Valve	CS
C5804 Anol Distillation Col	3.0	28.6	1.8/FV	190	30-Sieve	CS

## Detailed Process Description – Oximation Plant



Oximation Plant

The Oximation Plant uses 55 kmta of cyclohexanone along with some hydrogen and nitric acid (produced in the unit) to manufacture 62 kmta of the oxime intermediate. The hyam (hydrogen + nitric acid) reaction takes place in a large column reactor and the oximation reaction takes place in a series of seven agitated reactors followed by multiple distillation and separation steps. The plant, which is primarily 304 stainless steel construction, closed in 2009.



There is a complete new ammonium burner system which was never used. The original cost was \$2.5MM. This includes the burner, the NO<sub>x</sub> removal reactor, and some downstream boiler/exchanger equipment.

The reaction products from the ammonia burner proceed to the large absorber column. The column is 3.0 meters diameter by 54.1 meters tall. It is constructed of 304 stainless steel and is rated for 7.5 bar at 95°C. The column has 31 sieve trays.

The overheads from the absorber column proceed to the NO<sub>x</sub> removal reactor which uses palladium catalyst on an alumina support for destruction of the NO<sub>x</sub> products. The stream then proceeds to the tail-gas expander mentioned earlier to assist in driving the process air compressor. The expanded tail gas then exhausts through a tall stack.

The bottoms from the absorber column are pumped to the bleach tower. The bleach tower is 1.3 meters diameter by 7.3 meters tall. It is constructed of 304 stainless steel and is rated for 7.5 bar at 95°C. The column has 6 sieve trays and was constructed in 2005. The acid from the bottom of the bleach tower is pumped to the hyam reactor. The acid is about 37% concentration, which also includes a phosphoric acid component.



Absorber Column

The hyam product is produced by the reaction of hydrogen and nitric acid with a palladium catalyst. The hyam reactor is a gas-bubble reactor. There are six reactor head vessels at the top for separating the liquids and gases. The liquids drop down to six filter vessels at the bottom of the reactor for catalyst separation and recycle. The gases going overhead in the reactor head vessels are compressed and recycled back to the bottom of the reactor column. The hyam reaction takes place at 28 bar and 55°C with 9% palladium catalyst on a carbon substrate. The catalyst has been removed and recycled. The hyam reactor is 2.1 meters diameter by 23.2 meters tall. It is constructed of carbon steel and is rated for 31.8 bar at 115°C.



Hyam Reactor

The oximation reaction consists of the hyam reacting with cyclohexanone to produce the cyclohexanone-oxime with a toluene solvent. Approximately 98% of the cyclohexanone is converted in the oximation reaction section, while the remaining 2% is converted in the neutralization section of the plant. The seven agitated oximation reactors are 3.7 meters diameter by 3.0 meters tall. They are constructed of 304 stainless steel and are rated for 0.1 bar at 85°C.

The oximation reaction products then proceed through two vacuum distillation columns for removal of the toluene and impurities. The bottoms flow from the second vacuum distillation column is cyclohexanone-oxime product ready for rearrangement in the caprolactam unit described in the next section of this report. The overheads from the two vacuum distillation columns consist mainly of toluene. This stream goes through an extraction column and a toluene stripper column for recovery and recycle of the toluene back to the oximation reactors. The bottoms stream from the toluene stripper is primarily water and is recycled to the NO<sub>x</sub> absorber column in the nitric acid plant.



Oximation Reactor

## Detailed Process Description – Caprolactam Plant



Caprolactam Plant

The Caprolactam Plant uses 62 kmta of cyclohexanone-oxime along with some oleum (fuming sulfuric acid) and ammonia water to manufacture 60 kmta of the finished caprolactam product and ammonium sulfate byproduct. The Beckman rearrangement reaction takes place in relatively small section of the plant. This is followed by extraction with benzene solvent, distillation, and evaporation. The plant, which is primarily 304 stainless steel construction, closed in 2009.





The re-extraction column is another pulsating packed column. It is 1.7 meters diameter by 16.3 meters tall. It is constructed of 304 stainless steel and is rated for 4.0 bar and full-vacuum at 115°C. The overheads from the re-extraction column are condensed and go back to the benzene storage vessel. The bottoms stream is pumped to the top of the benzene stripper column.

The benzene stripper column is 1.8 meters diameter by 14.5 meters tall. It is constructed of 304 stainless steel and is rated for 2.3 bar at 165°C. This packed column boils the benzene overhead where it is condensed and sent back to the benzene storage vessel. The bottoms stream is pumped to the ion exchange beds.



Columns

There are six ion exchange beds operating in two groups of three beds. One group of beds will be in service while the other group is being regenerated. The first bed in each series is packed with anion resin, the second bed with cation resin, and the third and final bed again with anion resin.

The product from the ion exchange section is then hydrogenated in a two-stage hydrogenation reaction system rated for 10.8 bar. The system uses Raney nickel as catalyst. This process saturates and of the unsaturated compounds in the product.

The aqueous caprolactam solution which was just hydrogenated is now sent through two vacuum distillation columns to take the caprolactam concentration from 30% to 85%. The first vacuum distillation column is 1.4 meters diameter by 10.5 meters tall with eight sieve trays. It is constructed of 304 stainless steel and is rated for 4.8 bar and full vacuum at 165°C. The second vacuum distillation column is 2.7 meters diameter by 13.9 meters tall with 10 sieve trays. It is constructed of 304 stainless steel and is rated for 2.8 bar and full vacuum at 135°C. Vacuum is supplied by two liquid-ring vacuum pumps.

The 85% caprolactam solution is then sent through three evaporator stages which remove enough water to take it to 99.9% concentration. A small amount of caustic is added at this point to increase the stability of the caprolactam product. The evaporators have carbon steel shells with 304 stainless steel tubes and operate under a vacuum. The finished product is then pumped to storage or sent to the flaker operations. Vacuum is supplied by two liquid-ring vacuum pumps.




Evaporator

## Detailed Process Description – Ammonium Sulfate Plant



Ammonium Sulfate Plant

The Ammonium Sulfate Plant produces 108 kmta of solid ammonium sulfate byproduct. The plant consists of evaporation, crystallization, centrifugation, and drying processes. The plant, which is almost entirely 304 stainless steel construction, closed in 2009.



Ammonium Sulfate Plant Process Flow Diagram

The plant receives its feed as a 52% ammonium sulfate solution from the bottom of the ammonium sulfate extraction column in the Oximation Plant mentioned earlier in this report. The solution first enters the evaporator section of the plant. The evaporators take 30 m<sup>3</sup>/hr of solution from 52% to 60% ammonium sulfate in the first evaporator and from 60% to 65% in the second stage evaporator. This equates to about 8,750 lbs/hr of water removal capabilities.



1st Stage Evaporator



2nd Stage Evaporator

The solution drops from the second evaporator into a large crystallizer. The crystallizer is 7.2 meters diameter by 9.3 meters long. It is constructed of 304 stainless steel and is rated for atmospheric pressure at 100°C.

The solution is then pumped from the crystallizer to the two Escher Wyss centrifuges for thickening. Mother liquor from the centrifuges is recycled back to the crystallizer. Thickened product is transported by screw conveyor to the dryer.



Centrifuges

The dryer is 2.3 meters diameter by 8.4 meters long. It is constructed of 304 stainless steel and is rated for 0.1 bar at 180°C. Air for the dryer is steam-heated with a large 304 stainless steel exchanger. The heater is 1.4 meters diameter by 4.0 meters long and is rated for 1.8 bar at 103°C.

The dry ammonium sulfate discharges from the dryer onto a flat conveyor belt. The conveyor takes the product to a bucket elevator which transfers the product through some sieves and onto another conveyor belt going to the warehouse. The product dumps onto the large concrete warehouse floor and is moved with front-end loaders to desired warehouse locations.

## Detailed Process Description – Incinerator Unit

---



Incinerator

The incinerator unit was completely replaced in 1999. It is a vertical, water-cooled incinerator rated for 1200°C. The carbon steel burner unit is 3.4 meters diameter by 12.3 meters tall. It has the capacity to incinerate five cubic meters per hour of liquid waste. There are several large stainless steel components to this system such as the separator and the smelt dissolver. This incinerator unit was designed and constructed by the Tsukishima Kikai Company.

There is an older incinerator which is unused but still in place.

## Utilities & Tank Farm

There are two incoming electrical feeders with automatic switching gear which is included in the plant sale.

There are 13 transformers in the 1,000 to 2,000 kva range. The frequency for all electrical equipment in this facility is 60 Hz.

There are three cooling tower cells with three Worthington cooling tower water pumps. The cooling tower is in poor condition, but the pumps are in good condition.

There are four Trane chillers which appear to be about 300 tons of refrigeration capacity each.

There is a 500 kW emergency generator driven with a diesel motor.

There are two Centac instrument air compressors. The compressor is missing from one of the units.

There are two diesel-driven fire water pumps capable of 18 bar discharge pressure.

The flare is said to be 55 meters tall, but it appears to be much taller.

There are about 17 major tanks in the tank farms. They are a mix of carbon steel and 304 stainless steel construction.

## Equipment List

Major Equipment Description	Quantity	Diameter (m)	Height (m)	Pressure (bar)	Temp (°C)	Year	Comments	Material of Construction
<b>Cyclohexanone Plant (5000)</b>								
C5401 Cooling Scrubber	1	2.0	22.6	12.8	215		3-packed	304SS
C5402 Direct Heat Exchange Col	1	2.8	13.0	12.8	215		2-packed	CS
C5501 Cyclohexane Absorber	1	0.9	14.3	12.8	90		2-packed	304SS
C5601 Stripper	1	1.2	13.6	2.3	175		1-packed	304SS
C5602 Salt Extraction Col	1	1.8	11.4	5.2	115		1-packed	CS
C5701 1st Distillation Col	1	2.3	20.4	7.3	175		18-Sieve	CS
C5702 2nd Distillation Col	1	2.2	21.5	7.3	175		18-Sieve	CS
C5703 3rd Distillation Col	1	3.2	25.9	7.3	190		21-Sieve	CS
C5801 Drying Col	1	1.2	16.3	2.3	190		14-Sieve	CS
C5802 Fore Run Col	1	1.6	38.3	1.8/FV	190		60-Sieve	CS
C5803 Anone Distillation Col	1	3.0	49.7	1.8/FV	190		80-Valve	CS
C5804 Anol Distillation Col	1	3.0	28.6	1.8/FV	190		30-Sieve	CS
E5502 Ammonia Evaporator	1	1.3	6.2	26.4	75			CS
E5701A/B - C5701 Reboilers	2	1.1	5.5	16.8	280			CS
E5702 - C5702 Reboiler	1	1.7	6.7	7.3	175	1988		CS
E5703A/B - C5703 Reboiler	2	1.6	7.2	7.3	175			CS
E5705 Distillation Condenser	1	2.3	7.2	2.3	115			CS
E5801 - C5801 Reboiler	1	1.0	5.2	16.8	280	1987		CS
E5802 - C5802 Reboiler	1	1.1	4.0	16.8	280			CS
E5806 - C5803 Reboiler	1	1.0	5.2	16.8	280			CS
E5807 - C5803 Condenser	1	1.8	7.7	1.8	115			CS
E5812 - C5804 Reboiler	1	1.4	5.4	16.8	280	1999		CS
E5813 - C5804 Condenser	1	1.5	6.4	1.8	130			CS
F5901 Hot Oil Furnace	1	3.1	23.2	ATM	565			CS
R5411-14 Oxidation Reactors 1-4	4	3.4	6.0	12.8	190		Agitated	CS
R5419 Post Oxidation Reactor	1	3.4	6.5	12.8	190			CS
R5901 Anol Reactor	1	2.6	7.2				1,483 tubes	CS/CS
S5401 Water Separator	1	2.5	7.6	14.3	175			CS
S5601-3 Separator/Neutralizer 1-3	3	2.6	7.8	20.4	190			CS
S5702 Reflux Vessel	1	3.1	7.7	2.3	115			CS
V5004 Ammonia Storage Tank	1	1.5	8.2	27.5	62			CS
V5401A Cyclohexane Recirc Tank	1	3.8	8.4	2.3	115			304SS
<b>Cyclohexane Plant (5200)</b>								
C5201 Benzene Drying Col	1	0.7	12.5	2.6	115			CS
E5205 Benzene Evaporator	1	1.8	6.1	3.7	315			CS
E5208 Waste Heat Boiler	1	2.4	5.8	20.9	226			CS
R5201 1st Reactor (0.3% Pt on Al)	1	1.8	6.8	34.0	315		2,664 tubes	CS/CS
R5202 Post Reactor (Zn + Pt/Al)	1	2.2	5.2	34.0	315			CS
<b>Oximation Plant (6000)</b>								
C6301 Water Extraction Col	1	0.5	20.0	1.8	85		4-packed	304SS
C6401 1st Vacuum Col	1	1.9	20.8	2.0/FV	140		2-packed	304SS
C6402 2nd Vacuum Col	1	1.0	14.9	1.8/FV	165		1-packed	304SS
C6501 Extraction Col	1	2.0	11.8	3.5/FV	115		1-packed	304SS
C6502 Toluene Stripper	1	2.1	24.5	2.1	135		21-sieve	304SS
C6503 Waste Water Stripper	1	0.9	11.8	2.0	125		9-125	304SS
C6601 Ammonia Absorber	1	0.8	9.2	7.3	125		2-packed	304SS
C6701 NOx Absorber	1	3.0	54.1	7.5	95		31-sieve	304SS
C6702 Bleaching Tower	1	1.3	7.3	7.5	95	2005	6-trays	304SS
E6201 Hyam Reactor Cooler	1	1.3	9.5	5.0	55			CS
E6401 - C6401 Reboiler	1	1.2	5.3	3.3	185			CS
E6402 - C6401 Condenser	1	1.1	5.1	1.8	85			304SS
E6502 - C6502 Reboiler	1	1.2	5.0	5.3	190			CS
E6603 Ammonia Evaporator	1	2.0	6.2	26.4	75			CS
E6604 - R6601 Waste Heat Boiler	1	2.1	5.6	6.5	350			CS
E6802 - R6801 Waste Heat Boiler	1	1.6	4.6	6.0	350			CS
R6201 Hyam Reactor	1	2.1	23.2	31.8	115			CS
R6301-07 Oximation Reactors	7	3.7	3.0	0.1	85		Agitated	304SS
R6601 Ammonia Burner (+1 spare)	2	1.5	2.1	6.5	1000			
R6801 NOx Remover (+1 spare)	2	1.8	1.6	6.0	750			
S6201A-F Filtration Vessels	6	1.6	3.5	34.0	115			304SS
S6801 Mist Separator	1	1.6	7.0	7.5	75			304SS
T6201 - R6201 Let-down Tank	1	4.8	6.1	ATM	115			304SS
V6204 Buffer Vessel	1	5.8	7.6	ATM	115			304SS
V6403 Toluene Oxime Vessel	1	4.8	3.8	ATM	80			304SS
V6701/2 - C6701 Buffer Vessels	2	5.8	7.6	ATM	80			304SS
V7203A/B Crude Caprolactam Tanks	2	5.0	6.1	ATM	115			304SS
V7301 Benzene Storage Tank	1	4.8	6.1	ATM	65			304SS
<b>Caprolactam Plant (7000)</b>								
C7301 Ammonium Sulf Extraction Col	1	1.0	13.8	3.6/FV	115		Pulsating-Pack	304SS
C7302 CPL Extraction Col	1	1.7	18.1	1.8	85		Rotating Disc	304SS
C7303 Re-extraction Col	1	1.7	16.3	4.0/FV	115		Pulsating-Pack	304SS
C7304 Benzene Distillation Col	1	1.0	6.1	2.3	115		12-sieve	304SS
C7305 Benzene Stripper Col	1	1.8	14.5	2.3	165		2-packed	304SS
C7306 Condensate Stripper	1	0.4	3.7	2.3	165		1-packed	304SS
C7401-6 Ion Exchange Beds	6	1.7	4.4	7.3	115		1-packed	304SS
C7601 1st Distillation Col	1	1.4	10.5	4.8	165		8-sieve	304SS
C7602 2nd Distillation Col	1	2.7	13.9	2.8	135		10-sieve	304SS
C7801 Scrubber	1	0.9	3.8		115			304SS
E7202 Neutralization Cooler	1	1.0	7.4	3.8	115			304SS
E7601 1st Dist Col Reboiler	1	1.2	5.1	5.3	190			CS
E7602 2nd Dist Col Reboiler	1	1.5	4.7	4.8	165			CS
E7604 2nd Dist Col Condenser	1	1.5	7.5	2.8	115			CS
S7702 Lactam Distillation Separator	1	2.5	7.9	1.8	165			304SS
<b>Ammonium Sulfate Plant (8500)</b>								
E8502 Heater #2	1	1.4	4.0	1.8	103			304SS
E8504 Condenser #1	1	1.2	6.6	1.8	67			304SS
G8501 Dryer	1	2.3	8.4	0.1	180			304SS
V8501 1st Effect Evaporator	1	3.2	6.5	0.5/FV	120			304SS
V8504 2nd Effect Evaporator	1	3.8	7.1	0.9/FV	100			304SS
X8501 Crystallizer	1	7.2	9.3	ATM	100			304SS
X8503 Wet Scrubber	1	3.2	7.7	ATM	103			304SS
<b>Incinerator (0100)</b>								
F0101 Incinerator	1	3.4	12.3	0.3	1,200	1999		CS
F0201 Incinerator (abandoned)	1							CS
S0105 Separator	1	3.2	22.6	0.3	100			304SS
V0102 Smelt Dissolver	1	4.2	4.5	0.2	100	1999		304SS
<b>Tank Farms</b>								
T0201 Caustic Tank	1	5.8	6.9	ATM	132			304SS
T0202 Oleum Tank	1	1.5	2.7	ATM	172			304SS
T0203 Sulfate Tank	1	4.0	5.4	ATM	73			304SS
T0301 Sulfuric Acid (98%) Tank	1	8.2	10.6	ATM	45			CS
T0302 Oleum Tank	1	8.1	9.1	ATM	45			CS
T0303 Ammonium Sulfate Tank	1	10.4	12.1	ATM	60			304SS
T0304A Caustic Tank	1	4.8	6.1	ATM	55			304SS
T0304B Caustic Tank	1	2.9	20.0	17.6	343			CS
T5201A/B Benzene Tanks	2	8.5	10.6	ATM	65			CS
T5202A Cyclohexane Tank	1	8.2	10.6	ATM	65			CS
T5202B Cyclohexane Tank	1	13.4	15.6	ATM	65			CS
T5802A Intermediate Tank	1	5.7	7.6	0.1	190	1987		CS
T5803 Cyclohexanone Tank	1	11.6	14.4	ATM	90			CS
T7801A/B/C Caprolactam Tanks	3	9.0	12.1	ATM	140			304SS