

PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



Company Profile



Contact us @ www.primepower.co.uk

KADUNA

Primepower Limited
No. 6. Gwari Crescent,
U/Rimi GRA Kaduna.
P.O. Box 4420, Kaduna North,
Nigeria.
Tel: 234 (0)7088492649
[e-mail: nigeria@primepower.co.uk](mailto:nigeria@primepower.co.uk)

ABUJA

Primepower Limited
Plot 96, Abaji Close
Off Oyo Street, Area 2
Garki - Abuja
Nigeria
Tel: 234 (0)7088492649
[e-mail: nigeria@primepower.co.uk](mailto:nigeria@primepower.co.uk)

UNITED KINGDOM

Primepower International LTD
Leigh House, Lichfield Road,
Hamstall Ridware
Rugeley, Staff, WS15 3QG
England.
Tel/Fax: + 44 1889 504125
[e-mail: mailbox@primepower.co.uk](mailto:mailbox@primepower.co.uk)

CLYDEUNION PUMPS
Wain Pumps - Clyde Pumps - Mather & Platt -
Drysdale - WH Allen - Giribattens -
Allen Gwynnes - Hordard



UNION Pump
Union Pump - David Brown Pumps
DB Guinand Pumps - American Pump - Pumples



Primepower Limited based in Abuja and Kaduna, is a highly successful Company that has been operating in Nigeria since 1976 in the field of Mechanical and Electrical Engineering.

Over the years, Primepower has expanded and is now known throughout Nigeria as quality suppliers and installer of Diesel Engine Driven Generating Sets, Transformers, Switchgear, Pumps, Electrical and Mechanical Installations and other engineering products.

Our spacious workshop in Kaduna North are fully equipped to undertake assembly, testing and major overhauls of generating sets and associated equipment together with welding and machining. We have all the necessary tools, equipment and qualified staff to enable us to carry out large M & E projects and refer you to the attached list of projects, together with generating sets and pumps supplied and installed over the past years.

We are sole agent of SPX incorporating ClydeUnion Limited formerly Weir Pumps Limited who is one of the largest manufacturers of pumps in Europe and have supplied and installed many pumps in Nigeria over the last 70 years. We are also sole agent of SDMO who is one of the largest manufacturers of Generating sets in Europe.

In addition to the facilities we offer, our European Principals (SPX ClydeUnion Pumps and SDMO) are available to support us commercially and technically. In association with Primepower, SPX ClydeUnion Pumps and SDMO have undertaken many projects; Pumping Stations, Complete Water Works and Power Stations.

**PROFESSIONAL
CERTIFICATION**

PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



SOME EXAMPLES OF OUR HIGH LIFT TOWNSHIP WATER SUPPLY PROJECTS



Bauchi High lift Township Water supply pumps



Kaduna low lift pumps, From River



Manchok Township pumps

PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



SOME EXAMPLES OF OUR HIGH LIFT TOWNSHIP WATER SUPPLY PROJECTS

Kano High lift pumps Chalawa (Being installed)



Zonkwa High lift Township Water supply pumps



Ikara high lift pumps, Township Supply



PRIMEPOWER


Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



MECHANICAL & ELECTRICAL INSTALATIONS (SEE ATTACHED PROJECTS DONE)



Multiple swimming pool construction Abuja.



PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



SOME ELECTRIFICATION PROJECTS




Ministry of Raw Materials Abuja



Former N.M.A Abuja



British Embassy village Abuja



PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



GENERATING SETS

SUPPLIERS OF DIESEL ENGINE DRIVEN GENERATING SETS FROM 1KVA TO 2000 KVA, INCLUDING PORTABLE UNITS, SOUND-PROOF UNITS, TURNKEY POWER STATIONS, ELECTRIFICATION PROJECTS



For more information
visit www.sdmo.com



PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers




ELECTRIFICATION & DESIGN PROJECTS



Abuja housing complexes



Abuja housing complexes




PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



SWIMMING POOL WORK OVER THE YEARS



PRIMEPOWER

Suppliers, Installation, Maintenance & Contractors
Electrical & Mechanical Engineers



OTHER PRODUCTS & EQUIPMENT

Other products and equipment includes switchgear, transformers, motors, dumpers, vibrators, compactors, welding sets, irrigation pumps, UV water treatment equipments, auto-filters etc.



UV Water Treatment

Automatic Filter

Tank Agitators

Electric Motor



Dumper

Rotary Power Trowel

Transformer

All Voltage panels



Tractor

Bocart

Welding Genset

Vibrator & Poke

Compactor

Our European Partners

SPX ClydeUnion Pumps

formerly

Weir Pumps Limited.

Overview of SPX Profile

and Equipment.



100 YEARS OF
INNOVATION

ENGINEERED
SOLUTIONS

SPX Flow Technology Overview





Index

Index	2
SPX Flow Technology	3
Airpel Series.....	3
Anhydro.....	4
APV	5
APV Systems.....	6-10
Bran+Luebbe	11
Bran+Luebbe Processing Modules / Systems	12-13
ClydeUnion Pumps.....	14-16
Copes-Vulcan.....	17
Delair	18
Deltech	19
Dollinger	20-21
e&e Series.....	22
Gerstenberg Schröder	23
GD Engineering	24
Hankison	25-26
Jemaco.....	26
Johnson Pump Industrial	27
Johnson Pump Marine.....	28
LIGHTNIN	29
M&J Valve	30
Plenty Mirreles Pumps.....	31
Plenty Mixers	31
Plenty Filters.....	32
Plenty Process Filtration.....	33-34
Pneumatic Products.....	35
Seital Separation Technology.....	36
Tigerholm.....	37
Vokes.....	38
Waukesha Cherry-Burrell.....	39-40
Innovation Centers	41
R&D/Testing Capabilities	42
After-Sales Services	43

SPX is a Fortune 500 multi-industry manufacturing leader, headquartered in Charlotte, North Carolina. SPX manufactures and markets products, components, services and technologies that are integral to meeting today's challenges and tomorrow's needs. We are a place where innovation is fostered, and the real needs of business are understood. We transform ideas into powerful solutions to help our customers meet their goals, overcome business challenges and thrive in a complex, always changing marketplace.



100 YEARS OF INNOVATION

SPX's Flow Technology segment designs, manufactures and markets engineered solutions and products used to process, blend, meter and transport fluids. We also offer equipment for air and gas filtration and dehydration. Our leading brands have global operations which serve the food & beverage; power & energy; and industrial processes.

To learn more about our industry leading technologies and brands, please visit us at www.spx.com



Airpel Series

Email: airpel@spx.com

SPX Flow Technology

Hambridge Road
Newbury, Berkshire, UK RG14 5TR
Tel: +44 (0) 1635 42363
Fax: +44 (0) 1635 49758

SPX Flow Technology

19191 Hempstead Highway
Houston, TX 77065 USA
Tel: +1 (281) 469-0550
Fax: +1 (281) 807-2805

Established:

1939

Common Applications:

Oil & Gas, Chemical, Power, Marine, Mining, Pulp & Paper, Steel, Offshore, Automotive, Food, Heating, Cooling, Water, Waste & Sewerage, Refining



SELF-CLEANING FILTERS

- ④ Used where an automatic cleaning strainer is required even with low pressures
- ④ Ensures process continuity without manual labor or contact with hazardous materials
- ④ Fine Stainless Steel wedge wire or perforation elements down to 25 microns
- ④ Automation provides labor savings and allows use on un-manned sites
- ④ Positive scraping action efficiently cleans element while independent dumping minimizes fluid loss



OV SINGLE & OW DUAL BASKET STRAINERS

OV Single Basket Strainers:

- ④ Used for filtering liquids when flow can be interrupted for cleaning
- ④ Line sizes from 3/4" to 10" NB and pressure ratings to ANSI 300 available
- ④ Available in a wide range of materials to suit the application
- ④ OV & OW multi-basket designs available, filtration levels from 10mm down to 10 micron

OW Dual Basket Strainers:

- ④ Used for filtering liquids when flow cannot be interrupted for cleaning
- ④ Handle selects between operating chamber, allowing safe removal of basket from isolated chamber while filter is still in operation
- ④ Optional 100% shutoff facility to eliminate any leakage between chambers




Email: ft.dk.soeborg@spx.com

SPX Flow Technology
 105 Crosspoint Pkwy.
 Getzville, NY 14068 USA
 Tel: +1 (716) 692-3000
 Fax: +1 (716) 692-6416

SPX Flow Technology
 Oestmarken 7
 DK-2860 Soeborg
 Denmark
 Tel: +45 7027 8222
 Fax: +45 7027 8223

Established: 1948
Common Applications: Dairy, Food, Chemical, Pharmaceutical



PROCESSES

- ④ The Anhydro processes combine more than 60 years of experience and specialization in evaporation and drying for the dairy, food, chemical, pharmaceutical and other industries
- ④ Anhydro plants and equipment are renowned for their design, engineering, process quality and efficiency
- ④ Dedicated Process Technology Specialists



DRYERS

- ④ Dryers for virtually any powder application ranging from small-scale plant with capacities of a few kg/h to large-scale industrial plants, from single-stage to multi-stage, including the Anhydro Triple-A Dryer®
- ④ More than 20 different chamber designs including conical bottom, flat bottom, Tall Form, Uniflow and High Body
- ④ Spin Flash Dryers for drying of high-viscosity products, pastes and filter cakes



EVAPORATORS

- ④ Highly energy-efficient way of removing water
- ④ MVR
- ④ Falling film tubular
- ④ TVR
- ④ Forced circulation
- ④ Natural circulation
- ④ Gas-heated
- ④ Reduced falling film
- ④ Single pass falling film



FLUID BED TECHNOLOGY

- ④ Fluid Bed Dryers
- ④ Batch and continuous fluid beds, as well as fluid beds to be integrated into multi-stage spray drying plants
- ④ Fluid Bed Coolers



SMALL SCALE EQUIPMENT/LAB EQUIPMENT

- ④ Designed for scientific test work, industrial research and small scale production
- ④ Repeatability
- ④ High uptime and yield
- ④ Full process control
- ④ Adaptability
- ④ Compliance with the strictest factory standards



PARTS & SERVICE

- ④ All Anhydro systems are supported by our global service organization to enable you to achieve optimum 24x7 throughput and on-spec quality for the entire lifetime of the equipment
- ④ Plant retrofitting
- ④ Preventive maintenance agreements
- ④ Spare parts service
- ④ Troubleshooting
- ④ Plant performance optimization



TEST CENTER

- ④ Innovation center to support customers in trials and new developments
- ④ Training and support to customers on small scale equipment



Email: apv.nordic@apv.com

SPX Flow Technology
1200 West Ash Street
Goldsboro, NC 27530 USA
Tel: +1 (919) 735-4570
Fax: +1 (919) 581-1167

SPX Flow Technology
611 Sugar Creek Road
Delavan, WI 53115 USA
Tel: +1 (262) 728-1900
Fax: +1 (262) 728-4904

SPX Flow Technology
Zeichenstrasse 49
Unna D-59425 Germany
Tel: +45 (0) 2303 108-0
Fax: +45 (0) 2303 108210

SPX Flow Technology
Pasteursvej
8600 Silkeborg, DK
Tel: +45 70 278 278
Fax: +45 70 278 330

Established: 1910
Common Applications: Food, Dairy, Beverage, Brewery, Healthcare, Marine, Power, Chemical, Biotechnical, Petrochemical, HVAC, Industrial, Oil & Gas, Pulp & Paper, Automotive, Refining



HEAT EXCHANGERS

- ④ Invented Plate Heat Exchanger in 1923
- ④ Wide portfolio including Gasket, Brazed, and Semi-Welded Plate, Tubular, Scraped Surface, Hybrid and District Heating Units
- ④ Heat exchangers suitable for Hygienic and Industrial applications
- ④ Large range of plate, gasket, material and configurations available
- ④ Comply with international standard e.g. PED, ASME, SQL
- ④ Plate material includes AISI 316, AISI 304, Titanium and most alloys



HOMOGENIZERS

- ④ Rannie & Gaulin Brands
- ④ High Performance
- ④ Modular design for greater flexibility
- ④ Innovative service and maintenance concepts
- ④ Laboratory Testing Services
- ④ Quiet stability with low noise, low vibrations and optional sound proof cabinets available
- ④ Lower cost of ownership



PUMPS

- ④ Centrifugal Pumps, Positive Displacement Pumps, Self-Priming Pumps
- ④ Extensive product range including high capacity, aseptic, water for injection, high pressure
- ④ Energy efficient
- ④ Highest hygienic standards. EHEDG, 3A, FDA approved. Designed for CIP and SIP
- ④ Easy maintenance
- ④ Low noise and vibration levels
- ④ Low NPSH requirements



VALVES

- ④ Includes Butterfly, Single-Seat, Mixproof, Aseptic, Regulating and Process Valves
- ④ Highest hygienic and aseptic standards. 3A, EHEDG, PMO, FDA approved
- ④ Designed for CIP
- ④ Easy maintenance, adaptable and modular
- ④ Different control unit options - Direct Connect, AS Interface, Valve-Net DeviceNet, Valve-Net Profibus



TECHNOLOGIES

- ④ UHT & Thermal Processing Units; Membrane Filtration & Microparticulation, General Processing; Food; Fresh Dairy Products; Cheese, Butter & Spreads; Beverage & Brewery Units; Plate Evaporation & Distillation
- ④ Dedicated Process Technology specialists
- ④ Innovation Center to support customers in new developments
- ④ Long tradition and extensive references in the Dairy & Food industry
- ④ Excellent aftermarket support and service

FactoryExpert

Driving Manufacturing Excellence

AUTOMATION

- ④ APV FactoryExpert delivers automation and software solutions targeting Quality, Production Performance, Utility Management, Regulatory Compliance, Maintenance and Production Optimization
- ④ APV FactoryExpert provides highly functional automation solutions for new projects, migration of aging legacy control systems and upgrading existing automation controls



Email: apv.nordic@apv.com

SPX Flow Technology
 105 Crosspoint Pkwy.
 Getzville, NY 14068 USA
 Tel: +1 (716) 692-3000
 Fax: +1 (716) 692-6416

SPX Flow Technology
 Pasteursvej
 8600 Silkeborg, DK
 Tel: +45 70 278 278
 Fax: +45 70 278 330

Established: 1910
Common Applications: Food, Dairy, Beverage, Pharmaceutical, Personal Care

	<p style="text-align: center;">INFUSION / PURE-LAC</p> <ul style="list-style-type: none"> ④ Gentle and accurate heating ④ Fast heating 600°C/sec. ④ Accurate holding time ④ High bacteria spore kill rate ④ Shelf life up to 45 days ④ High product flexibility ④ Superior product quality - low chemical change, pasteurized milk flavor ④ Low fouling rate ④ Long operating time between CIP ④ Pre-assembled and factory-tested ④ As option designed according to ASME, PMO, 3A
	<p style="text-align: center;">TUBULAR</p> <ul style="list-style-type: none"> ④ High up-time ④ Flexible product range ④ Easy inspection of product and medium surface ④ High pressure tolerance ④ Low energy cost ④ Low maintenance cost ④ Pre-assembled and factory-tested ④ As option designed according to ASME, PMO, 3A
	<p style="text-align: center;">HIGH HEAT INFUSION</p> <ul style="list-style-type: none"> ④ Bacteria kill rate over Fo 40 (Fo is defined as total integrated lethal effect) ④ Increased operating time ④ Reduced maintenance costs ④ Efficient deaeration prior to heating ④ Non-aseptic flavor dosing of the vacuum chamber possible ④ Destruction of heat resistant spores (HRS) ④ Pre-assembled and factory-tested ④ As option designed according to ASME, PMO, 3A
	<p style="text-align: center;">INSTANT INFUSION</p> <ul style="list-style-type: none"> ④ Gentle and accurate heating ④ Fast heating 600°C/sec. ④ Efficient bacteria spore kill rate ④ Up to 70% less vitamin loss ④ Holding time down to 0.09 sec. ④ Very low chemical change ④ Superior product quality ④ High temperature treatment of +50% concentrate prior to spray drying ④ Long operating time between CIP ④ Pre-assembled and factory-tested ④ As option designed according to ASME, 3A
	<p style="text-align: center;">SPIRATHERM®</p> <ul style="list-style-type: none"> ④ Long running hours ④ Designed for high fouling products ④ No product / steam mixing ④ Remote and downstream homogenizing, one or two stage system ④ High velocity/natural scrubbing => less fouling ④ FDA and 3A approved ④ No gaskets at product side ④ Short CIP time ④ SpiraTherm tubular heat exchanger
	<p style="text-align: center;">MULTI-PURPOSE UHT PILOT PLANT</p> <ul style="list-style-type: none"> ④ Very reliable system for product trials before upscaling to commercial production ④ Highly flexible ④ Quick and easy installation ④ One unit with small footprint ④ Operator-friendly ④ Pre-assembled and factory-tested



Email: apv.nordic@apv.com

SPX Flow Technology
 105 Crosspoint Pkwy.
 Getzville, NY 14068 USA
 Tel: +1 (716) 692-3000
 Fax: +1 (716) 692-6416

SPX Flow Technology
 Pasteursvej
 8600 Silkeborg, DK
 Tel: +45 70 278 278
 Fax: +45 70 278 330

Established: 1910
Common Applications: Food, Dairy, Beverage



MICROFILTRATION (MF) SYSTEM

- ④ Proven components and system design
- ④ Very robust ceramic membranes
- ④ Long lifetime of the ceramic membranes
- ④ New generation GP membranes
- ④ Future option for SW polymer membranes
- ④ Very high quality and reliable engineered system
- ④ Pre-assembled in our workshop
- ④ Operator and maintenance friendly



ULTRAFILTRATION (UF)

- ④ Proven components and system design
- ④ Proven membranes for any dairy application
- ④ High performance and long membrane lifetime
- ④ High quality engineering, standardized system
- ④ Speed controllers on all motors
- ④ Optimized utility consumption
- ④ Pre-assembled in our workshop
- ④ Operator- and maintenance-friendly



UF CHEESE SYSTEMS

- ④ Proven membranes for various milk applications
- ④ High performance and long membrane lifetime
- ④ High quality engineering, standardized system
- ④ Proven process/UF cheese technology
- ④ High yield and product quality
- ④ Increased profitability
- ④ Large number of references
- ④ Complete line with pre-treatment and post-treatment (e.g. MF debacterization for Feta)




NANOFILTRATION SYSTEM (NF)

- ④ Proven components and system design
- ④ Proven membranes for NF dairy applications
- ④ Optimized performance and long membrane lifetime
- ④ Inline UF, NF, RO polisher
- ④ High quality engineering, standardized system
- ④ Optimized utility consumptions
- ④ Pre-assembled in our workshop
- ④ Operator- and maintenance-friendly



REVERSE OSMOSIS (RO)

- ④ Proven components and system design
- ④ Proven membranes for NF dairy applications
- ④ High performance and long membrane lifetime
- ④ Inline process: UF, RO, RO polisher
- ④ High quality engineering, standardized system
- ④ Optimized utility consumption
- ④ Pre-assembled in our workshop
- ④ Operator- and maintenance-friendly



APV LEANCREME™ PROCESS

- ④ A unique process ensuring optimal distribution of particle size
- ④ Ensures superior taste in low-fat products
- ④ Excellent functional properties
- ④ Ability to vary particle sizes
- ④ Fast payback, high ROI
- ④ Proven, high quality system design
- ④ Evaporation and spray-dry options
- ④ Increased yield



Email: apv.nordic@apv.com

SPX Flow Technology
105 Crosspoint Pkwy.
Getzville, NY 14068 USA
Tel: +1 (716) 692-3000
Fax: +1 (716) 692-6416

SPX Flow Technology
Pasteursvej
8600 Silkeborg, DK
Tel: +45 70 278 278
Fax: +45 70 278 330

Established: 1910
Common Applications: Food, Dairy



CHEESE VATS - CURDMASTER A VERTICAL DOUBLE O VAT

- ④ Fast foamless filling
- ④ Rapid mixing of all added components including rennet
- ④ Gentle and precise cutting
- ④ High yield
- ④ Fast whey draw
- ④ Controlled, fast heating and cooling
- ④ Vertical vat with 2 outlets for fast emptying
- ④ Efficient and gentle stirring
- ④ Fully automated with touch screen
- ④ CIP cleanable vats



OPD PRE-PRESS

- ④ Flexible pre-press for all cheese types, block sizes and shapes
- ④ Adapts easily to variations in fat and water content
- ④ Physical separation between the batches for clear identification
- ④ Easy change of cheese dimension and shape
- ④ Same unit can make Gouda- and Tilsit-types
- ④ Long running time between CIP cleaning
- ④ Higher yield and uniform water content
- ④ High weight accuracy due to curd distribution



SANIPRESS SYSTEM

- ④ Even pressing of cheeses in individual molds or multiple molds without using spring-loaded lids
- ④ A specific pressure of 400 g/cm² (5.7 lbs./sq.in.) is achieved at only 0.3 bar (4.3 lbs./sq.in. air pressure)
- ④ Optional pressing cylinders available
- ④ Applicable to a wide variety of cheese types, shapes and sizes
- ④ Integrated mold storage
- ④ Collecting of whey and CIP liquid
- ④ CIP cleanable

APV, AN SPX BRAND - EVAPORATION AND DISTILLATION

Established: 1910
Common Applications: Food, Dairy, Beverage, Brewery, Pharmaceutical, Chemical Industrial, Fuel Alcohol



PLATE EVAPORATOR

- ④ Enhanced quality of food products
- ④ Low head room requirement
- ④ Easy accessed for cleaning
- ④ Flexibility in capacity by adding plates



DISTILLATION

- ④ Modular design - pre-assembled
- ④ Full lab testing available
- ④ Customized for application









Email: apv.nordic@apv.com

SPX Flow Technology
 105 Crosspoint Pkwy.
 Getzville, NY 14068 USA
 Tel: +1 (716) 692-3000
 Fax: +1 (716) 692-6416

SPX Flow Technology
 Pasteursvej
 8600 Silkeborg, DK
 Tel: +45 70 278 278
 Fax: +45 70 278 330

Established: 1910
Common Applications: Food, Dairy

	<p style="text-align: center;">CONTINUOUS BUTTER MAKING MACHINE - HCT</p> <ul style="list-style-type: none"> ④ Built-in cream pre-heater ④ Built-in buttermilk cooling ④ Low air content in final product ④ Advanced dosing system for water, salt and culture ④ Internal CIP system ④ Factory-tested before shipping ④ Each machine size has a wide capacity range
	<p style="text-align: center;">BUTTER PACKAGING LINE - FMG</p> <ul style="list-style-type: none"> ④ Stainless steel throughout ④ Single, compact unit ④ Accurate filling for less giveaway of butter ④ Available with a troubleshooting system to reduce downtime ④ Advanced control system with data collection ④ Factory-tested before shipping ④ Each machine size has a wide capacity range ④ FMG+ is capable of packing two different carton sizes at the same time
	<p style="text-align: center;">DAIRY BLEND PLANT</p> <ul style="list-style-type: none"> ④ No vegetable oil residues in the buttermilk ④ Simultaneous injection of several oil types ④ Flexible end-product range, fat content in final product 40-80% ④ Stand-alone system, factory-tested before each shipping ④ Each machine has a wide capacity range ④ SPX patented process
	<p style="text-align: center;">BUTTER REWORKING PLANT</p> <ul style="list-style-type: none"> ④ Continuous, closed system minimizing the risk of bacteriological issues ④ Vacuum chamber for lowering of the air content in the product ④ Precise dosing of water, salt, culture, etc. to ensure a uniform end-product ④ Stand-alone system, factory-tested before shipping ④ Wide capacity range
	<p style="text-align: center;">BUTTER SILOS HRS</p> <ul style="list-style-type: none"> ④ Big diameter augers ensures reduced working softening of the product ④ Auger speed can be controlled by packaging capacity ④ Installed light and transparent man-way ensures easy inspection ④ Round corners inside ④ Inclined bottom to ensure drainage during CIP ④ Short CIP turn-around time
	<p style="text-align: center;">BUTTER SILO HCC</p> <ul style="list-style-type: none"> ④ Suitable for butter as well as dairy blend ④ No augers ④ No additional working of the product ④ 1 - 5 butter pumps ④ Low waste of product at shut down ④ Minimal floor space requirement









Email: apv.nordic@apv.com

SPX Flow Technology
105 Crosspoint Pkwy.
Getzville, NY 14068 USA
Tel: +1 (716) 692-3000
Fax: +1 (716) 692-6416

SPX Flow Technology
Pasteursvej
8600 Silkeborg, DK
Tel: +45 70 278 278
Fax: +45 70 278 330

Established: 1910

Common Applications: Food, Dairy, Beverage, Brewery, Personal Care, Pharmaceutical, Biotechnology, Paint

	<p style="text-align: center;">FLEX-MIX INSTANT</p> <ul style="list-style-type: none"> ④ Unique high shear mixing enables a high powder intake ④ Air is efficiently removed during mixing prolonging running time and ensuring consistent quality ④ Allows a closed, continuous production, resulting in higher throughput and reduce dust issues ④ Handles a large number of formulations
	<p style="text-align: center;">FLEX-MIX PROCESSOR</p> <ul style="list-style-type: none"> ④ Gentle agitation, internal circulation ④ High shear mixing for emulsification ④ Handles particulate inclusion ④ Heating via jacket or direct steam injection ④ Closed system with vacuum/flash options ④ Quick batch preparation (flip-flop)
	<p style="text-align: center;">FLEX-MIX LIQUIVERTER</p> <ul style="list-style-type: none"> ④ Simple but versatile ④ Flexibility at low CAPEX ④ Large dissolution capacity due to free vortex and square shape ④ Fully drainable for improved hygiene and minimum waste ④ Direct drive reduces spare parts wear ④ Flushed double mechanical shaft seal available in material of customer's choice, depending on application ④ Easy to maintain
	<p style="text-align: center;">POWER-MIXER</p> <ul style="list-style-type: none"> ④ Aseptic aeration ④ Emulsification ④ Continuous mixing ④ PLC standard in all aseptic systems ④ Operator-friendly, smooth and trouble-free operation ④ Pre-assembled and factory-tested
	<p style="text-align: center;">DEAERATOR - VFJ/VFN</p> <ul style="list-style-type: none"> ④ New, superior aroma-recovery system ④ Automatic parasol regulating valve ④ Improved hygiene ④ Reduced commissioning costs ④ Operator-friendly ④ Pre-assembled and factory-tested
	<p style="text-align: center;">VFN E-VAP CONCENTRATOR</p> <ul style="list-style-type: none"> ④ Fresh taste and odor ④ Increased viscosity in milk applications ④ Smooth and creamy texture in fermented products ④ Increased serum stability ④ Operator-friendly ④ Pre-assembled and factory-tested



Email: branluebbe@spx.com

SPX Flow Technology
 Werkstraße 4
 D-22844 Norderstedt, Germany
 Tel: +49 (0) 40 - 522 02-0
 Fax: +49 (0) 40 - 522 02-444

SPX Flow Technology
 611 Sugar Creek Road
 Delavan, WI 53115 USA
 Tel: +1 (800) 252-5200 or
 +1 (262) 728-1900
 Fax: +1 (262) 728-4904

SPX Flow Technology
 Ironstone Way, Brixworth
 Northants, NN6 9UD UK
 Tel: +44 (0) 1604 880751
 Fax: +44 (0) 1604 880145

Established: 1932
Common Applications: Oil & Gas, Petrochemical, Chemical, Food, Beverage, Personal Care, Pharmaceutical
 Pulp & Paper, Water Treatment



PROCAM METERING PUMPS

- ④ Modular, single and multi-stream pump configurations to match the process requirement
- ④ Double Diaphragm and Plunger Pumps
- ④ Pressures up to 20 bar / 300 PSI
- ④ Flow rates up to 3000 l/h / 790 GPH per pump head
- ④ ProCam Smart, a high quality, economic pump for customers with less demanding applications



NOVADOS METERING PUMPS

- ④ Horizontal and vertical metering pumps
- ④ Modular, single and multi-stream pump configurations to match the process requirements
- ④ Pressures up to 1000 bar / 15000 PSI
- ④ Flow rates up to 22600 l/h / 6000 GPH
- ④ Variable speed drive & variable stroke adjustment for manual or automatic flow control
- ④ Double diaphragm and plunger pumps, API 675 compliant
- ④ Remote condition monitoring with the NOVALINK-CSM online diagnostic system



NOVAPLEX PROCESS PUMPS

- ④ Reciprocating high performance diaphragm process pumps for high pressure and high capacity applications
- ④ Modular design, additions can be added on for future expansions
- ④ Pumping chamber hermetically sealed
- ④ Pressures up to 1000 bar / 15000 PSI
- ④ Flow rates up to 80 m3/h / 21000 GPH
- ④ Hydraulic power up to 260 kW / 350 HP with variable speed control option
- ④ Remote condition monitoring with the NOVALINK-CSM online diagnostic system



ONLINE ANALYZERS

- ④ Wide range of applications
- ④ Fully automatic systems
- ④ Multi-stream measurements
- ④ Low operation costs
- ④ Remote control and diagnostics
- ④ Inline probes
- ④ Innovative technology
- ④ Single parameter and multi parameter systems



Email: branluebbe@spx.com





SPX Flow Technology
 Werkstraße 4
 D-22844 Norderstedt, Germany
 Tel: +49 (0) 40 - 522 02-0
 Fax: +49 (0) 40 - 522 02-444

SPX Flow Technology
 611 Sugar Creek Road
 Delavan, WI 53115 USA
 Tel: +1 (800) 252-5200 or
 +1 (262) 728-1900
 Fax: +1 (262) 728-4904

SPX Flow Technology
 Ironstone Way, Brixworth
 Northants, NN6 9UD UK
 Tel: +44 (0) 1604 880751
 Fax: +44 (0) 1604 880145

Established: 1932

Common Applications: Color, Fragrance, Shampoo, Shower Gel, Fabric Conditioner, Liquid Detergent, Mayonnaise, Tomato Ketchup, Margarine, Polyurethanes, Resins, Bitumen, Shaving Gel, Orange Juice, Soft Drinks, SLES Dilution, Bakery Additives, Brewing, Medical Gels and Paper Wipes

	<p style="text-align: center;">STANDARD SYSTEMS FOR ADDITIVE INJECTION</p> <ul style="list-style-type: none"> ④ Space efficient ④ Standard design ④ Cost-effective ④ Quick Delivery ④ Food quality available ④ High quality and fit for purpose ④ 1-500 l/hr dosing flowrate ④ Control options, (inverter, flowmeter, controller)
	<p style="text-align: center;">TOILETRIES MASTERBATCH SYSTEMS</p> <ul style="list-style-type: none"> ④ Product pumped direct from storage vessels ④ Inline mixing removes need for large batch vessel ④ Inline quality assurance (pH, viscosity) ④ Manufacture "white" common base ④ Minimal clean out ④ Custom designed, built and fully tested ④ Continuous or batch applications
	<p style="text-align: center;">FINISHING UNIT SYSTEMS</p> <ul style="list-style-type: none"> ④ Using common "white" base, makes several variants ④ Dosing perfume, color, pH adjust, viscosity adjust, etc. ④ Inline mixing removes need for large batch vessel ④ Inline quality assurance (pH, viscosity) ④ Minimal clean out ④ Fast changeover to different recipes with minimal waste
	<p style="text-align: center;">FOOD MANUFACTURING PACKAGES</p> <ul style="list-style-type: none"> ④ Sanitary design ④ Consistent product quality ④ Single skid unit ④ Small footprint compared with batch ④ Continuous process - make only as much as you need ④ Control automation available ④ Proven technology ④ Bakery application includes dosing glycerine and palm oil into dough to make tortillas
	<p style="text-align: center;">CHEMICAL PROCESSING</p> <ul style="list-style-type: none"> ④ Blending processes or single chemical dosing ④ Heating, cooling and mixing options ④ ATEX designs available ④ Suitable for hostile environments ④ Custom designed, built and fully tested ④ Minimal onsite installation ④ Continuous or batch applications ④ Control Options (PLC to full SCADA)
	<p style="text-align: center;">PROCESS UNITS FOR LIQUID LAUNDRY DETERGENT</p> <ul style="list-style-type: none"> ④ Continuous flow process ④ Sanitary design ④ Flexible production ④ Excellent mixing performance ④ Quality check by inline measurements ④ Efficient and fast cleaning procedures ④ Very high dosing accuracy



Email: branluebbe@spx.com

SPX Flow Technology
 Werkstraße 4
 D-22844 Norderstedt, Germany
 Tel: +49 (0) 40 - 522 02-0
 Fax: +49 (0) 40 - 522 02-444

SPX Flow Technology
 611 Sugar Creek Road
 Delavan, WI 53115 USA
 Tel: +1 (800) 252-5200 or
 +1 (262) 728-1900
 Fax: +1 (262) 728-4904

SPX Flow Technology
 Ironstone Way, Brixworth
 Northants, NN6 9UD UK
 Tel: +44 (0) 1604 880751
 Fax: +44 (0) 1604 880145

Established: 1932

Common Applications: Methanol, Glycol, Corrosion Inhibitor, Scale Inhibitor, Demulsifier, Antifoam, Biocide, Flocculant, Oxygen Scavenger, Condensate, Polymer, Odorant, Hypochlorite, Drag Reducer, Polyelectrolyte

	<p style="text-align: center;">BASIC INJECTION PACKAGES</p> <ul style="list-style-type: none"> ④ Single chemical/single injection point ④ Duty or duty/standby arrangement ④ Simple design ④ Space efficient ④ Fast and easy to operate and maintain ④ Quick delivery ④ Long term aftermarket and service support ④ Fit for purpose, but higher quality
	<p style="text-align: center;">MULTI-PUMPHEAD PACKAGES</p> <ul style="list-style-type: none"> ④ Multi-pumphead injection and storage package ④ Single chemical/single injection point ④ High volume/high pressure/high temperature applications ④ Designed for hazardous area installations ④ Suitable for hostile environments ④ Custom designed, built and fully tested ④ Minimal on-site installation ④ Continuous or batch applications
	<p style="text-align: center;">MULTI-POINT CHEMICAL INJECTION PACKAGES</p> <ul style="list-style-type: none"> ④ Multi-compartment storage volume with different chemicals ④ Horizontal modular duty/standby multi-headed pumps ④ Single source - single accountability ④ Comprehensive solution, tailor made to client requirements ④ Topsides or subsea applications ④ Easy operation and maintenance ④ Designed for low and high temperatures
	<p style="text-align: center;">VERTICAL MULTI-PUMPHEAD PACKAGES</p> <ul style="list-style-type: none"> ④ Patented Vertical modular pump configuration ④ Space and weight efficiency ④ Design concept permits future expansion ④ High accuracy, repeatability and durability ④ Self-contained storage and injection package ④ Extensive global reference list of installations ④ Highly engineered components to meet stringent requirements
	<p style="text-align: center;">SOLAR PANEL PACKAGES</p> <ul style="list-style-type: none"> ④ Completely self-contained including solar panels and battery backup ④ Suitable for remote desert and hostile locations ④ Low power consumption of motor ④ Minimum friction losses giving high reliability & high efficiency ④ Low maintenance/low life cycle costs ④ Higher returns on investment ④ Environmentally friendly
	<p style="text-align: center;">FLOW CONTROL VALVE PANELS</p> <ul style="list-style-type: none"> ④ Self-regulating injection metering valves ④ Multi-injection points with either a dedicated or common flow meter ④ More than one chemical can be accommodated ④ Duty/standby pumps recommended per chemical ④ Stand-alone or inclusive panels supplied ④ Manual or remote control ④ Space and weight efficient

ClydeUnion Pumps

Email: sales@clydeunion.com

SPX Flow Technology
 149 Newlands Road
 Glasgow, G44 4EX
 United Kingdom
 Tel: +44 (0)141 637 7131
 Fax: +44 (0)141 633 2399

Established: 1871
Common Applications: Exploration & Production - Onshore/Offshore/Sand & Shale, Crude Transportation & Storage, Downhole & Subsea, Refinery, Petrochemicals, Product Storage & Distribution, Gas Processing & Treatment



OVERHUNG PUMPS

- ④ Comprehensive range of class leading API 610 compliant units including CUP-OH2, CUP-OH3, CUP-OH4 and CUP-OH5 designs
- ④ Various material options to suit commercial and technical requirements
- ④ Various bearing and sealing options optimized to pump duty
- ④ Heavy duty robust construction



BETWEEN BEARINGS PUMPS

- ④ Full range of between bearings pumps CUP-BB1, CUP-BB2, CUP-BB3, CUP-BB4 and CUP-BB5 compliant to API 610 standards
- ④ API material options as well as material upgrades for arduous duties
- ④ Flanged, bolted or clamped nozzle options
- ④ Rigid rotor design ensures reliability
- ④ Fully packaged with numerous sealing, bearing drive and instrumentation options
- ④ Large eye and double entry impeller options for low NPSH conditions
- ④ High power test facilities available



VERTICALLY SUSPENDED PUMPS

- ④ API 610 compliant range of vertically suspended pumps including CUP-VS1, CUP-VS4 and CUP-VS6/7 units
- ④ FEA optimized designs reduce vibration and improve reliability
- ④ Direct drive or via line shaft with motor or diesel drivers
- ④ Fully packaged systems
- ④ Available in materials suited for hydrocarbons, crudes, seawater etc.



RECIPROCATING PUMPS

- ④ Market leading range of API 674 reciprocating pumps
- ④ Non-geared, geared and power/direct-acting designs available across a wide range to suit specific duty
- ④ Simplex, duplex, triplex and quintuplex designs available
- ④ V-belt or gear reduction and various drivers available optimized to duty



SPECIALIZED PUMPS & SYSTEMS

- ④ Downhole multiphase pumps for oil and gas recovery in difficult wells
- ④ Submersible motor driven pumps with superior corrosion resistance
- ④ Specialized pump sealing systems to minimize environmental emissions
- ④ Cryogenic designs for LNG and other specialist systems
- ④ Anti-fouling equipment to inhibit marine growth
- ④ Innovative reel system for jack-up rigs and semi-submersibles
- ④ High temperature refinery pump systems

ClydeUnion Pumps

Email: sales@clydeunion.com

SPX Flow Technology

149 Newlands Road

Glasgow, G44 4EX

United Kingdom

Tel: +44 (0)141 637 7131

Fax: +44 (0)141 633 2399

Established:

1871

Common Applications:

Thermal, Combined Cycle, Concentrated Solar, Geothermal, Cogeneration, Carbon Capture & Storage, Class 2/3 & commercial pumps for all key reactor designs, Modular Reactors, Naval & Defense Related Reactors



BOILER FEED PUMPS

- ④ Through-bolt, split case or full cartridge designs available
- ④ Stable H/Q curves and high efficiency hydraulic design extends time between overhauls
- ④ Balanced drum or disc designs available optimized to operating conditions
- ④ Stiff-shaft design and able to withstand thermal shock
- ④ Various sealing and bearing options available to suit commercial and technical requirements
- ④ Fully packaged with various drives and skid arrangements available
- ④ High power test facilities available



CONDENSATE EXTRACTION PUMPS

- ④ Single or double entry
- ④ Above or below floor discharge options
- ④ Wide range of hydraulics to optimize selection to duty point
- ④ Low NPSH to minimize civil expense
- ④ Vertical or horizontal pumps available depending on site layout



CIRCULATING WATER PUMPS

- ④ Vertical or horizontal configurations available depending on duty and site
- ④ Excellent NPSH characteristics to minimize civil expense
- ④ Large capacity concrete volute pumps available for larger flows
- ④ Various metallurgies available optimized to water type and suspended solid layout content, including highly resistant super duplexes
- ④ Full intake modeling capability to maximize and prove design



ADDITIONAL PUMPS FOR POWER APPLICATIONS

- ④ Specialized units designed for the specific need of concentrated solar, geothermal and other power applications
- ④ A wide range of power auxiliaries of centrifugal and reciprocating design



CODED PUMPS FOR NUCLEAR APPLICATIONS

- ④ Large range of ASME Class II or III pumps to recover a wide range of nuclear duties
 - Safety injection and containment spray
 - Residual heat removal
 - Charging and CVCS
 - Auxiliary feed
 - Component cooling water
 - Reactor core isolation cooling
 - Emergency core cooling and many more
- ④ Unique and proven designs such as integral steam turbine, water lubricated pump for reactor feed and cooling duties, the ClydeUnion Pumps TWL
- ④ Designed and manufactured in ASME N Stamp and/or RCCM facilities with class leading in-house nuclear specific capabilities – clean assembly rooms, vibration testing, anechoic chamber etc.




ClydeUnion Pumps

Email: sales@clydeunion.com

SPX Flow Technology
 149 Newlands Road
 Glasgow, G44 4EX
 United Kingdom
 Tel: +44 (0)141 637 7131
 Fax: +44 (0)141 633 2399







Established: 1871

Common Applications: Water Supply/Treatment & Transportation, Desalination, Metals, Marine, General Industrial, Minerals and Mining

	<h3 style="text-align: center;">SINGLE & TWO STAGE PUMPS</h3> <ul style="list-style-type: none"> ④ Frequently fitted with stainless steel impellers as standard for improved through life costs ④ High efficiency designs with wide range of low NPSH hydraulics to provide optimum pump for duty ④ Horizontal or vertical configurations, long or close coupled ④ Various material combinations optimized to pump duty ④ Solids handling units available
	<h3 style="text-align: center;">MULTI STAGE PUMPS</h3> <ul style="list-style-type: none"> ④ Split case, through-bolt and full cartridge designs available ④ Large range of high efficiency hydraulics to best meet duty ④ Material and coatings chosen to optimize pump life ④ Rigid rotor design ensures reliability ④ Fully packaged with numerous sealing, bearing drive and instrumentation options
	<h3 style="text-align: center;">VERTICAL PUMPS</h3> <ul style="list-style-type: none"> ④ Low NPSH and double entry designs available to reduce civil costs ④ Various bearing, seal and headpiece options available optimized to duty ④ Numerous material and coatings available to optimize pump life and efficiency ④ Intake test facilities available to prove operation before installation ④ Robust, easy to maintain designs reduce downtime ④ Long line shaft experience for deep wells
	<h3 style="text-align: center;">RECIPROCATING PUMPS</h3> <ul style="list-style-type: none"> ④ Market leading range of API 675 reciprocating pumps ④ Non-gearred, geared and power/direct-acting designs available across a wide range to suit specific duty ④ Simplex, duplex, triplex and quintuplex designs available ④ V-belt or gear reduction and various drivers available optimized to duty
	<h3 style="text-align: center;">SPECIALIZED PUMPS</h3> <ul style="list-style-type: none"> ④ Specialised units available for niche applications offering superior performance such as: <ul style="list-style-type: none"> - High capacity concrete volute pumps for flood prevention schemes or land irrigation / drainage schemes - HPRO, radially split diffuser pump designed specifically for RO applications offers maximized efficiency and low footprint - Submersible motor pumps - Pumps for mining and marine applications

Established: 1903
Common Applications: Power, Pulp & Paper, Oil & Gas, Petrochemical

Manufacturing Standards: Certifications - ISO-9001, ASME SECTION III "N" & "NPT" Stamps, ASME SECTION I "S" Stamp, CSA-Z299.2, .3, & .4, 97/23/EC-PED-CE

	<p style="text-align: center;">SPECIAL APPLICATION GLOBE & ANGLE STYLE CONTROL VALVES</p> <ul style="list-style-type: none"> ④ General Service applications ④ Severe Duty applications ④ High turndown ④ .75 - 24" Sizes ④ 150 - 4500 ANSI Ratings ④ Special ANSI & API Ratings ④ Meets ASTM/ASME Standards ④ Butt/Socket Weld, Flanged & Hub Connections
	<p style="text-align: center;">STEAM CONDITIONING EQUIPMENT (DESUPERHEATERS)</p> <ul style="list-style-type: none"> ④ 7 Styles ④ Mechanical Atomizing ④ Variable Orifice ④ Integral cooling water function available ④ High turn downs ④ 150 - 2500 ANSI Ratings ④ Special ANSI & API Ratings ④ Meets ASTM/ASME Standards
	<p style="text-align: center;">TRIM TYPES</p> <ul style="list-style-type: none"> ④ 13 Types ④ RAVEN ④ HUSH™ ④ CAV B9 ④ One Stage HUSH™ ④ Noise control ④ Cavitation elimination ④ Velocity & Erosion control
	<p style="text-align: center;">ACTUATORS</p> <ul style="list-style-type: none"> ④ Diaphragm Style. Model 700 ④ Diaphragm Style. Model 1000 ④ Manual Style 820 ④ Electric available ④ Electro/Hydraulic available ④ Piston ④ Reverse acting ④ Direct acting
	<p style="text-align: center;">NUCLEAR CONTROL VALVES</p> <ul style="list-style-type: none"> ④ Pneumatic, Motor, Manual Operators ④ Metal & Resilient Seats ④ Widest Selection of Trim in the Industry ④ Globe, Angle Isolation & Three Way Body Configurations ④ Size Range: 3/8" - 20" class 150-2500 ④ ASME Section III "N" & "NPT" Stamp Certified
	<p style="text-align: center;">NUCLEAR HIGH PERFORMANCE BUTTERFLY AND BALL VALVES</p> <ul style="list-style-type: none"> ④ Bi-Directional Class VI Shut off ④ Metal & Resilient Seats ④ Torque Seated/Position Seated (Butterfly only) ④ Pneumatic, Motor, Manual Operators ④ Modulating or Isolation ④ Two & Three Piece Ball Valve design ④ ASME Section III "N" & "NPT" Stamp Certified

Established: 1936
Common Applications: Petrochemical, Electronics, Oil & Gas, Power Generation, Food, Beverage, Packaging, Manufacturing



COMPRESSED AIR TREATMENT

- ④ Refrigerated dryers
- ④ Heatless desiccant dryers
- ④ Heat regenerated desiccant dryers
- ④ Heat of compression desiccant dryers
- ④ Filtration media
- ④ Consistent pressure dew points
- ④ Multiple industries
- ④ Low energy consumption dryers



GAS TREATMENT

- ④ Gas separation
- ④ Inert gas dryers
- ④ Vent gas purification systems
- ④ Wide range of applications
- ④ Reduce concentration of water vapor
- ④ Decreased pressure dew point
- ④ Regeneration loop gas dryers



COMPRESSED NATURAL GAS DRYERS

- ④ No gas losses
- ④ Steady dew point under any operating conditions
- ④ Low maintenance and trouble free duty



NITROGEN GENERATORS

- ④ For purging tanks and vessels
- ④ Oil & gas production
- ④ Inerting storage tanks
- ④ Purging pipelines
- ④ Food and packaging industries
- ④ Wine production
- ④ Heat treatment and production of metals



CABLE & WAVEGUIDE

- ④ Easy to install and service
- ④ Simple to operate
- ④ Low noise and vibration
- ④ High reliability
- ④ Safe
- ④ Low power consumption
- ④ High efficiency
- ④ Reduced risk of corrosion



ATMOSPHERIC AIR TREATMENT






- ④ RFB atmospheric air dryer
- ④ CFB heavy duty dryers
- ④ MVB dehumidifier
- ④ HRB desiccant ambient air dryer
- ④ Custom engineered systems
- ④ Close control of humidity during production
- ④ On site service & support



Email: deltech.inquiry@spx.com

SPX Flow Technology
 1000 Philadelphia Street
 Canonsburg, PA 15317-1700
 Tel: 724-745-8647
 Fax: 724-745-4967

Established: 1961
Common Applications: General Manufacturing, Automotive, Electronics, Petrochemical, Laboratory, Pharmaceutical

	<p style="text-align: center;">REFRIGERATED DRYING AIR TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ HG/HGE Series delivers durability in a small package. Flow rates: 10 to 500 scfm ④ HYDROGARD® Series with dew point stabilization and optional Pyramid™ filtration. Flow rates: 100-3000 scfm ④ HYDROGARD® Series Dryers match power consumed to real-time demand. Flow rates: 800-3000 scfm ④ DES Series Cycling Dryers offer a load matching profile for energy savings. Flow rates: 80-675 scfm ④ DHC and ES High Volume Dryers available
	<p style="text-align: center;">DESICCANT DRYING AIR TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ HCS, HCL, and HCT Series Heatless Dryers empower users with three designs to match your demands. Flow rates of 40-5,400 scfm ④ ZP Series Blower Purge Desiccant Compressed Air Dryers provide flow rates of 250-3200 scfm ④ WM Series Wall-mountable Heatless Dryers offer the choice of -40°F or -100°F pressure dew point performance ④ RP Series Externally Heated Desiccant Compressed Air Dryers provide point of use dew point control
	<p style="text-align: center;">FILTRATION TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ 300 Series: Sustainable Filtration Solutions! Flow rates: 35-3500 scfm ④ DF Series: 7 Grades of Filtration. Flow rates: 20-21250 scfm ④ 810 Series: High Efficiency Filtration. Flow rates: 1000-15000 scfm ④ DTA Series Filters, flow rates: 100-11400 scfm ④ ME Series Mist Eliminators: The lowest system pressure drop! Flows rates: 125-3000 scfm ④ Color-Change KC Series Filters: Maximum Vapor Protection. Flow rates: 12-280 scfm
	<p style="text-align: center;">AIR TREATMENT FOR HIGH INLET TEMPERATURES AND PRESSURES</p> <ul style="list-style-type: none"> ④ HTD Series High Inlet Temperature Dryers replaces four components with a complete air system that accepts high temperature air to 180°F, 82°C with flow ranges from 20-197 scfm ④ DHT Series High Pressure Dryers accepts air inlet temperature directly from an air compressor to 180°F and operates in ambient up to 110°F with flow ranges from 20-100 scfm
	<p style="text-align: center;">CONDENSATE MANAGEMENT AND MEMBRANE TECHNOLOGY</p> <ul style="list-style-type: none"> ④ DMD Series Membrane Dryers deliver energy savings through select permeation ④ ESM Series Energy Saving Membrane Dryers save energy for fluctuating process air demands ④ Hydroclean® CS, CSC and CSG Series Condensate Separators and Hydroclean® OWS & CS Series Oil Water Separators with flow rates up to 4500 scfm ④ NLD Series electronic and pneumatic drains ④ ADV Series automatic drains available
	<p style="text-align: center;">DEL-MONOX® BREATHING AIR SYSTEMS</p> <ul style="list-style-type: none"> ④ Del-Monox® air purification systems provide a highly effective means to control exposure to respiratory hazards in the work place and serves flow rates of 18 - 1130 scfm



US Email: dollinger.sales@spx.com
 UK Email: sales.dollinger@spx.com

SPX India Pvt Ltd
 Mansarovar, Jaipur
 India
 Tel: +91 141 2398158
 Fax: +91 141 2395046

SPX FlowTechnology
 Killarney, Co Kerry
 Ireland
 Tel: +353 64 6633322
 Fax: +353 64 6633371

SPX Flow Technology
 4647 SW 40th Ave.
 Ocala, FL 34474
 Tel: 800-344-2621
 Fax: 800-628-4778

Established: 1921

Common Applications: Oil & Gas: (Offshore & Production, Processing & Refining, Storage, Transportation & Distribution), Power Generation, Air Separation, Petrochemical, Nitric Acid/Fertilizer Production, Waste Gas and Biofuels, Glass Container Manufacturing



PROCESS PIPELINE FILTERS

SPX offers Process Filtration Equipment for the Oil & Gas, Petrochemical and Power Generation Industries around the globe.

- ④ This product range includes both gas and liquid fabricated pressure vessel filters
- ④ Custom designs can be incorporated

- ④ Options available to package filter vessels onto a skid arrangement with any required instrumentation or control equipment
- ④ Ensures compliance to all relevant codes with every product



AIR INTAKE FILTRATION SYSTEMS

Our technical development facilities are located throughout Europe, North America, South America and Asia.

- ④ Built around the globe, Dollinger is able to simulate a diverse range of environmental conditions, in order to provide a detailed technical assessment of all current and desired filter systems

- ④ Ability to manufacture a small retrofit weather hood, through to a large air intake system with full enclosure
- ④ 18 Standard Models with flow rates up to 72,000 scfm
- ④ Efficiency to be 99% of 10 microns



FUEL AND LUBRICATING OIL FILTERS

The Dollinger Oil Mist Eliminator (OME) is a filtration system of superior efficiency.

- ④ Collects 99.97% of oil droplets 0.3 micron and larger, thus removing virtually 100% of visible oil mist emissions
- ④ The extracted oil mist droplets can be Rating returned back to the lube oil system of

the Gas or Steam Turbine, Gas or Diesel Engine and Compressors

- ④ Removes health, safety and environmental concerns as well as making significant cost savings
- ④ ASME VIII Vessel



ENGINEERED PACKAGES

Keeping fluids clean and free from contaminant and moisture, is an essential requirement for maintaining efficiency. We can supply both replacement filter systems or design engineered packages. SPX can also

provide Liquid Coalescers, Fuel Filtration, Lubricating Oil Filtration and Stream-Line Systems for insulating fluid treatment.



US Email: dollinger.sales@spx.com
 UK Email: sales.dollinger@spx.com




SPX India Pvt Ltd
 Mansarovar, Jaipur
 India
 Tel: +91 141 2398158
 Fax: +91 141 2395046

SPX FlowTechnology
 Killarney, Co Kerry
 Ireland
 Tel: +353 64 6633322
 Fax: +353 64 6633371

SPX Flow Technology
 4647 SW 40th Ave.
 Ocala, FL 34474
 Tel: 800-344-2621
 Fax: 800-628-4778

Established: 1921

Common Applications: Power Generation, Oil & Gas

	<p style="text-align: center;">POWER SYSTEMS - PULSE JET FILTERS</p> <ul style="list-style-type: none"> ④ High dust holding capacity ④ Low pressure drop due to sharp pleat tips and even spacing ④ Ideally suited for desert style environments
	<p style="text-align: center;">POWER SYSTEMS - LIQUID & GAS FILTERS</p> <ul style="list-style-type: none"> ④ Fuel & Lubricating Oil Filters ④ Fuel Gas Filters & Coalescers ④ Oil/Water Coalescers ④ Lubricating Oil Mist Eliminators ④ Engineered skid packages
	<p style="text-align: center;">POWER SYSTEMS - AIR INTAKE SYSTEMS</p> <ul style="list-style-type: none"> ④ 18 Standard Models ④ 3,000 - 1,000,000 scfm ④ Low pressure loss/high efficiency ④ Efficiency from 0.3 to 10 microns ④ Optional silencing feature ④ Weather hoods standard equipment ④ Custom systems

e&e Series

Email: info@extraction.de

SPX Flow Technology Warendorf GmbH
 Splieterstraße 70 a
 48231 Warendorf
 Germany
 Tel: +49 2581 63601-0
 Fax: +49 2581 63601-20

Established: 1998

Common Applications: Food, Coffee, Pharmaceutical, Cosmetics, Chemical



TURNKEY PLANTS

- ④ Leading extraction, evaporation, vacuum and freeze drying technology for the food, pharmaceutical, cosmetics, coffee and chemical industry
- ④ Factories for instant coffee
- ④ Factories for herbal extracts, medicinal plants
- ④ Factories for freeze dried fruits and natural ingredients. From the raw material to final product.
- ④ Turnkey plants, includes building design, according to: ATEX, Non-ATEX, GMP, Supply of utilities
- ④ Product and process development



EXTRACTION PLANTS

- ④ Batch size 50 l up to 20 m³
- ④ -1 bar up to 24 bar
- ④ Single or multi-stage
- ④ Counter-current flow extraction ("semi-continuous")
- ④ Extraction batteries for coffee
- ④ Easy raw material discharge
- ④ Excellent cleanability for fast product changeover
- ④ Various solvents
- ④ Extraction process variability: Steaming, vacuum stripping, percolation, solvent recovery



EVAPORATION PLANTS

- ④ Single and multi-stage
- ④ Various thermal and flow operations
- ④ High concentrators
- ④ Plate evaporators
- ④ Falling film evaporators
- ④ Economical systems
- ④ Solvent recovery



VACUUM DRYERS/FREEZE DRYERS

- ④ Vacuum belt dryers
- ④ Freeze belt dryers
- ④ Drying cabinets
- ④ Continuous tray freeze dryers
- ④ Batch tray dryers
- ④ 1 m² up to 250 m²
- ④ Vacuum 0.3 up to 300 mbar abs.
- ④ Ice condensers
- ④ Direct/indirect heating
- ④ Pre-freezing and freezing systems



DISTILLATION AND RECTIFICATION PLANTS

- ④ Aroma recovery plants
- ④ Solvent recovery plants
- ④ High concentration of solvents
- ④ Columns and flash systems
- ④ Aroma fractionations
- ④ Biodiesel production
- ④ Bioethanol purification



TEST CENTER

- ④ Pilot extraction unit
- ④ Pilot evaporation unit
- ④ Vacuum belt dryer
- ④ Freeze belt dryer
- ④ Batch dryer
- ④ Test trials in close cooperation with the customer
- ④ Tailoring of product properties
- ④ Product and process development
- ④ Determination of energy requirement
- ④ Production of test samples







Established: 1901

Common Applications: Margarine, Shortening, Butter, Bakery Filling Cream, Mayonnaise, Ketchup, Dressing, Ice cream

	<h3 style="text-align: center;">SCRAPED SURFACE HEAT EXCHANGERS</h3> <ul style="list-style-type: none"> ④ For crystallization of fat ④ Low and high pressure ④ Various certifications available (PED, ASME, etc.) ④ Up to very high capacities ④ Low-noise systems ④ Known under the brand names: Nexus, Perfector, Kombinator, Consistator®
	<h3 style="text-align: center;">HIGH PRESSURE PLUNGER PUMPS</h3> <ul style="list-style-type: none"> ④ For pumping liquids to process line ④ Low noise level ④ High pressure ④ Few wearing parts ④ Fast and simple servicing and maintenance ④ Constant product flow
	<h3 style="text-align: center;">EMULSIFYING EQUIPMENT</h3> <ul style="list-style-type: none"> ④ Systems for batch and continuous processing ④ Flexible solutions ④ Gentle product treatment ④ Ensure homogeneous distribution of the disperse phase into the continuous phase
	<h3 style="text-align: center;">ICE CREAM PRODUCTION</h3> <ul style="list-style-type: none"> ④ For additional freezing of traditional ice cream ④ Low temperature extrusion ④ Low energy consumption ④ Easy access to all main refrigerant valves ④ Built-on frequency converter and control cabinet with PLC and control panel
	<h3 style="text-align: center;">BUTTER EQUIPMENT</h3> <ul style="list-style-type: none"> ④ For production of butter, butter spreads and blends ④ Flexible process solution ④ Easy maintenance ④ Focus on product safety ④ Efficient mixing ④ Stable product quality
	<h3 style="text-align: center;">CUSTOMER SERVICE</h3> <ul style="list-style-type: none"> ④ Commissioning of machines and complete production lines ④ Spare parts delivery ④ Maintenance plans for your equipment ④ Repair of equipment ④ Service agreements ④ System and/or product optimization

Established: 1944

Common Applications: Oil & Gas, Gas Transmission, Offshore and Onshore

	<p style="text-align: center;">BANDLOCK 2 QUICK OPENING CLOSURE</p> <ul style="list-style-type: none"> ④ Benchmark closure design for global high-pressure apps. up to ASME Class 2500 ④ Quick access to pipelines, filters and pressure vessels ④ Approved to international design codes; ASME VIII Div. 1 & Div. 2, PD5500, EN 13445
	<p style="text-align: center;">ROTALOCK QUICK OPENING CLOSURE</p> <ul style="list-style-type: none"> ④ Horizontal or vertical installation ④ Developed for smaller/low pressure applications up to ASME Class 300 ④ Low cost solution ④ Superior alternative to screwed type closures
	<p style="text-align: center;">HI-T PIG ALERT</p> <ul style="list-style-type: none"> ④ Intrusive Pig Signaller ④ Simple & proven technology ④ Wide range of models including: mechanical flag and electrical switch ④ Bi-directional operation ④ Under pressure removal using valved models
	<p style="text-align: center;">SPECIAL PROJECTS</p> <ul style="list-style-type: none"> ④ Automated multiple pig launching ④ Fully automatic vessel closures for waste treatment plants ④ Closures for medical waste treatment vessels ④ High Pressure Test Vessels ④ Industrial Dry Cleaning Closure
	<p style="text-align: center;">SERVICE & AFTERMARKET</p> <ul style="list-style-type: none"> ④ Onshore and offshore inspection and maintenance ④ In-situ machining/seal face refurbishment ④ Pig trap refurbishment ④ Training
	<p style="text-align: center;">HI-T MAGALERT & ULTRALERT</p> <ul style="list-style-type: none"> ④ Non Intrusive Pig Signaller ④ Magnetic or Ultrasonic Technology ④ ATEX Compliant ④ Use both Onshore & Offshore ④ User Friendly Display / Operator Interface









Email: hankison.inquiry@spx.com

SPX Flow Technology
 1000 Philadelphia Street
 Canonsburg, PA 15317
 Tel: 724-745-1555
 Fax: 724-745-6040

Established: 1948

Common Applications: General Industrial and Manufacturing, Chemical Processing, Automotive, Laboratories, Pharmaceutical, Hospitals, Food Processing

	<p style="text-align: center;">REFRIGERATED AIR DRYING TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ HPR Series affordable non-cycling dryers offer flow ranges from 5-500 scfm ④ HPR<i>plus</i> Series for continuous air demand profiles, flow ranges from 100-3000 scfm ④ HES Series 90-675 scfm, your sustainable energy saving solution! ④ HES Series dryers serves flow ranges from 800 to 3000 scfm for systems with varying levels of air demand ④ HV and HES Series high volume dryers offer flow ranges from 4000-20000 scfm
	<p style="text-align: center;">DESICCANT AIR DRYING TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ HHS, HHL, & HHE Series heatless desiccant air dryers offer 3 specific control systems, flow rates: 40-5400 scfm ④ DHW Series wall-mountable heatless desiccant dryers, flow rates: 7-50 scfm ④ HDF Series single tower dryers: Ideal for low flow applications, 5-30 scfm <p>Other available desiccant systems: AAA-AT & ACAT Series Adsorber Towers, HPD Series Heated Purge Dryers, HBP Series Blower Purger Dryers, and HEDS Series Drying Systems</p>
	<p style="text-align: center;">COMPRESSED AIR FILTRATION TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ NGF Series air filters are designed accordance to ISO 12500 standards, flow ranges from 20-1500 scfm ④ HF Series air filters offer 7 grades of filtration, flow rates from 20-21250 scfm ④ HFM Series filter monitor with audit control ④ M Series mist eliminators-the auditor's choice ! ④ Specialty filtration technologies include: HTA Series high temperature afterfilters, HF High Pressure Series and HF Corrosion Resistant Series
	<p style="text-align: center;">MEMBRANE TECHNOLOGIES & CONDENSATE MANAGEMENT</p> <ul style="list-style-type: none"> ④ HMM Series modular membrane air dryers offer "point-of-use" alternative ④ SMM with Sweepsaver™ Series modular membrane air dryers reduce power costs ④ HMD Series dryers operate in any orientation ④ HGS Series oil/water separators and HPE Series oil/water condensate separators are available for system flow rates to 4500 scfm ④ Condensate Drains include: Snap Trap®, Trip-L-Trap and 531, 532, and 533 Series automatic condensate drains
	<p style="text-align: center;">HIGH PRESSURE & INLET TEMPERATURE TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ HIT Series high inlet temperature refrigerated dryers cool, dry and clean your compressed air supply in one compact, easy-to-use package with flow rates from 20-125 scfm ④ HPET Series high pressure refrigerated air dryers are designed for 725 psig operations and are important for PET blow molding installations around the world with flow rates from 13-3750 scfm
	<p style="text-align: center;">BREATHING AIR PURIFICATION SYSTEMS</p> <ul style="list-style-type: none"> ④ Catalite® purifiers offer a way to use your compressed air system as a source for breathing quality air and can be safely used to supply air to breathing devices such as masks, hoods and helmets ④ Removes excessive moisture, solid particles (dust and dirt), oil aerosols and mists, carbon monoxide, and hydrocarbon vapors commonly present in compressed air






SPX Flow Technology
 9029 Governors Row
 Dallas, TX 75247 USA
 Tel: 800-379-3711
 Fax: 214-905-1282

Email: rentaldryers@spx.com

Established: 1948

Common Applications: Petrochemical, Power Generation, Electronics, Manufacturing

	<p style="text-align: center;">COOL - WITH AN AFTERCOOLER/SEPARATOR</p> <ul style="list-style-type: none"> ④ Reduce the temperature of hot compressed air leaving the compressor to safe, usable levels (within 5°F of ambient temperature) ④ Precondition the air for further drying and filtering ④ Remove up to 70% of water
	<p style="text-align: center;">DRY - WITH A REFRIGERATED OR DESICCANT DRYER</p> <ul style="list-style-type: none"> ④ Eliminate troublesome liquid water from downstream air lines and equipment ④ Choose a dryer to produce a dew point temperature below the lowest temperature that your air lines are exposed <ul style="list-style-type: none"> - Dew point temperature at which water vapor changes to a liquid
	<p style="text-align: center;">FILTER - WITH A PACKAGED FILTER SYSTEM</p> <ul style="list-style-type: none"> ④ One micron air line filter <ul style="list-style-type: none"> - Removes solid particles ④ High efficiency coalescing type oil removal filter <ul style="list-style-type: none"> - Removes oil aerosols (also called oil mist, fog, or smoke) - Provides virtually oil free air ④ Optional system includes oil vapor removal system <ul style="list-style-type: none"> - Eliminates odor from compressed air - Protects products and processes from contamination





Jemaco, South Korea
 #940-1, Yerim-ri, Jeonggwan-myeon
 Gijang-gun, Busan, 619-961, South Korea
 Tel: +82 51 726 5010
 Fax: +82 51 726 5049

Email: jemaco@spx.com

Established: 1987

Common Applications: General Industrial, Automotive, Manufacturing

	<p style="text-align: center;">REFRIGERATED AIR DRYERS</p> <ul style="list-style-type: none"> ④ Stainless steel brazed plate heat exchanger, No rust water and corrosion ④ Integral structure, air-to-air heat exchanger, evaporator & moisture separator ④ User friendly controllers ④ Optimal dew point performance under all conditions ④ Low pressure drop reduces operating costs ④ Reliable timed electric drain
	<p style="text-align: center;">DESICCANT AIR DRYERS & ENGINEERED PRODUCTS</p> <ul style="list-style-type: none"> ④ Stable dew point performance and low dust creation ④ High quality process switching valve, long component life cycle ④ Basic design : ASME, IEC, DNV ④ No energizer control system (Pneumatic control) ④ Low noise let down system (80 dB) ④ Transmitter design : Motion load analysis



Email: johnson-pump@spx.com







SPX Flow Technology
 Box 1436, SE-701 14 Örebro, Sweden
 Tel: +46 (0)19 21 83 00

SPX Flow Technology
 P.O. Box 9, NL-9400 AA Assen, Netherlands
 Tel: +31 (0)592 37 67 67

SPX Flow Technology
 Evenbroekveld 2-6, BE-9420 Erpe-Mere, Belgium
 Tel: +32 (0)53 60 27 15

SPX Flow Technology
 Survey No. 275, Odhav Road, Odhav
 Ahmedabad 382 415, India
 Tel: +91 (0)79 2287 03 11

Established: 1968
Common Applications: Food, Beverage, Petrochemical, Pharmaceutical, Chemical, Horticulture, Water Applications, Shipbuilding, Pulp & Paper, General Industry

	<p style="text-align: center;">ROTARY LOBE PUMPS – POSITIVE DISPLACEMENT RANGE</p> <ul style="list-style-type: none"> ④ Hygienic stainless steel tri-lobe, multi-lobe and bi-wing lobe pumps easy to clean ④ High volumetric efficiency for thin and viscous liquids ④ Accurate and gentle flow with minimal pulsation ④ Front loaded hygienic mechanical seals easy to access for inspection and cleaning ④ Different hygienic certificates available
	<p style="text-align: center;">INTERNAL GEAR PUMPS – POSITIVE DISPLACEMENT RANGE</p> <ul style="list-style-type: none"> ④ Robust, heavy-duty design in several material options for extended life ④ Suitable for both thin and viscous liquids ④ Pulsation-free flow for accurate and gentle pumping ④ A variety of sealing options and seal-less mag drive ④ Simple design with few parts, easy to service with back and front pull-out for access to rotating parts
	<p style="text-align: center;">SELF-PRIMING CENTRIFUGAL PUMPS</p> <ul style="list-style-type: none"> ④ Horizontal and vertical versions – Single and multi stage executions ④ Hydraulics according to EN 733 ④ Modular designs based on interchangeable parts ④ High pump efficiency, minimal internal losses ④ A variety of sealing options – packed gland, mechanical seals and cartridge seals
	<p style="text-align: center;">CENTRIFUGAL PUMPS</p> <ul style="list-style-type: none"> ④ General purpose pumps, heavy duty chemical and process pumps, in-line pumps, close-coupled pumps, submersible pumps ④ Modular designs based on interchangeable parts ④ Horizontal and vertical versions – Single and multi stage executions ④ Comply with ISO, DIN and API standards ④ A variety of sealing options and seal-less mag drive
	<p style="text-align: center;">MAG DRIVE PUMPS</p> <ul style="list-style-type: none"> ④ Heavy duty 100% leak-free centrifugal and gear pumps for applications which convey corrosive, toxic, aggressive or expensive liquids ④ Modular pumps based on interchangeable parts ④ Environmentally friendly and improved safety in chemical and process plant environments ④ Centrifugal ranges comply with ISO5199 and EN22858 and are interchangeable with existing (ISO 2858) pumps
	<p style="text-align: center;">FLEXIBLE IMPELLER PUMPS</p> <ul style="list-style-type: none"> ④ Easy-to-handle, positive displacement pump with excellent self-priming ability ④ Pulsation free and gentle pump action for sensitive liquids, able to handle large soft solids without damage ④ Fast, simple and inexpensive maintenance with low operational cost and short down time ④ Different versions for a broad field of applications meeting a variety of industrial demands, hygienic or non hygienic









SPX Flow Technology
P.O. Box 1436
SE-701 14 Örebro, Sweden
Tel: +46 (0)19 21 83 00

SPX Flow Technology
1625 Hunter Road, Suite B
Hanover Park, Illinois 60133 USA
Tel: +1 847-671-7867

SPX Flow Technology
P.O. Box 427
Cannon Hill, QLD. 4170, Australia
Tel: +61 (0)7 3899 9933

Email: johnson-pump@spx.com

Established: 1968
Common Applications: Water Pressure Systems, Engine Cooling, Bilge Pumping, Oil & Diesel Refueling, Water Circulation, Deckwashing, Wastewater and Toilet Handling, Emergency Pumping for example Fire Fighting, etc.

	<p style="text-align: center;">HEAVY-DUTY FLEXIBLE IMPELLER PUMPS</p> <ul style="list-style-type: none"> ④ A range of multi-purpose bronze pumps ④ Compact design. Pedestal or electro-magnetic clutch versions ④ Self-priming ④ Available in sizes from 3/8" to 2 1/2" 4 L/min to 620 L/min (1-165 USGPM) ④ Ideally suited as cooling water pumps for marine engines, bilge, deckwash and fuel transfer pumps and other self-priming multi-purpose applications ④ Also suited on shore to empty septic tanks, to flush clean and to fill water tanks
	<p style="text-align: center;">WATER PRESSURE SYSTEM - AQUA JET SERIES</p> <ul style="list-style-type: none"> ④ Suitable where low amperage and sound levels in relation to water flow are placed at a premium such as in shower and galley applications ④ Quiet and pulsation-free even at low speeds ④ Five chamber diaphragm pump ④ Perfect water pressure or deck wash solution ④ Efficient and compact ④ Available in sizes from 9 L/min to 40 L/min (2.4-10.4 USGPM) ④ Integrated pressure switch for automatic operation
	<p style="text-align: center;">SUBMERSIBLE BILGE PUMP SERIES</p> <ul style="list-style-type: none"> ④ A variety of mounting options, available with capacities of 30 to 250 L/min (500-4000 USGPH) ④ Heavy-duty motors with stainless steel shaft and tough thermoplastic bodies provide for a long pump life ④ Can handle most bilge pump applications ④ With an automatic switch installed, the pump turns on and off automatically
	<p style="text-align: center;">DC DRIVEN FLEXIBLE IMPELLER PUMPS</p> <ul style="list-style-type: none"> ④ High level of flexibility & self-priming ④ Ideally suited for use as bilge and deckwash pumps, fresh water pumps, refueling pumps for oil and diesel ④ May be combined with a vacuum or pressure switch for automatic operation ④ Capacities vary from max 14 L/min to 55 L/min (3.7-14.5 USGPM) ④ All motors are heavy-duty to provide long service life even under heavy use ④ Available in 12 or 24 volts
	<p style="text-align: center;">COMPACT TOILET HANDLING AND WASTEWATER PUMPS</p> <ul style="list-style-type: none"> ④ Maximum flow 32 L/min (8.5 USGPM) ④ Engineered to pump black wastewater with uncompromising odor-prevention features ④ Whisper quiet operation ④ Non-choke valves - no waste shredding required ④ Pump head rotatable 360° ④ Self-priming up to 2.5 meters (8.2 ft.) ④ Can be run dry and can pump air/water mixture ④ Electric motor with power-out, manual-crank backup
	<p style="text-align: center;">AquaT™ MARINE TOILETS MANUAL OR ELECTRICAL POWERED</p> <ul style="list-style-type: none"> ④ Hygienic, easy-to-clean vitreous china bowl and exterior surfaces ④ Low water consumption ④ Versatile plumbing connection options and automatic back-flow prevention ④ Designed for virtually any on-board mounting position and may be installed above or below the water line ④ Suitable for OEM or replacement installation ④ Innovative brake bushing prevents annoying leakage at the handle



Email: lightnin@spx.com

SPX Flow Technology
135 Mt. Read Blvd.
Rochester, NY 14611 USA
Tel: +1 (585) 436-5550
Fax: +1 (585) 436-5589

SPX Flow Technology
Ocean House, Towers Business Park
Didsbury, Manchester
M20 2LY
Tel: +44 161 249 1170







SPX Flow Technology China
2F, Treasury Centre
No. 1568 Huashan Road
Shanghai 200052, China
Tel: +86 (21) 22085889

Established: 1923

Common Applications: Chemical Processing, Flue Gas Desulfurization, Food, Beverage, Mining & Minerals, Oil & Petroleum, Personal Care, Pharmaceutical, Biotech, Pulp & Paper, Water & Wastewater Treatment

	<p style="text-align: center;">PORTABLE/FIXED MOUNT/STATIC MIXERS</p> <ul style="list-style-type: none"> ④ Laboratory and general purpose ④ Industry-standard, single-purpose and full-featured mixers for small batch applications ④ Single-speed to digital-controlled mixers for bench top open and closed tank service ④ Direct and gear models ④ Rapid response time for continuous dosing/sampling ④ Shear control for blending sensitive products
	<p style="text-align: center;">SANITARY MIXERS</p> <ul style="list-style-type: none"> ④ Dry running, aseptic mixers for blending, solids suspension and cell culture for biotech, pharmaceutical, cosmetic and food processing industries ④ Sanitary mixers for the complete range of small batch applications ④ Bottom and top mounted, magnetically coupled hermetically sealed mixers for sanitary applications, including injectables
	<p style="text-align: center;">SIDE-ENTRY MIXERS</p> <ul style="list-style-type: none"> ④ Rugged belt drives and gearboxes ④ Easy seal change and maintenance while tank is full ④ A312 impeller provides the most flow per unit of power in a focused pattern ④ FGD slurry seal designed to excel in harsh environments on VSF mixer
	<p style="text-align: center;">HEAVY MIXERS</p> <ul style="list-style-type: none"> ④ Mechanical design technology proven up to 2600 kW/3500 HP for all process mixing applications ④ Belt and gear drive side entry units ④ Robust, state-of-the art design delivers value and performance for process and environmental control applications
	<p style="text-align: center;">PROCESS SYSTEMS AND EQUIPMENT</p> <ul style="list-style-type: none"> ④ Attrition Scrubbers ④ Minerals processing equipment ④ Static and dynamic mixers
	<p style="text-align: center;">PROCESS TECHNOLOGY</p> <ul style="list-style-type: none"> ④ Highly efficient, axial flow impellers for flow-controlled purposes like blending, solid suspension, and heat transfer ④ Radial flow impellers for dispersion and mass transfer ④ Circulator impellers for pumping applications

Established: 1970
Common Applications: Liquid, Geothermal, Oil & Gas

	<p style="text-align: center;">GATE VALVES</p> <ul style="list-style-type: none"> ④ Offered in sizes 2" - 84" ANSI 150-2500 ④ Top entry - Inline maintenance capability ④ Thru conduit, piggable, double block and bleed capability ④ Built in accordance to API 6D standards and ISO 9001 certification ④ Utilized in pipeline applications for Oil/Gas Products
	<p style="text-align: center;">CONTROL VALVES</p> <ul style="list-style-type: none"> ④ Offered in sizes 2" - 30" ANSI 150-2500 ④ Rangeability of 350: 1 turn down ratio ④ Full Port in open position with Bi-directional flow capacity ④ Noise abatement and cavitation trim available ④ High Cv characteristics allows reduced valve size ④ Prime application to oil/gas products and refineries
	<p style="text-align: center;">SURGE RELIEF VALVES</p> <ul style="list-style-type: none"> ④ Axial 'straight path' smooth flow pattern for high flow capacities Cv ④ Fast response-rapid open/close, seals 900 tight without slamming shut ④ Low-noise and cavitation trim available ④ Large annular flow area allows high pressure recovery, low pressure drop ④ Offered in sizes 2" - 24" ANSI 150-
	<p style="text-align: center;">SKID MOUNTED DESIGN</p> <ul style="list-style-type: none"> ④ Complete package design with M&J manufactured products ④ Single source offering with proven Danflo Surge Valve ④ Factory training and field commissioning available at site ④ System designed to customer specific flowing conditions
	<p style="text-align: center;">4-WAY DIVERTER VALVES</p> <ul style="list-style-type: none"> ④ Offered in sizes 3" - 24" ANSI 150-1500 ④ For use in Bi-Directional Meter Prover Systems ④ Top entry design allows replacement of the seals in the field ④ Rapid operation with zero leakage for positive proving capabilities ④ Provided with SID feature to show positive indication of plug sealing
	<p style="text-align: center;">EXPANDING GATE VALVES</p> <ul style="list-style-type: none"> ④ Offered in sizes 2" - 36" ANSI 150-1500 ④ Thru conduit, piggable, double block and bleed capacity ④ Top entry design for field repair capability ④ Mechanically seated design to provide maximum sealing capability in both low and high differential pressure conditions ④ Built in accordance to API 6D standards, ISO 9001 certification, and fire tested to API 6FA



Email: plentypumps@spx.com




SPX Flow Technology
Earl Haig Road, Hillington
Glasgow, G52 4JN UK
Tel: +44 (0) 141 883 0314
Fax: +44 (0) 141 882 2752

SPX Flow Technology
611 Sugar Creek Road
Delavan, WI 53115 USA
Tel: +1 (800) 252-5200
Fax: +1 (800) 252-5012

SPX Flow Technology
27 Int'l Business Park
04-02, Primefield Landmark Bldg.
Singapore 609924 Singapore
Tel: +65 6264 4366
Fax: +65 6265 9133

Established: 1790

Common Applications: Oil & Gas, Chemical, Petrochemical, Power Generation, Marine, Mining, Pulp & Paper, Steel, Offshore, Automotive, Food, Gas Processing, Gas Transmission, Refining, LNG, Protection Systems, Heating, Cooling, Water, Waste & Sewerage

MAGMO SUGAR PUMPS		
	<ul style="list-style-type: none"> ④ Designed to handle high viscosity abrasive sugar products, such as molasses and massecuite. 	<ul style="list-style-type: none"> ④ Primary application in sugar processing
	TWINRO TWIN AND TRIRO TRIPLE SCREW PUMPS	
	<p>TWINRO TWIN</p> <ul style="list-style-type: none"> ④ Bulk transfer of liquids ④ Terminal distribution ④ Fuel oil transfer ④ Ships bunkering / cargo pumping ④ Rail / road car unloading / loading ④ Pipeline and process flow requirements 	<p>TRIRO TRIPLE</p> <ul style="list-style-type: none"> ④ Fuel oil firing ④ Forced lubrication (API614 / 676) ④ Crude oil ④ Heavy fuel oil pumping ④ Lube oil transfer
	VANE PUMPS	
	<ul style="list-style-type: none"> ④ U2000 - variable flow rotary pumps ④ G2000 & P2000 - fixed flow rotary pumps 	<ul style="list-style-type: none"> ④ Used in almost any process plant requiring variable flow rates ④ Typical applications: Lube oil blending, bitumen/asphalt, ships bunkering



Email: plentymixers@spx.com


SPX Flow Technology
135 Mt. Read Blvd.
Rochester, NY 14611 USA
Tel: +1 (585) 436-5550
Fax: +1 (585) 436-5589

SPX Flow Technology
Ocean House, Towers Business Park
Didsbury, Manchester
M20 2LY
Tel: +44 161 249 1170

SPX Flow Technology China
2F, Treasury Centre
No. 1568 Huashan Road
Shanghai 200052, China
Tel: +86 (21) 22085889

Established: 1790

Common Applications: Oil & Gas, Oil Storage

BELT AND GEAR DRIVE MIXERS		
	<p>FIXED ANGLE</p> <ul style="list-style-type: none"> ④ For blending, homogenizing and temperature uniformity duties 	<p>SWIVEL ANGLE</p> <ul style="list-style-type: none"> ④ For tank cleaning operations and the prevention of harmful sludge build-up







Email: plentyfilters@spx.com

SPX Flow Technology
Hambridge Road
Newbury, Berkshire, UK RG14 5TR
Tel: +44 (0) 1635 42363
Fax: +44 (0) 1635 49758

SPX Flow Technology
19191 Hempstead Highway
Houston, TX 77065 USA
Tel: +1 (281) 469-0550
Fax: +1 (281) 807-2805

Established: 1790

Common Applications: Oil & Gas, Chemical, Power, Marine, Mining, Pulp & Paper, Steel, Offshore, Automotive, Food, Heating, Cooling, Water, Waste & Sewerage, Refining

	<p style="text-align: center;">SIMPLEX TYPE STRAINERS</p> <ul style="list-style-type: none"> ④ Used in liquids and gases ④ Quick release cover eliminating the need for tools ④ Designed for pressure ratings up to ASME class 300 (51 Barg) ④ Fine stainless steel mesh inserts can provide capabilities for particle removal down to 10 microns for liquid & 1 micron for gas ④ Fitted with cleanable baskets and inserts or disposable gas cartridges ④ Fabricated filters to suit unique specifications
	<p style="text-align: center;">BACK FLUSH STRAINERS</p> <ul style="list-style-type: none"> ④ Used where an automatic cleaning strainer is required ④ Ensures process continuity without manual labor ④ Provide a high level of cleaning efficiency with minimal product loss ④ Straining element is manufactured from stainless steel 316 ④ Fine stainless steel mesh lined baskets provide capabilities for particle removal down to 50 microns
	<p style="text-align: center;">DUPLEX DUAL BASKET STRAINERS</p> <ul style="list-style-type: none"> ④ Designed for applications where continuous operation is required ④ Integral flow changeover valve permits basket removal and cleaning without interruption of flow ④ Designed for pressure ratings up to ASME Class 300 ④ Fine stainless steel mesh inserts can reduce particle removal down to 10 microns ④ Quick release covers eliminate the need for maintenance tools
	<p style="text-align: center;">GAS FILTRATION</p> <ul style="list-style-type: none"> ④ Designed to remove solids from gas streams ④ Elements include cleanable stainless steel or disposable fiberglass or polypropylene ④ High pressure rated to Fas PD5500/E13 & ASME VIII specification ④ Quick opening or bolted closures ④ Designed to meet customers operating conditions



Email: plentyfilters@spx.com

SPX Flow Technology
Hambridge Road
Newbury, Berkshire, UK RG14 5TR
Tel: +44 (0) 1635 42363
Fax: +44 (0) 1635 49758

SPX Flow Technology
19191 Hempstead Highway
Houston, TX 77065 USA
Tel: +1 (281) 469-0550
Fax: +1 (281) 807-2805

Established: 1790

Common Applications: Oil & Gas, Chemical, Petrochemical, Power Generation, Marine, Mining, Pulp & Paper, Steel, Offshore, Automotive, Food, Gas Processing, Gas Transmission, Refining, LNG, Protection Systems, Heating, Cooling, Water, Waste & Sewerage, Refining



FILTRATION ELEMENTS

- ④ Complete range of liquid and gas elements
- ④ Available in various materials of construction including metal, fiberglass and polypropylene
- ④ Degree of filtration from 10mm - 1 micron
- ④ Flow tested both liquid and gas elements to ensure process warranties can be offered



LIQUID FILTERS

- ④ A wide range of filters in a variety of materials in accordance with international pressure vessel codes
- ④ Single basket and dual basket (Duplex) filters
- ④ Fully automatic backflush filters
- ④ Hi-Flow Filters
- ④ Designed to incorporate either quick release or bolted closures
- ④ Elements are either cleanable or disposable



CARTRIDGE FILTERS

- ④ Custom designed filters to meet specific application details
- ④ Designed and manufactured in accordance with international pressure vessel code
- ④ Range of materials of construction to meet customers specific operating parameters



BACKFLUSH FILTERS - METAL

- ④ Custom designed range available
- ④ Stand alone or skid mounted
- ④ Internals available in a range of materials to meet specific applications
- ④ Line sizes 6" - 90"



BACKFLUSH FILTERS - GRP

- ④ Developed primarily for sea water with high corrosion where metal bodies are unsuitable
- ④ Custom designed range available
- ④ Stand alone or skid mounted
- ④ Internals available in a range of materials to meet specific applications
- ④ Line sizes 6" - 90"



DRY GAS FILTERS

- ④ Designed to remove solids from gas streams
- ④ Available in both horizontal or vertical units, in a variety of materials to meet international codes
- ④ Quick opening or bolted cover
- ④ Elements include cleanable stainless steel or disposable fiberglass or polypropylene
- ④ Designed to meet customer operating conditions



Email: plentyfilters@spx.com

SPX Flow Technology
Hambridge Road
Newbury, Berkshire, UK RG14 5TR
Tel: +44 (0) 1635 42363
Fax: +44 (0) 1635 49758

Established: 1790

Common Applications: Oil & Gas, Chemical, Petrochemical, Power Generation, Marine, Mining, Pulp & Paper, Steel, Offshore, Automotive, Food, Gas Processing, Gas Transmission, Refining, LNG, Protection Systems, Heating, Cooling, Water, Waste & Sewerage, Refining



FILTER SEPARATORS

- ④ Designed to remove both solids and liquids from gas streams
- ④ Constructed using Plenty coalescing cartridges, vane units and/or cyclones to achieve required solid and liquid removal efficiency
- ④ Unit available from pipe sizes 2" and above to suit any pressure class
- ④ Available in a range of materials suitable for all operating conditions



COALESCERS

- ④ Designed to coalesce fine liquid mist in gas streams into droplets considerably larger than their original size, such that they can be drained by gravity from the vessel
- ④ Units available in both horizontal and vertical orientation with single or two stage construction



CARBON BED FILTERS

- ④ Custom design filters to meet specific application details
- ④ Designed and manufactured in accordance with international pressure vessel code
- ④ Range of materials of construction to meet customers specific operating parameters



SKID MOUNTED PACKAGES - LIQUID

- ④ Custom designed range available
- ④ Skid mounted packages
- ④ Modular
- ④ Can include mechanical, electrical, instrumentation, ladders, platforms to be compatible with site requirements



SKID MOUNTED PACKAGES - GAS

- ④ Custom designed to application requirements
- ④ Skid mounted packages
- ④ Modular
- ④ Can include mechanical, electrical, instrumentation, ladders, platforms to be compatible with site requirements



SKID MOUNTED PACKAGES - CARBON BED

- ④ Custom designed to application requirements
- ④ Skid mounted packages
- ④ Modular
- ④ Can include mechanical, electrical, instrumentation, ladders, platforms to be compatible with site requirements

Established: 1946
Common Applications: Chemical, Oil & Gas, Power Generation, Pharmaceutical, Electronics, Petrochemical Manufacturing

	<p style="text-align: center;">HEATLESS DESICCANT AIR DRYERS</p> <ul style="list-style-type: none"> ④ LHA Series low flow desiccant dryer ④ DHA/CDA Series standard and custom ④ DSE/DSS/DHD Series industrial grade ④ CHA Series large flow heatless dryers ④ Consistent outlet dew points ④ Critical applications and hostile environments ④ Durable economic industrial applications ④ Corrosive, toxic or explosive environments
	<p style="text-align: center;">HEATED DESICCANT AIR DRYERS</p> <ul style="list-style-type: none"> ④ DEA Series internally heated ④ CAB/IBP Series blower regenerated ④ PHD Series externally heated ④ NRG-Les Series waste heat ④ Low purge energy savings ④ No process gas lost to purge ④ All weather dew point control ④ Compressor outlet heat regeneration
	<p style="text-align: center;">HIGH VOLUME REFRIGERATED COMPRESSED AIR DRYERS</p> <ul style="list-style-type: none"> ④ PNC Series non-cycling constant dew point ④ ESR Series cycling variable demand ④ Controls provide energy efficiency ④ Fully automatic cycling under rated conditions
	<p style="text-align: center;">FILTERS AND ADSORBERS</p> <ul style="list-style-type: none"> ④ Small flow filtration ④ P2000 Series high performance filters ④ PCC Series large flow filtration ④ PCS Series premium quality filtration ④ Oil and water vapor adsorbers ④ PME Series mist eliminators ④ High performance air and gas filter cartridges ④ State-of-the-art filtration media ④ Exceptional air quality and low pressure drop ④ Critical applications and hostile environments ④ Remove unwanted hydrocarbon vapors ④ Minimal pressure drop improves demand
	<p style="text-align: center;">SPECIALTY DEHYDRATION TECHNOLOGIES</p> <ul style="list-style-type: none"> ④ BAP Series breathing air purification ④ CNG Series single tower natural gas dryer ④ CNG Series twin tower natural gas dryer ④ HCP Series hydrogen coolant purifiers ④ Prevents compressed air respiratory hazards ④ Removes water vapor in small-medium flows ④ Specifically engineered for large flows ④ Electrical power plant generator applications
	<p style="text-align: center;">FLAME ARRESTERS</p> <ul style="list-style-type: none"> ④ Explosion prevention and containment ④ Available for class C and class D gasses ④ Special designs available for class B gasses ④ Eliminate straight through heat conduction ④ Prevent the flow-through of hot particles ④ Maximum protection at minimum cost ④ Custom engineered arresters per application ④ The protected side of the barrier remains cool

Seital Separation Technology

Email: seital@seital.it

Seital srl
Via delle Prese, 14
36014 Santorso (VI)
Italy
Tel: +39 0445 540232
Fax: +39 0445 540214

Established: 1983

Common Applications: Chemicals, Dairy, Food & Beverage, Industrial, Oils & Fats, Pharma & Biotech

	<h3 style="text-align: center;">VERTICAL DISK STACK CENTRIFUGES</h3> <ul style="list-style-type: none"> ④ Solids-retaining and self-cleaning centrifuges ④ Self-cleaning nozzle centrifuges ④ Wide range of hydraulic capacities, from 132 to 2641 g/h (500 to 10,000 l/h) for solids-retaining models and from 132 to 18,492 g/h (500 to 70,000 l/h) for self-cleaning models ④ Hygienic & Gas-tight design ④ Most common applications: corn oil recovery from bioethanol production, milk skimming and bacteria clarification, tea clarification, wine & beer clarification, yeast and bacteria recovery
	<h3 style="text-align: center;">TECHNOLOGY SOLUTIONS</h3> <ul style="list-style-type: none"> ④ High performance Centrifuges ④ Focused on R&D for continuous improvement on performance and materials ④ Excellence in design, mechanical and hydraulic analysis and testing ④ Internal manufacturing of all components and parts that are strategic for separators efficiency, quality and safety ④ Standards conformity checked by CMM machine on all strategic parts ④ On-site testing available with complete separation units or in SPX lab and/or pilot plant
	<h3 style="text-align: center;">CUSTOMIZED SOLUTIONS</h3> <ul style="list-style-type: none"> ④ Study and design of specific centrifuge lay-out in order to meet customer demands and separation requirements ④ Proper selection of monitoring instrumentation for accurate control of customer process ④ Specific software development to properly fit into customer logic & controls platform
	<h3 style="text-align: center;">OTHER PRODUCTS</h3> <ul style="list-style-type: none"> ④ Rotary brush strainers ④ Hydro-cyclones ④ Automatic milk and cream standardization units ④ Skid units for separation processes
	<h3 style="text-align: center;">PARTS AND SERVICE</h3> <ul style="list-style-type: none"> ④ All Seital brand equipment is supported by our service organization to enable you to achieve optimum throughput and on-spec quality for the entire life-time of the equipment ④ Unit performance optimization ④ Preventive maintenance agreements ④ Spare parts ④ Customer training service ④ Troubleshooting ④ On-line Monitoring






Tigerholm Series

Email: tigerholm.se@processequipment.spx.com

SPX Flow Technology
 Bryggavägen 113
 178 31 Ekerö, Sweden
 Tel: +46 (0)8 560 340 30
 Fax: +46 (0)8 560 342 60

Established: 1971

Common Applications: Tigerloop® and oil products are applicable on oil burner systems for light oil or kerosene. Tigex® is applicable on all kinds of boilers where a stable draught is required. NoTap® is applicable on all types of metal pipes; galvanized, stainless steel, copper and iron.

	<p style="text-align: center;">TIGERLOOP® OIL DE-AERATORS</p> <ul style="list-style-type: none"> ④ Remove gas/air bubbles from oil lines ④ Increased efficiency - reduced oil consumption ④ Eliminate oil pump and nozzle problems ④ Remove pressurized oil return line to tank ④ Eliminate risk for leakage in return line ④ Preheat oil to avoid problems with cold oil ④ Models for Biofuel applications now available
	<p style="text-align: center;">OIL FILTERS</p> <ul style="list-style-type: none"> ④ Filters available in different sizes from 1/4" to 2" ④ Filter inserts in various materials available from 10 to 150 microns ④ Oil filters of brass construction and are available with or without an isolating valve ④ The filter inserts are easily exchangeable ④ Oil filters available in combination with the Tigerloop® Combi ④ Spin-on paper filter available in combination with Tigerloop® Plus
	<p style="text-align: center;">FLEXIBLE OIL HOSES</p> <ul style="list-style-type: none"> ④ Complete program of high quality oil hoses ④ Sizes available from 300 mm up to 1500 mm ④ Manufactured in the highly oil resistant rubber quality NBR/PVC ④ Hoses are covered with zinc coated iron wire ④ Hoses are tested and approved according to DIN EN ISO 6806 ④ An assortment of connections are available for different applications
	<p style="text-align: center;">TIGEX® DRAUGHT REGULATORS</p> <ul style="list-style-type: none"> ④ Draught regulator, developed and patented by Tigerholm ④ Manufactured in stainless steel ④ Helps improve boiler efficiency ④ Reduces risk of chimney damage caused by condensation ④ Markets only draught regulator with a fully balanced damper ④ Can be fitted in almost any position (angled, vertical or horizontal) ④ Gas-tight door design available
	<p style="text-align: center;">NOTAP® METHOD</p> <ul style="list-style-type: none"> ④ Pipe blocking on "live" pressurized piping systems ④ Branch connections on "live" pressurized piping systems ④ Draining the pipe system is not necessary ④ Adding new water or venting radiators is not necessary ④ Simple installation as no soldering, cross cutting or welding is necessary ④ No need to handle chemicals when modifying cooling systems ④ Minimizes job time




Vokes Series

Email: vokes.sales@spx.com

SPX Flow Technology
 Killarney, Co Kerry
 Ireland
 Tel: +353 6466 33633
 Fax: +353 6466 26362

Established: 1921

Common Applications: Diesel Engines, Gas Turbines, Transformers, Natural Gas Engines, Steam Turbines

	<h3 style="text-align: center;">FUEL & LUBRICATING OIL FILTERS</h3> <p>Vokes' Fuel and Lubricating Oil Filtration systems are designed to protect critical equipment as utilized by the power generation, marine and locomotive industries.</p> <ul style="list-style-type: none"> ④ Simplex & duplex designs available ④ Drop sump & top servicing filters available ④ Robust design and construction <ul style="list-style-type: none"> ④ Cartridges incorporate on integrated gasket ④ Every filter element incorporates high dirt loading media and are corrosion resistant ④ Filter media is unaffected by water, salt or engine acids
	<h3 style="text-align: center;">LIQUID COALESCERS</h3> <p>Vokes filter coalescer is a static device for the removal of solids and free water from distillate and light liquid fuels and mineral lubricating oils.</p> <ul style="list-style-type: none"> ④ Eliminates the requirement for a separate pre-filter ④ Robust filter and cartridge design ④ Easy maintenance <ul style="list-style-type: none"> ④ No moving parts allows for quiet operation ④ No external supplies (power, air) required ④ Ideal for marine installations (i.e. use on board both surface and sub-surface vessels) ④ Free water removal in marine applications ④ Can be designed for military specifications ④ Steam turbine applications
	<h3 style="text-align: center;">OIL MIST ELIMINATORS</h3> <p>Vokes oil mist eliminators are designed to eliminate oil mist present in compressed air systems. Failure to do so can cause operational hazards and obstruct machine operation.</p> <ul style="list-style-type: none"> ④ Ideal for diesel or natural gas engines ④ Discharges clean air to the local atmosphere <ul style="list-style-type: none"> ④ Can be mounted away from the engine ④ APB automatically balances sump pressures
	<h3 style="text-align: center;">STREAMLINE® - INSULATING FLUID TREATMENT SYSTEMS</h3> <p>Insulating fluid is vitally important for the safe and efficient operation of many types of electrical equipment. This fluid is also used as a coolant in transformers and as an arc suppressant in circuit breakers. Vokes' Streamline systems ensure the purity of insulating fluid to optimize performance.</p> <ul style="list-style-type: none"> ④ Removes water and particulates ④ For electrical insulating oil purification <ul style="list-style-type: none"> ④ Improves the dielectric strength ④ Extends insulating oil and transformer life ④ Available as fixed site or mobile units ④ Removes free and dissolved water ④ Water reduction to 90% in single pass

Waukesha Cherry-Burrell®

Email: wcb@spx.com

SPX Flow Technology
 611 Sugar Creek Road
 Delavan, WI 53115 USA
 Tel: +1 (262) 728-1900
 Fax: +1 (262) 728-4904

Established: 1880

Common Applications: Food, Dairy, Beverage, Pharmaceutical, Personal Care, Pulp & Paper, Automotive Paint, Hydro-Carbon Processing, Films, Coatings, Adhesives



UNIVERSAL I AND II SERIES - POSITIVE DISPLACEMENT PUMPS

- ④ Models available in rectangular flange or aseptic configurations with non-galling 88 alloy rotors
- ④ Pumps can be remanufactured
- ④ Close-coupled Tru-Fit mounting options available
- ④ Universal II - Pressures up to 500 psi (34 bar), CIP design
- ④ Universal I - Pressures up to 200 psi (14 bar), COP design



CENTRIFUGAL PUMPS

- ④ High efficiency, minimal vibration, longer life pumps
- ④ One size seal fits all 200 Series models
- ④ Available models include 200 Series, C-Series, Multi-Stage, Self-Priming, Water for Injection, and stub shaft pump versions



C-SERIES PUMPS

- ④ Versatile pump offers strong performance
- ④ Easy-cleaning, open type impeller delivers smooth pumping performance
- ④ Enlarged inlets available for larger suction lines
- ④ Standard CIP capability
- ④ Parts are interchangeable with other C-Series brands



VALVES

- ④ Sanitary, hygienic valves manufactured of stainless steel
- ④ Rising stem, butterfly, ball, manual, and specialty valve designs
- ④ Designed to be cleaned in place or out
- ④ Heavy-duty construction for long service life
- ④ Easy to maintain
- ④ Adaptable and modular



BUTTERFLY & BALL VALVES

- ④ **Butterfly Valves**
 - Available 1" through 4"
 - T304 and T316 construction
 - Finishes are 32 Ra ID and OD
 - 13 position handle
- ④ **Ball Valves**
 - Available 1/2" through 4"
 - T316 construction
 - Finishes are 32 Ra ID
 - Meets 3A and FDA requirements
 - Locking 4 position handle



VOTATOR HEAT EXCHANGERS

- ④ Models available for processing moderate to ultra high viscosity products
- ④ Options for controlling residence time and for maintaining product integrity
- ④ Material selection to meet specific process requirements
- ④ Horizontal and Vertical mounting choices
- ④ Vast applications database from over 50 years of process experience







Waukesha Cherry-Burrell®

Email: wcb@spx.com

SPX Flow Technology
611 Sugar Creek Road
Delavan, WI 53115 USA
Tel: +1 (262) 728-1900
Fax: +1 (262) 728-4904

Established: 1880

Common Applications: Food, Dairy, Beverage, Pharmaceutical, Personal Care, Pulp & Paper, Automotive Paint, Hydro-Carbon Processing, Films, Coatings, Adhesives

	<h3 style="text-align: center;">DISPERSION EQUIPMENT</h3> <ul style="list-style-type: none"> ④ Colloid Mills - Greater capacity with 50% more flow rate with less heat, CIPable ④ CR Mixers - For high shear emulsifying, and controlled and precise aeration ④ Shear Pumps - Processes as it pumps, interchangeable stator and rotor combinations
	<h3 style="text-align: center;">ANCO BACON PRESS</h3> <ul style="list-style-type: none"> ④ New lock down head feature helps control belly thickness ④ The patented "Maximizer" bladder inflates to fill the void on the thin end of the belly reducing wrinkles during the pressing cycle ④ The timer feature allows you to compensate for wide variations in belly temperatures and minimizes over or under pressing ④ The press is capable of up to 16 bellies per minute
	<h3 style="text-align: center;">SANITARY FITTINGS</h3> <p>Constructed of T304 & T316 L Stainless Steel</p> <ul style="list-style-type: none"> ④ S-line ④ Sanitary Weld ④ Bevel Seat ④ I-line ④ Tube OD weld (Industrial) ④ John Perry ④ Schedule 5 and 10 ④ "Cam" style unions ④ Pipe to Tube adapters ④ Aseptic Unions ④ DIN and SMS
	<h3 style="text-align: center;">BPE FITTINGS</h3> <ul style="list-style-type: none"> ④ Manufactured in accordance to ASME BPE standards ④ Available in 1/2" through 6" ④ Made of T316L stainless steel (Other alloys available) ④ Electropolished fittings available ④ MTR (Material Test Reports) provided with each shipment and available online for download ④ Packaged in resealable bags
	<h3 style="text-align: center;">SPECIALTY PRODUCTS</h3> <ul style="list-style-type: none"> ④ Extensive metal working capabilities ④ Designed and constructed to customer specific requirements ④ Unique tangents and configurations ④ Dedicated production cells to shorten lead times ④ Digital imaging equipment for quality validation ④ Weld mapping, logs and documentation programs
	<h3 style="text-align: center;">RELATED PRODUCTS</h3> <ul style="list-style-type: none"> ④ Rath manufactured tubing in T304 and T316 L stainless steel ④ Tube Hangers ④ Special alloy products in AL6XN® and Hastalloy® ④ Sampling Valves ④ T316 S-Line Clamps ④ Check Valves ④ Torque Nuts for S-line Clamps

Research and development are important elements in SPX Flow Technology's (SPX FT) activities in general. Processors are increasingly seeking cost-effective engineered solutions for the production of high quality, innovative products.

In this process, SPX Innovation Centers play an important role with customers around the world.

Our services cater to the needs of multiple industries in the broadest possible sense, including after sales service, laboratory analysis, technical information and training of SPX employees and customers.

SPX Innovation Centers are used for development, testing and application of SPX equipment, systems and processing lines. All of our facilities and services are designed to provide added value by minimizing waste and energy requirements into new, competitive products.

Technical Facilities

The Innovation Center has the facilities to test and demonstrate profitable solutions to common production problems. The center can also participate in trouble shooting, making the customer's operations more flexible, cutting energy costs, increasing production volumes or meeting new environmental regulations without sacrificing the quality of the final product.

Flexibility of the Equipment

The Innovation Center is designed for maximum flexibility. All equipment can be interconnected and new equipment is easily installed. Some of the equipment is mounted on frames for mobility and easy connection to other units, and most of it is controlled by variable speed controllers (VLT). Specialist equipment can be brought in as required and process lines configured to suit individual requirements.

Process Hall

The process hall is well-equipped and is laid out so as to provide for maximum flexibility in conducting test, trials and training. We have several semi-industrial scale plants and have found that up scaling to industrial scale is easily done from this plant size. We also have small scale and industrial scale plants.

Service Facilities

Water, ice water, air, glycol, power (380 V, 220 V) and steam are available.

Tank Facilities

According to customer's request. Various mobile tanks are available.

Storage Facilities

Temperature controlled storage rooms are available with both cooling and heating possible (0° C/32° F to 40° C/104° F).

Workshop

Our experienced fitters are involved in the installation of trial plants, building new plants or modifying existing equipment for special trial runs. To allow for maximum flexibility and rapid response, a fitter is always available during trial runs to undertake any on-site modifications.

Laboratory Facilities

Our laboratory performs chemical, microbiological and functional analysis of all kinds of food products. All analysis is carried out in accordance with international standards.

Homogenizer Application Laboratory

The SPX homogenizer application laboratory offers new and advanced small-scale application development assistance to customers.

Situated in Denmark, the laboratory serves customers with homogenizing tests and analyses to help troubleshoot processing problems, optimize existing products and develop new ones.

Finding the right homogenizer - The SPX homogenizer application laboratory helps customers document the benefits of a particular homogenization process for their application and optimize the homogenizing efficiency by determining process parameters such as optimum pressures, type of homogenizing valve, premix, temperature, etc. Customers can choose to move forward with pilot tests on their own premises using a new APV brand homogenizer, a rented homogenizer from SPX - or use the facilities at the SPX Innovation Center, where more extensive pilot testing results are possible in a valid production-scale process.

Technical Facilities

Customers running trials on their own premises can choose to rent whatever new plant and equipment they require to complete their testing. Rentals cover both pilot and full production-scale plant equipment.

For more information please visit www.spx.com.



Testing Flexibility


SPX lab facilities are highly sophisticated and equipped with leading edge technology. They were specifically designed to accommodate a broad range of tests with the highest degree of flexibility. Depending on your specific need, we offer testing and consulting services on a fee basis.

- ④ *Whenever possible we prefer to test your actual materials. This may range from a simple rheology definition to the preparation of a complete recipe in our laboratory. Or, we may run a full-scale test at your facility.*
- ④ *We guarantee our recommendations and are available to assist all the way through installation and plant start up.*
- ④ *If we cannot process your material due to safety concerns or process conditions we will work with you to find a material to mimic the properties of your process.*





Our brands pride themselves on offering a range of products designed to meet the most arduous of conditions. The result of extensive research and development, all of our equipment has been engineered to offer a selection of benefits, which can be simulated in the company's laboratories across the world. Whether the product is a fully engineered process system or a small fitting, each has received a level of engineering expertise and testing that is your assurance of product suitability, even in the most extreme conditions.

With a focus on performance with minimum energy input, SPX products have been designed to give you the output you need, while keeping your energy cost under control and helping you to reduce your carbon footprint.



- ④ *Pumps, valves, drives, heat exchangers, mixers and mills in an endless variety*
- ④ *Vessels from 200 ml to 450,000 gallons*
- ④ *State-of-the-art digital data acquisition systems*
- ④ *Viscometer with Small Sample Adapter & Temperature Control*
- ④ *High Shear Viscometer*
- ④ *Accelerometers, Torque Cells, Load Cells, Pressure Transducers, Flow Meters, Sound Level Meters*
- ④ *Motion analyzer for pump cavitation analysis*
- ④ *Laser Doppler Velocimeter*
- ④ *Microtrac and Horiba particle size analyzer*
- ④ *High power microscopes with digital image capture*
- ④ *Spectrophotometer*
- ④ *Gloss Meter*
- ④ *Full Computational Fluid Dynamic and Finite Element Analysis using the latest software*
- ④ *Feasibility studies for process systems*



Visit www.spxft.com to learn more.

An International Customer-Focused Service Platform



SPX Flow Technology - Service and Parts Solutions

- ④ *Repair and exchange services*
- ④ *Equipment upgrade services*
- ④ *Installation and start-up support*
- ④ *Predictive and preventive maintenance*
- ④ *Remote diagnostics*
- ④ *Process and mechanical consulting*
- ④ *Asset management*
- ④ *On-site field support*
- ④ *Training*



SPX Flow Technology provides innovative ways to improve your productivity and profitability. We'll help you minimize your asset investments, while ensuring that you continue to meet your production requirements. Multiple service facilities are strategically located throughout the world, providing a wide range of support 24 hours a day.

Service locations are the hub for our parts distribution. We can analyze your spare parts inventory to identify critical, damaged and obsolete spare parts, and help you create an inventory reduction program.

- ④ *High quality OEM spare parts and consumables*
- ④ *Quick-ship delivery services available*

After-Sales Solutions from SPX Flow Technology

SPX brands offer a full range of after-sales products to ensure that the original equipment continues to operate at its maximum performance.



A worldwide network of companies and distributors ensures that you are never far from the help you need to get back up and running quickly and get the ultimate performance from your investment.

See specific brand pages for additional contact details.

After-Sales Valve Service

SPX provides a full range of valve and wellhead service, repair, remanufacturing and inventory management of customer assets for the pipeline, petrochemical, hydrocarbon storage well and geothermal industries. We specialize in reconditioning of valves from all manufacturers, and turnkey valve field services. SPX continues to manufacture the complete underground storage wellhead hook-up in accordance to our API 6A and 6D license.

Email: OFM@spx.com

Pump Solutions

The technical services team consists of a dedicated group of experienced pump engineers specializing in providing expert pump systems advice to our customers across all industries. Possessing a wealth of pump and system design knowledge, fully equipped with the latest design, analytical and pump testing equipment, our technical services team can be employed across a range of services to ensure your critical rotating plant is operating reliably, safely and at optimal levels of efficiency. Working in partnership with our customers the focus of these important aspects of pump operation deliver increased mean time between failures and plant life, reduced parts consumption, increased production and very importantly minimizing energy costs and carbon emissions.





Global locations

USA

SPX GLOBAL HEADQUARTERS

13515 Ballantyne Corporate Place
Charlotte, NC 28277
United States of America
+1 704 752 4400

APAC

SPX ASIA PACIFIC

2F, Treasury Building
1568 Hua Shan Road
Shanghai 20000523
Peoples Republic of China
+86 21 2208 5888

EMEA

SPX EUROPE

The Beehive, City Place
Beehive Ring Road
Gatwick, West Sussex RH6 0PA
United Kingdom
+44 (0) 1293 527777

SPX reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit www.spx.com.

The green ">" is a trademark of SPX Corporation, Inc.

ISSUED 07/2012 SPX-001

COPYRIGHT © 2012 SPX Corporation