

Homeothermic Monitoring System



KEY FEATURES

- NEW Easy to use LCD touchscreen
- Flexible rectal probe
- Easy to clean, flexible heating pad
- Multiple heating pad sizes available

The Homeothermic Monitoring System is a closed loop temperature control system for small rodents. Utilizing a small, flexible rectal probe to monitor the animal's core temperature and a heating pad to provide heat input, the subject's core body temperature can be accurately controlled. The control unit receives temperature feedback from the rectal probe and adjusts the current to the pad accordingly.

The easy to use LCD touch screen allows users to set a target temperature and clearly view the subject's current core body temperature, as well as the set temperature, at all times. Additionally, audible alarms can be set to advise the user should the animal's core body temperature deviate ±1° from the set temperature.

Heating pads are available in four sizes to fit all your surgical needs. The standard size is appropriate for mice and small rats and fits nicely into standard stereotaxic instruments, while the large size is for rats and other liked-sized rodents. Two additional sizes are available to fit the common stereotaxic instrument adapters. The pads are flexible enough to fully wrap the animal, which allows the animal to be warmed from all sides rather than just the front or back.

Harvard Apparatus Homeothermic Monitoring System

| Specifications | |
|------------------------|---|
| Temperature Range | 20-50°C (68-122°F) |
| Resolution | 0.1°C/F |
| Integrated Temp Sensor | Yes |
| Temperature Stability | ±0.1°C |
| Temperature Display | User selectable °C and °F |
| Pad Material | Silicone |
| Probe | Flexible rectal probe |
| Probe Shaft Length | 100 mm (3.94 in) |
| Probe Shaft Diameter | 1.6 mm (0.06 in) |
| Probe Tip Diameter | 1.6 mm OD flexible rectal probe |
| Information Displayed | Current Body Temperature (rectal temperature) and Set Temperature |
| Serial Communication | RS-485 |
| Analog Output | 0-5V, 20-50°C |
| Analog Input | 0-5V, 20-50°C |
| Dimensions (H x W x D) | 12.0 x 22.6 x 15.8 cm (4.72 x 8.91 x 6.21 in) |
| Weight | 0.68 kg (1.5 lbs) |
| Power | 100-240 VAC, 50-60 Hz |
| Regulatory | CE, ETL (UL, CSA), WEEE, EU RoHS |
| Warranty | 1 year |

| Ordering Information | |
|----------------------|--|
| Order# | Systems |
| 55-7020 | Homeothermic Monitoring System includes: Homeothermic Control Unit, Flexible Rectal Probe, Standard Size Heating Pad (12.0 x 20.5 cm), Insulation Pad and USB cable |
| 55-7034 | Homeothermic Monitoring System Includes: Homeothermic Control Unit, Flexible Rectal Probe, Large Heating Pad (20.3 x 25.4 cm), Insulation Pad and USB Cable |
| 55-7030 | Homeothermic Monitoring System Includes: Homeothermic Control Unit, Flexible Rectal Probe, Heating Pad for Mouse Stereotaxic Adpater (7.0 x 14.5 cm), Insulation Pad and USB Cable |
| 55-7031 | Homeothermic Monitoring System Includes: Homeothermic Control Unit, Flexible Rectal Probe, Heating Pad for Stereotaxic Anesthesia Platform (3.7 x 14.5 cm), Insulation Pad and USB Cable |
| Replacement Parts | |
| 55-7021 | Flexible Rectal Probe, 1.6 mm OD |
| 55-7022 | *Heating Pad, standard, 12.0 x 20.5 cm |
| 55-7032 | *Heating Pad, large, 20.3 x 25.4 cm |
| 55-7023 | *Heating Pad, for mouse stereotaxic adapter, 7.0 x 14.5 cm |
| 55-7024 | *Heating Pad, for stereotaxic gas anesthesia platform, 3.7 x 14.5 cm |
| 55-7025 | Insulation Pad, for standard heating pad, 12.0 x 20.5 cm |
| 55-7033 | Insulation Pad, for large heating pad, 20.3 x 25.4 cm |
| 55-7026 | Insulation Pad, for mouse stereotaxic adapter heating pad, 7.0 x 14.5 cm |
| 55-7027 | Insulation Pad, for stereotaxic gas anesthesia platform, heating pad, 3.7 x 14.5 cm |





84 October Hill Road, Suite 10, Holliston, MA 01746 USA phone 508.893.8999 • fax 508.429.5732 email support@hbiosci.com