




Sign Essentials & Lighting

1-800-631-8375 www.outwater.com New Jersey & Arizona









Sign Essentials

0	
Cable Display System	
3 in 1 Cable Hardware Kits	S-8
15 Series Cable Signage Kit	S-9
30 Series Cable Signage Kit	S-10
30 Series Cable Shelving	S-11~12
Adjustable Cable Hook Hardware	S-18
Double Loop Cables	S-18
LED MR16 Rod	S-13
Heavy Duty 3mm Ceiling to Floor	S-5
Heavy Duty 3mm Ceiling to Sign	S-7
Standard 1.5mm Ceiling to Floor	S-4
Standard 1.5mm Ceiling to Sign	S-6
Trackless 2mm Hanging System	S-16~17
Wall Track 2mm For Art	S-15
Exhibit Systems	
Aluminum Framing Systems	S-95~102
Klem® Connecting Systems	S-104~105
Extrusions	
Angle Moulding	S-68~71
Cap & Divider Moulding	S-76~80
Corner Moulding	S-74~75
Price Tag Moulding	S-72~73
U-Channel Moulding	S-62~67
Z Panel Moulding	S-26
Fastmount Panel Mounting Systems	S-106~110
rames & Profiles	
Aluminum Frame Profiles	S-52~54
Fully Assembled, Front Loading	
Aluminum Frames	S-55~58
LED Crystal Light Box	S-59
LED Fully Assembled, Front	S-60
Loading Aluminum Frames	
PVC Frame Profiles	S-48
Slide In Frames	S-61
Great Wall PVC & Aluminum Slatwall	S-103
Hangman® Hanging Products	S-19~25
SEG Modular Frames/Components	
Banner Ups® SEG Design™	S-82~85
Modular SEG Frames	3 52 65
Foga® Fabric Flex	S-86~94
Framing System (for SEG)	
Sign Components	
Free Standing & Wall Mount	S-81
Sign Holders	
Magnaclamps®	S-48
Sign/Banner Holders	S-47, 49-51
Standoffs	
Cap It Off Series	S-45~46
Easy Fasten	S-27~30, 34
Edge It - No Drill	S-37~38
Grip It - No Drill	S-39~42
Invitai Cariaa	S-44
Invisi Series	S-43
LED	***************************************
LED Secure Fasten	S-30~33
LED	***************************************
LED Secure Fasten	S-30~33

Table of Contents

	•	1	114		
11		n	١Ť١	n	
ы	Ч		L		U
	\sim				\sim

Angled Power Strips	L-170~171
Backlighting Panel Series	L-1~16, 119~121
Bulbs	L-151~152
Cables, Connectors & Switches	L-145~149
Canister Lighting 120V	L-115
Ceiling Panel Lighting	L-153
Channel Letter Modules	L-131~133
Closet Rod Kit 12V	L-100
Controllers	L-150
Dimmers	L-134~136, 142~144
Display Arms	L-127~130
Edge Lighting	L-54
Fiber Optic 110V	L-116
Fixtures 24V 120V	L-84~85 L-79~83
Indirect Lighting Profiles	L-172~176
LED Channels	L-55~62
LED Standoffs	L-117~118
Light Frames/Boxes	L-122~124
Light Ceiling Panels	L-141
Linear Flexible 12V 24V 120V	L-45~54 L-23~44 L-17~22
Linear Rigid	
12V 24V Power Track System 12V/24V Omni Wand System	L-66~67, 86~89, 92~93 L-63~65, 90~91, 94~96 L-97~99 L-68~78
Power Hubs	L-158~167
Power Supplies	L-137~141
Puck Lighting 12V 24V 120V	L-104~112 L-102~103, 113 L-101
QI Chargers	L-168~169
Spot Lighting 12V	L-114, 125
WAC 120V LED Track Heads	L-154~157
Wall Washers	L-126

STANDARD Duty Cable System

1.5mm Cable & Fittings Supports up to 110 lbs. per cable



This low cost system includes 1.5mm cables with aluminum fittings. This system is designed for small display areas up to 6'6" high.



Contents

3 in 1 Cable Hardware Kits For Both Standard 1.5mm & Heavy Duty 3mm
Standard 1.5mm Ceiling to Floor Cable Signage S-4
Heavy Duty 3mm Ceiling to Floor Cable Signage S-5
Standard 1.5mm Ceiling to Sign Cable Signage S-6
Heavy Duty 3mm Ceiling to Sign Cable Signage S-7
15 Series Cable Signage Kit S-9
30 Series Cable Signage Kit Illuminating
30 Series Cable Shelving S-11~12
Adjustable Cable Hook Sign Hanging Hardware & Double Loop Cables S-18
LED MR16 Rod S-13



HEAVY Duty Cable System

3mm Cable & Fittings Supports up to 220 lbs per cable




This premium system includes 3mm cables with solid brass fittings. This system is designed for large display areas up to 13' high. A wide range of shelving options are possible with this

system as well as illuminated and non-illuminated signage options.



Standard 1.5mm Ceiling to Floor Cable Signage



English measurements converted from metric. Metric is the most accurate.

1. Mounting Channel

CSK-ALU

Material: Aluminum Finish: Clear Anodized

Cable Diameter: 1.5mm Length: 6'6"

Price: \$19.95 ea. Carton Price: \$18.95 ea. (10 Pieces Per Ctn.)



2. Channel/Ceiling Top Fitting

CSKE-CHTF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm

Price: \$3.95 ea. Carton Price: \$3.70 ea.

(50 Pieces Per Ctn.) Comes with both toggle & screw mount



3. Ceiling Top Fitting

CSKE-CSTF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm

Price: \$5.65 ea. Carton Price: \$5.25 ea. (50 Pieces Per Ctn.)



4. Channel/Floor Bottom Fitting

CSKE-CHBF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm

Price: \$5.25 ea. Carton Price: \$4.95 ea. (25 Pieces Per Ctn.)

Comes with both toggle & screw mount



5. Bottom Fitting

CSKE-BF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm Price: \$15.75 ea.

Carton Price: \$14.60 ea. (25 Pieces Per Ctn.)




6. 1.5mm Bulk 304 Grade Stainless Steel Cables

Part #	Description	Cable Length Price		Carton Qty.	Carton Price
	304 Stainless Stee	l Cables			
CSKE-CABLE	Standard 7x7 Construction	13′	\$3.25 ea.	50	\$2.95 ea.
	Coated Stainless St	eel Cable	S		
CSKE-CABLE-C	Nylon Coating Over 7x7 Cable	13′	\$4.90 ea.	50	\$4.55 ea.
	· ·				




Horizontal Sign Clamps **CSKE-SSGC-ALU** CSKE-DSGC-ALU Double Material: Aluminum Material: Aluminum Finish: Clear Anodized Single (16mm) Finish: Clear Anodized Cable Diameter: 1.5mm 5/8" (16mm) Cable Diameter: 1.5mm Price: \$3.25 ea. Price: \$3.95 ea. 11/2" Carton Price: \$2.95 ea. 11/16" (39mm Carton Price: \$3.75 ea. (50 Pieces Per Ctn.) (50 Pieces Per Ctn.)



Use 3mm Hex Key

Use 3mm Hex Key


Heavy Duty 3mm Ceiling to Floor Cable Signage 1. Mounting Channel




English measurements converted from metric. Metric is the most accurate.













Part #	Description	Cable	Price	Carton	Carton Price	
rart#	Description Stainless Steel C	Length ables	rrice	Qty.	Frice	204
CSK-CABLE		13′	\$9.85 ea.	25	\$7.45 ea.	304 Stainless
CSK-CABLE-26	Standard 7x7 Construction	26'	\$15.00 ea.	10	\$13.95 ea.	Steel
CSK-CABLE-100		100'	\$49.80 ea.	10	\$47.95 ea.	
	Coated Steel Ca	ables				
CSK-CABLE-C	Nylon Coating Over 7x7 Cable	13′	\$10.95 ea.	25	\$9.95 ea.	





Standard 1.5mm Ceiling to Sign Cable Signage



English measurements converted from metric. Metric is the most accurate.



1. Mounting Channel

CSK-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 3mm

Length: 6'6"
Price: \$19.95 ea.
Carton Price: \$18.95 ea.
(10 Pieces Per Ctn.)



2. Channel/Ceiling Top Fitting

CSKE-CHTF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm Price: \$3.95 ea.

Carton Price: \$3.70 ea. (50 Pieces Per Ctn.)

Comes with both toggle & screw mount



3. Ceiling Top Fitting

CSKE-CSTF-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm Price: \$5.65 ea.

Carton Price: \$5.25 ea. (50 Pieces Per Ctn.)






4. Sign Fitting (Holds 3/16" Thick Signage)

CSKE-CSSC-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 1.5mm

Price: \$3.25 ea. **Carton Price:** \$2.95 ea.

(50 Pieces Per Ctn.)
Use 3mm Hex Key



Vertical Double Sign Clamp


CSK-DSSC-*

Use 3mm Hex Key

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC)

Cable Diameter: 1.5mm

Price: \$7.60 ea. Carton Price: \$6.95 ea. (25 Pieces Per Ctn.)





6. 1.5mm Bulk 304 Grade Stainless Steel Cables

Part #	Description	Cable Length	Price	Carton Qty.	Carton Price
1 411 11	304 Stainless Stee			(1)	
CSKE-CABLE	Standard 7x7 Construction	13′	\$3.25 ea.	50	\$2.95 ea.
	Coated Stainless St	eel Cable	s		
CSKE-CABLE-C	Nylon Coating Over 7x7 Cable	13′	\$4.90 ea.	50	\$4.55 ea.



English measurements converted from metric. Metric is the most accurate.

Heavy Duty 3mm Sign to Floor Cable Signage



1. Mounting Channel

CSK-ALU

Material: Aluminum Finish: Clear Anodized Cable Diameter: 3mm Length: 6'6"

Price: \$19.95 ea. Carton Price: \$18.95 ea. (10 Pieces Per Ctn.)



2. Channel/Ceiling Top Fitting

CSK-CHTF-*

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC) Cable Diameter: 3mm

Price: \$5.95 ea. Carton Price: \$5.45 ea. (25 Pieces Per Ctn.)

Comes with both toggle & screw mount



3. Ceiling Top Fitting

CSK-CSTF-*

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC)

Cable Diameter: 3mm Price: \$11.95 ea. Carton Price: \$11.10 ea.

(25 Pieces Per Ctn.)



4. Sign Fitting (Holds 3/16" Thick Signage)

CSK-CSSC-*

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC)

Cable Diameter: 3mm Price: \$4.50 ea.

Carton Price: \$4.20 ea. (50 Pieces Per Ctn.) Use 3mm Hex Key



15/16"



4. Sign Fitting (Holds 1/2" Thick Signage)

CSK-CSSC12-*

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC)

Cable Diameter: 3mm Price: \$5.95 ea.

(50 Pieces Per Ctn.)

Carton Price: \$5.55 ea. Use 3mm Hex Key






Vertical Double Sign Clamp

CSK-DSSC-*

Material: Solid Brass Finish: Satin Chrome (*SC) & Polished Chrome (*PC)

Cable Diameter: 1.5mm Price: \$7.60 ea.

Carton Price: \$6.95 ea. (25 Pieces Per Ctn.) Use 3mm Hex Key






6. 3mm Bulk 304 Grade Stainless Steel Cables

Part #	Description	Cable Length	Price	Carton Qty.	Carton Price			
Stainless Steel Cables								
CSK-CABLE		13′	\$9.85 ea.	25	\$7.45 ea.			
CSK-CABLE-26	Standard 7x7 Construction	26'	\$15.00 ea.	10	\$13.95 ea.			
CSK-CABLE-100		100'	\$49.80 ea.	10	\$47.95 ea.			
Coated Steel Cables								
CSK-CABLE-C	Nylon Coating Over 7x7 Cable	13′	\$10.95 ea.	25	\$9.95 ea.			





3 in 1 Cable Hardware Kits For Both Standard 1.5mm & Heavy Duty 3mm









English measurements converted from metric. Metric is the most accurate.

Standard 1.5mm 3 in 1 Kit

MATERIAL = Aluminum (*Fittings*) 304 Grade Stainless Steel (*Cable*)

FINISH = Clear Anodized

- Aluminum universal fittings are hinged to allow or use in Wall-to-Wall and Wall-to-Floor applications
- For 8-1/2" x 11" and 11" x 17" graphics
- Can be used for single or double sided displays

Each Hardware Kit Contains:

- 1 universal top fitting
- 1 universal bottom fitting
- 1 cables 13' length -1.5mm thick (trimmable)

	Pr	ıce
Part #	Each Set	10+ Sets
CSKE-GN-ALII	\$25.05	\$24.45.62

For 1.5mm: Horizontal Sign Clamps & Clear Acrylic Sign Holders, See Page S-4

Heavy Duty 3mm 3 in 1 Kit

MATERIAL = Solid Brass (*Fittings*) 304 Grade Stainless Steel (*Cable*)

FINISHES = Polished Chrome (*PC) & Satin Chrome (*SC)

- Solid Brass universal fittings are hinged to allow for use in Wall-to-Wall, Wall-to-Floor and Floor-to-Ceiling applications
- For 8-1/2" x 11" and 11" x 17" graphics
- Can be used for single or double sided displays

Each Hardware Kit Contains:

- 1 universal top fitting
- 1 universal bottom fitting
- 1 cables 13' length -3mm thick (trimmable)

Pr	ice
Each Set	10+ Sets
\$39.95	\$38.25 ea
	Each Set

For 3mm: Horizontal Sign Clamps & Clear Acrylic Sign Holders, See Page S-5

15 Series Cable Signage Kit Non-Illuminating



2 Graphic Kits

Complete Graphic Kit

MATERIAL = Aluminum (*Fittings*) 304 Grade Stainless Steel (Cable)

FINISH = Clear Anodized

- Aluminum universal fittings are hinged to allow or use in Wall-to-Wall and Wall-to-Floor applications
- For 8-1/2" x 11" and 11" x 17" graphics
- Can be used for single or double sided displays



Easy to replace graphics












Each kit contains:

- 2 universal top fittings
- 2 universal bottom fittings
- 2 cables 6'6" length 1.5mm thick (trimmable)
- 12 mounting screws & anchors
- 1 hex key
- 4 sign clamps per graphic holder

4 Graphic Kits

• 1/8" thick clear acrylic graphic holders w/polished edges

Hinged Fittings are adjustable:



	Part #	Size	Type	Price
2	CSKE-LITKIT2-8-*	8½" x 11"		\$67.93 kit
Graphic Kit	CSKE-LITKIT2-11-*	11" x 17"		\$91.58 kit
3	CSKE-LITKIT3-8-*	8½" x 11"	Portrait (*P)	\$87.45 kit
Graphic Kit	CSKE-LITKIT3-11-*	11" x 17"	Landscape (*L)	\$122.93 kit
4	CSKE-LITKIT4-8-*	8½" x 11"		\$106.98 kit
Graphic Kit	CSKE-LITKIT4-11-*	11" x 17"		\$154.28 kit

CSKE-LITKIT2-8-P CSKE-LITKIT2-8-L CSKE-LITKIT3-8-P CSKE-LITKIT3-8-L CSKE-LITKIT4-8-P CSKE-LITKIT4-8-L CSKE-LITKIT2-11-L CSKE-LITKIT3-11-L CSKE-LITKIT4-11-L CSKE-LITKIT2-11-P CSKE-LITKIT3-11-P CSKE-LITKIT4-11-P

3 Graphic Kits

30 Series Cable Signage Kit Illuminating

Illuminate your signs all night, without breaking your budget!




Complete Illuminating Graphic Kit

MATERIAL = Solid Brass (Fittings) 304 Grade Stainless Steel (Cable)

FINISH = Polished Chrome

- · Solid Brass universal fittings are hinged to allow for use in Wall-to-Wall, Wall-to-Floor and Floor-to-Ceiling applications
- For 8-1/2" x 11" and 11" x 17" graphics
- Illuminated


Hinged Fittings are adjustable:







Portrait (*P)



Each kit contains:

- 2 universal top and bottom fittings
- 2 cables 13' length 3mm thick (trimmable)
- 12 mounting screws & anchors
- 1 hex key
- 1 UL 12V power supply w/plug
- 1/8" thick clear acrylic graphic holders w/polished edges





	Part #	Graphic Size	A Reveal Dimensions (nominal)	B Overall Dimensions (nominal)	Total Wattage	Туре	Price
2	CSK-ILITKIT2-8-*	8-1/2" x 11"	8-1/4" x 10-1/4"	12-1/8" x 13-3/8"	1.8W		\$271.00
Graphic Kit	CSK-ILITKIT2-11-*	11" x 17"	10-3/8" x 16-3/8"	13-1/2" x 19-1/2"	3.6W		\$324.00
3	CSK-ILITKIT3-8-*	8-1/2" x 11"	8-1/4" x 10-1/4"	12-1/8" x 13-3/8"	1.8W	Portrait (*P)	\$348.00
Graphic Kit	CSK-ILITKIT3-11-*	11" x 17"	10-3/8" x 16-3/8"	13-1/2" x 19-1/2"	3.6W	Landscape (*L)	\$428.00
4	CSK-ILITKIT4-8-*	8-1/2" x 11"	8-1/4" x 10-1/4"	12-1/8" x 13-3/8"	1.8W		\$434.00
Graphic Kit	CSK-ILITKIT4-11-*	11" x 17"	10-3/8" x 16-3/8"	13-1/2" x 19-1/2"	3.6W		\$542.00

Lighting Specifications

Color	Cool White
Temperature	CW: 6100K
Lumens	CSK-CLB-8*: 186 CSK-CLB-11*: 93
Color Rendering Index	CW: 70
Rated Average Life	CW: 50,000 hrs.
Constant	Voltage
Chip Size	SMD 2835

4 Graphic Kits



Insert and remove graphic from top



Can be set to varying heights




U-Shaped Cut Out



Beveled edge creates outer glow illumination!

2 Graphic Kits 3 Graphic Kits



30 Series Cable Shelving

Shelf Hardware Sets

MATERIAL = Solid Brass (Fittings), 304 Grade Stainless Steel (Cable) FINISHES = Polished Chrome (*PC), Satin Chrome (*SC)

· Load Rating: 220 lbs. per cable





Includes:

Wall-to-Wall







6"or 8" Shelf Stabilizer (2)



Bottom Fixing (1)


Part # Description Price CSK-WWSH-6-* w/6" Shelf Stabilizer \$61.95 set CSK-WWSH-8-* w/8" Shelf Stabilizer \$61.95 set

Note: 2 Sets needed for single unit display

Wall-to-Floor







Note: 2 Sets needed for single unit display

Floor-to-Ceiling





Top Fixing (1)



13 Ft. Cable (1)



Bottom Fixing (1)

Price Part # **CSK-FC-*** \$47.25 set

Note: 4 Sets needed for

A Few Examples of the Many Possible Shelving Configurations:

Wall-to-Wall 1 CSK-WWSH-*/Shelf Hardware Set pg. S-11

2 CSK-ASH-11P/Acrylic Sign Holder pa. S-5 3 CSK-SSGC/Horizontal Sign Clamp pg. S-5 4 CSK-SHF-1212/Clear Acrylic Flat Shelf pg. S-12 5 CSK-SHF-1224/Clear Acrylic Flat Shelf pg. S-12 6 CSK-SSC-*/Horizontal Shelf Clamp

pg. S-12

Wall-to-Floor

1 CSK-WFSH-*/Shelf Hardware Set 2 CSK-SSC-*/Horizontal Shelf Clamp pg. S-12 3 CSK-DSC-*/Double Horizontal Shelf Clamp pg. S-12

4 CSK-SHF-1224/Clear Acrylic Flat Shelf

1 CSK-FC-*/Shelf Hardware Set pg. S-11 2 CSK-CUBE/Clear Acrylic Display Cube pg. S-12 3 CSK-FSHF-12/Clear Folded Acrylic Display Shelf pg. S-12


Floor-to-Ceiling

30 Series Cable Shelving

Acrylic Shelves

Clear Folded Acrylic Display Shelves with Polished Edges





Part #	Overall Size	Price				
CSK-FSHF-12	12"D x 12"L x 6"H	\$35.00 ea.				
CSK-FSHF-24	12"D x 24"L x 6"H	\$48.00 ea.				
*Nominal Size						



Clear Acrylic Display Cubes with Polished Edges





ACRYLIC

 Part #
 Overall Size
 Price

 CSK-CUBE
 12"W x 12"L x 12"D
 \$80.00 ea.

*Nominal Size



Clear Acrylic Flat Shelves with Polished Edges





Part #	Overall Size	Price
CSK-SHF-1212	12"W x 12"D	\$17.60 ea.
CSK-SHF-1224	24"W x 12"D	\$35.00 ea.
	*Nominal Size	

Shelf Clamps Sold Separately

Clear Acrylic Angled Shelves

with Polished Edges
ACRYLIC THICKNESS =







 Part #
 Overall Size
 Price

 CSK-ASHF-9
 9"W x 11-1/2"L x 1" Lip
 \$17.00 ea.

Works with CSK-ADJ-* Adjustable Sign/Shelf Clamp

30 Series Shelf Clamps


Horizontal Shelf Clamps

MATERIAL = Solid Brass

FINISHES = Polished Chrome (*PC), Satin Chrome (*SC)

- Works with material up to 5/16" thick
- Use 3mm Hex Key

Part #	Type	Price	
CSK-SSC-*	Single	\$5.35 ea.	
CSK-DSC-*	Double	\$7.60 ea.	



1800

Rotation

Adjustable Sign/Shelf Clamps

MATERIAL = Solid Brass

FINISHES = Polished Chrome (*PC), Satin Chrome (*SC)

- Rotates for sign or shelf applications
- Works with material up to 5/16" thick
- Use 3mm Hex Key


Part #	Price	
CSK-ADJ-*	\$8.25 ea.	

Undermount Shelf Support

MATERIAL = Solid Brass

FINISHES = Polished Chrome (*PC), Satin Chrome (*SC)

- Shelf support for use under drilled or slotted shelves
- Works with material up to 5/16" thick
- Hole Size: 5/16" 3/8" (8-10mm)
- Slot Size: 1/8" (3.5mm)



Optional Cable Display Accessories





1/4" nominal

LED MR16 Rod














- Works With Any 30 Series Cable System
- 180° Rotation of lamp holder
- Built in heat sink
- Energy efficient
- Adjustable
- MR16, 5W bulb included










Lighting Specifications

Temperature	WW: 2700K-3500K
Beam Spread	30°
Lumens	CW: 340 WW: 290
Color Rendering Index	WW: 75 CW: 80
Rated Average Life	CW/WW: 30,000-50,000 hrs.
Constant	Voltage
Chip Size	SMD2835

		Width	# Of LED	Total	Price	
Part #	Part # Color Temp		Chips	Wattage	Each	10+ Pcs.
CSK-MR16-100-WW	Warm White	5-7/8" to 7-7/8" 11-13/16" to 15-3/4"			\$12.00	\$9.95 ea.
CSK-MR16-100-CW	Cool White		4	514 /	\$12.00	\$9.95 ea.
CSK-MR16-200-WW	Warm White		4	5W	\$12.00	\$9.95 ea.
CSK-MR16-200-CW	Cool White				\$12.00	\$9.95 ea.





Power Supply (3A / 12V / 36W)

- 3.41" L x 2.31" W x 1.26" H
- 18AWG Output Cord: 6'
- Polarized 2 Prong Plug

LED-12V-3A Each: \$16.15 6+ Pcs.: \$14.70 ea.

Works with our Cable Display System, see pgs. S-11~12

Picture & Art Hanging Systems

Outwater's hanging systems allows you to easily add, reposition/remove art or wall objects without wall damage.

- Hanging & display solutions for residential & commercial use
- Easy to adjust and change artwork
- Eliminates wall repairs and repainting
- No tools needed
- Aluminum track load capacity: 110 lbs per length
- Nylon cable load capacity: 33 pounds per length
- Stainless cable load capacity: 44 pounds per length









2 Select Your Vertical Cables



3 Select Your Picture Hooks

New! Click Track


Versatile • Discreet • Easy to Install

The Click Track is secured to the wall using click buttons that conceal all fittings and wall anchors

Secure Click Buttons to Wall




Track Attaches to Click Buttons



Slide Fitting in to Track & Install End Cap




Wall Track in 2mm Cable For Art





Ver	rtical Cables	2		4		5	
	Part #	Description	Cable Material	Length	Price	Carton Qty.	Carton Price
1	GPX-T48-N	T-End Cable Work With Track: GPX-TK100-*	Nulan	48"	\$2.45 ea.	50	\$2.35 ea.
1	GPX-T120-N		Nylon	120"	\$4.25 ea.	50	\$4.05 ea.
1	GPX-T48-SS		Stainless	48"	\$2.55 ea.	50	\$2.45 ea.
1	GPX-T120-SS		Steel	120"	\$4.35 ea.	50	\$4.15 ea.
2	GPX-B48-SS	Ball End Cable	Stainless	48"	\$2.30 ea.	50	\$2.15 ea.
2	GPX-B120-SS	Work With Track: GPX-TK100-*	Steel	120"	\$4.45 ea.	50	\$4.15 ea.
3	GPX-V48-SS	V-End Cable Work With Track:	Stainless	48"	\$7.25 ea.	50	\$6.95 ea.
3	GPX-V120-SS	ALU851-*	Steel	120"	\$9.95 ea.	50	\$9.55 ea.
4	GPX-P48-N	P-End Cable	Nylon	48"	\$1.80 ea.	50	\$1.65 ea.
4	GPX-P120-N	Work With Tracks:	Nylon	120"	\$2.95 ea.	50	\$2.80 ea.
4	GPX-P48-SS	GPX-TK101-*,	Stainless	48"	\$1.90 ea.	50	\$1.75 ea.
4	GPX-P120-SS	GPX-TR102-* & ALU851-*	Steel	120"	\$3.10 ea.	50	\$2.95 ea.
5	GPX-H48-N	Hex End Cable	Nylon	48"	\$1.95 ea.	50	\$1.85 ea.
5	GPX-H120-N	Work With Track:	•	120"	\$2.85 ea.	50	\$2.65 ea.
5	GPX-H48-SS	GPX-TK100-*	Stainless	48"	\$2.10 ea.	50	\$1.95 ea.
5	GPX-H120-SS		Steel	120″	\$2.95 ea.	50	\$2.75 ea.




Trackless 2mm Cable Hanging System For Wall & Ceiling


Option 1: Stand Alone 2mm Cables 2. Standoff 1. Adjustable Cable Carton Ctn. Hinged **End Cable** Part # Material Length Price Qty. Price **Fitting Cable GPX-ADJ48-N** 48" \$4.20 ea. 50 \$3.95 ea. Mounts on Nylon GPX-ADJ120-N 120" \$4.95 ea. 50 \$4.60 ea. Mounts on Walls **GPX-ADJ48-SS** 48" \$4.45 ea. 50 \$4.15 ea. Walls & Ceilings Stainless Steel **GPX-ADJ120-SS** 120" \$5.50 ea. 50 \$4.80 ea. **GPX-STD48-N** 48" \$3.15 ea. \$3.00 ea. 50 Nylon GPX-STD120-N \$3.95 ea. \$3.80 ea. 120" 50 **GPX-STD48-SS** 48" \$3.25 ea. 50 \$3.10 ea. Stainless Steel 2 GPX-STD120-SS 120" \$4.05 ea. \$3.90 ea.





Trackless 2mm Cable Hanging System For Wall & Ceiling






Accessories For All Cables







Adjustable Cable Hook Sign Hanging Hardware

Locking Adjustable Cable Hook Kit w/Top Fitting

• Material:

304 Grade Stainless Steel Cable with Polished Chrome Steel Hook & Top Fitting

• Wire Gauge:

1.5mm



Field Cuttable to Any Length Mounting Screw Not Included Kit Includes: Toggle Option Available, Please Inquire TOP FITTING (Polished Chrome) Press/hold to release lock on cable 8 FT. / 15 FT. 3 ½" STEEL CABLE (1.5mm Thick) 5/8" Pull cable to adjust and level sian Spring gate prevents sign ADJUSTABLE from detaching Fits CABLE HOOK off hook (Polished Chrome 1/4" hole Description Each 25 Pcs. Part # FWH-8-PC 8 ft. Cable \$7.15 \$6.70 ea.

Locking Adjustable Cable Hook Kit w/2" Loop End

• Material:


304 Grade Stainless Steel Cable with Polished Chrome Steel Hook & Top Fitting

• Wire Gauge:

1.5mm







Part #	Description	Each	50 Pcs.
GSH-8	8 ft. Cable	\$3.55	\$3.40 ea.
GSH-15	15 ft. Cable	\$4.25	\$3.95 ea.

Double Loop Cables



FWH-15-PC 15 ft. Cable

\$7.95

7.50 ea.

	Part #	Length	Price	Carton Qty.	Carton Price
ĺ	LRF-CLP6-1	1′	\$1.92 ea.	25	\$1.82 ea.
	LRF-CLP6-18	18"	\$2.67 ea.	25	\$2.54 ea.
	LRF-CLP6-2	2′	\$3.42 ea.	25	\$3.25 ea.
	LRF-CLP6-3	3′	\$4.94 ea.	25	\$4.69 ea.
	LRF-CLP6-4	4′	\$6.45 ea.	25	\$6.13 ea.
	LRF-CLP6-6	6′	\$9.48 ea.	25	\$9.00 ea.



Apartment Hanger

HGHB-APT-*

- Material: Aluminum
- · No drill, easy to install
- Foam liner, so no damage to walls
- · Wall bracket holes drilled every inch
- Patented/Made in USA

The Hangman Apartment Hanger consists of two aluminum interlocking brackets modeled after the French Cleat featuring a built in level which ensures an accurate installation. The aircraft grade aluminum brackets will not corrode and can be used indoors or outdoors. The system uses small nails which leave pin size holes and a foam back to protect walls from scuffs and marks. Once installed it can be adjusted left or right.







		Load	(1) Mounting Bracket				
Part #	Size	Rating	#8 x 5/8" Screws	Nails	Each	30 Sets	50 Sets
HGHB-APT-6	6" Long	50 lbs.	2	5	\$3.97/st	\$3.61/st	\$3.29/st
HGHB-APT-12	12"Long	100 lbs.	3	14	\$6.22/st	\$5.66/st	\$5.16/st
HGHB-APT-18	18"Long	150 lbs.	5	20	\$8.69/st	\$7.91/st	\$7.22/st

.... I... de de contact

Heavy Duty Mirror & Picture Hanger

HGHB-HM-*

- Material: Aluminum
- · Wall bracket holes drilled every inch
- Brackets are angled to ensure a flush mount
- Patented/Made in USA

The Hangman Heavy Duty Mirror & Picture Hanger is our classic and best selling product. It consists of two aluminum interlocking brackets modeled after the French Cleat featuring a built in level which ensures an accurate installation. The aircraft grade aluminum brackets will not corrode and can be used indoors or outdoors on all surfaces. The system includes walldog anchorless fasteners.







		Load	Hardware Include (1) Mounting Brack				
Part #	Size	Rating	#8 x 5/8" Screws	Walldog Screws	Each	30 Sets	50 Sets
HGHB-HM-6	6" Long	75 lbs.	2	2	\$4.66/st	\$4.24/st	\$3.87/st
HGHB-HM-10	10" Long	100 lbs.	3	3	\$6.28/st	\$5.71/st	\$5.21/st
HGHB-HM-12	12"Long	100 lbs.	3	3	\$6.78/st	\$6.17/st	\$5.63/st
HGHB-HM-18	18" Long	200 lbs.	5	5	\$9.49/st	\$8.64/st	\$7.88/st
HGHB-HM-30	30" Long	300 lbs.	8	8	\$12.56/st	\$11.43/st	\$10.42/st
HGHB-HM-42	42" Long	300 lbs.	10	10	\$16.55/st	\$15.06/st	\$13.73/st



Professional French Cleat Hanger

HGHB-CBH-*

- Material: Aluminum
- Two piece system includes inset mounting bracket for a flush fit
- · Aircraft grade aluminum
- Patented/Made in USA

The Hangman Professional French Cleat Hanger is a variation of the Heavy Duty Hangman and has several unique features. The overlapping design of the mounting bracket provides high torque leverage for use in hanging cantilevered shelves. The wall track is punched every inch making it easy to hit at least one stud. In addition to hanging shelves, it works great on cabinets, mirrors, and other heavy wall déco.





		Load	Hardware Includes (1) Mounting Brack				
Part #	Size	Rating	#8 x 5/8" Screws	Walldog Screws	Each	30 Sets	50 Sets
HGHB-CBH-18	18" Long	200 lbs.	5	5	\$9.24/st	\$8.41/st	\$7.67/st
HGHB-CBH-30	30" Long	300 lbs.	8	8	\$13.46/st	\$12.25/st	\$11.17/st
HGHB-CBH-42	42" Lona	300 lbs.	10	10	\$17.47/st	\$15.90/st	\$14.50/st

Self Leveling Flushmount Hanger

HGHB-SCH-2

- Material: Aluminum
- · Inset for a flush fit
- · Aircraft grade aluminum
- Patented
- Works well with open back canvas

The Hangman Self Leveling Flushmount Hanger is a single piece hanger that attaches to the back of your canvas and hangs on the provided Bear Claw Hanger. The inset created allows the canvas to hang flush

against the wall. Ideal for unframed canvas art. Also works on wooden frames.





Hardware Includes:

- (2) #4 x 5/8" Screws
- (2) Double Headed Bear Claw Screws
- (2) Sawtooths

Part #	Size	Rating	Each	30 Sets	50 Sets	
HGHB-SCH-2	38 x 22 mm	20 lbs.	\$1.03/st	\$0.94/st	\$0.85/st	

Canvas Hanger

HGHB-CH-5

- Material: Aluminum
- · Brackets are angled to ensure a flush mount
- Patented/Made in USA

Hardware Includes:

- (2) #4 x 5/8" Screws
- (2) #8 x 1" Screws
- (1) Bubble Level
- (1) Mounting Bracket
- (1) Wall Bracket

The Hangman Canvas Hanger is a two piece bracket system that hangs giclees, gallery wraps, canvas or open back frames flush to the wall.

The wall track includes a bubble level for an accurate installation.





Part #	Size	Rating	Each	30 Sets	50 Sets
HGHB-CH-5	5" Long	20 lbs.	\$2.73/st	\$2.48/st	\$2.27/st



Aluminum Frame Hanger


HGHB-ALH-5

- Material: Aluminum
- Offset almost flush
- · Single piece wall hanger

Hardware Includes:

- (2) Walldog Screws
- (1) Bubble Level
- (1) Frame Hanger

The Hangman Aluminum Frame Hanger is a one bracket system that is designed to hook into standard aluminum frames or specially designed wooden frames with an undercut. The track includes a bubble level and anchorless Walldog fasteners for a fast and accurate installation.



Z-Hanger

HGZ-6948-* Z-Hanger HGZL-6986-* Z-Lite Hanger

- Material: Aluminum
- Load Rating: 100 lbs. per ft. (HGZ-6948-*) 60 lbs. per ft. (HGZL-6986-*)
- Offset .22" (5.6 mm)
- Alternating holes every 1" (3/16" dia. & 1/4" dia.)
- Sold as pairs, including:
 1" walldog screws & 5/8" bear claw screws
- *HGZL-6986-**: Slight flexibility allows for easier engagement on non-plumb walls
- Sold in full cases only, where indicated (■)

The Hangman Z-Hanger consists of two aluminum interlocking brackets modeled after the French Cleat. The aircraft grade aluminum brackets will not corrode and can be used indoors or outdoors on all surfaces. The system is compatible with various fasteners, and can be adjusted left or right. Hangman's unique Z-Hanger comes with alternating holes punched every inch.





			<u>Hardware Includes</u> : (1) Wall Bracket,					
		Load	(1) Mountii	ng Bracket,	Case			
Part #	Size	Rating	#8 x 5/8" Screws	Walldog Screws	Quantity	Each	30 Sets	50 Sets
HGZ-6948-18	18"Long	120 lbs./ft.	5	5	-	\$5.82/st	\$5.29/st	\$4.83/st
HGZ-6948-30	30"Long	120 lbs./ft.	8	8	-	\$8.65/st	\$7.87/st	\$7.18/st
						1-5 Cases	6-10 Cases	10+ Cases
HGZ-6948-18-12	18"Long	120 lbs./ft.	Hardware N	ot Included	6 sets	\$69.59/bx	\$63.33/bx	\$57.76/bx
HGZ-6948-30-12	30"Long	120 lbs./ft.	Hardware Not Included		6 sets	\$105.42/bx	\$95.93/bx	\$87.50/bx
HGZL-6986-18-12	18" Long	60 lbs./ft.	Hardware Not Included		6 sets	\$40.11/bx	\$36.50/bx	\$33.29/bx
HGZL-6986-30-12	30"Long	60 lbs./ft.	Hardware N	ot Included	6 sets	\$56.45/bx	\$51.37/bx	\$46.85/bx

Z-Man Mounting Bracket

HGZM-6318-*

- Material: Aluminum
- Slight flexibility allows for easier engagement on non-plumb walls
- Aircraft grade aluminum
- Alternating holes every 1" (3/16" dia. & 1/4" dia.)
- Easily cuttable with a carbide tip saw
- Load Rating: 60 lbs. per ft.
- Sold in full cases only, 6 sets/case



Part #	Size	Load Rating	Case Quantity	1-5 Cases	6-10 Cases	10+ Cases
HGZM-6318-18-12	18" Long	60 lbs./ft.	6 sets	\$46.03/bx	\$41.89/bx	\$38.21/bx
HGZM-6318-30-12	30" Long	60 lbs./ft.	6 sets	\$64.68/bx	\$58.86/bx	\$53.38/bx

Machine Thread Double-Headed Screw

HGSCR-MT-*

- Material: Steel
- #10-24 x 2-1/4" Long
- · Machine screw threading
- Double-headed hanging surface
- Load Rating: 100 lbs.
- Works w/Toggler TA-1013 snap-toggle
- · Sold in full cases only

	Case	1-5	6-10	10+
Part #	Quantity	Cases	Cases	Cases
HGSCR-MT-10P	10 pcs.	\$4.83/bx	\$4.40/bx	\$4.01/bx
HGSCR-MT-100	100 pcs.	\$44.10/bx	\$40.13/bx	\$36.60/bx
HGSCR-MT-1000	1000 ncs	\$357.00/hx	\$324.87/hx	\$296.31/hy



HGSCR-WDS-*

- Material: Steel
- 1-1/4" Screws
- #8 Pan head
- Hi-Lo thread, 1/4" bore hole
- Load Rating: 60 lbs. sheer, 40 lbs. tension in drywall
- · Sold in full cases only



The Hangman Walldog Screws are an all steel, one piece, threaded fastener, which is used to fasten various fixtures directly to drywall. Walldog fasteners are fast. Unlike conventional screw anchors, which require the secondary step of threading a sheet metal screw into an anchor, the Walldog is installed directly through the fixture into the drywall.

		Case	1-5	6-10	10+
	Part #	Quantity	Cases	Cases	Cases
	HGSCR-WDS-100	100 pcs.	\$23.10/bx	\$21.02/bx	\$19.17/bx
	HGSCR-WDS-1000	1000 pcs	\$189 00/bx	\$171 99/hx	\$156.87/bx

Walldog Safety Hanger

HGSH-WDH-*

- Material: Aluminum
- · Aircraft grade aluminum
- Security lip prevents wire from slipping out
- 8 wide pivot point prevents frames from slipping
- Patented/Made in USA

The Hangman Walldog Safety Hanger is an extruded aluminum track that has a security lip to prevent picture hanging wire from slipping out. The wire is easy to insert and won't come out if bumped. The brackets are installed using anchorless Walldog fasteners that require no drilling and no stud. Friction bumpers included to keep walls clean and keep art from shifting.



		Load				
Part #	Length	Rating	Hardware Includes:	Each	30 Sets	50 Sets
HGSH-WDH-40	1-1/2"	40 lbs.	(1) Walldog, (1) Pair Bumper, (1) Hanger	\$1.66/st	\$1.51/st	\$1.38/st
HGSH-WDH-80	3"	80 lbs.	(2) Walldogs, (1) Pair Bumper, (1) Hanger	\$2.18/st	\$1.99/st	\$1.81/st

Bear Claw Hanger


HGSCR-*

- Material: Steel
- Self-drilling tip, no pilot hole required
- Works with D-rings, wire, keyhole & sawtooths
- Load Rating: 30 lbs. drywall, 100 lbs. stud
- Sold in full cases only

The Hangman Black Bear Claw Hangers work with D-rings, wire, sawtooths and keyholes for simple mirror and picture hanging solutions. Installs with a hand-held Phillips screwdriver. Self-drilling tip for easy installation.



				Case	1-5	6-10	10+
	Part #	Length	Description	Quantity	Cases	Cases	Cases
	HGSCR-BCD-10P		Black Oxide	10 pcs.	\$1.97/bx	\$1.80/bx	\$1.64/bx
Α	HGSCR-BCD-100	#8 x 1-1/4"		100 pcs.	\$17.64/bx	\$16.05/bx	\$14.64/bx
	HGSCR-BCD-1000			1000 pcs.	\$136.92/bx	\$124.60/bx	\$113.64/bx
	HGSCR-BCK-10P	#8 x 1"	Zinc Plated	10 pcs.	\$1.64/bx	\$1.49/bx	\$1.36/bx
В	HGSCR-BCK-100			100 pcs.	\$14.28/bx	\$12.99/bx	\$11.85/bx
	HGSCR-BCK-1000			1000 pcs.	\$115.92/bx	\$105.49/bx	\$96.21/bx
	HGSCR-BCO-10P		Special Outdoor	10 pcs.	\$6.20/bx	\$5.64/bx	\$5.14/bx
C	HGSCR-BCO-100	#8 x 1-5/8"		100 pcs.	\$58.80/bx	\$53.51/bx	\$48.80/bx
	HGSCR-BCO-1000		Coating	1000 pcs.	\$455.70/bx	\$414.69/bx	\$378.23/bx
	HGSCR-KH-10P		25" Hood	10 pcs.	\$1.64/bx	\$1.49/bx	\$1.36/bx
D	HGSCR-KH-100	#8 x 1"	.25" Head Size	100 pcs.	\$14.28/bx	\$12.99/bx	\$11.85/bx
	HGSCR-KH-1000			1000 pcs.	\$115.92/bx	\$105.49/bx	\$96.21/bx





Christmas Light Hangers

HGSH-QH-*

- Material: Stainless Steel
- Screws have an open loop (5/32" opening)
- Load Rating: 100 lbs. in wood beam or stud
- · Sold in full cases only

The Hangman Christmas Light Hangers are an all year outdoor stainless steel wire holder. A simple way to hang holiday lights, bird feeders, bird houses, wind chimes, etc. Installs easily and is wind and weather resistant with a lifetime warranty. These are made to last.

Part #	Size	Case Quantity	1-5 Cases	6-10 Cases	10+ Cases
HGSH-QH-12	38 x 22 mm	12 pcs.	\$6.26/bx	\$5.69/bx	\$5.19/bx
HGSH-QH-20		20 pcs.	\$10.23/bx	\$9.31/bx	\$8.49/bx



Elephant Hook Ceiling Hook

- Material: Steel
- Weather resistant coating
- Swivels & locks
- Load Rating: Holds 20 lbs. in drywall, 100 lbs. in wood

Hardware Includes:

- (1) Elephant hook
- (1) #8 x 1-1/4" Double-headed screw
- (1) Snap skru

Part #	Finish	Each	30 Sets	50 Sets
HGH-EHO-B	Bronze	\$4.77/st	\$4.37/st	\$3.96/st
HGH-EHO-N	Nickel	\$4.77/st	\$4.37/st	\$3.96/st
HGH-EHO-W	White	\$4.77/st	\$4.37/st	\$3.96/st

Elegant and easy, the Elephant Hook ceiling hook installs in under a minute. No drilling or pilot hole necessary. Simply screw in the self-drilling double-headed Bear Claw Hanger. Snap the Elephant Hook in place over the exposed collar. Swivel to desired angle and allow the weight of your item to lock into place. Comes in three finishes to match decor. For use indoor or outdoors, holds 100 lbs. in wood, 20 lbs. in drywall.



Push and hang. Absolutely the simplest and easiest to use picture hanger on the planet! Simply push into



Push and Hang

HGSH-PSH-*

- Material: Steel Plating
- Pushed directly into drywall
- · Creates an easy hanging surface
- · Sold in full cases only

		Load	Case	1-5	6-10	10+
Part #	Size	Rating	Quantity	Cases	Cases	Cases
HGSH-PSH-S-100	9 x 26 mm	10 lbs.	100 pcs.	\$39.48/bx	\$35.93/bx	\$32.77/bx
HGSH-PSH-S-1000			1000 pcs.	\$294.00/bx	\$267.54/bx	\$244.02/bx
HGSH-PSH-L-100	16 x 35.5 mm	20 lbs.	100 pcs.	\$45.78/bx	\$41.66/bx	\$38.00/bx
HGSH-PSH-L-1000			1000 pcs.	\$336.00/bx	\$305.76/bx	\$278.88/bx

drywall, no tools needed.



New HANGMAN' WHOLESALER

Furniture Anti-Tip Kit

HGA-TK-400

- Material: Steel
- · Aircraft grade steel cables
- Secures dressers, curio cabinet, chests and entertainment centers
- Load Rating: 400 lbs.
- · Also available for leaner mirrors

Hardware Includes:

- (2) #8 x 5/8" Screws
- (2) #8 x 1-1/2" Screws
- (2) Steel Brackets
- (2) Clevis Pins
- (2) Hair Pins
- (1) 6" Stainless Steel Cable

The Hangman Furniture Anti-Tip Kit consists of an aircraft grade steel cable that connects on one end to your furniture with a bracket installed into a stud on the wall. The cable prevents the furniture from tipping over. This kit is a leader in furniture safety.





Part #	Each	30 Sets	50 Sets
HGA-TK-400	\$3.70/st	\$3.36/st	\$3.07/st

Here's How It Works

No Stud TV Hanger

HGA-S2040-A

- Material: Aluminum
- Built-in level
- Hangs 26" 55" flat screen TV's
- 1" Clearance from the wall
- · No stud, no anchors required
- Won't damage walls, installs with tiny picture hanging nails
- Installs in 10 minutes
- Security cable included
- · Black anodized finish
- UL rated to hold 80 lbs.
- Easy tilt for access to cables
- Only tools required are a hammer and a screwdriver
- Bracket length is 18"

Hardware Includes:

- (1) 18"TV mount bracket
- (1) 18" wall bracket
- Hardware

The Hangman No Stud TV Hanger will hang any LED thin screen TV in less time than it takes to unpack it. Consists of two 18" interlocking aircraft-grade aluminum brackets. One bracket attaches to the back of the TV and the other bracket installs on the wall. Once installed a 1" clearance from the wall provides easy access and space for cords and cables. The wall track has a foam backing to minimize wall damage. Once removed all that is left behind are tiny pinholes that can be easily covered up. Comes in Black Anodize Finish. Patented & UL Rated.





Part #
 Each
 30 Sets
 50 Sets

 HGA-S2040-A
 \$22.79/st
 \$20.73/st
 \$18.91/st



Gallery Track

HGGS-GT-*

- Material: Aluminum
- Paintable

The Hangman Gallery Track is a part of Hangman's new gallery track system. They are a professional system that can be used at home or the office. Enjoy the ease of changing frames whenever you desire without damaging your walls. Available in 2', 3', 4', 6' and 8' lengths.





		Hardware Includes:			
Part #	Length	(1) Connector, (1) Pair of End Caps, +	Each	30 Sets	50 Sets
HGGS-GT-24	24"	(2) #8 x 1-1/2" Screws, (2) Anchors, (2) Sliders	\$14.24/st	\$12.96/st	\$11.82/st
HGGS-GT-36	36"	(2) #8 x 1-1/2" Screws, (2) Anchors, (3) Sliders	\$19.82/st	\$18.04/st	\$16.45/st
HGGS-GT-48	48"	(3) #8 x 1-1/2" Screws, (3) Anchors, (4) Sliders	\$25.75/st	\$23.43/st	\$21.37/st
HGGS-GT-72	72"	(3) #8 x 1-1/2" Screws, (3) Anchors, (6) Sliders	\$35.99/st	\$32.75/st	\$29.88/st
HGGS-GT-96	96"	(3) #8 x 1-1/2" Screws, (3) Anchors, (8) Sliders	\$47.88/st	\$43.57/st	\$39.74/st



Accessories for Gallery Track

GALLERY HOOKS

- Material: Chrome Plated Zinc
- Tension hooks grip when pulled down
- Push button to move upwards



Each | \$4.58 ea. **60 Pcs.** | \$4.17 ea. **100 Pcs.** | \$3.80 ea.





GALLERY WIRE

- Material: Chrome Plated Zinc
- High Grade Wire
- Works only with our gallery track
- · Can be coiled to control length
- Available in 6' and 8' lengths

HGGS-GT-6W

6 ft. Length Each | \$1.87 ea. 60 Pcs. | \$1.70 ea. 100 Pcs. | \$1.55 ea.

HGGS-GT-8W

8 ft. Length Each | \$2.50 ea. 60 Pcs. | \$2.27 ea. 100 Pcs. | \$2.07 ea.

GALLERY HANGING BRACKET

- Material: Chrome Plated Zinc
- Works only with our gallery track
- Slides left or right for positioning
- Holds our gallery track cables

HGGS-GT-SL

Each | \$1.03 ea. **60 Pcs.** | \$0.94 ea. **100 Pcs.** | \$0.85 ea.



GALLERY TRACK CONNECTOR

- Material: Chrome Plated Zinc
- Makes aligning tracks easy

HGGS-GT-C Each | \$0.63 ea. 60 Pcs. | \$0.57 ea. 100 Pcs. | \$0.52 ea.

GALLERY TRACK END CAPS

- Material: Plastic
- Gives a finished look


HGGS-GT-EC

Each | \$0.88 ea. **60 Pcs.** | \$0.80 ea. **100 Pcs.** | \$0.73 ea.



Z-Panel Hangers & Clips

"A FAST, EASY & COST EFFECTIVE METHOD OF HANGING CABINETS, WALL PANELS, PARTITIONS & SIGNAGE!"









0.673

Projection: 0.198'

Lift-Off: .673"

Attaches to Cabinet

Part #

ALU211-4

AIII211 0

ALUHA4049-8-MH

Part #

AL


HOLES & SPACING:

- Pre-cut pieces:
 - 1-1/2" distance (except where noted)
- 4 ft., 8 ft. & 12 ft. Lengths:

8" on center

Note: All holes are 3/16" diameter and accommodate #10 screws.

For our Acrylic Z & W Bar, Please Inquire



Pre-Cut with 2 Punched Holes Part # **ALU111-2**

	Length	TOU PCS.	500 + PCS.
-M	1.5 in.	\$0.42 ea.	\$0.39 ea.
		Lauratha	



Pre-Cut with 2 Punched Holes Length

4 ft. & 8 ft. Lengths

2 in.


ALU112-2-M

100 Pcs.

\$0.49 ea.


500 + Pcs.

\$0.45 ea.



<u> </u>	
Projection: 0.250"	
lift-Off: 360"	

4 ft. & 8 ft. Lengths				
	without Ho	oles		
Part #	Length	120 Ft.	600+ Ft.	
ALU333-4-M	4 ft.	\$0.86'	\$0.77'	
ALU333-8-M	8 ft.	\$0.86'	\$0.77'	
witl	h Punched	Holes		
Part #	Length	120 Ft.	600+ Ft.	
ALU333-4-MH	4 ft.	\$1.09'	\$0.99'	
ALU333-8-MH	8 ft.	\$1.09'	\$0.99'	
ALU333-8-MH	8 ft.	\$1.09'	\$0.99'	



Part #	Length	120 Ft.	600+ Ft.				
	without	Holes					
4 ft. & 8 ft. Lengths							
.U211-2-M	2 in.	\$0.70 ea.	\$0.61 ea				

\$1.56

¢1 56'

Length 100 Pcs.

500 + Pcs.

\$1.30'


¢1 201

Pre-Cut with 2 Punched Holes

ALU211-0	oit.	31.30	\$ 1.5U				
with Punched Holes							
Part #	Length	120 Ft.	600+ Ft.				
ALU211-4H	4 ft.	\$1.77'	\$1.48'				
ALU211-8H	8 ft.	\$1.77'	\$1.48'				

4 ft.


0 f+



4 0.125

0.750

without Holes					
Part #	Length	120 Ft.	600+ Ft.		
ALU112-4	4 ft.	\$1.35'	\$1.14'		
ALU112-8	8 ft.	\$1.35'	\$1.14'		
wi	th Punche	d Holes			
Part #	Length	120 Ft.	600+ Ft.		
ALU112-4H	4 ft.	\$1.57'	\$1.32'		
ALU112-8H	8 ft.	\$1.57'	\$1.32'		



	- 1	1	0.230
Proi	iectio	n: 0	.240"
	Off.		

Pre-Cut with 2 Punched Holes (1-3/4" Distance)					
Part #	Length	100 Pcs.	500 + Pcs.		
ALUHA4049-25-M	2.5 in.	\$1.00 ea.	\$0.90 ea.		

4 ft. & 8 ft. Lengths

without Holes					
Part # Length 120 Ft. 600+ Ft.					
ALUHA4049-4-M	4 ft.	\$2.24'	\$1.88'		
ALUHA4049-8-M	8 ft.	\$2.24'	\$1.88'		
with Punched Holes					
Part # Length 120 Ft. 600+ Ft.					
ALUHA4049-4-MH	4 ft.	\$2.45'	\$2.06'		


8 ft.

\$2.45

120 Ft.

\$2.06

600+ Ft.



12 ft. Lengths					
w	without Holes				
Part #	Length	120 Ft.	600+ Ft.		
ALUHAC22-M	12 ft.	\$2.23'	\$1.96'		
with Punched Holes					
Part #	Length	120 Ft.	600+ Ft.		
ALUHAC22-MH	12 ft.	\$2.47'	\$2.15'		

Pre-Cut with 2 Punched Holes

Length 100 Pcs. 500 + Pcs.

\$1.13 ea. \$1.00 ea.

\uparrow	.800	
1.449 	• ↓ 	
	.580	

Projection: 0.250	
Lift-Off: .440"	


Pre-Cut with 2 Punched Holes (1-3/4" Distance					
Part #	Length	100 Pcs.	500 + Pcs.		
ALUS4049-25-M	2.5 in.	\$0.70 ea.	\$0.63 ea.		

4 ft. & 8 ft. Lengths without Holes

Lenath

with Punched Holes						
ALUS4049-8-M	8 ft.	\$1.74′	\$1.46′			
ALUS4049-4-M	4 ft.	\$1.74'	\$1.46'			

with			
Part #	Part # Length 120 F		
ALUS4049-4-MH	4 ft.	\$1.96'	\$1.64'
ALUS4049-8-MH	8 ft.	\$1.96′	\$1.64′



Pre-Cut with 2 Punched Holes Length 100 Pcs. Part # 500 + Pcs. ALUHAC23-2-M 2 in. \$1.08 ea. \$0.98 ea.

12 ft. Lengths						
without Holes						
Part # Length 120 Ft. 600+ Ft.						
ALUHAC23-M	12 ft.	\$1.89'	\$1.66'			
with Punched Holes						
Part # Length 120 Ft. 600+ Ft.						
ALUHAC23-MH	12 ft.	\$2.06'	\$1.85'			

Bubble Level

Acrylic bubble level used for leveling our panel clips, or any other horizontal surface. 9/16"W x 1-9/16"L



For any quantities less than 120 ft. add 15% to the 120 ft. price For any quantities less than 100 pieces add 15% to the 100 piece price

Easy Fasten Standoffs


Eco Lite Series

MATERIAL = 202 Stainless Steel **FINISH** = Brushed Stainless (**BSS**)



- Lightweight construction
- #6 flat head screws and drywall anchors included

















Part #	Panel Thickness	Barrel Length	Thread Length	Diameter	Price
■ STDE-1313-BSS	Up to 3/8"	1/2"	1/2"	1/2"	\$0.69 ea.
■ STDE-1324-BSS	Up to 1/2"	3/4"	3/4"	1/2"	\$0.77 ea.
■ STDE-1332-BSS	Up to 1/2"	1″	3/4"	1/2"	\$0.85 ea.
STDE-1348-BSS	Up to 1/2"	1-1/2"	3/4"	1/2"	\$0.93 ea.
■STDE-1364-BSS	Up to 1/2"	2"	3/4"	1/2"	\$1.01 ea.
■ STDE-1396-BSS	Up to 1/2"	3"	3/4"	1/2"	\$1.15 ea.
STDE-13128-BSS	Up to 1/2"	4"	3/4"	1/2"	\$1.36 ea.
STDE-2024-BSS	Up to 1/2"	3/4"	3/4"	5/8"	\$0.90 ea.
STDE-2032-BSS	Up to 1/2"	1″	3/4"	5/8"	\$0.98 ea.
STDE-2048-BSS	Up to 1/2"	1-1/2"	3/4"	5/8"	\$1.19 ea.
STDE-2064-BSS	Up to 1/2"	2"	3/4"	5/8"	\$1.28 ea.
STDE-2096-BSS	Up to 1/2"	3"	3/4"	5/8"	\$1.58 ea.
STDE-20128-BSS	Up to 1/2"	4"	3/4"	5/8"	\$1.77 ea.
STDE-2424-BSS	Up to 1/2"	3/4"	3/4"	3/4"	\$1.21 ea.
STDE-2432-BSS	Up to 1/2"	1″	3/4"	3/4"	\$1.56 ea.
STDE-2448-BSS	Up to 1/2"	1-1/2"	3/4"	3/4"	\$1.76 ea.
STDE-2464-BSS	Up to 1/2"	2"	3/4"	3/4"	\$1.94 ea.
STDE-2496-BSS	Up to 1/2"	3″	3/4"	3/4"	\$2.43 ea.
STDE-24128-BSS	Up to 1/2"	4"	3/4"	3/4"	\$2.81 ea.

Easy mounting design

	Panel	Barrel	Thread		
Part #	Thickness	Length	Length	Diameter	Price
STDE-3224-BSS	Up to 1/2"	3/4"	3/4"	1″	\$1.77 ea.
STDE-3232-BSS	Up to 1/2"	1"	3/4"	1"	\$2.21 ea.
STDE-3248-BSS	Up to 1/2"	1-1/2"	3/4"	1"	\$2.43 ea.
STDE-3264-BSS	Up to 1/2"	2"	3/4"	1"	\$2.65 ea.
STDE-3296-BSS	Up to 1/2"	3"	3/4"	1"	\$3.20 ea.
STDE-32128-BSS	Up to 1/2"	4"	3/4"	1"	\$3.65 ea.
STDE-32192-BSS	Up to 1/2"	6"	3/4"	1"	\$4.41 ea.
STDE-4024-BSS	Up to 5/8"	3/4"	3/4"	1-1/4"	\$2.56 ea.
STDE-4032-BSS	Up to 5/8"	1″	3/4"	1-1/4"	\$2.68 ea.
STDE-4048-BSS	Up to 5/8"	1-1/2"	3/4"	1-1/4"	\$3.22 ea.
STDE-4064-BSS	Up to 5/8"	2"	3/4"	1-1/4"	\$3.55 ea.
STDE-4096-BSS	Up to 5/8"	3"	3/4"	1-1/4"	\$4.64 ea.
STDE-40128-BSS	Up to 5/8"	4"	3/4"	1-1/4"	\$5.54 ea.
STDE-40192-BSS	Up to 5/8"	6"	3/4"	1-1/4"	\$6.84 ea.
STDE-4824-BSS	Up to 5/8"	3/4"	3/4"	1-1/2"	\$3.01 ea.
STDE-4832-BSS	Up to 5/8"	1″	3/4"	1-1/2"	\$3.34 ea.
STDE-4848-BSS	Up to 5/8"	1-1/2"	3/4"	1-1/2"	\$4.02 ea.
STDE-4864-BSS	Up to 5/8"	2"	3/4"	1-1/2"	\$4.58 ea.
STDE-4896-BSS	Up to 5/8"	3″	3/4"	1-1/2"	\$5.90 ea.
STDE-48128-BSS	Up to 5/8"	4"	3/4"	1-1/2"	\$6.91 ea.
STDE-48192-BSS	Up to 5/8"	6"	3/4"	1-1/2"	\$9.22 ea.

Clear Acrylic Transparent Standoffs






MATERIAL = Acrylic FINISH = Clear (CL)

- 2 Part Assembly
- Lightweight, durable construction
- Transparent acrylic
- #6 flat head screws and drywall anchors included





Please Inquire for our wall anchor selections







Part #	Panel Thickness		Thread Length	Diameter	Price
STDY-2424-CL	Up to 5/16"	3/4"	5/8"	3/4"	\$1.94 ea.
STDY-2432-CL	Up to 1/2"	1"	7/8"	3/4"	\$2.05 ea.
STDY-3232-CL	Up to 1/2"	1″	7/8"	1″	\$2.83 ea.

Tamper Proof Standoffs



Eco Lock Series

MATERIAL = 201 Stainless Steel **FINISHES** = Polished Stainless (*PSS), Brushed Stainless (*BSS)

- 2 Part Assembly
- Medium weight construction
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included



Barrel

Length







Barrel Thread Length Length Diameter Thickness Part # Price STDE-TM1313-* Up to 1/2' 1/2" 1/2" \$1.81 ea. STDE-TM1324-* Up to 1/2" 3/4" 1/2" \$1.93 ea. 3/4 **STDE-TM1332-*** Up to 3/4" 1/2" \$2.08 ea. STDE-TM2024-* Up to 1/2" 3/4" 5/8" \$2.31 ea. STDE-TM2032-* Up to 3/4" \$2.49 ea. 5/8" STDE-TM2424-* Up to 1/2" 3/4" 3/4" \$2.38 ea. **STDE-TM2432-*** Up to 3/4" 3/4" \$2.66 ea. **STDE-TM2448-*** Up to 3/4" 1-1/2" 3/4" \$3.17 ea. **STDE-TM2464-*** Up to 3/4" 3/4" \$2.48 ea.



	Panel	Barrel	Thread		
Part #	Thickness	Length	Length	Diameter	Price
STDE-TM3224-*	Up to 1/2"	3/4"	1″	1″	\$3.30 ea.
STDE-TM3232-*	Up to 3/4"	1"	1″	1"	\$3.58 ea.
STDE-TM3248-*	Up to 3/4"	1-1/2"	1″	1″	\$4.40 ea.
STDE-TM3264-*	-TM3264-* Up to 3/4"		1"	1"	\$5.59 ea.
STDE-TM4024-*	4024-* Up to 1/2"	3/4"	1″	1-1/4"	\$4.79 ea.
STDE-TM4032-*	Up to 3/4"	1"	1"	1-1/4"	\$5.20 ea.
STDE-TM4048-*	Up to 3/4"	1-1/2"	1″	1-1/4"	\$6.21 ea.
STDE-TM4064-*	Up to 3/4"	2"	1″	1-1/4"	\$6.80 ea.

Need Extra Hex Keys? 2 mm Hex Key

STD-ALANKEY-2 \$0.37 ea.

Easy Fasten Standoffs

Eco Solid Barrels

MATERIAL = 201 Stainless Steel **FINISH** = Brushed Stainless

- Must be used with 1" diameter "ECO Lock Series" standoffs STDE-TM32*
- 2 Part Assembly

Part #

STDE-32BAR-1

STDE-64BAR-1

STDE-96BAR-1

STDE-32BAR-2

STDE-64BAR-2

STDE-96BAR-2

- Medium weight construction
- Ideal for layering signage designs

Panel

Thickness

Up to 3/4"

Up to 3/4"

Up to 3/4"

Up to 1"

Up to 1"

Up to 1"

Barrel

Length

3"

1"

2"

1-1/2"



Barrel		
Length	Diameter	Price
1"	1″	\$1.67 ea.
1"	1"	\$2.33 ea.
1"	1″	\$2.95 ea.
1-1/2"	1"	\$1.82 ea.
1-1/2"	1″	\$2.48 ea.

\$3.10 ea.



Easy Fasten Standoffs



Eco Aluminum Standoffs



New 1-1/2" & 2" Barrel Length

MATERIAL = Aluminum

FINISHES = Cherry Red (*RD), Purple (*PL), Rosy Pink (*RP), Steel Grey (*SG), Champagne Brown (*BR), Copper (*CP), Blue (*BL), Black (*BK), Gold (*GD), Green (*GN), Silver (*SL)

- 2 Part Assembly
- · Lightweight, durable aluminum construction
- #6 flat head screws and drywall anchors included





Finishes:



	Panel	Barrel	Thread	Thread		
Part #	Thickness	Length	Length	Size	Diameter	Price
STDE-A1313-*	Up to 1/4"	1/2"	1/2"	M8	1/2"	\$1.97 ea.
STDE-A1324-*	Up to 1/2"	3/4"	3/4"	M8	1/2"	\$2.08 ea.
STDE-A2424-*	Up to 1/2"	3/4"	3/4"	M10	3/4"	\$2.77 ea.
STDE-A2432-*	Up to 5/8"	1"	1"	M10	3/4"	\$2.98 ea.

	Panei	Barrei	inread	inread		
Part #	Thickness	Length	Length	Size	Diameter	Price
STDE-A3224-*	Up to 1/2"	3/4"	3/4"	M10	1″	\$3.91 ea.
STDE-A3232-*	Up to 5/8"	1"	1"	M10	1"	\$4.12 ea.
STDE-A3248-*	Up to 3/4"	1-1/2"	1"	M10	1"	\$4.82 ea.
STDE-A3264-*	Up to 3/4"	2"	1"	M10	1"	\$5.40 ea.



Euro Square Standoffs



MATERIAL = Solid Carbon Steel or Aluminum

FINISHES = Polished Chrome (**PC**), Matte Chrome (**MC**), Aluminum (ALU)

- 2 Part Assembly
- Heavyweight, durable steel construction
- Modern look complements any design
- #6 flat head screws and drywall anchors included





Panel

Thickness

Up to 1/2"

Up to 1/2"

Barrel

Length

3/4'

3/4

Thread

Length

3/4"

3/4

Cap Size

3/4" sq.

 $3/4'' \, \text{sq.}$

Price

\$10.54 ea.

\$10.57 ea.





Part #

STD-SQ2424-PC

STD-SQ2424-MC



_ Сар: 1/8"

Diameter

Barrel Length

Thread: M8

Easy Fasten Standoffs

Euro Mini Series

MATERIAL = Solid Carbon Steel **FINISHES** = Polished Chrome (**PC**), Matte Chrome (MC)

- 2 Part Assembly
- · Lightweight, durable steel construction
- Euro Style
- #6 flat head screws and drywall anchors included

Finishes:








	Panel	Barrel	Thread		
Part #	Thickness	Length	Length	Diameter	Price
STD-1313-PC	Up to 3/16"	1/2"	5/16"	1/2"	\$2.64 ea.
STD-1313-MC	Up to 3/16"	1/2"	5/16"	1/2"	\$2.69 ea.
STD-1319-PC	Up to 5/16"	3/4"	1/2"	1/2"	\$3.32 ea.
STD-1319-MC	Up to 5/16"	3/4"	1/2"	1/2"	\$3.35 ea.



Euro Aluminum Standoffs






• #6 flat head screws and drywall anchors included







Part #	Panel Thickness	Barrel Length	Diameter	Price
STD-MH3264-SII	Un to 1"	2"	1"	\$6.27 ea

Secure Fasten Standoffs



Cone Topped Standoffs

MATERIAL = Carbon Steel **FINISH** = Polished Chrome (**PC**)

- 2 Part Assembly
- · Medium weight, durable steel construction
- · Modern look complements any design
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included





STD-C2424-PC Up to 3/8"

STD-C2432-PC Up to 1/2"

STD-C2464-PC Up to 3/4"

STD-C24128-PC Up to 1"






Thickness




















Chrome





Need Extra Hex Keys? 2.5mm Hex Key

Secure Fasten Standoffs

Premium Steel Series

for indoor use only

MATERIAL = Solid Carbon Steel **FINISHES** = Polished Chrome (*PC), Matte Chrome (*MC), Black Nickel (*BN), Bright Brass (*BB), Brushed Stainless (*BSS), Satin Copper (*SC), Oil Rubbed Bronze (*ORB)

- 3 Part Assembly
- Medium weight construction
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included







Finishes:













See page S-46 for Caps

(PC)	(MC)	(BN)	(BB)	(BSS)	(SC)	(ORB)
Polished	Matte	Black	Bright	Brushed	Satin	Oil Rubbed
Chrome	Chrome	Nickel	Brass	Stainless	Copper	Bronze

Part #	Panel Thickness	Barrel Length	Thread Length	Diameter	Finish	Price	Part #	Panel Thickness	Barrel Length	Thread Length	Diameter	Finish	Price
STD-2424-*	Up to 1/2"	3/4″	3/4" and 1"	3/4"	*PC *MC *BN *BB *BSS *SC	\$6.27 ea.	STD-4024-*	Up to 1/2"	3/4"	3/4" and 1"	1-1/4″	*PC *MC *BN *BB *BSS *ORB	\$9.22 ea.
STD-2432-*	Up to 1/2"	1"	1"	3/4"	*ORB *PC *MC *BN *BB *BSS	\$6.77 ea.	STD-4032-*	Up to 1/2"	1"	1"	1-1/4"	*PC *MC *BN *BB *BSS *ORB	\$10.66 ea.
STD-2448-*	Up to 1/2"	1-1/2"	1"	3/4"	*SC *ORB *PC *MC *BN *BB	\$749 ea.	STD-4048-*	Up to 1/2"	1-1/2"	1″	1-1/4"	*PC *MC *BN *BB *BSS *ORB	\$12.94 ea.
STD-24128-*	Up to 1/2"	4"	1"	3/4"	*BSS *ORB *PC *MC *BN *BB	\$11.07 ea.	STD-40128-*	Up to 1/2"	4"	1"	1-1/4"	*PC *MC *BN *BB *BSS *ORB	\$13.91 ea.
	1/2 **BD **RCC	STD-40192-*	Up to 1/2"	6"	1″	1-1/4"	*MC *BSS	\$15.19 ea.					



Need Extra Hex Keys? 2.5mm Hex Key


Secure Fasten Standoffs

Premium Steel X Series


MATERIAL = Carbon Steel

FINISH = Polished Chrome (*PC), Matte Chrome (*MC), Black Nickel (*BN), Bright Brass (*BB), Brushed Stainless (*BSS), Oil Rubbed Bronze (*ORB)

- 3 Part Assembly
- Medium weight construction
- Holds thicker panels (longer cap thread)
- Includes both 1" & 1-1/2" cap threads
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included



Finishes:



Part #	Panel Thickness	Barrel Length	Thread Length	Diameter	Price
STD-LG2448-*	Up to 3/4"	1-1/2"	1" & 1-1/2"	3/4"	\$6.85 ea.
STD-LG24128-*	Up to 3/4"	4"	1" & 1-1/2"	3/4"	\$9.95 ea.
STD-LG4048-*	Up to 3/4"	1-1/2"	1" & 1-1/2"	1-1/4"	\$11.75 ea.
STD-LG40128-*	Up to 3/4"	4"	1" & 1-1/2"	1-1/4"	\$12.25 ea.
STD-LG40192-*	Up to 3/4"	6 ″	1" & 1-1/2"	1-1/4"	\$13.25 ea.

■ 6" Available in MC or BSS only





Need Extra Hex Keys? 2.5mm Hex Key STD-ALANKEY \$0.53 ea.

Barrel

Length

3/4"

1-1/2

4"

3/4"

Thread

1" 1"

Length Diameter

3/4"

3/4"

3/4"

3/4"

1-1/4"

1-1/4"

1-1/4"

1-1/4"

Price

\$12.56 ea.

\$13.08 ea.

\$13.67 ea.

\$17.50 ea.

\$18.03 ea.

\$18.99 ea.

\$20.13 ea.

\$26.81 ea.

Panel

Thickness

Up to 1/2"

Up to 1/2"

Up to 1/2"

Part #

STD-2424-SS

STD-2432-SS

STD-4024-SS

STD-2448-SS Up to 1/2"

STD-24128-SS Up to 1/2"

Premium Stainless Series

MATERIAL = 316 Stainless Steel **FINISH** = Satin Stainless (SS)

- 3 Part Assembly
- Medium weight construction
- · Marine grade Will not rust!
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included








Finish:



Satin Stainless





Cap: 5/16"











Secure Fasten Standoffs



Premium Aluminum Series MATERIAL = Aluminum **FINISHES** = Polished Chrome (*PC),

• 3 Part Assembly

 Lightweight, durable aluminum construction

Will not rust!

• Flat Cap - 1/4-20 thread

· 2.5mm Hex Key included (One per order)

• #6 flat head screws and drywall anchors included



Barrel

Length



Panel Barrel Thread Part # Thickness Length Length Diameter Price STDA-2020-SS Up to 3/8" 5/8" 3/4" 5/8" \$2.39 ea. STDA-2032-SS 5/8" \$2.75 ea. Up to 1/2" STDA-2048-SS Up to 1/2" 5/8" \$3.28 ea. 1-1/2 STDA-2064-SS Up to 1/2" 5/8" \$3.93 ea. STDA-2096-SS Up to 1/2" 3" 5/8" \$4.78 ea. STDA-20128-SS Up to 1/2" 4" 5/8" \$5.04 ea. 3/4" 3/4" 3/4"-1 STDA-2424-* Up to 1/2" \$4.85 ea. STDA-2432-* Up to 1/2" 1" 3/4" \$5.04 ea. STDA-2448-* 1-1/2 3/4" \$5.23 ea. Up to 1/2" STDA-24128-* Up to 1/2" 4" 3/4" \$6.12 ea. 1-1/4" STDA-4024-* Up to 1/2" 3/4" \$6.36 ea. Up to 1/2" 1" 1" STDA-4032-* 1-1/4" \$6.68 ea. STDA-4048-* Up to 1/2" 1-1/2 1-1/4" \$7.68 ea. STDA-40128-* \$8.71 ea. Up to 1/2" 1-1/4"

















Conference Room


205

Counter Series





- 3 Part Assembly
- · Medium weight construction
- · Screws in a counter-clockwise direction to deter tampering
- Fingerprint proof finish
- · 1.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included










1.5mm Hex Key **STD-ALANKEY-1** \$0.26 ea.









\$6.15 ea. **Need Extra Hex Keys?**




Easy Fasten Standoffs



Eco Solid Series

MATERIAL = 201 Stainless Steel FINISHES = Polished Stainless (*PSS) Brushed Stainless (*BSS)

- 2 Part Assembly
- Medium weight construction
- #6 flat head screws and drywall anchors included



	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STDE-S3264-PSS	Up to 1/2"	2"	1″	\$3.72 ea.
STDE-S4048-*	Up to 5/8"	1-1/2"	1-1/4"	\$3.68 ea.
STDE-S4064-PSS	Up to 5/8"	2"	1-1/4"	\$4.28 ea.









for indoo use only




Tamper Proof Standoffs

Latte X Standoffs

MATERIAL = Die Cast Zamac

FINISHES = Polished Chrome (*PC), Matte Chrome (*MC), Bright Brass (*BB), Satin Copper (*SC), Brushed Stainless (*BSS), Antique Brass (*AB)

- 2 Part Assembly
- · Medium weight, durable construction
- Euro style round cap pops into place inside barrel
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included



Part #	Panel Thickness	Barrel Length	Diameter	Price
CTD D1020 *	Un to 1/2"	12/16"	0/16"	\$2.20.02



(BB) Matte **Bright** Chrome Chrome Brass



Copper







Need Extra Hex Keys? 2 mm Hex Key **STD-ALANKEY-2** \$0.37 ea.



Tamper Proof Standoffs






MATERIAL = Die Cast Zinc

FINISHES = Polished Chrome (*PC), Matte Chrome (*MC), Bright Brass (*BB), Satin Copper (*SC), Brushed Stainless (*BSS), Antique Brass (*AB)

- · 2 Part Assembly
- Medium weight construction
- Unique and special shape designs
- · Plug system with tamper proof set screw
- · 2mm Hex Key included (One Per Order)
- #6 flat head screws and drywall anchors included



Part #	Panel Thickness	Barrel Length	Diameter	Price
STD-3C2126-*	Up to 7/16"	13/16"	5/8"	\$3.00 ea.
STD-4C1826-*	Up to 7/16"	13/16"	9/16"	\$3.00 ea.
		/!!	0/4 4"	40.00

STD-6C1826-* Up to 7/16" 13/16" 9/16" \$3.00 ea.

> **Need Extra Hex Keys?** 2 mm Hex Key **STD-ALANKEY-2** \$0.37 ea.




Euro Mini Stainless Standoffs



MATERIAL = 304 Stainless **FINISH** = Brushed Stainless (**BSS**)

- 2 Part Assembly
- · Lightweight construction
- 1.5mm Hex Key included (One Per Order)
- #6 flat head screws and drywall anchors included

Finish:





Brushed Stainless

	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STD-TMS1313-BSS	Up to 3/8"	1/2"	1/2"	\$3.35 ea.
STD-TMS1324-BSS	Up to 3/8"	3/4"	1/2"	\$5.45 ea.

Need Extra Hex Keys? 1.5mm Hex Key **STD-ALANKEY-1** \$0.26 ea.



gourmet!

Tamper Proof Standoffs



Cubby Series

MATERIAL = Die Cast Zinc **FINISH** = Brushed Nickel (**BHN**)

- 2 Part Assembly
- Medium weight construction
- Smooth even head blends with panels
- Tamper proof plug thread stops head from moving
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included

23/64" Panel Hole Diameter
3/32" Barrel Length
Set Screw
M8.5/9.5 Thread
IIIIcau

	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STD-CBX24-BHN	Up to 3/8"	3/4"	3/4"	\$5.05 ea.
STD-CBX40-BHN	Up to 3/4"	1-1/4"	1-1/4"	\$8.30 ea.

(BHN)
Brushed
Nickel

X40-BHN Up to 3/4″ 1-1/4″ 1-1/4″ \$8.30 ea.

Need Extra Hex Keys? 2 mm Hex Key STD-ALANKEY-2 \$0.37 ea.


Low Profile Tamperproof

MATERIAL = Solid Brass FINISH = Polished Stainless (PSS) Brushed Stainless (BSS)

- 2 Part Assembly
- · Medium weight construction
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included

	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STDL-2032-PSS	Up to 1/2"	1"	5/8"	\$2.78 ea.
STDL-2032-BSS	Up to 1/2"	1"	5/8"	\$2.90 ea.
STDL-3232-PSS	Up to 1/2"	1"	1"	\$3.98 ea.
STDL-3232-BSS	Up to 1/2"	1"	1"	\$4.11 ea.

Need Extra Hex Keys? 2 mm Hex Key STD-ALANKEY-2 \$0.37 ea.









Edge It- No Drill Standoffs



Edge Grip: Eco Easy Edge Standoffs



MATERIAL = 201 Stainless Steel **FINISH** = Brushed Stainless (**BSS**)

- Lightweight construction
- Ideal for one panel
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included for 5/8" & 3/4" diameter



	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
■ STDE-ED1313-BSS	Up to 1/2"	1/2"	1/2"	\$2.59 ea.
■ STDE-ED1324-BSS	Up to 1/2"	3/4"	1/2"	\$2.71 ea.
■ STDE-ED1332-BSS	Up to 1/2"	1″	1/2"	\$2.84 ea.
■ STDE-ED1348-BSS	Up to 1/2"	1-1/2"	1/2"	\$3.20 ea.
STDE-ED2024-BSS	Up to 1/2"	3/4"	5/8"	\$3.39 ea.
STDE-ED2032-BSS	Up to 1/2"	1"	5/8"	\$3.58 ea.
STDE-ED2048-BSS	Up to 1/2"	1-1/2"	5/8"	\$3.95 ea.
STDE-ED2432-BSS	Up to 1/2"	1″	3/4"	\$3.76 ea.
STDE-ED2448-BSS	Up to 1/2"	1-1/2"	3/4"	\$4.25 ea.

Screws & anchors not included


Need Extra Hex Keys?

2 mm Hex Key

STD-ALANKEY-2 \$0.37 ea.








- Ideal for up to 4 panels
- · No drilling required
- Will hold multiple signs
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included
- Tamper proof











	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STDE-SP-3224-PSS	Up to 5/16"	3/4"	1″	\$4.10 ea.
STDE-SP-3224-BSS	Up to 5/16"	3/4"	1"	\$3.57 ea.
STDE-SP-3232-PSS	Up to 5/16"	1"	1"	\$4.58 ea.
STDE-SP-3232-BSS	Up to 5/16"	1"	1"	\$3.99 ea.
STDE-SP-3248-PSS	Up to 5/16"	1-1/2"	1"	\$5.36 ea.
STDE-SP-3248-BSS	Up to 5/16"	1-1/2"	1"	\$4.70 ea.
STDE-SP-3264-PSS	Up to 5/16"	2"	1"	\$5.84 ea.
STDE-SP-3264-BSS	Up to 5/16"	2"	1"	\$5.10 ea.

Need Extra Hex Keys? 2.5mm Hex Key

STD-ALANKEY \$0.53 ea.



Edge It- No Drill Standoffs

Edge Grip: Easy Edge Premium Series

MATERIAL = Solid Carbon Steel FINISHES = Polished Chrome (PC), Matte Chrome (MC)


- · Medium weight, durable steel construction
- · Ideal for one panel
- 2mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included

	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STD-EDGE-PC	Up to 1/2"	1″	1″	\$7.76 ea.
STD-EDGE-MC	Up to 1/2"	1"	1"	\$7.76 ea.



Polished

Chrome





Need Extra Hex Keys? 2 mm Hex Key **STD-ALANKEY-2** \$0.37 ea.

Edge Grip: 4 Way Premium Series

MATERIAL = Solid Carbon Steel FINISHES = Polished Chrome (PC), Matte Chrome (MC)

- Medium weight, durable steel construction
- Ideal for up to 4 panels
- 2.5mm Hex Key included (One per order)
- #6 flat head screws and drywall anchors included

		Barrel		
Part #	Panel Thickness	Length	Diameter	Price
STD-4WAY-PC	Up to 5/16"	1″	1″	\$11.86 ea.
STD-4WAY-MC	Up to 5/16"	1″	1"	\$11.86 ea.

Matte

Chrome





Please Inquire for our wall anchor selections

(PC) Polished

Chrome

Need Extra Hex Keys? 2.5mm Hex Key STD-ALANKEY \$0.53 ea.

Grip It- No Drill Standoffs







Vertical





Slotted Standoffs

MATERIAL = Solid Brass FINISHES = Polished Chrome (PC), Matte Chrome (MC)

- Can be mounted either vertically or horizontally
- Perfect for holding partition panels, signage or shelving
- · No drilling required
- · Hex key to tighten

STD-SL12-MC

C

• 2.5mm Hex Key included (One per order)

Up to 1/2"

- 1-1/2" L x 5/16" Hanger Bolt included
- Maximum Load Rating: 17 lbs.

Maximum Louc	anding. 17 io	· ·		
	Panel	Barrel		
Part #	Thickness	Length	Diameter	Price
STD-SL14-PC	Up to 1/4"	1-5/8"	1-1/4"	\$8.25 ea.
STD-SL14-MC	Up to 1/4"	1-5/8"	1-1/4"	\$8.25 ea.
STD-SL38-PC	Up to 3/8"	1-5/8"	1-1/4"	\$8.25 ea.
STD-SL38-MC	Up to 3/8"	1-5/8"	1-1/4"	\$8.25 ea.
STD-SL12-PC	Up to 1/2"	1-5/8"	1-1/4"	\$8.25 ea.

1-5/8"

1-1/4"



Finishes:



Polished Chrome




Matte Chrome











Need Extra Hex Keys? 2.5mm Hex Key STD-ALANKEY \$0.53 ea.

Signage Grips



- Rubber pads included to adjust for different panel thickness
- #6 screw and anchor included



\$8.25 ea.

• 4 Screws included



- Rubber pads included to adjust for different panel thickness
- #6 screw and anchor included

D	
	21/2"

• 4 Screws included

	Part #	Panel Thickness	Finish	Material	Price
Α	SSFZ-618F-SC	3/16" - 3/8"	Brushed Stainless Steel	Zamac	\$6.85 ea.
В	S83-108F-BR	1/4"	Polished Brass	Brass	\$12.75 ea.
c	SSF-618FADJ-SC	1/4" - 5/16"	Brushed Stainless Steel	304 Grade Satin Stainless Steel	\$12.00 ea.
D	S83-108F-CH	1/4"	Polished Stainless Steel	Stainless Steel	\$17.50 ea.

Grip It- No Drill Standoffs





Uno Clamp

Ideal for Lightweight 1mm Materials

MATERIAL = Polyethylene and Nylon **FINISH** = White Silver Matte

- · Can be mounted vertically or horizontally
- Great for panels without holes so you don't have to drill through your material
- Max weight 11 lbs.
- · All screws and anchors included





	Panel			
Part #	Thickness	Price		
GRP-2464-HI DR	Un to 16"	\$5.45 ea		










Table Sign Clamp

MATERIAL = 304 Grade Stainless Steel **FINISHES** = Stainless Steel (**SS**)

- Perfect for nameplates and small desktop signs
- · Sleek modern look
- Quality stainless steel construction







Grip It- No Drill Standoffs

Grip It Clamp *Non-Illuminated*



MATERIAL = Clear Anodized Aluminum
FINISHES = Polished Chrome (*PC)
Matte Chrome (*MC)

- 2mm Hex Key included (one per order)
- #6 flat head screws and drywall anchors included
- · No drilling required

Kit Includes:






	Panel		▲ Maximum _	P	rice
Part #	Thickness	Thickness Length Sign Size		Each	20+ PCS
SC-80-*	1/8" - 1/2"	3-1/8"	6-5/16" x 9-1/2"	\$9.45	\$8.65 ea.
SC-120-*	1/8" - 1/2"	4-3/4"	9-1/2" x 14-3/16"	\$12.32	\$11.17 ea.
SC-180-*	1/8" - 1/2"	7-1/16"	14-3/16" x 21-1/4"	\$15.00	\$13.69 ea.

[▲] Maximum sign size per piece






Finishes:



Polished Matte Chrome Chrome











Grip It- No Drill Standoffs









MATERIAL = Clear Anodized Aluminum **FINISH** = Matte Chrome (MC)

- 2mm Hex Key included (one per order)
- #6 flat head screws and drywall anchors included
- No drilling required
- The clamp wire is 38" long

Lighting Specifications

Color Temperature	CW: 6000K-6500K
Beam Spread	120°
Lumens	CW: 40-80
Color Rendering Index	CW: 70
Rated Average Life	CW: 50,000 hrs.
Chip Size	SMD3528



		LEC
i i	7/16"	LED
Please Inquire for our wall anchor		LED
selections		▲ Ma
Finish: (MC) Matte Chrome 1"		

								Price
Part #	Color Temp	Panel Thickness	Maximum Sign Size	Length	# Of LED Chips	Total Wattage	Each	20+ PCS
LED-SC80-MC		3/16" - 5/16"	6-5/16" x 6-5/16"	3-1/8"	6	.4W	\$14.06	\$12.85 ea.
LED-SC120-MC	Cool White	3/16" - 5/16"	9-1/2" x 9-1/2"	4-3/4"	9	.6W	\$19.42	\$18.26 ea.
LED-SC180-MC		3/16" - 5/16"	14-3/16" x 14-3/16"	7-1/16"	12	.8W	\$20.63	\$18.85 ea.

laximum sign size per piece

Power Supplies (Required)



Color: Black

Junction Box (Required)

Function: Is to join multiple fixtures to one power supply.



LED-STD-JB10 \$3.00 ea.

2"L x 1-1/4"W x 1/2"D Number of Outputs: 10 Input Cord: 19-11/16" Color: White









LED Standoffs

Standons



Thread

Length: 3/4"





Cap: 15/64'

11/32

LED


Perfect for lobbies & reception areas

12V MATERIAL = Aluminum

• The standoff wire is 38" long

• Up to 10 pieces can be connected to one power supply

• #6 screws & drywall anchors included



Maximum Recommended Spacing: 20" x 20" for 4 Standoffs

Finishes:



Polished Chrome

Matte Chrome

Black

Lighting Specifications

Color Temperature	CW: 6000K-6500K
Beam Spread	120°
Lumens	CW: 30-40
Color Rendering Index	CW: 70
Rated Average Life	CW: 10,000 hrs.
Chip Size	SMD2908



Panel Thickness (when graphic Barrel Thread Total # of **Color Temp Finish** Length Length Diameter LED Wattage Each 60+ Part # is routed) Polished STD-LED-2525-PC Cool White Up to 1/2" 3/4" .4W \$7.83 \$6.83 ea. Chrome Matte STD-LED-2525-MC Cool White Up to 1/2" 1" 3/4" 1" .4W \$7.83 \$6.83 ea. 6 Chrome STD-LED-2525-BK Cool White Black Up to 1/2" 1" 3/4" 1" .4W \$9.00 \$8.16 ea. Red (*RD) Matte STD-LED-2525-M-* Blue (*BL) 1" 3/4" 1" .4W Up to 1/2" 6 \$9.00 \$8.16 ea. Chrome Green (*GR) Red (*RD) Blue (*BL)

Power Supplies (Required)



Input Cord: 5'

Color: Black

Junction Box (Required) Function: Is to join multiple fixtures

Green (*GR)

STD-LED-2525-B-*



2"L x 1-1/4"W x 1/2"D Number of Outputs: 10 Input Cord: 19-11/16" Color: White

Forstner Drill Bit (Optional) LED-STD-DB75 \$10.50 ea.

1"

3/4"

1"

6

.4W

- Extra sharp cutting edges for smooth, flat bottomed holes
- · Hole Size: 3/4"

Up to 1/2"

• Shank: 3/8"

Black



\$9.00 \$8.16 ea.

Invisi Series Standoffs




Eco Invisible Standoffs

for indoor & outdoor use

MATERIAL = Polycarbonate FINISH = Clear

- No screws visible on the letter or sign front
- For letters & signs weighing up to .75 lbs.
- · Available with or without adhesive
- #8 flat head screw & drywall anchor included





1/2"

		Barrel		
Part #	Description	Length	Diameter	Price
STDI-6875	Invisible Standoff	11/16"	9/16"	\$0.28 ea.
STDI-6875-A	Invisible Standoff with Adhesive	11/16"	9/16"	\$0.35 ea.



Casper Invisible Standoffs


MATERIAL = Polycarbonate & Brass



- FINISH = ChromeMust be purchased in increments of 4
- No screws visible on the sign front
- Removable
- Tamper proof

Kit Includes:





		ľ
Part#		Barrel Length
STDI-CASP	ER	11/16"

 Barrel

 Length
 Diameter
 Price

 11/16"
 9/16"
 \$5.40 ea.

outdoor use


Radio 3

Please Inquire for our wall anchor selections




Crystal Round Standoffs

MATERIAL = Clear Polycarbonate **FINISH** = Clear



- Tamper proof
- · Cap snaps into body of standoff
- Metal spring clamp locks standoff in place





5	Panel	Barrel	5	
Part #	Thickness	Length	Diameter	Price
STD-P2026-CL	Up to 1/2"	13/16"	5/8"	\$2.00 ea.

Cap It Off Series


for indoor & outdoor use

Colorful Wall

MATERIAL = Polypropylene

- · Sold in sets of 4. Each Kit includes 4 caps, 4 bases, 4 #6 x 1" screws & 4 anchors
- · All caps are made from polypropylene
- All metallic finishes are vacuum plated
- Polypropylene caps are UV stabilized for outdoor use (does not apply to metallics)







Part #	Diameter	Finish	Part #
STDC-24-BK	11/16"	Black	STDC-24-GR
STDC-24-WH	11/16"	White	STDC-24-BL
STDC-24-BR	11/16"	Brown	STDC-24-OR
STDC-24-BE	11/16"	Beige	STDC-24-PL
STDC-24-LG	11/16"	Light Gray	STDC-24-DB

		,	0.00
	STDC-24-BL	11/16"	Blue
	STDC-24-OR	11/16"	Orange
	STDC-24-PL	11/16"	Purple
ay	STDC-24-DB	11/16"	Dark Blue

Diameter

11/16"

	Part#	Diameter	rinisn
	STDC-24-LP	11/16"	Light Pink
	STDC-24-RD	11/16"	Red
š	STDC-24-TQ	11/16"	Turquoise
	STDC-24-YW	11/16"	Yellow
ie	STDC-24-FG	11/16"	Forest Green

3100-24-30	11/10	Jatin Chionic
STDC-24-CH	11/16"	Bright Chrome
STDC-24-BRS	11/16"	Bright Brass
STDC-24-SCOP	11/16"	Satin Copper
STDC-24-COP	11/16"	Bright
	11/10	Copper

Diameter

Metallic Pricing Per Finish \$4.21/Set...25 Sets \$3.37/Set

Color Pricing Per Finish \$3.16/Set...25 Sets \$2.53/Set

Eco Lite Wall Mount



MATERIAL = 202 Stainless Steel FINISH = Brushed Stainless (BSS)



Part #	Diameter	Price
STD-32AMC-BSS	1″	\$2.41/set of 4
STD-40AMC-BSS	1-1/4"	\$2.87/set of 4
STD-48AMC-BSS	1-1/2"	\$3.42/set of 4





Eco Wall Mount Signage Caps

Finish

Green



MATERIAL = 201 Stainless Steel **FINISHES** = Brushed Stainless (**BSS**) Polished Stainless (PSS)



15/64" Panel Hole Diameter	

Part #	Diameter	Price
STDE-32CAP-BSS	1″	\$0.92 ea.
STDE-32CAP-PSS	1″	\$0.92 ea.

Finishes:



Stainless

Stainless Stainless


Eco Solid Stainless Wall Mount

Part #



Finish

MATERIAL = 202 Stainless Steel **FINISH** = Brushed Stainless (BSS)











Part #	Diameter	Price
STD-C2P20-BSS	5/8"	\$4.47/set of 4
STD-C2P24-BSS	3/4"	\$5.06/set of 4
STD-C2P32-BSS	1"	\$5.65/set of 4

Cap It Off Series

Premium Steel Wall Mount Signage Caps




MATERIAL = Solid Carbon Steel

FINISHES = Polished Chrome (*PC), Matte Chrome (*MC), Black Nickel (*BN), Bright Brass(*BB),

Brushed Stainless (*BSS), Oil Rubbed Bronze (*ORB)

Part #	Diameter	Price
STD-24CAP-*	3/4"	\$2.65 ea.
STD-40CAP-*	1-1/4"	\$3.85 ea.














Premium Aluminum Wall Mount Signage Caps



MATERIAL = Aluminum

FINISHES = Polished Chrome (PC),
Polished Stainless (PS)




Part #	Diameter	Price
STDA-24CAP-PC	3/4"	\$2.19 ea.
STDA-24CAP-PS	3/4"	\$2.19 ea.
STDA-40CAP-PC	1-1/4"	\$2.37 ea.
STDA-40CAP-PS	1-1/4"	\$2.37 ea.



Chrome



Insert Nuts






Button It

MATERIAL = Chrome Plated Solid Brass FINISHES = Polished Chrome (PC), Matte Chrome (MC)

- Used to make "Sandwich" style signs
- Tightens with 2mm Hex Key included (One per order)



Panel				
Part #	Thickness	Diameter	Price	
STD-13CAPSET-PC	Up to 1/2"	9/16"	\$1.58 ea.	
STD-13CAPSET-MC	Up to 1/2"	9/16"	\$1.56 ea.	

Need Extra Hex Keys?

2 mm Hex Key

STD-ALANKEY-2 \$0.37 ea.

Polished Chrome



Matte Chrome

Sign / Banner Holders



THE "SNAP-EASE" ALUMINUM BANNER HANGING SYSTEM


CLEAR ANODIZED ALUMINUM 24", 36", 48" & 96" LENGTHS

NOTE: ALL LENGTHS ARE NOMINAL



- Clear anodized aluminum finish with 4 black plastic end caps for a "finished" look.
- The spring clips inside the rail will "snap" close to securely hold your banner in place.
- Ideal for paper, fabric and vinyl banners up to .08" thick.
- Recommend to be used at the bottom of your banner for added stability.
- Includes removable hanging clips. The banner hanging system can be attached to the wall or hung from the ceiling using our ceiling hooks, **Please Inquire**.





		Price	
Part #	Length	Per Set	10+ Sets
SNAP-24	24"	\$9.14 ea.	\$8.55 ea.
SNAP-36	36"	\$11.29 ea.	\$10.59 ea.
SNAP-48	48"	\$13.44 ea.	\$12.61 ea.
SNAP-96	96"	\$26.34 ea.	\$24.70 ea.

Components To Complete Your Customization





SNAP-HC \$0.27 ea.

End Caps



SNAP-EC \$0.54 pr.

Spring Clips



SNAP-SC \$0.23 ea.


4" Joiner Bar



HGR-JOIN Each: \$0.79 100 pcs. \$0.65 ea.



Snap Ease Sign Kits



- · Vertical or Horizontal mounting
- · All inclusive kits:
 - 2 length banner holders
 - 2 hanging clips
 - 4 end caps
 - 2 spring clips

Part #	Length	Price
SNAP-KIT-8	8-1/2"	\$9.14 ea.
SNAP-KIT-11	11"	\$10.48 ea



Front Loading Plastic Frame Profiles

These plastic profiles can be easily cut & mitered to a variety of frame sizes. The flip open & snap close design will allow you to change graphics without disassembling the whole unit!



8 Ft. Lengths W/Adhesive High Gloss Black (BK)


· Material: PVC

		Price		
Part #	Description	120 Ft.	600 Ft.	1000 Ft.
DFL-8-BK	High gloss black- 2 piece frame	\$1.40 ft.	\$1.30 ft.	\$1.19 ft.





DFL-8-BK



		Price		
Part #	Description	120 Ft.	600 Ft.	1000 Ft.
BSF-8-BK	Black bullnose snap frame	\$2.90 ft.	\$2.75 ft.	\$2.55 ft.






12 Ft. Lengths White (*WH), Black (*BK), Silver (*SI)


• Material: Dual Durometer PVC

PFLF-	
.775"	
	.437"
	3.737
.825"	1/2" Black Foam Tape

Part #	Description	120 Ft.	600 Ft.
PFLF-1040-*	w/o Adhesive	\$1.24 ft.	\$1.16 ft.
PFLF-1040A-*	w/ Adhesive	\$1.37 ft.	\$1.27 ft.









PFLF-	
1.00"	.600"

12 Ft. Lengths White (*WH), Black (*BK), Silver (*SI)

- Material: Dual Durometer PVC
- Metal corner to hold miter cut

Part #	Description	120 Ft.	600 Ft.
PFLF-1200-*	w/o Adhesive	\$1.55 ft.	\$1.49 ft.
PFLF-1200A-*	w/ Adhesive	\$1.64 ft.	\$1.59 ft.


METAL CORNER		
Part #	Each	1000
PFI F-1200-CORN	\$0.45	\$0.25 ea



Magnaclamp®


THE EFFICIENT WAY OF HANGING SIGNS, BANNERS AND DISPLAY MATERIAL

- Unaffected by frost
- · Wash over, squeegee over
- Neat appearance no unsightly residue
- · Leaves no residue if removed
- LASTS FOR YEARS!



ADHESIVE BACK


Part #	Length	Price
MC-03-WH	3"	\$0.61 ea.
MC-06-WH	6"	\$1.30 ea.
MC-24-WH	24"	\$4.60 ea.
MC-36-WH	36"	\$6.65 ea.




Magnaclamp II®

THE HARD-SHELL MAGNACLAMP' FOR THE UPSCALE LOOK

- · Attaches to a flat surface with permanent adhesive
- Integrated hinge opens to accept signage and clamp shut for a secure hold.
- · Black or White, 24"long with adhesive









Part #	Length	Price	
MCHS-24-BK	24"	\$5.50 ea.	
MCHS-24-WH	24"	\$5.50 ea.	

Sign / Banner Holders

POP&SIGN DESIGN NOW! 1 PROTURE RICKLORP OUTMANDER PLANTS ALL ADMANDS OUTMANDD OUTMAND OUTMANDD OUTMAN

"KLEMMFIX" SIGN HOLDERS

A quick & easy way to install and replace signs. Simply snap open, insert material & close. No notching or stapling required.

Available In Black, White & Clear PVC • 8 Ft. Lengths








KLEMMFIX 18

SPECIFICATIONS:

- Suitable for paper thickness up to .04 inch.
- Stocked with & without adhesive backing.
- Hooks are available for hanging applications.



		Price	
Part #	Color	Per Ft.	100+ Ft.
Withou	ıt Adhesiv	e Backing	
3000-18BK	Black	\$0.76'	\$0.70'
3000-18WH	White	\$0.76'	\$0.70'
3000-18CL	Clear	\$0.76'	\$0.70'

With Adhesive Backing 3000-18BK-T Black \$0.82' \$0.75' 3000-18WH-T White \$0.82' \$0.75' 3000-18CL-T Clear \$0.82' \$0.75'

KLEMMFIX 28

SPECIFICATIONS:

- Suitable for paper thickness up to .08 inch.
- Hooks are available for hanging applications.






		Price		
Part #	Color	Per Ft.	100+ Ft.	
3000-28BK	Black	\$1.60'	\$1.44'	
3000-28WH	White	\$1.60'	\$1.44'	
3000-2801	Clear	\$1.60'	\$1.44'	

SPECIFICATIONS:

Suitable for paper thickness

- up to .04 inch.Hooks are available for hanging
- applications.

 End caps are also available in
- End caps are also available in black or white to give the finishing touch.



		Price	
Part #	Color	Per Ft.	100+ Ft.
3002-36BK	Black	\$1.66'	\$1.50'
3002-36WH	White	\$1.66'	\$1.50'

END CAPS For Klemmfix 36 MATERIAL: Polypropylene



		Price		
Part #	Color	Per Pr.	50+ Prs.	
3003-END-BK	Black	\$1.60 pr.	\$1.45 pr.	
3003-END-WH	White	\$1.60 pr.	\$1.45 pr.	

HANGING CLIPS

For Klemmfix 18, 28 & 36 MATERIAL: Polypropylene



		Price	
Part #	Color	Each	100+ Pcs.
3001-PH-BK	Black	\$0.13	\$0.12 ea.
3001-PH-WH	White	\$0.13	\$0.12 ea.
3001-PH-CL	Clear	\$0.13	\$0.12 ea.

Sign / Banner Holders

- An easy & affordable way to emphasize brands & your marketing message.
- Channels can easily be cut-to-size to accommodate a variety of banner widths.
 - · All channels can be used as a top & bottom rail.



Part #


142F-CL

142F-BK

142F-WH

142F-

- Material: Styrolux
- Flared legs for easy graphic insertion




→ √- 5/64"	
1/2"	
←→ 3/16"	

7	
	Holds up to 1/4" thick material

670-A-

- Material: Styrolux
- · Classic universal clip design



			Price	
Part #	Color	Length	120 Ft.	600 Ft.
670-A-BK	Black	8′	\$1.10'	\$1.04'
670-A-WH	White	8′	\$1.10'	\$1.04'

12' HS-447- "Super Clamp"

Length

12

12

Price

600 Ft.

\$0.69

\$0.68

\$0.68'

120 Ft.

\$0.74

\$0.73'

\$0.73'



Material: PVC


Color

Clear

Black

White


· Each 4' length piece comes with 6 hanging hardware (BH-788-H) to hang banner onto the wall or from the ceiling



- 5/16" →	
3/4"	Holds up to 1/8" thick material

130-"Banner Clamp"

• Material: Clear PVC or Black & White Styrene



			Price		
Part #	Color	*Length	120 Ft.	600 Ft.	
130-CL-*	Clear	(*8) = 8 ft. (*10) = 10 ft.	\$0.28'	\$0.26'	
130-BK-*	Black		\$0.24'	\$0.22'	
130-WH-*	White		\$0.24'	\$0.22'	

2326-"Banner Channel"

			Price		
Part #	Color	Length	120 Ft.	600 Ft.	
HS-447-CL	Clear	4′	\$0.51'	\$0.48'	
HS-447-BK	Black	4′	\$0.49'	\$0.48'	
HS-447-WH	White	4′	\$0.51'	\$0.48'	

131-"Clamp It"

• Material: Clear PVC or Black & White Styrene




L		
←5/	16"→	

T.	
	Holds 1/8"- 3/16"
	thick material

Material: Black ABS with

high gloss film on the front of the profile



			Price		
Part #	Color	Length	120 Ft.	600 Ft.	
2326-BK	Black	12′	\$0.29'	\$0.28'	


			Price		
Part #	Color	*Length	120 Ft.	600 Ft.	
131-CL-*	Clear	(*O) O f4	\$0.28'	\$0.26'	
131-BK-*	Black	(*8) = 8 ft. (*10) = 10 ft.	\$0.24'	\$0.22'	
131-WH-*	White	(10) = 1011.	\$0.24	\$0.22	

1059-"Banner Channel"



Holds up to 1/4" thick material

• Material: Rigid PVC



			Price		
Part #	Color	Length	120 Ft.	600 Ft.	
1059-CL	Clear	12′	\$0.38'	\$0.35'	

HS-2010-"The Great Gripper"



- Material: PVC
- Each 8' length piece comes with 4 hanging hardware (BH-788-H) to hang banner onto the wall or from the ceiling



			Price		
Part #	Color	Length	120 Ft.	600 Ft.	
HS-2010-CL	Clear	8′	\$1.32'	\$1.22'	


Sign / Banner Holders

- An easy & affordable way to emphasize brands & your marketing message.
- Channels can easily be cut-to-size to accommodate a variety of banner widths.
 - · All channels can be used as a top & bottom rail.



PFLF-1200-

- Material: Dual Durometer PVC
- · With or without adhesive



			Price		
Part #	*Color	Length	120 Ft.	600 Ft.	
PFLF-1200-*	(*WH) = White	12′	\$1.55'	\$1.49'	
PFLF-1200A-*	(*BK) = Black (*SL) = Silver	12′	\$1.64'	\$1.59′	

PFLF-1040-

- Material: Dual Durometer PVC
- With or without adhesive




			Price		
Part #	*Color	Length	120 Ft.	600 Ft.	
PFLF-1040-*	(*WH) = White	12′	\$1.24'	\$1.16'	
PFLF-1040A-*	(*BK) = Black (*SL) = Silver	12′	\$1.37′	\$1.27′	

BH-788-"Banner Holder" w/Snap Action



- Material: Styrene
- Contoured shape allows for 2 sided graphics
- Easy mount channel for hanging hardware (BH-788-H), hang banner onto the wall or from the ceiling.

0.144






			Price		
Part #	Color	Length	120 Ft.	600 Ft.	1000 Ft.
BH-788-BK	Black	8′	\$1.51'	\$1.38'	\$1.28'
BH-788-WH	White	8′	\$1.51'	\$1.38'	\$1.28'

2799- "Mini Snap"



- Material: Rigid PVC
- · Clear rubber based film tape for wall mounting



			Price			
Part #	Color	Length	8 Ft.	120 Ft.	600 Ft.	1000 Ft.
2799-BK	Black	8′	\$0.85'	\$0.79'	\$0.72'	\$0.63'
2799-WH	White	8′	\$0.85'	\$0.79'	\$0.72'	\$0.63'

For any quantities less than 120 ft. add 10% to the 120 ft. price

BH-788-H-"Universal Hanger"



Fits into channels up to 1/4" wide

- Material: Clear Polyethylene
- Easily slides into the BH-788-* "Banner Holder", HS-2010-CL "The Great Gripper" and HS-447-* "Mini Snap".



		Pr	ice
Part #	Color	100 Pcs.	1000 Pcs.
BH-788-H	Clear	\$0.18 ea.	\$0.17 ea.

Aluminum Frame Profiles


"SNAP-EASE" FRONT LOADING FRAME PROFILES

MAKE YOUR OWN FRAMES WITH OUR COMPONENTS!









FOR 1/8" INSERT

With Matching Base & Cap Finish

		Price	
Part #	Base & Cap Finish	120 Ft.	600+ Ft.
FLF-29S-AL	Clear Anodized	\$3.17 ft.	\$2.62 ft.

REQUIRED ACCESSORIES







FLF-29S-SPRING to open/close frame (min. 2 per 10") \$0.59 ea. \$0.19 ea./100+ pcs.

Aluminum Frame Profiles

"SNAP-EASE" FRONT LOADING FRAME PROFILES

FLF-19P1-

MAKE YOUR OWN FRAMES WITH OUR COMPONENTS!

Stocked in 8 ft. lengths

2 CORNER ASSEMBLY METHODS TO CHOOSE FROM!

MITERED • ROUNDED










FOR 1/16" INSERT


With Matching Base & Cap Finish

		Price	
Part #	Base & Cap Finish	120 Ft.	600+ Ft.
FLF-19P1-AL	Clear Anodized	\$2.54 ft.	\$2.13 ft.
FLF-19P1-BK	Black Matte	\$3.23 ft.	\$2.71 ft.
FLF-19P1-BRN	Brushed Nickel	\$3.93 ft.	\$3.35 ft.
FLF-19P1-ORB	Oil Rubbed Bronze	\$3.42 ft.	\$2.87 ft.
FLF-19P1-KP	Knotty Pine Wood Grain	n/a	n/a
FLF-19P1-CF	Cherry Flame Wood	n/a	n/a
FLF-19P1-M	Mill	\$1.55 ft.	\$1.26 ft.

With Mill Base & Finished Cap			
		Pri	ice
Part #	Cap Finish	120 Ft.	600+ Ft.
FLF-19P1M-AL	Clear Anodized	\$2.06 ft.	\$1.86 ft.
FLF-19P1M-BK	Black Matte	\$2.41 ft.	\$2.16 ft.
FLF-19P1M-BRN	Brushed Nickel	\$3.54 ft.	\$3.18 ft.
FLF-19P1M-ORB	Oil Rubbed Bronze	\$2.48 ft.	\$2.24 ft.
FLF-19P1M-KP	Knotty Pine Wood Grain	\$6.26 ft.	\$5.57 ft.
FLF-19P1M-CF	Cherry Flame Wood	\$6.26 ft.	\$5.57 ft.







REQUIRED ACCESSORIES



FLF-19P-CORNER joins mitered profiles (Requires 4 per frame) \$0.85 ea. \$0.45 ea./100+ pcs.




FLF-19P-SPRING to open/close frame (min. 2 per 10") \$0.59 ea. \$0.19 ea./100+ pcs.


FLF-8-














REQUIRED ACCESSORIES



FLF-CORNER ins mitered profiles (Requires 4 per frame) \$0.85 ea. \$0.45 ea./100+ pcs.



FLF-SPRING to open/close frame (min. 2 per 10") \$0.59 ea. \$0.19 ea./100+ pcs.

FOR 1/8" INSERT

With Matching Base & Cap Finish

	Price		ice
Part #	Base & Cap Finish	120 Ft.	600+Ft.
FLF-8-AL	Clear Anodized	\$3.31 ft.	\$2.78 ft.
FLF-8-BK	Black Matte	\$3.11 ft.	\$2.56 ft.
FLF-8-BRN	Brushed Nickel	\$4.73 ft.	\$3.98 ft.
FLF-8-ORB	Oil Rubbed Bronze	\$4.00 ft.	\$3.35 ft.
FLF-8-KP	Knotty Pine Wood Grain	n/a	n/a
FLF-8-CF	Cherry Flame Wood	n/a	n/a
FLF-8-M	Mill	\$2.15 ft.	\$1.81 ft.
FLF-8-BRN FLF-8-ORB FLF-8-KP FLF-8-CF	Brushed Nickel Oil Rubbed Bronze Knotty Pine Wood Grain Cherry Flame Wood	\$4.73 ft. \$4.00 ft. n/a n/a	\$3.98 ft. \$3.35 ft. n/a n/a

With Mill Base & Finished Cap

	Pri	ce
Cap Finish	120 Ft.	600+Ft.
Clear Anodized	\$2.73 ft.	\$2.29 ft.
Black Matte	\$2.73 ft.	\$2.32 ft.
Brushed Nickel	\$4.13 ft.	\$3.79 ft.
Oil Rubbed Bronze	\$3.07 ft.	\$2.58 ft.
Knotty Pine Wood Grain	\$6.73 ft.	\$5.99 ft.
Cherry Flame Wood	\$6.73 ft.	\$5.99 ft.
	Clear Anodized Black Matte Brushed Nickel Oil Rubbed Bronze Knotty Pine Wood Grain	Clear Anodized \$2.73 ft. Black Matte \$2.73 ft. Brushed Nickel \$4.13 ft. Oil Rubbed Bronze \$3.07 ft. Knotty Pine Wood Grain \$6.73 ft.

FOR 1/4" INSERT With Mill Base & Finished Cap

		Price	
Part #	Cap Finish	120 Ft.	600+Ft.
FLF-8QM-AL	Clear Anodized	\$3.02 ft.	\$2.72 ft.
FLF-8QM-BK	Black Matte	\$3.28 ft.	\$2.95 ft.
FLF-8QM-BRN	Brushed Nickel	\$4.91 ft.	\$4.43 ft.
FLF-8QM-ORB	Oil Rubbed Bronze	\$3.45 ft.	\$3.11 ft.
FLF-8QM-KP	Knotty Pine Wood Grain	\$7.37 ft.	\$6.57 ft.
FLF-8QM-CF	Cherry Flame Wood	\$7.37 ft.	\$6.57 ft.
FLF-8Q-M	Mill	\$2.80 ft.	\$2.43 ft.

Aluminum Frame Profiles

"SNAP-EASE" FRONT LOADING FRAME PROFILES


Stocked in 8 ft. lengths

MAKE YOUR OWN FRAMES WITH OUR COMPONENTS!


FLF-19N-











REQUIRED ACCESSORIES



FLF-19N-CORNER joins mitered profiles (Requires 4 per frame) \$0.85 ea. \$0.45 ea./100+ pcs.



FLF-19N-SPRING to open/close frame (min. 2 per 10") \$0.59 ea. \$0.19 ea./100+ pcs.

FOR 1/8" INSERT With Matching Base & Cap Finish

		Price	
Part #	Base & Cap Finish	120 Ft.	600+ Ft.
FLF-19N-AL	Clear Anodized	\$3.18 ft.	\$2.68 ft.
FLF-19N-BK	Black Matte	\$3.59 ft.	\$3.02 ft.
FLF-19N-BRN	Brushed Nickel	\$4.88 ft.	\$4.10 ft.
FLF-19N-ORB	Oil Rubbed Bronze	\$3.96 ft.	\$3.32 ft.
FLF-19N-KP	Knotty Pine Wood Grain	n/a	n/a
FLF-19N-CF	Cherry Flame Wood	n/a	n/a
FLF-19N-M	Mill	\$2.60 ft.	\$2.18 ft.

With Mill Base & Finished Cap			
		Price	
Part #	Cap Finish	120 Ft.	600+ Ft.
FLF-19NM-AL	Clear Anodized	\$2.60 ft.	\$2.40 ft.
FLF-19NM-BK	Black Matte	\$3.01 ft.	\$2.77 ft.
FLF-19NM-BRN	Brushed Nickel	\$4.30 ft.	\$3.76 ft.
FLF-19NM-ORB	Oil Rubbed Bronze	\$3.03 ft.	\$2.69 ft.
FLF-19NM-KP	Knotty Pine Wood Grain	\$6.70 ft.	\$5.97 ft.
FLF-19NM-CF	Cherry Flame Wood	\$6.60 ft.	\$5.97 ft.
	FOR 1/4" INSERT		


With Mill Base & Finished Cap

		Price	
Part #	Cap Finish	120 Ft.	600+Ft.
FLF-19NQM-AL	Clear Anodized	\$3.36 ft.	\$2.88 ft.
FLF-19NQM-BK	Black Matte	\$3.71 ft.	\$3.29 ft.
FLF-19NQM-BRN	Brushed Nickel	\$5.05 ft.	\$4.58 ft.
FLF-19NQM-ORB	Oil Rubbed Bronze	\$3.81 ft.	\$3.31 ft.
FLF-19NQM-KP	Knotty Pine Wood Grain	\$7.34 ft.	\$6.55 ft.
FLF-19NQM-CF	Cherry Flame Wood	\$3.34 ft.	\$6.55 ft.
FLF-19NQ-M	Mill	\$2.88 ft.	\$2.49 ft.


FLF-37S-











REQUIRED ACCESSORIES



FLF-37S-CORNER joins mitered profiles (Requires 4 per frame) \$0.85 ea. \$0.45 ea./100+ pcs.



FLF-37S-SPRING to open/close frame (min. 2 per 10") \$0.59 ea. \$0.19 ea./100+ pcs.

FOR 1/8" INSERT With Matching Base & Cap Finish

		Pri	ice
Part #	Base & Cap Finish	120 Ft.	600+Ft.
FLF-37S-AL	Clear Anodized	\$3.63 ft.	\$3.05 ft.
FLF-37S-BK	Black Matte	\$3.86 ft.	\$3.27 ft.
FLF-37S-BRN	Brushed Nickel	\$5.85 ft.	\$4.91 ft.
FLF-37S-ORB	Oil Rubbed Bronze	\$4.32 ft.	\$3.63 ft.
FLF-37S-KP	Knotty Pine Wood Grain	n/a	n/a
FLF-37S-CF	Cherry Flame Wood	n/a	n/a
FLF-37S-M	Mill	\$2.42 ft.	\$2.00 ft.
2000-1		_	

With Mill Base & Finished Cap

	Price		ice
Part #	Cap Finish	120 Ft.	600+ Ft.
FLF-37SM-AL	Clear Anodized	\$3.06 ft.	\$2.57 ft.
FLF-37SM-BK	Black Matte	\$3.41 ft.	\$3.06 ft.
FLF-37SM-BRN	Brushed Nickel	\$5.46 ft.	\$4.92 ft.
FLF-37SM-ORB	Oil Rubbed Bronze	\$3.50 ft.	\$3.16 ft.
FLF-37SM-KP	Knotty Pine Wood Grain	\$7.08 ft.	\$6.31 ft.
FLF-37SM-CF	Cherry Flame Wood	\$7.08 ft.	\$6.31 ft.
	FOR 1/4" INSERT		

With Mill Base & Finished Cap

	Price	
Cap Finish	120 Ft.	600+ Ft.
Clear Anodized	\$3.76 ft.	\$3.33 ft.
Black Matte	\$4.11 ft.	\$3.59 ft.
Brushed Nickel	\$6.17 ft.	\$5.55 ft.
Oil Rubbed Bronze	\$4.21 ft.	\$3.68 ft.
Knotty Pine Wood Grain	\$7.73 ft.	\$6.89 ft.
Cherry Flame Wood	\$7.73 ft.	\$6.89 ft.
	Clear Anodized Black Matte Brushed Nickel Oil Rubbed Bronze Knotty Pine Wood Grain	Cap Finish 120 Ft. Clear Anodized \$3.76 ft. Black Matte \$4.11 ft. Brushed Nickel \$6.17 ft. Oil Rubbed Bronze \$4.21 ft. Knotty Pine Wood Grain \$7.73 ft.

Fully Assembled, Front Loading **Aluminum Frames**

CHOOSE FROM.

ATTRACTIVE AND EASY-TO-USE!

Built-in spring loaded hinge enables you to change graphics in a snap without disassembling the frame.



- Fully assembled frame comes with clear non-glare lens and back panel

- Screw holes on the back for easy mounting - portrait or
- Screws and drywall anchors are included
- Custom sizes and finishes available at a minimum.



Strong aluminum construction

Snap/Spring loaded

- landscape
- Please inquire for more details.

...AN ARRAY OF STYLES!

1" Easy-Frame With Clear Anodized, Black Powder Coat Or Woodgrain Finish







	.
Mounts Portrait or Landscape	•
2 Holes on 2 sides	
Screws & Anchors included	•
0.3mm PET Non-Glare Lens	- 1″
e/Poster ene Backer - tches Frame Finis	11/16"
	or Landscape 2 Holes on 2 sides Screws & Anchors included 0.3mm PET Non-Glare Lens //Poster

A A A A A A A A A A A A A A A A A A A	
	Management of the contract of
British Control of The Control	
	Management (1977)
the amount to court	B0000000000000000000000000000000000000
	B0000000000000000000000000000000000000
	E0000000000000000000000000000000000000
	B0000000000000000000000000000000000000
	B0000000000000000000000000000000000000
	B0000000000000000000000000000000000000
Control of the Contro	The second secon
	B0000000000000000000000000000000000000
Contract Con	gastatatatatata
	Manufacture Control of the last of the las
All the second s	And in concession of the last

_	Graphic	Reveal	Overall			rice
Part #	Size	Dimensions	Dimensions	Finish	Each	10+ Pcs.
FRM-O57-SIL	5" x 7"	4-1/4" x 6-1/4"	6-1/4" x 8-1/4"	Clear Anodized	\$5.10	\$4.60 ea.
FRM-O57-BK	5" x 7"	4-1/4" x 6-1/4"	6-1/4" x 8-1/4"	Black Powder Coat	\$5.15	\$4.65 ea.
FRM-O57-WG	5" x 7"	4-1/4" x 6-1/4"	6-1/4" x 8-1/4"	Woodgrain	\$10.80	\$9.80 ea.
FRM-O8511-SIL	8-1/2" x 11"	7-3/4" x 10-1/4"	9-3/4" x 12-1/4"	Clear Anodized	\$9.45	\$8.50 ea.
FRM-08511-BK	8-1/2" x 11"	7-3/4" x 10-1/4"	9-3/4" x 12-1/4"	Black Powder Coat	\$10.90	\$9.80 ea.
FRM-08511-WG	8-1/2" x 11"	7-3/4" x 10-1/4"	9-3/4" x 12-1/4"	Woodgrain	\$15.30	\$13.75 ea.


Custom sizes & finishes can be produced. Please Inquire.

Packed 5 per carton. \$5.00 broken box fee (BB5) for less than full carton.

Fully Assembled, Front Loading Aluminum Frames

Built-in spring loaded hinge enables you to change graphics in a snap without disassembling the frame.

1" Frame With Clear Anodized Or Black Powder Coat Finish



1-1/4" Frame With Clear Anodized Or Black Powder Coat Finish

16" x 20"

FRM-1620-BK



15-1/8" x 19-1/8"

Part #	Size	Dimensions	Dimensions	Finish	Each	10+ Pcs.
FRM-2228-SIL	22" x 28"	21-5/8" x 27-11/16"	24-1/8" x 30-1/8"	Clear Anodized	\$32.45	\$29.35 ea.
FRM-2228-BK	22" x 28"	21-5/8" x 27-11/16"	24-1/8" x 30-1/8"	Black Powder Coat	\$42.72	\$39.79 ea.
FRM-2436-SIL	24" x 36"	23-1/2" x 35-5/8"	26-1/8" x 38-1/8"	Clear Anodized	\$46.87	\$44.18 ea.
FRM-2436-BK	24" x 36"	23-1/2" x 35-5/8"	26-1/8" x 38-1/8"	Black Powder Coat	\$53.28	\$49.56 ea.


17-3/16" x 21-3/16"

1-1/4" Frame With Clear Anodized Finish









Black Powder Coat

\$24.45

\$23.51 ea.

Backer: 1.5mm Gray Polystyrene (for N8511 & N1117) or 3mm Foam Board (for N1620, N2228 & N2436)

Overall

Part #	Size	Dimensions	Dimensions	Each	10+ Pcs.
FRM-N8511-SIL	8-1/2" x 11"	8-1/16" x 10-5/8"	10-3/16" x 13-3/16"	\$17.95	\$17.05 ea.
FRM-N1117-SIL	11" x 17"	10-1/4" x 16-3/16"	12-3/16" x 18-1/8"	\$24.07	\$21.17 ea.
FRM-N1620-SIL	16" x 20"	15-1/2" x 19-1/2"	18" x 22-1/8"	\$28.44	\$25.68 ea.
FRM-N2228-SIL	22" x 28"	21-5/8" x 27-5/8"	24-1/8" x 30-1/8"	\$42.56	\$40.08 ea.
FRM-N2436-SIL	24" x 36"	22-5/8" x 35-1/2"	26-1/4" x 38-1/16"	\$52.49	\$50.17 ea.

Reveal

Custom sizes & finishes can be produced. Please Inquire.

Packed 5 per carton. \$5.00 broken box fee (BB5) for less than full carton.


Granhic

Price


Fully Assembled, Front Loading
Aluminum Frames

Built-in spring loaded hinge enables you to change graphics in a snap without disassembling the frame.


1-1/4" Frame With High Quality Anodized Satin Silver Finish




1-1/4" Frame With High Quality Anodized Satin Silver Finish



1-7/16" Frame With High Quality Anodized Satin Silver Finish



1-5/8" Frame With High Quality Anodized Satin Silver Finish




Custom sizes & finishes can be produced. Please Inquire.

Packed 5 per carton. \$5.00 broken box fee (BB5) for less than full carton.

Fully Assembled, Front Loading Aluminum Frames

Built-in spring loaded hinge enables you to change graphics in a snap without disassembling the frame.


1-3/4" Frame With High Quality Anodized Satin Silver Finish



1-1/4" Jumbo Frame With Clear Anodized Finish



1-3/4" Jumbo Frame With Clear Anodized Finish



1-1/4" Lockable Waterproof Frame With Clear Anodized Or Black Powder Coat Finish



Custom sizes & finishes can be produced. Please Inquire.

Packed 5 per carton. \$5.00 broken box fee (BB5) for less than full carton.

LED Lighting

Crystal Light Box







For Counter & Wall Mount Displays Material: Acrylic with Aluminum Post

- Super thin 3/8"
- Available in wall mount & counter top
- Power supply included
- Includes On / Off Switch

COUNTER TOP













Cap

Washe

. I"Depth

~½" Dia.→



			Reveal Dimensions	Overall Dimensions	Total	Р	rice
Part #	Color Temp	Size	(Nominal)	(Nominal)	Wattage	Each	5+
CLB-LED-0811-W	Cool White	8.5" x 11"	8" x 10-5/8"	10-13/16" x 13-5/16"	1.8	\$60.48	\$50.40 ea.
CLB-LED-1117-W	Cool White	11" x 17"	10-5/8" x 16-5/8"	13-3/4" x 19-3/4"	3.6	\$92.99	\$77.49 ea.
CLB-LED-1620-W	Cool White	16" x 20"	15-1/2" x 19-3/4"	18-1/4" x 23-11/16"	6	\$130.41	\$108.68 ea.
CLB-LED-2228-W	Cool White	22" x 28"	21-9/16" x 27-9/16"	24-3/4" x 30-3/4"	9	\$232.85	\$194.04 ea.
CLB-LED-2436-W	Cool White	24" x 36"	23-1/2" x 35-5/8"	27-1/8" x 39-1/8"	11	\$340.20	\$282.50 ea.
CLB-LED-0811-C	Cool White	8.5" x 11"	8" x 10-5/8"	10-13/16" x 13-5/16"	1.8	\$62.78	\$52.32 ea.
CLB-LED-1117-C	Cool White	11" x 17"	10-5/8" x 16-5/8"	13-3/4" x 19-3/4"	3.6	\$95.29	\$79.41 ea.

Available for either wall mount (-w) or counter top (-c) applications.

INSIDE & LIGHT IS GUIDED

THROUGH PANEL

LED Lighting

Fully Assembled Front Loading Aluminum Frames







Material: Aluminum Frame with Acyclic Light Guide Panel

- Comes ready to use: Clear PVC cover, mounting hardware & power supply included
- Easy front load feature
- Can be used either landscape or portrait
- Low profile, should meet ADA requirements
- Plug & Play

FRONT VIEW






SUPER BRIGHT! EVEN ILLUMINATION!

BACK VIEW





BEVELED EDGE PROFILE



SHOWN ILLUMINATED



İ	g	h	ti	in	g	S	p	e	ci	fi	c	a	ti	0	n	S	

WW: 7500K-8500K
FLF-LED-0811: 275 FLF-LED-1117: 475 FLF-LED-1620: 625 FLF-LED-2228: 1000 FLF-LED-2436: 1250
CW: 75-80
50,000 hrs.
SMD2835

			Graphic	Reveal Dimensions	Overall Dimensions	Total		Price
Part #	Color Temp	Finish	Size	(Nominal)	(Nominal)	Wattage	Each	5+
FLF-LED-0811	Cool White	Anodized Aluminum	8.5" x 11"	8-1/8" x 10-11/16"	10-1/8" x 12-3/4"	3	\$88.20	\$70.56 ea.
FLF-LED-1117	Cool White	Anodized Aluminum	11" x 17"	10-5/8" x 14-3/8"	12-1/2" x 18-5/16"	4	\$116.55	\$92.40 ea.
FLF-LED-1620	Cool White	Anodized Aluminum	16" x 20"	15-19/32" x 19-5/8"	17-3/8" x 21-3/8"	6	\$141.75	\$113.40 ea.
FLF-LED-2228	Cool White	Anodized Aluminum	22" x 28"	21-1/2" x 27-1/2"	23-3/8" x 29-3/8"	10	\$199.50	\$162.23 ea.
FLF-LED-2436	Cool White	Anodized Aluminum	24" x 36"	23-5/8" x 35-1/2"	25-1/2" x 37-3/8"	13	\$333.90	\$267.12 ea.

Slide In Frames

Single Sided Slide In Frame

(New)

- Comes with mounting hardware (2 Screws & 2 Anchors)
- Anti-Glare 3mm PVC Lens
- White Backer Board
- · Silver (Clear Anodized) Finish
- Can be used for either portrait or landscape orientation
- 4 Mounting Holes at 5/32" Diameter
- Frame Profile is 1"Wide
- Frame Thickness is 9/16" Thick


Part #	Graphic Size	Reveal Dimensions	Overall Dimensions	Each
HGR-SL-845	8-1/2" x 11"	7-9/16" x 10-1/16"	9-13/16" x 12-5/16"	\$15.95
HGR-SL-1117	11" x 17"	10-1/16" x 16-1/16"	12-5/16" x 18-5/16"	\$18.54
HGR-SL-1824	18" x 24"	17-1/16" x 23-1/16"	19-5/16" x 25-5/16"	\$23.19
HGR-SL-2228	22" x 28"	21-1/16" x 27-1/16"	23-5/16" x 29-5/16"	\$27.81
HGR-SL-2436	24" x 36"	23-1/16" x 25-1/16"	25-5/16" x 27-5/16"	\$34.10












Color U-Channel Moulding




PROTOTYPE SAMPLES


We are happy to provide samples for prototypes & design builds. - Please Inquire

Color U-Channel Moulding



Colors Available





Fits 2"

PROTOTYPE SAMPLES

We are happy to provide samples for prototypes & design builds -Please inquire.




ALUMINUM PROFILES & SHAPES

Wide Variety of Finishes

Available in 12 Ft. Lengths

Angle (Even/Uneven) Mouldings...pgs. S-70~71
Cap & Divider Mouldings...pgs. S-77, 79
Channel Mouldings...pgs. S-66~67
Corner Mouldings...pg. S-74
Cove Mouldings...pg. S-68
Filler Tee Mouldings...Please Inquire
No Notch & Real Tee Mouldings...Please Inquire
Price Tag Mouldings...pg. S-73
Rounded Trim Mouldings...Please Inquire
Tubes, Rods, Bars & Squares Shapes...Please Inquire
Showcase Mouldings...Please Inquire
Sliding Door Track Mouldings...Please Inquire
Z Bar Mouldings...Please Inquire




PROTOTYPE SAMPLES

We are happy to provide samples for prototypes & design builds.
- Please Inquire


Flexible U-Channel Moulding


Lengths: 250 Ft. Coils • Material: Dense Neoprene • Rubber Black






- channel provides and aesthetic and protective edge trim







Aluminum "No Bow" Shelf Channel


Lengths: 8 Ft. - For 1/2", 5/8" & 3/4" Shelves

*S - Clear Anodized - Dull, Matte Finish • *BK - Black Powder Coated Gloss Finish • *WH - White Powder Coated Gloss Finish





				Satin		Black (Or White
Part #	Α	В	C	120 Ft.	600 + Ft.	120 Ft.	600 + Ft.
SHF-A500-*	43/64"	3/4"	1/2"	\$1.90'	\$1.73'	\$2.31'	\$1.94'
SHF-A625-*	51/64"	3/4"	5/8"	\$1.83'	\$1.60'	Please Inquire	
SHF-A750-*	15/16"	3/4"	3/4"	\$1.92'	\$1.75'	\$2.35' \$1.98'	



Plastic Metallic Angle Moulding w/Adhesive

*POL/B - Polished Brass

Lengths: 12 Ft. Material: ABS/Mylar **Finishes Available**

*POL/C - Polished Chrome *BRU/B - Brushed Brass Please inquire as finishes vary from style to style


.995 1.025

*BRU/C - Brushed Chrome

.750/ .770 Таре .240/ **≯** .260 Part # 120 Ft. 600 Ft. 1000 Ft.

\$0.60'

2163-* \$0.65'



Fits 3/8"

.740/ .760 -1/2" 720/ Part # 120 Ft. 600 Ft. 1000 Ft. Part # 120 Ft. 600 Ft. 1000 Ft. **2001-*** \$0.93' \$0.88' \$0.80'

Fits 3/4"

For any quantities less than 120 ft. add 10% to the 120 ft. price.


Aluminum & Stainless Steel Cove Moulding

Lengths: 12 Ft.

Finishes Available

*S - Satin/Clear Anodized - Dull, Matte Finish *P, *PH (w/holes) - Mechanical Polish - Shinv/Mirror Finish *BS, BSH (w/holes) - Brushed Satin - Lightly Brushed (Shows Grain) Satin Finish We can also supply custom orders without holes - minimums apply - please inquire.

Reverse cove moulding is used to cover up seams or joints wherever two perpendicular planes meet. The sink top to its backsplash or the ceiling to a wall surface represent typical applications for which our reverse cove moulding was designed. The leg of the profile seals tightly against both surfaces to lend a cleanly trimmed appearance to the finished product.



3/8


S- 68

Sign Essentials




600 Ft. +


Fits 1/2"








\$1.18






Plastic Color Right Angle Moulding




Plastic Color Uneven Angle Moulding



For any quantities less than 120 ft. add 10% to the 120 ft. price.

Plastic Flexible Uneven Angle Moulding



Aluminum Even Angle Moulding

Lengths: 12 Ft. Material: Aluminum


Finishes Available

*M - Mill - Dull Finish: As Extruded - May or May Not Have "Scratches"/Die Lines

*S - Satin/Clear Anodized - Dull, Matte Finish

*P - Polished/Mechanical- Shiny/Mirror Finish
*BK - Black Anodized Finish

Special Order: Other Colors Available, Please Inquire



Aluminum Even Angle Moulding

Lengths: 12 Ft. **Material: Aluminum**


Finishes Available


*M - Mill - Dull Finish: As Extruded - May or May Not Have "Scratches"/Die Lines


*P - Polished/Mechanical - Shiny/Mirror Finish


*S - Satin/Clear Anodized - Dull, Matte Finish

Special Order: Other Colors Available, Please Inquire









Aluminum Uneven Angle Moulding

Lengths: 12 Ft. **Material: Aluminum**

Finishes Available

*M - Mill - Dull Finish: As Extruded - May or May Not Have "Scratches"/Die Lines


1/4" x 1/2"


*BSH (w/holes) - Brushed Satin - Lightly Brushed (Shows Grain) Satin Finish

*P, PH (w/holes) - Polished/Mechanical - Shiny/Mirror Finish

*S - Satin/Clear Anodized - Dull, Matte Finish

3/8" x 3/4"






Part #	Length	Mill	Satin
ALU555-*	120 Per Ft.	\$1.21'	\$1.71'
	600 Ft. +	\$1.11'	\$1.52'

For any quantities less than 120 ft. add 15% to the 120 ft. price.

1/2" x 3/4"


Plastic Flat Back Price Tag Color Moulding



With Adhesive Backing

Lengths: 12 Ft. • Material: Styrene





PROTOTYPE SAMPLES

\$0.81' \$0.77' \$0.73'

25-200-*

We are happy to provide samples for prototypes & design builds.
- Please Inquire

For any quantities less than 120 ft. add 10% to the 120 ft. price.

25-1-500-* \$0.73' \$0.70' \$0.69'


\$0.95' \$0.90' \$0.84'

25-2-500-*

Plastic Flat Back Price Tag Clear Moulding

43A-3

\$1.78' \$1.77' \$1.57'



For any quantities less than 120 ft. add 10% to the 120 ft. price.

43A-1-500 \$1.18' \$1.13' \$1.03'

43A-1-250 \$1.06' \$1.00' \$0.96'

600 Ft.+ Inquire \$1.72'

43A-2

\$1.38' \$1.34' \$1.19'

For any quantities less than 120 ft. add 15% to the 120 ft. price.





Aluminum Outside Corners


Lengths: 12 Ft. • Fits 3/4" Panel Boards • Patent #4840440





*S - Satin/Clear Anodized - Dull, Matte Finish















600 Ft. +





600 Ft. +

\$6.57


Part #: CW-TOOLS \$1,250.00 (sold separately, please inquire)

Aluminum Corners

Lengths: 12 Ft.

\$5.75'

Finishes Available
nes *P - Polished - Shiny/Mirror Finish



For any quantities less than 120 ft. add 15% to the 120 ft. price.

Plastic Corner Channel Moulding

90° Corner Channel



Lengths: 12 Ft. **Material: Styrene**

Colors Available

*WH - White *BK - Black *BR - Brown ▲ *DG - Dove Gray ▲ unless otherwise noted

Fits 1/8"

Fits 1/4"

Fits 5/8"

▲ 5000 ft. minimum apply



Fits 1/16"

Fits 1/4"

Fits 1/2"


Fits 3/4"



Fits 1/16"

Part Tapers For Friction Fit

Part #	120 Ft.	600 Ft.	1000 Ft.
107-680-*	\$0.31'	\$0.27'	\$0.24'





Gloss finish closely matches

Acrylic and PETG sheets


Color Clear Others Available Min. Apply Styrolux - 8 Ft. Lengths

Part #	120 Ft.	600 Ft.	1000 Ft.
107-681-*	\$0.60'	\$0.52'	\$0.48'







Part #	120 Ft.	600 Ft.	1000 Ft.	
184-*	\$0.56'	\$0.47'	\$0.43'	



1/4" PÁNEL				
	Polyprop	ylene		
Part #	120 Ft.	600 Ft.	1000 Ft.	
107-685-BR	\$0.61'	\$0.50'	\$0.46'	







Also Stocked in Dove Gray -No Minimum Required

8 Ft. Lengths


Part #

107-687-*

120 Ft. 600 Ft. 1000 Ft. \$1.25' \$1.14' \$1.02'

23/32" →
5/8"

8 Ft. Lengths				
Part # 120 Ft. 600 Ft. 1000 Ft.				
107-688-*	\$1.34'	\$1.23'	\$1.11'	




- 8 Ft. Lengths					
	Part #	120 Ft.	600 Ft.	1000 Ft.	
	107-689-*	\$1.54'	\$1.49'	\$1.44'	


60° Corner Channel

Lengths: 8 Ft. **Material: Styrene**

Colors Available

Fits 1/4"






1000 Ft.

\$1.02'

Fits 1/2"



For any quantities less than 120 ft. add 10% to the 120 ft. price.

4069-*

1/8"

1/8"

1135-* Works with 1134-*


Part #

120 Ft. 600 Ft. 1000 Ft.

P751H-* \$0.56' \$0.53' \$0.49'

Works with

P750-*



For any quantities less than 120 ft. add 10% to the 120 ft. price.

Polished

\$1.62'

\$1.45'

Part #

SS851-P

Length

120 Per Ft.

600 Ft. +

Polished

\$1.63'

\$1.48'

Length

120 Per Ft.

600 Ft. +

Part #

SS1451-P

Part#

SS1450-P

Length


120 Per Ft.


600 Ft. +

Polished

\$2.12'

\$1.80'





For any quantities less than 120 ft. add 10% to the 120 ft. price.

120 Ft. 600 Ft. 1000 Ft.

\$0.48' \$0.40' \$0.36'

Part #

11340B/C

120 Ft. 600 Ft. 1000 Ft.

\$0.52' \$0.43' \$0.40'

Part #

2469-*

120 Ft. 600 Ft. 1000 Ft.


1976-POL/C \$0.49' \$0.42' \$0.38'



Lengths: 12 Ft. A = Available with Adhesive (1/2" Clear Tape) unless otherwise noted




Fits 1/8"



Material: PVC 120 Ft. 600 Ft. 1000 Ft. \$0.42' \$0.38' \$0.36'


Part #

12A-CL




8 Ft. Lengths - Material: Styrolux

120 Ft. 600 Ft. 1000 Ft. **220-CL-A** \$0.57' \$0.51' \$0.47'



Material: PVC


Part #	120 Ft.	600 Ft.	1000 Ft.
210-CL	\$0.26'	\$0.22'	\$0.21'
210A-CL	\$0.33'	\$0.26'	\$0.25'



Fits 1/4"

Material: Polyester

Part #	120 Ft.	600 Ft.	1000 Ft
23-CL	\$0.53'	\$0.50'	\$0.44'
23A-CL	\$0.59'	\$0.54'	\$0.49'




8 Ft. Lengths - Material: Styrolux					
Part #	120 Ft.	600 Ft.	1000 Ft.		
55-5949	\$0.86'	\$0.840'	\$0.730'		
55-5949A	\$0.97'	\$0.91'	\$0.82'		




Fits 3/32"

Material: Butyrate					
Part # 120 Ft. 600 Ft. 1000 Ft.					
847-CL	\$0.73'	\$0.71'	\$0.67'		
847A-CL	\$0.91'	\$0.88'	\$0.85'		




120 Ft. 600 Ft. 1000 Ft. Part # 846-CL \$0.55' \$0.48' \$0.42' \$0.66' \$0.56' *846A-CL \$0.53' \$0.50' **846-CL-CLA \$0.62' \$0.54'



Material: Butyrate Part # 120 Ft. 600 Ft. 1000 Ft. 2030-CL \$0.87' \$0.83' \$0.76' **2030-CL-CLA** \$0.99' \$0.90' \$0.89


Earring Card Holder Fits 5/32"






Lengths: 12 Ft. • Material: Butyrate

A = Available with Clear Adhesive




Part #	120 Ft.	600 Ft.	1000 Ft.
2028-CL	\$0.61'	\$0.57'	\$0.53'
2028-CL-CLA	\$0.70'	\$0.62'	\$0.59'




Part #	120 Ft.	600 Ft.	1000 Ft.
2029-CL	\$0.62'	\$0.58'	\$0.54'
2029-CL-CLA	\$0.71'	\$0.66'	\$0.65'


Clear Plastic Joiner Moulding


Lengths: 8 Ft. • Material: Butyrate • Fits 1/4" Material














For any quantities less than 120 ft. add 10% to the 120 ft. price.

Merchandising Essentials

Free Standing & Wall Mount Sign Holders

MOST CAN BE USED IN HORIZONTAL AND VERTICAL APPLICATIONS

COUNTER TOP SIGN HOLDER

- Material: PVC
- · Lengths: 12 in.
- Color: Available in Black *(BK), White *(WH) & Silver *(SI)
- · Holds material 1/16" 1/8" thick
- 3.25"W x 12"L with dual durometer grip




Part #	100 Pcs.	500 Pcs.	1000 Pcs.
SNH-325-12*	\$2.70 ea.	\$2.60 ea.	\$2.25 ea.

COUNTER TOP SIGN CHANNEL



- · Material: PVC
- · Lengths: 8 ft.
- Color: Available in Black *(BK), White *(WH) & Silver *(SI)
- Holds material 1/16" 1/8" thick
- 3.25"W x 8'L with dual durometer grip




Part #	120 Ft.	600 Ft.	1000 Ft.
SNH-325-*	\$2.63'	\$2.33'	\$2.24'

For quantities less than 120 ft. please add 10% to the 120 ft. price.

SPECIALTY SIGN HOLDER



- · Material: Clear Butyrate
- Holds material up to 0.100" thick
- 1/2" H tension grip sign holder w/ 1-1/4" L x 1" deep curved mounting base to work w/shelving and showcases




Part #	Length	100 Pcs.	500 Pcs.	1000 Pcs.	
6201-01	1-1/4"	\$0.17 ea.	\$0.16 ea.	\$0.13 ea.	
For quantities less than 100 pieces please inquire.					

SIGN CHANNEL PVC/DUAL DUROMETER



- Material: PVC · Lenaths: 8 ft.
- · Holds material 1/8" thick
- Peel and stick foam back
- 1/2'W base x 7/16" H with dual durometer grip



Part #	Color	120 Ft.	600 Ft.	1000 Ft.
106-4808-BK	Black	\$1.12'	\$1.08'	\$1.02'
106-4808-WH	White	\$1.12'	\$1.08'	\$1.02'

For quantities less than 120 ft. please add 10% to the 120 ft. price.

FREE STANDING CARD HOLDER WITHOUT ADHESIVE






Part #	Fits Card	120 Ft.	600 Ft.	1000 Ft.
32-CL	1/16"	\$3.57'	\$3.21'	\$2.94'
33-CL	1/8"	\$3.57'	\$3.21'	\$2.94'

FREE STANDING CARD HOLDER



- Material: White Styrene
- · Lengths: 12 ft.
- Fits material 1/8" and 1/16"-1/4" thick
- 1" or 2"W flat base x 1/2" or 1" H




600 E4

Part #	А	В	Fits Card	120 Ft.	ouu rt.	1000 Ft.
24SM125-WH	1/2"	1″	1/8"	\$0.49'	\$0.47'	\$0.41'
24-WH	1″	2"	1/16"-1/4"	\$1.37'	\$1.20'	\$1.17'
For quantities less than 120 ft, please add 10% to the 120 ft, price						

CLEAR/PVC



- · Lengths: 12 ft.
- Holds material up to .060" thick
- 1-1/2"W base x 3/4"H



Part #	120 Ft.	600 Ft.	1000 Ft.
1255-CI	\$0.81'	\$0.74'	\$0.66'

SEGDesigns™: Modular SEG Frames

MODULAR SEG FRAMES

SEG simply beautiful.



BANNER UPS

SEG Made Simple...and Beautiful!




Stock Color: Silver Aluminum Material: ABS



Modular system - fast and easy to assemble

- No assembly tools needed. Snaps together instantly.
- Can be pressure fit, screw-secured, or glued.
- Corner pieces and T-Connectors make unlimited size and shapes easy.
- No mitered corners / all straight cut sides.
- Cut with any hand or power saw. Custom sizes a breeze!





Superior to Aluminum

- Lower total cost than aluminum.
 100% MADE IN THE USA (PAT. pending)
- Lighter weight than aluminum easier to ship and hang.
- Breaks down to shippable sizes NO UPS/FedEx surcharge.
- No hidden hardware or cutting charges.

Unlimited length with T-Connectors

Environmentally-friendly polymer

• ABS, Non-PVC recyclable polymer

Enhances the value of complementary products:

- Ask us for a list of approved recommend textile media.
- Works with all Latex, Dye Sub, and Eco-Solvent printers.



Add DESIGN to your SEG frames - wrapable, paintable, designable!

- Add color easily with common spray paint (Krylon Fusion 28 colors*)
- Match customers logo or image color!

Graphic NOT included

 $\bullet \ Let \ your \ creativity \ flow! \ "Upsell" \ through \ beautiful \ design.$



Krylon is a registered trademark of Sherwin-Williams*



Works great with KederTape[™] - a complete simple solution

• Enter the SEG market NOW, with no equipment cost.



SEGDesigns™: Modular SEG Frames








Stock Color: Silver Aluminum **Material: ABS**

- Fast & easy to assemble, no mitering!
- · Lightweight, easy to ship!
- · Paintable, wrappable...designable!
- · No aluminum, no tools, no hassle!

Buy SEG Modular Frames In Bulk!


		# Of Pieces	Price P	er Case
Part #	Description	Per Case	1-3 Cases	4+ Cases
BU-SEGD15-1824	15mm frame, 18" x 24" O.A.	5	\$150.00 (\$30.00 ea.)	\$130.00 (\$26.00 ea.)
BU-SEGD15-2436	15mm frame, 24" x 36" O.A.	5	\$190.00 (\$38.00 ea.)	\$165.00 (\$33.00 ea.)
BU-SEGD15-3648	15mm frame, 36" x 48" O.A.	5	\$240.00 (\$48.00 ea.)	\$210.00 (\$42.00 ea.)



Create Any Size Frame You Want!


Buy SEG Components Separately in Bulk and Cut Size as Needed!

		# Of Pieces	Price P	er Case
Part #	Description	Per Case	1-3 Cases	4+ Cases
BU-SEGD15-R15	15mm side rail, 15"	48	\$158.40 (\$3.30 ea.)	\$136.80 (\$2.85 ea.)
BU-SEGD15-R21	15mm side rail, 21"	48	\$220.80 (\$4.60 ea.)	\$189.60 (\$3.95 ea.)
BU-SEGD15-R33	15mm side rail, 33"	48	\$348.00 (\$7.25 ea.)	\$297.60 (\$6.20 ea.)
BU-SEGD15-R45	15mm side rail, 45"	48	\$472.80 (\$9.85 ea.)	\$405.60 (\$8.45 ea.)
BU-SEGD15-R93	15mm side rail, 93"	48	\$960.00 (\$20.00 ea.)	\$816.00 (<i>\$17.00 ea.</i>)
BU-SEGD15-CORNER	15mm 90°corner	48	\$64.80 (\$1.35 ea.)	\$57.60 (\$1.20 ea.)
BU-SEGD15-TCON	15mm t-connector	48	\$72.00 (\$1.50 ea.)	\$62.40 (\$1.35 ea.)
BU-SEGD15-CLEAT	15mm wall cleat	48	\$24.00 (\$0.50 ea.)	\$19.20 (\$0.40 ea.)




· Use T-Connector to connect rails for unlimited lengths & provide cross support









When ordering, take overall frame size and subtract 3" from each rail. (ie) 18" - 3" = 15" rail, 24" - 3" = 21" rail. The 90° corners add 3" to meet overall frame dimension of 18" x 24".



Make Silicone Edge Graphic (SEG) Signs without sewing by using KederTape[™]!



KederTape" is a high-quality keder that is laminated with a premium pressure sensitive adhesive which allows the product to be "peel and stick" applied to textiles for SEG (Silicone Edge Graphic) applications. KederTape™ adhesive has been engineered to aggressively adhesive to textiles.



Crystal Clear BravoTabs®

Banner Ups®: Banner Tabs & Tape



- 1.875" x 3.875" clear tab, folds to 1.875" square shape
- Works great both at corners and along banner edges
- BravoTabs® are a great grommets/eyelet replacement
- · Faster to install translates to lower cost
- No neck loop for improved appearance
- Crystal clear banner tab, allowing your color graphics to shine through





One Size Fits All - Corner and Edges






# Of Pieces		Price		
	Part #	Per Case	1-3 Cases	4+ Cases
	BU-BAN017	500	\$195.00 (\$0.39 ea.)	\$165.00 (\$0.33 ea.)

POLYTABS

- 1.5" x 3.125" clear tab, folds to 1.5" square shape
- Perfect for hanging posters & indoor banners
- Apply to corners of plastic film and then secure using a rope or stake through the center hole
- 2000 Tabs per dispenser roll; roll liner is perforated every four tabs
- Our most economical tab

# Of Pieces Part # Per Case		Price		
		1-3 Cases	4+ Cases	
BU-BAN062	2000	\$330.00 (\$0.165 ea.)	\$270.00 (\$0.135 ea.)	

Clear Polytabs for high volume jobs









Clear PowerTape® Reinforce banner edges without

folding or sewing a hem




• 1.5" wide, 36 yard clear roll

Part #

BU-PTAPECLEAR

- Use PowerTape® to create a super strong banner of any length
- \bullet Singe-sided super strong film. No need to fold hem
- Duplicates the strength of folded hem and double sided banner tape, but eliminates the hassle!
- Eliminate the risk of damage to image by post-print sewing
- Create a perfectly sharp digital banner. No rippled hem
- Fabricate a mighty banner in only 3 minutes








TRY A BANNER UPS® STARTER KIT

Enough for about 20 banners, The Starter Kit will let you give **Banner Ups**® a good trial and find out why so many banner makers <u>LOVE</u> **Banner Ups**® when it comes to custom banner finishing products!



Square shape works great on banner edge or corners. Durable for outdoor use. Use with PowerTape for banners over 6 ft.

1 roll of Banner Ups® Clear PowerTape®

Super-strong single sided hem tape. No folding of hem required! Perfect for double-sided banners.

1 Banner Ups® PowerPunch®

Perfectly sized heavy duty hole punch. Touch enough to cleanly punch tab, tape, and media.

Great for punching 4mm corrugated plastic or foam board too!

BU-STARTKT4AS

S-84 Sign Essentials INTRO SPECIAL

Banner Ups®: Banner Tabs & Tape



Ultra High Strength Double Sided Clear MegaTape® Banner hem tape that withstood winds up to 108 MPH!



- 1.5" wide, 30 yard double sided clear roll
- Double sided banner hem reinforcing tape that is made of a super strong film
- Wind tunnel tested improved MegaTape® banner hem tape withstood winds up to 108 MPH!
- Clear film is less visible / more attractive when used in mesh banners
- Produces a fold-finished banner edge
- Easy to apply banner hem tape. Wears like steel!
- Much cleaner appearance and twice as strong as ordinary double sided banner hem tape.

	# Of Rolls	Price	
Part #	Per Case	1-3 Cases	4+ Cases
BU-MEGATAPE-CL	5	\$195.00 (\$29.50 ea.)	\$130.00 (\$26.00 ea.)



Premium Double Sided Clear TigerTape™ High-performance banner hem tape



- 1" wide, 36 yard length double sided roll
- Double coated polyester (PET) carrier film (.005") on both sides with high deposition of a high tack acrylic pressure sensitive adhesive (PSA)
- A high performance banner hem tape specifically designed for the most demanding bonding applications
- Provides a permanent bond of foams, plastics, metal and composite materials subjected to a broad range of environmental conditions
- Highly UV, temperature and plasticizer resistant making it ideal for banner hemming applications


	# Of Rolls	Pr	ice
Part #	Per Case	1-3 Cases	4+ Cases
BU-TIGTAPE1036	12	\$141.00 (\$11.75 ea.)	\$120.00 (\$10.00 ea.)





BANNER UPS


PowerPunch® -The perfect punch for Powertabs®




- · Powerful and durable, lightweight to handle
- · Portable and much less expensive
- Cut cleanly through tabs, PowerTape® and banner media
- Cuts a 5/16" banner hole
- · Easily punch holes in 4mm corrugated plastic and foamboard without deforming the board

	Pr	ice
Part #	1-3 Pcs.	4+ Pcs.
DII DDIINCH	\$44.00.00	\$20,00.00







S- 86 Sign Essentials Please Inquire



The System with profile







OPTIONS			LICHTIN			
			MOUNTING OPTIONS LIGHTING OPTIONS			
ding Bases Wall	g Bases V	Hanging		Non-Illuminated		
< /		×	×	1		
< /		×	×	1		
< /		1	/	1		
×		1	×	1		
′ /		1	×	1		
×		1	×	1		
/		✓	✓	1		
<i>,</i>		1	/	1		
		×	/	1		
		1	✓	1		
		√ quired	/	1		
	<	od frames ×	od frames × ✓	od frames X X V V		


Foga® Systems



The System with profile

All Dimension Are In Millimeters

SEG Profiles











I UI C TT	
ECDO1TY CL	
L2B011Y-CF	

Finish
Clear Anodized
Aluminum

Le	n	g	τn
1	6	F	t.

Graphic Sides Non-Illuminated Single


Corner FS613

Mounting Options Price Wall only \$1.79 Ft. Screw to the wall

CONVERSION CHART 4 15.5 25.5 FRACTION 5/32" 39/64" 1" DECIMAL .16" .61"







Ш		
	Mounting	
orner	Options	Price
S613	FS520	\$3.39 Ft.
3013	Wall Mount Bracket	75.571 6.



CONVERSION CHART				
MM	4	20	30	40
FRACTION	5/32"	25/32"	1-3/16"	1-37/64"
DECIMAL	.16"	.79"	1.18"	1.58"

Part # FSB03TX-CL

Finish
Clear Anodized
Aluminum

Len	gu
16	Ft.


Graphic Sides
Non-Illuminated
Single

Corner	
FS613	W

(Options	Price
	FS520 lount Bracket	\$3.39 Ft

FSB41TX-CL







	- N. T.
La San Carlo	

Part #
FSR41TY-CI

Finish
lear Anodized
Aluminum

Length 16 Ft.

Graphic Sides Single Illuminated, Double Non-Illuminated

Corner FS613

Mounting Options Price Freestanding, Wall \$3.62 Ft. or Hanging

CONVERSION CHART 35.6 MM 10 40 FRACTION 25/64" 1-13/32" 1-37/64" DECIMAL 1.402" 1.58" .394"

Foga® Systems



The System with profile

SEG Profiles

All Dimension Are In Millimeters





9 40	

	EKSI	ON CHA	
MM	4	9	40

MM	4	9	40
FRACTION	5/32"	23/64"	1-37/64"
DECIMAL	.16"	.35"	1.58"

Part #	Finish	
FSB43TX-CL	Clear Anodized	
	Aluminum	

Length **Graphic Sides** Non-Illuminated 16 Ft. Single or Double

Corner FS613

Mounting Options Floor, Hanging & Foga 194 Series

Price \$8.28 Ft.



FSB92TX-CL	
9 40	

CONVERSION CHART

CONTRACTOR CONTRACT			
MM	4	9	40
FRACTION	5/32"	23/64"	1-37/64"
DECIMAL	16"	35"	1 58"

Part #	Finish
FSB92TX-CL	Clear Anodized
	Aluminum

Length 16 Ft.

Graphic Sides Non-Illuminated Double

FSB80TX-CL

Corner FS614

Mounting Options Freestanding, Wall or Hanging

Price \$3.57 Ft.

· ·

T
•

2	3/1-
	4
9 80	04

CONVERSION CHART

MM	4	9	40	80
FRACTION	5/32"	23/64"	1-37/64"	3-5/32"
DECIMAL	16"	35"	1 58"	3 15"

Finish Part # Clear Anodized FSB80TX-CL Aluminum

Length 16 Ft.

Graphic Sides Non-Illuminated Double

Corner FS614

Mounting Options Freestanding or Hanging

Price \$7.99 Ft.


Foga® Systems



The System with profile

SEG Profiles

All Dimension Are In Millimeters



Length

0

FCD01TV CI	Cle
FSB81TX-CL	

Part #

ear Anodized Aluminum	16 Ft
Alullillulli	
Aluminum	


Finish

Graphic Sides					
Single					
Illuminated,					
Double					
Many III to a fee al.					

Mounting Options Corner Price Freestanding, FS613 Wall or \$4.89 Ft. Hanging Non-Illuminated

CONVERSION CHART									
MM 3 4 14 20 80									
FRACTION	25/32"	3-5/32"							
DECIMAL	DECIMAL 0.1181" .16" .55" .79" 3.15"								

FSB150TX-CL





Part #	Finish	Length	Graphic Sides	Corner	Mounting Options	Price
FSB150TX-CL	Clear Anodized Aluminum	16 Ft.	Single Illuminated, Double Non-Illuminated	FS613	Freestanding, Wall or Hanging	\$7.99 Ft.

CONVERSION CHART						
MM 4 20 40 75 80 150						
FRACTION	5/32"	25/32"	1-37/64"	2-61/64"	3-5/32"	5-29/32"
DECIMAL	.16"	.79"	1.58"	2.95"	3.15"	5.91"





The System with profile

SEG Profiles

For Wood Frame Applications









CONVERSION CHART									
MM 3 4 12 14 28									
FRACTION	35/64"	1-7/64"							
DECIMAL									

Part #	Finish
FSB02TX-CL	Clear Anodized Aluminum

Length

16 Ft. S

Graphic Sides


Single or Double T

Miter
To Mount
Inside Frame

Options Price

Mounts Inside Your Own Frame \$1.27 Ft.

Mounting




Part # Finish

FSB04TX-CL Clear Anodized Aluminum



FSB04TX-CL



Mounting Options Hanging Options -Please Call To Discuss

Price \$5.69 Ft.

	111/	ED		NI C	TIA	DT
 UI.	Vν	EK.	SIU	IN C	HA	ĸІ

MM	4	9.2	14	20	44
FRACTION	5/32"	23/64"	35/64"	25/32"	1-47/64"
DECIMAL	.16″	.362"	.55″	.79″	1.732"

Required Accessories

FSB80TX-CL

Length

16 Ft.

Part	#	Description	Price
FSB04TX-	TNIOL	3-Way Corner Joint, 1 Per Corner Required	\$6.50 Ft.

Graphic Sides

For Cubes







Part #	Finish	Length	Graphic Sides	Mounting Options
FSB80TX-CL	Clear Anodized	16 Ft.	For Cubes	Hanging Options

Required Accessories

Part #	Description	Price
FS614	Corner Coupling, 3 Per Corner Required	\$4.29 Ea.
FST92LTX	Steel End Cap	\$15.50 Ea.

Price

\$9.95 Ft.

Foga® Systems



The System with profile

Accessories

CORNERS

FS613



Works With:
FSB01TX, FSB03TX,
FSB41TX, FSB81TX,
FSB150TX (2 per corner required),
FSB43TX
\$3.63 ea.



FS614

Works With: FSB92TX, FSB80TX, FSB92TX **\$4.29 ea.**

WALL BRACKET

FS520



Works With: FSB03TX, FSB41TX, FSB81TX, FSB92TX, FSB80TX, FSB150TX \$3.08 ea.

SUPPORT BEAM KITS

FS01CL-KIT-*





Consists of: (1) FS01CL & (2) FS600QF

8 Ft. or 16 Ft. Lengths *Consists of*: (1) FS01CL & (2) FS600QF

Works With: FSB01TX

Please Inquire for Pricing

FS90CL-KIT-



Consists of: (1) FS90CL, (1) FS600QFL & (1) FS600QFR

8 Ft. or 16 Ft. Lengths

Works With:

FSB92TX, FSB81TX, FSB150TX, FSB03TX, FSB80TX, FSB43TX Please Inquire for Pricing

SPLICE CONNECTOR



Works With: FSB81TX, FSB150TX

FSB-2200B



Nominal 17-3/4" x 3-3/4" x 3/16" Thick Rectangle \$26.82 ea. Ideal for Signage Under

8' High, Use Every 3'

BASES



FSB-740B

Nominal 16" x 16" x 3/16" Thick Square \$55.00 ea. Ideal for Signage Over 8' High, Use Every 3'

LOCKING HOOKS WITH CABLE

FWH-8-PC (8 Ft. Length)
FWH-15-PC (15 Ft. Length)

8 Ft. or 15 Ft. Lengths

Works With:

FSB73TX, FSB92TX, FSB80TX, FSB81TX, FSB150TX, FSB04TX, FSB41TX **\$7.15 ea.** (8 Ft. Length) **\$7.95 ea.** (15 Ft. Length)

8 FT. / 15 FT.
STEEL CABLE
(1.5mm Thick)

ADJUSTABLE
CABLE HOOK
(Polished Chrome)

GSH-8 (8 Ft. Length) **GSH-15** (15 Ft. Length)

8 Ft. or 15 Ft. Lengths

Works With:

FSB73TX, FSB92TX, FSB80TX, FSB81TX, FSB150TX, FSB04TX, FSB41TX **\$3.10 ea.** (8 Ft. Length)

\$3.10 ea. (8 Ft. Length) \$3.85 ea. (15 Ft. Length)





Foga® Systems



The System with profile









2 Powerful LED Options Illuminates SEG Graphics Evenly Without Hot Spots

- Designed to fit inside the frame of FSB81TX and FSB150TX-CL.
- Comes complete with finger lift hi-tack acrylic permanent tape.



FESTIVAL

*#8



Of LED Total Color Max # Can Modules Wattage Part # Price 20+ Pcs. Length Connect Temp STANDARD BRIGHTNESS LED-FBF83-CW Cool White \$12.50 ea. \$11.25 ea. LED-FBF14-CW 14" Cool White 5 10 7 \$19.14 ea. \$17.23 ea. **DELUXE BRIGHTNESS** LED-FBF7-DLX-CW Cool White 8 \$11.59 ea. 6-1/8 3 \$12.88 ea. LED-ERE84-DLX-CW Cool White \$13.05 ea. 8" 8 10 \$14.50 ea. LED-FBF18-DLX-CW Cool White 20 4 \$35.00 ea. \$31.50 ea.

Lighting Specifications				
Color Temperature	CW: 6000K-7000K			
Beam Spread	40°			
Initial Lumens	LED-FBF83-CW: 550-650 per ft. LED-FBF14-CW: 1000-1100 per ft. LED-FBF7-DLX-CW: 550-650 per ft. LED-FBF84-DLX-CW: 700-800 per ft. LED-FBF18-DLX-CW: 2000-2100 per ft.			
Color Rendering Index	75+			
Rated Average Life	30,000 hrs.			
Constant	Voltage			
Chip Size	SMD3535			
Warranty	3 Years Limited			

Lighting Specifications

Accessories

(LED-FBF-PWL*) that work with these lights.

LED

Fab Strip

Required

However, if you "split" the load using a 2-way connector then you can have more lights on each side. The 2-way connector requires 2 power linking cables



Optional (Pick One Option)

Dimmer Switch

See Pages
L-144 See Page L-149

Multi Output
Cable
See Below

Optional

Connecting
Cable

See Below



Required

Power Supplies



						r	rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-2.5A-HWSL	Hardwire	2.5A	24V	60W	11.8" L x 1.25"W x 0.78"H	\$45.36	\$40.50 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.
					C D 1.407.440		

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Descrip

Power Lin

Power Linking Cable Required for power supplies, dimmers & multi output cables.



Part #

LED-FBF-CC-12

Works With	
FAB LED Strip	
FAB LED Strip	

otion	Length
lı Cabla	18"
k Cable	40"

Overall

Finish

Black & Red

Length

12

18"

40"

Each	6+ Pc
\$3.10	\$2.90
\$4.55	\$4.30
	\$3.10

Each

\$1.65

\$2.75

\$4.50

Price

Price

ea.

ea.

6+ Pcs.

\$1.49 ea.

\$2.48 ea.

\$3.95 ea.

Optional

Multi Output Cables	
)
look topi with)

		Arm	s #of	Overali	Max # of Power _		Price
Part # D	escription Fin	ish Size	Arms	Length	Linking Cables	Each	6+ Pcs
	Power Linking	g Cable Re	quired Fo	r Each Ou	tlet		
LED-2WAY-BK 2-\	Way Sweep Bla	ack 3"	2	6-3/4"	2	\$2.95	\$2.50 ea

Description

Allows the designer to get

Connecting Cables

-	

,		

	Dimensions	Price	
LED-FBF-CC-40	FAB LED Strip	multiple power supplies	Black & Red
LED-FBF-CC-18	FAB LED Strip	around unlit areas without	Black & Red

Works With

FAB LED Strip



Part #	Color	Height	Width	Max. Panel Thickness	100 Pcs.	1000 Pcs.
FSB-WB	Black	.500"	.465"	.156″	\$5.80/C	\$52.00/M

Foga® Systems

LED Ladder Backlight System










Available Lengths: Nominal 20" & 40"

Material: Aluminum with White Coating


- Ultra Bright: Latest 2835 chip technology produces up to 1440 lumens per length.
- Works with FSB41TX-CL, FSB81TX-CL & FSB150TX-CL. See Pages S-88 & S-90
- Backlight as little as 1-1/2" depth without hotspots
- Easily connect ladders together for versatile sizing
- · No heat sink required





IP33 Ladder

Limited Protection From Touch, Tools & Splashing Water




Color Temp

Cool White

Cool White

Cool White

Cool White



Of LED

Chips

24

36



Total Max # Can Each 10+ Pcs. Wattage Connect \$15.90 \$12.75 ea. \$23.75 \$18.90 ea. 43 3 \$20.75 ea. \$26.00 1.5 \$39.00 \$31.25 ea.

Color Temperature	CW: 6500K
Beam Spread	168°
Lumens	436 per ft.
Color Rendering Index	85+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chin Size	2835

Lighting Specifications

Required

Description

4- Row 19.69" Length

6- Row 19.69" Length

4- Row 39.37" Length

6- Row 39.37" Length



Optional (Pick One Option)				
Dimmer	Switch			
See Page L-144	See Page L-149			

	Required
	Ladder
⊦	· • • • • • • • • • • • • • • • • • • •
	For Pricing
	See Page S-94

Required

Part #


LED-LDR196-CW

LED-LDR394-CW

LED-LDR396-CW


LED-LDR194-CW

Power Supplies (IP20)



							TICC
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.
LED-12V-9A	Desktop	9A	12V	108W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$40.35 ea.


For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery




Our Aluminum Framing System is Available in 3/4", 1" & 1-1/2" Square Tubing and corresponding Tubing Connectors & Accessories



- **★** Tradeshows
- ★ Greenhouses
- **★** Menus
- **★** Signs





Our experienced design staff can work with the simplest drawings to the newest CAD drawings to produce an aesthetically pleasing, totally functional final product. Our Fabrication Department can cut all tubing to size, notch flanges, and drill or punch holes to exacting standards so the fit and finish is unmatched. Finally, we can help with packing your order so it arrives in excellent condition.





Great Ideas Need Accessories!

Shown 1" Tubing with Cladding Fittings & Wide Variety of LED Lighting Options

BAR OF LIGHT


RGB RIBBON FLEX

TRI-MOD BACKLIGHT PANELS

For more information go to www.outwater.com (see lighting)

Aluminum Framing System

3/4" Square Aluminum Tubing







Clear anodized finish is suitable for indoor and outdoor use. Black for indoor only.

For any quantities less than 120 ft. add 15% to the 120 ft. price

3/4" Tubing Connectors & Accessories

Material: Dupont™ Super Toughened Nylon Available in Black or Grey



2Way Right Angle Connector

Part #	Finish	Each	10 Pcs.
F24521BK	Black	\$1.74	\$1.66 ea.
F24521GY	Grey	\$1.74	\$1.66 ea.



Part #	Finish	Each	10 Pcs.
F245323BK	Black	\$1.98	\$1.89 ea.
F245323GY	Grey	\$1.98	\$1.89 ea.

Perpendicular Joiner/Splicer For 3/4" At Tubing W/3/4" Long Self Tapping Screw



Part #	Finish	Each	10 Pcs.
F245112MCBK	Black	\$1.37	\$1.30 ea.
F245112MCGY	Grey	\$1.37	\$1.30 ea.



5Way Connector

Part #	Finish	Each	10 Pcs.	
F24558BK	Black	\$2.36	\$2.25 ea.	
F24558GV	Grov	\$2.36	\$2.25.62	



Part #	Finish	Each	10 Pcs.
F24532BK	Black	\$1.98	\$1.89 ea.
F24532GY	Grey	\$1.98	\$1.89 ea.

4Way Connector



Part #	Finish	Each	10 Pcs.	
F24545BK	Black	\$2.09	\$2.00 ea.	
F24545GY	Grey	\$2.09	\$2.00 ea.	

	End Cap			
	Material: Low-Density Polyethylene			
Part #	Color	100 Pcs.	1000 Pcs.	
DNW-S24-BK	Black	\$24.50/C	\$69.50/M	

Cavity Insert For 3/4" Connector Legs

This accessory fits any 3/4" connector increasing surface area for a tighter fit



Part #	Finish	Each	10 Pcs.
F24007BK	Black	\$0.42	\$0.40 ea.
F24007GV	Grev	\$0.42	\$0.40 ea

3Way Corner Connector



Part #	Finish	Each	10 Pcs.
F24533BK	Black	\$1.98	\$1.89 ea.
F24533GY	Grey	\$1.98	\$1.89 ea.





Straight Connector



4Way Cross Connector



Part #	Finish	Each	10 Pcs.
F24544BK	Black	\$2.09	\$2.00 ea.
F24544GY	Grey	\$2.09	\$2.00 ea.


6Way Connector



Part #	Finish	Each	10 Pcs.
F24568BK	Black	\$2.51	\$2.39 ea.
F24568GY	Grey	\$2.51	\$2.39 ea.


1" Square Aluminum Tubing Wall Thickness: .044"

Lengths: 8 Ft.



For any quantities less than 120 ft. add 15% to the 120 ft. price

Sliding Door Track



Plastic Finger Pulls

With high quality pressure sensitive adhesive backing. No holes to drill. Peel off protective backing paper and apply directly to surface of glass.

Part #	Finish	Each	100 Pcs.
170-BK	Black	\$0.50	\$0.45 ea.
170-CL	Clear	\$0.55	\$0.50 ea.




Packed 100 pieces per carton. \$2.00 broken box fee (BB2) for less than full carton.


Aluminum Framing System

1" Square Aluminum Tubing Wall Thickness: .065"


Lengths: 8 Ft.



Part #	Finish	120 Ft.	600 Ft.
AT-2CL-8	Clear Anodized	\$2.97 ft.	\$2.58 ft.
AT-2BK-8	Black Anodized	\$3.20 ft.	\$3.05 ft.



Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
	Clear Anodized			
AT-4BK-8	Black Anodized	\$3.93 ft.	\$3.74 ft.	\$3.16 ft.



Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
AT-8CL-8	Clear Anodized	\$3.53 ft.	\$3.33 ft.	\$3.28 ft.
AT-8BK-8	Black Anodized	\$4.00 ft.	\$3.79 ft.	\$3.72 ft.

Note: For All Tubing


Clear anodized finish is suitable for indoor and outdoor use. Black for indoor only.

For any quantities less than 120 ft. add 15% to the 120 ft. price










Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
AT-6CL-8	Clear Anodized	\$3.17 ft.	\$3.02 ft.	\$2.56 ft.
AT-6BK-8	Black Anodized	\$3.72 ft.	\$3.54 ft.	\$3.01 ft.



			u —	
Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
AT-7CL-8	Clear Anodized	\$3.05 ft.	\$2.89 ft.	\$2.85 ft.
AT-7BK-8	Black Anodized	\$3.55 ft.	\$3.35 ft.	\$3.29 ft.

Slotted 1" Tubing

Finish

Clear

Anodized Black

Anodized

Part #

AT-5CL-8

AT-5BK-8



Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
AT-9CL-8	Clear Anodized	\$5.70 ft.	\$5.40 ft.	\$5.05 ft.
	Black Anodized			

Slots are $1/8"x\ 1/2"-1"$ on center for hardware support



Steel Shelf

Brackets

120 Ft.

600 Ft.

\$3.30 ft. \$3.14 ft. \$2.66 ft.

\$3.93 ft. \$3.74 ft. \$3.16 ft.

1000 Ft.

Brac	kets	Tap-In		
Part #	Description	Finish/Color	Each	Qty. Break
	Tap-In -	.080 Thick Mat	erial	
6KB-BC	6" Long Bracket	Bright Chrome	\$1.37	\$1.16 ea.@48 pcs.
6KB-AL	6" Long Bracket	Almond	\$1.18	\$0.99 ea.@48 pcs.
6KB-BK	6" Long Bracket	Black	\$1.18	\$0.99 ea.@48 pcs.
8KB-BC	8" Long Bracket	Bright Chrome	\$1.45	\$1.26 ea.@25 pcs.
8KB-AL	8" Long Bracket	Almond	\$1.25	-
10KB-BC	10" Long Bracket	Bright Chrome	\$1.59	\$1.49 ea.@48 pcs.
12KB-BC	12" Long Bracket	Bright Chrome	\$1.78	\$1.66 ea.@48 pcs.
12KB-BK	12" Long Bracket	Black	\$1.56	\$1.36 ea.@25 pcs.
12KB-SC	12" Long Bracket	Satin Chrome	\$2.66	\$2.31 ea.@25 pcs.
14KB-BC	14" Long Bracket	Bright Chrome	\$2.09	\$1.96 ea.@48 pcs.
14KB-AL	14" Long Bracket	Almond	\$1.80	-
14KB-WH	14" Long Bracket	White	\$1.80	-
16KB-BK	16" Long Bracket	Black	\$2.03	-
16KB-WH	16" Long Bracket	White	\$2.03	-
16KB-BC	16" Long Bracket	Bright Chrome	\$2.36	\$2.05 ea.@25 pcs.

1" Tubing Connectors & Accessories

Material: Dupont™ Super Toughened Nylon Available in Black or Grey

2Way Right Angle Connector



Part #	Color	Each	10 Pcs.
F521BK	Black	\$2.68	\$2.55 ea.
F521GY	Grev	\$2.68	\$2.55 ea.

3Way Corner Connector





Part #	Color	Each	10 Pcs.
F533BK	Black	\$2.78	\$2.65 ea.
F533GY	Grey	\$2.78	\$2.65 ea.

5Way Connector



Part #	Color	Each	10 Pcs.
F558BK	Black	\$3.44	\$3.28 ea.
F558GY	Grey	\$3.44	\$3.28 ea.

3Way Tee Connector



Part #	Color	Each	10 Pcs.
F532BK	Black	\$2.93	\$2.79 ea.
F532GY	Grey	\$2.93	\$2.79 ea.

4Way Cross Connector




Part #	Color	Each	10 Pcs.
F544BK	Black	\$3.25	\$3.10 ea.
F544GY	Grey	\$3.25	\$3.10 ea.

4Way Connector



Part #	Color	Each	10 Pcs.
F545BK	Black	\$3.25	\$3.10 ea.
F545GY	Grey	\$3.25	\$3.10 ea.

6Way Connector



Part #	Color	Each	10 Pcs.
F568BK	Black	\$3.64	\$3.47 ea.
F568GY	Grev	\$3.64	\$3.47 ea

** 3Way Connector w/Heavy Duty Caster Socket



**NOTE: #F533C will accept a 3/8" diameter x 1" long friction fit caster stem (not included) See Below for Caster

Part #	Color	Each	10 Pcs.
F533C/BK	Black	\$3.05	\$2.91 ea.
F533C/GY	Grey	\$3.05	\$2.91 ea.

3Way Connector w/2-3/8" Dia Caster w/Friction Ring Stem





Without Brake			
Part #	Color	Each	10 Pcs.
F533C/BK-CST	Black	\$4.08	\$3.83 ea.
F533C/GY-CST	Grey	\$4.08	\$3.83 ea.
	With Brak	e	
Part #	Color	Each	10 Pcs.
F533C/BK-CSTB	Black	\$4.29	\$4.04 ea.
F533C/GY-CSTB	Grev	\$4.29	\$4.04 ea.

3Way Connector w/Leveler 1/4-20 x 1" Long



1-3/8" Base Dia. w/Thread Stem & Insert

Part #	Color	Each	10 Pcs.
F533C/BK-LEV	Black	\$3.77	\$3.52 ea.
F533C/GY-LEV	Grey	\$3.77	\$3.52 ea.

1" Tubing Connectors & Accessories

Material: Dupont™ Super Toughened Nylon Available in Black or Grey

90° Base Connector



Part #	Color	Each	10 Pcs.
F5323SPBK	Black	\$2.11	\$2.01 ea.
F5323SPGY	Grey	\$2.11	\$2.01 ea.

The Invisible Coupling







Part #	Color	Each	10 Pcs.
F5101BK	Black	\$2.08	\$1.98 ea.
F5101GY	Grey	\$2.08	\$1.98 ea.

End Cap



Material: **Low-Density** Polyethylene

Part #	Color	100 Pcs.	1000 Pcs.
SHK-32S-BK	Black	\$30.00/C	\$85.70/M

Straight Base Connector



Part #	Color	Each	10 Pcs.
F5323BK	Black	\$1.98	\$1.89 ea.
F5323GY	Grey	\$1.98	\$1.89 ea.

Straight Connector



Part #	Color	Each	10 Pcs.
F500BK	Black	\$2.75	\$2.61 ea.
F500GY	Grey	\$2.75	\$2.61 ea.









Part #	Color	Each	10 Pcs.
F4PSPGY	Grey	\$1.65	\$1.58 ea.

Perpendicular Joiner/Splicer For 1" AT Tubing with 1 x #8 3/4" Long Self Tapping Screw





Part #	Color	Each	10 Pcs.
F5112MCBK	Black	\$1.79	\$1.70 ea.
F5112MCGY	Grey	\$1.79	\$1.70 ea.

All Metal Heavy Duty Shelf Rest For Glass Or Wood Shelving



Part #	Finish	Each	100 Pcs.
F514BK	Black Anodized	\$1.65	\$1.50 ea.
F514CL	Clear Anodized	\$1.65	\$1.50 ea.

U-Clip

4" Lengths



FMJ557-4-S...\$1.45 ea.



Cavity Insert For 1" **Connector Legs**

This accessory fits any 1" connector increasing surface area for a tighter fit






Color Pair 10 Pcs. Part # F007BK Black \$0.42 \$0.40 pr. **F007GY** Grey \$0.42 \$0.40 pr.

1" Tubing Connectors & Accessories

Fits 1" Tube & Holds 1/4" Panel Cladding Rigid Vinyl

Available in Clear
Material: PVC 12' lengths



Shown in Black (no longer available)


 Part #
 Finish
 120 Ft.
 600 Ft.
 1000 Ft.

 109-CL
 Clear
 \$0.56 ft.
 \$0.52 ft.
 \$0.47 ft.



Casing Trim





All cast trim sides can come apart for easy access to insert or remove signage



Cast trim with adhesive tape is shown attached to our 1" tubing

Casing Trim For 1/4" Panels 1" Base Available in Black or Nickel With Adhesive Tape Material: PVC 6' lengths





Part #	Finish	Price
CT8NC	Nickel	\$5.95 ft.
CT8BK	Black	\$5.95 ft.

Casing Trim for 1/2" Panels 1" Base Available in Black or Nickel With Adhesive Tape Material: PVC 6' lengths





Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
CT16NC	Nickel	PI	ease Inqu	ire
CT16BK	Black	Pl	ease Inqu	ire

Casing Trim for 3/4" Panels 1" Base Available in Black or Nickel With Adhesive Tape Material: PVC 6' lengths





rart#	rinisn	120 Ft.	OUU FL.	1000 Ft.
CT24NC	Nickel	PI	ease Inqui	ire
CT24BK	Black	Please Inqui		ire

For any quantities less than 120 ft. add 15% to the 120 ft. price

Material: Dupont™ Super Toughened Nylon Available in Black or Grey



Adjustable 2Way Connector

Material: PVC

15° Incremental locking from 90° to 180° for 1" Tubing

Part #	Finish	Each	10 Pcs.
FJ22BK	Black	\$8.47	\$8.06 ea.
FJ22GY	Grev	\$8.47	\$8.06 ea.



Adjustable 2Way In-Line Base Connector For 1" tubing to connect with another tube at multiple angles Material: PVC

Part #	Finish	Each	10 Pcs.
FJ31BH	Slack	\$12.94	\$12.33 ea.
FJ31G	/ Grev	\$12.94	\$12.33 ea.



Adjustable Tee Style Connector With Rotating Base Vertical/Horizontal For 1" Tubing Material: PVC

 Part#
 Finish
 Each
 10 Pcs.

 FJ32BK
 Black
 \$12.94
 \$12.33 ea.

 FJ32GY
 Grey
 \$12.94
 \$12.33 ea.

Adjustable 2Way Connector W/Locking Nut For 1"Tube



OF DIUS

 Part#
 Color
 Each
 10 Pcs.


 F52AJNBK
 Black
 \$4.84
 \$4.61 ea.

 F52AJNGY
 Grey
 \$4.84
 \$4.61 ea.

Aluminum Framing System

1-1/2" Heavy Duty Aluminum Tubing

Wall Thickness: 1/8" • Lengths: 8 Ft.





Part #	Finish	120 Ft.	600 Ft.	1000 Ft.
AT48-2CL-8	Clear Anodized	\$5.72 ft.	\$5.45 ft.	\$4.54 ft.
AT48-2BK-8	Black Anodized	\$6.29 ft.	\$5.99 ft.	\$4.99 ft.

Clear anodized finish is suitable for indoor and outdoor use. Black for indoor only.

For any quantities less than 120 ft. add 15% to the 120 ft. price

1-1/2" Tubing Connectors & Accessories

Material: Dupont™ Super Toughened Nylon Available in Black or Grey



2 Way Right Angle Connector

Part #	Color	Each	10 Pcs.
F48521BK	Black	\$6.62	\$6.30 ea.
F48521GY	Grey	\$6.62	\$6.30 ea.



3 Way Corner Connector



3 Way Tee

Connector

Part #	Color	Each	10 Pcs.
F48533BK	Black	\$9.00	\$8.57 ea.
F48533GY	Grey	\$9.00	\$8.57 ea.



 Part #
 Color
 Each
 10 Pcs.

 F48532BK
 Black
 \$11.36
 \$10.82 ea.

 F48532GY
 Grey
 \$11.36
 \$10.82 ea.

Connectors fit any 1-1/2" O.D. Aluminum or Steel Tubing with 1/8" wall thickness



Straight Connector

Part #	Color	Each	10 Pcs.
F48500GY	Grey	\$8.42	\$8.02 ea.
F48500BK	Black	\$8.42	\$8.02 ea.

End Cap



Material: Low-Density Polyethylene

Part #	Color	100 Pcs.	1000 Pcs.
SHK-48S-BK	Black	\$58.00/C	\$200.00/M



4 Way Connector

Part #	Color	Each	10 Pcs.
F48545BK	Black	\$13.78	\$13.13 ea.
F48545GY	Grey	\$13.78	\$13.13 ea.

Perpendicular Joiner/Splicer with 4 x #10 1-1/4" Long Self Tapping Screws



Part #	Color	Each	10 Pcs.
F485112MCBK	Black	\$3.68	\$3.51 ea.
F485112MCGY	Grey	\$3.68	\$3.51 ea.



PROTOTYPE SAMPLES

We are happy to provide samples for prototypes & design builds.
- Please Inquire


Great Wall PVC & Aluminum Slatwall System

UNIQUE INTERLOCKING DESIGN SECURELY FITS TOGETHER

Panel 11/32" thick

HERCULES HEAVY DUTY PANELS **Material: Aluminum**

Length: 6"x 8' • 3" on center



- 300 lbs. per sq. ft. load capacity
- Aluminum slatwall designed to interlock

with standard duty PVC slatwall (above) when extra strength is needed. Part # Finish Per Ft 120 Ft 600 Ft

ALU6969-S Satin \$9.91' \$9.76' \$8.88' ALU6969-M \$8.50' \$8.35' \$7.46' **FOR USE WITH ALL** ACCESSORIES IN THE **Material: PVC**

WH - White

SLATWALL HARDWARE SECTION

STRONG

STANDARD DUTY GREAT WALL PANELS

STANDARD DUTY PVC PANEL

HERCULES HEAVY DUTY PANEL

STANDARD DUTY PVC PANEL

Mix &

Матсн

Please

Inquire

For Garage

Hardware

- Panel 11/16" thick
- · 25 lbs. per sq. ft. load capacity

Part #	Size	Price
GRW-1X4-WH	1'x 4'	\$11.20 ea.
GRW-1X4-BK		\$11.20 ea.
GRW-1X4-AL		\$11.70 ea.
GRW-1X8-WH	1'x 8'	\$22.00 ea.
GRW-1X8-BK		\$22.00 ea.
GRW-1X8-AL		\$23.00 ea.



Lengths: 1'x 4' and 1'x 8' • 3" on center

(only Heavy Duty) Must be ordered in full boxes of 8 pcs. x 4 ft. or 4 pcs. x 8 ft.

HIGH DENSITY HEAVY DUTY GREAT WALL PANELS

- Panel 11/16" thick
- 100 lbs. per sq. ft. load capacity

Part #	Size	Price
GRW-HD1X4BX-WH		\$130.52 box
GRW-HD1X4BX-BK	1' x 4'	\$134.94 box
GRW-HD1X4BX-GY	8 pcs. per box	\$130.52 box
GRW-HD1X4BX-AL		\$130.52 box
GRW-HD1X4BX-MP		\$149.65 box
GRW-HD1X8BX-WH		\$130.52 box
GRW-HD1X8BX-BK	1' x 8'	\$134.94 box
GRW-HD1X8BX-GY	4 pcs. per box	\$130.52 box
GRW-HD1X8BX-AL		\$130.52 box
GRW-HD1X8BX-MP		\$149.65 box

Screws & Mouldings For Great Wall Panels

COLOR MATCH MOULDINGS Material: PVC • Length: 8'

Joint Trim Part # Price **GRW-JNR8-WH** \$2.75 ea. GRW-INR8-RK \$2.75 ea. **GRW-JNR8-AL** \$2.95 ea. **GRW-JNR8-MP** \$3.10 ea.

İ	← .67"→	↑
→	.79" —.89"→	.63"
		'

	End Cap	
	Part #	Price
<u> </u>	GRW-END8-WH	\$1.50 ea.
3"	GRW-END8-BK	\$1.50 ea.
Ľ	GRW-END8-AL	\$1.65 ea.
	GRW-END8-MP	\$1.75 ea.

Colors Available AL - Almond

BK - Black MP - Maple

COLOR MATCH SCREWS Material: Steel • Length: 2-1/2"


Part # 100 Pcs. 1000 Pcs. **GRW-2500SCR-*** \$16.00 box \$13.00 box

Screws packed 100 pcs. per box - No Broken Boxes


Slatwall Accessories

HANGMAN

Ticket Holder



Aluminum Slatwall 3/4" Thick Shelf Support Bracket



Clear Anodized



Works with 3/4" shelf

· Holds up to 12" deep shelf

 Load Rating: 20 lbs. per linear ft.



sizes available for extra cutting charge. A great way to improve your garage or slatwall systems.

Shelf Bracket _3/4" Shelf Size Finish




Part # Each HGSW-750-24-C 24"Long \$8.55 \$8.10 ea. \$7.65 ea. Clear HGSW-750-48-C 48"Long \$14.95 \$14.25 ea. \$13.75 ea. Anodized HGSW-750-96-C 96" Long \$2<u>8.50 ea.</u> \$2<u>7.00 ea.</u> \$30.95 HGSW-750-24-B 24"Long Black \$8.55 \$8.10 ea. \$7.65 ea. HGSW-750-48-B 48"Long Powder \$14.95 \$14.25 ea. \$13.75 ea. HGSW-750-96-B 96"Long \$28.50 ea. \$27.00 ea. Coated \$30.95

3 - HANG ON SLATWALL



MULTIPLE PANELS







- Join panels in thicknesses ranging from 1/8" to 3/4"!
- The Klem® connector makes it easy to create angles from 90° to 270°!
- Ideal for straight or curved walls, prisms, squares cubes, pyramids, domes or any type of display!
- Made of nickel plated zinc alloy and synthetic rubber inserts. The Klem[®] connector provides great strength and long term durability.
- Standard gap between panels

Mini: 1/2" **Super**: 3/4"

• To Close gap between panels, Notch the panels

Mini: 1/4" x 15/16" **Super**: 5/16" x 1-3/8"










SHOWCASE

PARTITION







MUSEUMS & GALLERIES



TRADE SHOWS

ANY PANEL! ANY ANGLE! ANY DISPLAY!

For panel thicknesses from 1/8" to 5/16"

1-19 Sets 20+ Sets 7123M-* \$14.18 set \$11.91 set

* Please specify panel size

2 = 1/8", **4** = 3/16", **6** = 1/4", **8** = 5/16"

Example: for 1/4" panels, Part# is 7123M-6



Gap Between Panels = 1/2"

SUPER |

For panel thicknesses from 1/4" to 3/4"

20+ Sets Part # 1-19 Sets 7123S-* \$22.00 set \$17.98 set

* Please specify panel size

6 = 1/4, "**10** = 3/8", **12** = 1/2", **16** = 5/8", **19** = 3/4" Example: for 1/2" panels, Part# is 7123S-12

2-7/16" 1-11/16 1-5/8"

Gap Between Panels = 3/4"

BODIES ONLY without inserts

MINI KLEM 7123M

1-19 Sets 20+ Sets \$10.19 ea. \$9.04 ea. Fits 3/4" Tubing

SUPER KLEM 7123S

1-19 Sets 20+ Sets \$16.03 ea. \$13.01 ea.

Fits 1-1/8" Tubing

BODY WITH LEVELING FOOT

MINI KLEM 7123M-LF

1-19 Sets 20+ Sets \$15.17 set \$14.11 set



SUPER KLEM 7123S-LF 1-19 Sets 20+ Sets \$21.19 set \$20.18 set

To be used with a single insert or tubing

MINI KLEM

\$2.98 pr.

0802PR = 1/8" 0804PR = 3/16" 0806PR = 1/4" 0808PR = 5/16" 1-19 Sets 20+ Sets

\$4.17 pr.



INSERT PAIRS ONLY SUPER KLEM

0206PR = 1/4" 0210PR = 3/8" 0212PR = 1/2" 0216PR = 5/8"

0219PR = 3/4" 1-19 Sets 20+ Sets

\$6.34 pr. \$4.68 pr.

BODY WITH TWIN WHEEL CASTER W/BRAKE

MINI KLEM 7123M-CSTR

20+ Sets 1-19 Sets \$20.55 ea. \$18.52 ea.



SUPER KLEM 7123S-CSTR 20+ Sets 1-19 Sets

\$23.15 ea.

Caster Diameter is 2" - Load Rating = 75 lbs per caster To be used with a single insert or tubing

SINGLE INSERTS ONLY

MINI KLEM 0802 = 1/8"

0804 = 3/16" 0806 = 1/4" 0808 = 5/16"

1-19 Sets 20+ Sets \$2.08 ea. \$1.54 ea.





SUPER KLEM 0206 = 1/4" 0210 = 3/8" 0212 = 1/2" 0216 = 5/8" 0219 = 3/4"

1-19 Sets 20+ Sets

To be used when connecting panels

BODY WITH WALL MOUNT

MINI KLEM 7123M-WM

1-19 Sets 20+ Sets

\$3.36 ea. \$2.54 ea.

\$19.96 ea.

To be used with a single insert or tubing

SUPER KLEM 7123S-WM 1-19 Sets 20+ Sets \$22.39 ea.

TUBING INSERTS ONLY

MINI KLEM 0713 1/2"ROUND TUBING 1-19 Sets







SUPER KLEM 0320 3/4"ROUND TUBING 1-19 Sets 20+ Sets \$3.09 ea. \$2.31 ea.

To be used when connecting tubes.

HEX KEY

MINI KLEM 0160

1-19 Sets 20+ Sets \$1.28 ea. \$1.22 ea.



SUPER KLEM 0170 1-19 Sets 20+ Sets \$1.28 ea. \$1.22 ea.

MINI KLEM 7123M-NB

1-19 Sets 20+ Sets \$0.36 ea. \$0.30 ea.



SUPER KLEM 7123S-NB 1-19 Sets 20+ Sets

\$0.66 ea. \$0.60 ea.









MANY CONNECTION OPTIONS!







Fastmount Panel Mounting Systems







This revolutionary panel mounting system will work with a wide range of panel sizes and materials. Unlike traditional Z bar and panel clips, this system can be utilized for ceiling and wall panels.


Panels are installed head-on and can be affixed in any sequence, ultimately saving the installer time and money.

There are 3 systems to choose from:

Standard Profile


- Maximum panel weight: Up to 88 lbs. for wall panels. Up to 66 lbs. for ceiling panels.
- Support substrate should be 9/16" or thicker
- Easily installed with the CT-08 tool kit
- Can be used in ceiling applications in conjunction with the panel control system, see page S-110.
- For use with steel, wood, plywood and MDF frames






Low Profile

- Maximum panel weight: Up to 88 lbs. for wall panels.
- Support substrate should be 3/8" or thicker
- · Easily installed with the LP-08Y tool kit
- Ideally suited for drywall applications when LP-DF8 is used, see page S-109.



Very Low Profile

- For lightweight panels/light duty applications
- No minimum support substrate thickness because female clips can be surface mounted
- Easily installed with 2-part epoxy and the center point alignment tool
- Perfect for mounting removable panels and facing such as wall panels, headboards and inspection panels
- Ideally suited for mounting panels where no drilling is preferred









Fastmount Panel Mounting Systems

Standard Profile

- Maximum panel weight: Up to 88 lbs. for wall panels.
 Up to 66 lbs. for ceiling panels.
- Support substrate should be 9/16" or thicker
- Easily installed with the CT-08 tool kit
- Can be used in ceiling applications in conjunction with the panel control system, see page S-110.
- For use with steel, wood, plywood and MDF frames









SUGATSUNE


Female clips for Standard Profile are mounted to the support substrate. Choose from these 4 options:


Standard Self-Tapping




PC-F1 \$0.85 ea.

- Best option for most applications. Must be used for 9/16" or thicker substrates.
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- 16.8mm (.66") hole drill required. Install with CT-08 tool kit, see page S-110.








Surface Mount



PC-SF1 \$0.85 ea.

- Can be used with thinner support materials such as steel frames.
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- Affix with #6 screws





Side Surface Mount



PC-RF1-B \$0.85 ea.

- Ideally suited for corner detail at cabinet, shelf or cabinet floor, (Not for use on actual flooring).
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- · Affix with #6 countersunk screws






Auto Fit



PC-AF1 \$1.87 ea.

- Ideally suited for curved panels. Lateral adjustment provides perfect panel alignment and secure mounting.
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- Affix with #6 countersunk screws



Fastmount Panel Mounting Systems

Standard Profile





Male clips for Standard Profile are mounted to the panel. Choose from these 6 options:

Standard Self-Tapping




- Mounts into 3/8" hole
- 11 lb. Pull out force

• Install with CT-08 tool kit, see page S-110.

PC-M1B

\$0.85 ea.




Heavy Duty Self-Tapping



- Mounts into 3/8" hole
- 22 lb. Pull out force
- Install with CT-08 tool kit, see page S-110.

PC-M2H \$1.02 ea.





Vario Standard Self-Tapping



- Mounts into 3/8" hole
- Variable gap 1/8"~1/4"
- 11 lb. Pull out force
- Install with CT-08 tool kit, see page S-110.

PC-VM1 \$1.02 ea.







Vario Heavy Duty Self-Tapping



- Mounts into 3/8" hole
- Variable gap 1/8"~1/4"
- 22 lb. Pull out force
- Install with CT-08 tool kit, see page S-110.

PC-VMX \$1.35 ea.






Surface Mount



- Mounts with 2-part epoxy
- 11 lb. Pull out force
- Affix using a 2-part epoxy adhesive

PC-SM2 \$0.85 ea.




Heavy Duty Surface Mount



- Mounts with 2-part epoxy
- 22 lb. Pull out force
- Affix using a 2-part epoxy adhesive

PC-SM2H \$1.02 ea.



Fastmount Panel Mounting Systems

Low Profile

- Maximum panel weight: Up to 88 lbs. for wall panels.
- Support substrate should be 3/8" or thicker
- · Easily installed with the LP-08Y tool kit
- Ideally suited for drywall applications when LP-DF8 is used, see page S-109.









Female clips for Low Profile are mounted to the support substrate. Choose from these 3 options:


Self-Tapping

- Ideally suited for plywood and MDF boards 3/8" or thicker
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- · Mounts into 1" hole
- Install with LP-08Y tool kit, see page S-110.












Self-Tapping Coarse Thread



- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.

LP-DF8 \$0.77 ea.






Auto Fit

- Ideally suited for curved panels 7/16" or thicker
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see page S-110.
- · Lateral adjustment provides perfect panel alignment and secure mounting.
- · Affix with #4 countersunk screws

LP-AF8 \$1.96 ea.




Male clips for Low Profile are mounted to the panel. Choose from these 2 options:

Self-Tapping



- Mounts into 3/8" hole
- 11 lb. Pull out force
- Install with LP-08Y tool kit, see page S-110.






Surface Mount



- Affix with #4 screw or a 2-part epoxy adhesive
- 11 lb. Pull out force
- Install with LP-08Y tool kit, see page S-110.



Fastmount Panel Mounting Systems

Very Low Profile





- · For lightweight panels/light duty applications
- No minimum support substrate thickness because female clips can be surface mounted
- Easily installed with 2-part epoxy and the center point alignment tool
- · Perfect for mounting removable panels and facing such as wall panels, headboards and inspection panels
- Ideally suited for mounting panels where no drilling is preferred

Female clips for Very Low Profile are mounted to the support substrate. Male clips are mounted to the panel. Choose from these 2 clip sets:

Standard Male/Female Clip Set




VL-03 Pull out Force: 11 lbs. \$1.11/set

Heavy Duty Male/Female Clip Set





VL-03H Pull out Force: 22 lbs. \$1.42/set

- Surface or recess mount into 1"hole
- Can be installed with included stainless steel screw or affixed with 2-part epoxy glue
- CP Stainless Steel tip accessory works with female clips and used to mark hole center in panel for correct clip alignment, see below.



Male Clip





Accessories

Installation Tool Sets include carbide tipped drill bits, installation tools, panel removal tool. (*Required for 1st purchase*)




Use with: Standard Profile \$280.50/set



LP-08Y Use with: Low Profile \$144.50/set


to provide additional security and control. This allows for convenient service behind the panel or controlled removal of the panel by releasing the wire. The drop length for this stainless steel cable is 5-7/8".

Panel Control System used in conjunction with standard profile clips





PS-S150E Use with: Surface Mount Standard Profile \$28.90/set



Stainless Steel Center Point Tip works with female clips and used to mark hole center in panel for correct clip alignment. *(Optional)*



CP-01ST Use with: Standard Profile \$6.80 ea.



CP-08ST Use with: Low Profile \$6.80 ea.



VL-CP3 Use with: Very Low Profile \$8.25 ea.

Striplox

STRIPLOX

Fully Concealed Hidden Joining System

- Material: Glass Reinforced Nylon
- UV and Fire Rated
- Guaranteed to save on production time and labor costs because it's easy to install and you do not need to wait for glue to dry.
- Units can ship knock down. Less money will be spent on transportation.
- Reduce inventory levels on other fastening components when you switch to this system. Very cost effective and requires less fasteners.
- There is no need to buy expensive new tooling because this system allows you to use standard router, screw drivers or CNC machine.





Striplox Pro 23



Striplox Pro 55



This connector has over 100 uses and can be used in a variety of applications ranging from large scale Architectural projects to hanging artwork or building floating shelves

Striplox Clip 50



Designed for small and precise applications, while providing a secure connection in the tightest of places.

Striplox Mini 60



Striplox Mini 120



Allows the user to create fully concealed joints.

Striplox 90D 98



Designed to quickly and easily connect any right angle, miter box and flush joints.

Striplox 180D



Allows you to easily join tables together at conference venues and restaurants in less then a minute.

Striplox Griplox



Is a great alternative to traditional wood biscuits.

No more glue, no more waiting time and no more bulge.

Striplox Megalox



Megalox is ideal for bench, table top installations with mitre joints, T joints or box joints.

Striplox



Striplox Pro 23 & 55

- Type of Application: Ceiling panels, acoustic panels, timber battens, floating shelves, furniture, bookcases, mirrors, RV and marine, exhibition/tradeshow events, shop fitting displays and signage.
- **Connection:** Male and female, ideally male is mounted to the wall, ceiling or other surfaces.
- Designed for panels, frames or components. This hidden mounting system delivers a flawless finish with a perfect alignment every time.
- Very strong and durable and will support the load capacity evenly over the entire product.
- Cabinetry or panels can be fitted permanently or removed and re-used with ease.
- 2 sizes to choose from with slim design for easy concealment.
- Mounting Options: Horizontal, Vertical and Ceiling Mount
- Board or Panel Materials To Use: Solid Wood, MDF, Composite Materials, Aluminum, Acrylic and More
- Lock Tab: Lock tab for permanent mounting or remove when repeated access is needed.

Part #	Description	Color	Price
SPX-P23	Striplox Pro 23	Black	\$2.20 ea.
SPX-P55	Striplox Pro 55	Black	\$3.45 ea.


See Mounting Accessories On Page S-114

Striplox Pro 23



- Lift Clearance (Direction of Travel): 1/2" (12.7mm)
- Projection- Surface Mounted: .38" (9.5mm)
- Projection- Recessed Mounted: Sits flush against the wall
- Projection- Set Back Mounted: .08" to .30"
- Size of Screws: #8 x 5/8"
- # of Screws: 5 pieces
- Screw Adjustment: Yes
- 32MM Compatible

Striplox Pro 55



- Lift Clearance (Direction of Travel): 3/4" (19mm)
- Projection- Surface Mounted: .50" (12.8mm)
- Projection- Recessed Mounted: Sits flush against the wall
- Projection- Set Back Mounted: .15" or .35"
- Size of Screws: #8 x 5/8"
- # of Screws: 16 pieces
- Screw Adjustment: Yes32MM Compatible
- ·


Striplox Clip 50

- Type of Application: Wall, cabinetry, commercial panels, acoustic panels, signage, exhibition & shop fitting.
- Connection: Male and female, ideally male is mounted to the wall, ceiling or other surfaces.
- Its unique design allows you to mount your products to uneven walls.
- · Can be screw or glue mounted.
- \bullet Stronger then many panel mounting options on the market today.
- Mounting Options: Horizontal, Vertical and Ceiling Mount
- Board or Panel Materials To Use: Solid Wood, MDF, Composite Materials, Aluminum, Acrylic and More
- Lock Tab: Lock tab for permanent mounting or remove when repeated access is needed.
 - Lift Clearance (Direction of Travel): 1/4" (6.4mm)
 - Projection- Surface Mounted: .38" (9.5mm)
 - Projection- Recessed Mounted: Sits flush against the wall
 - Projection- Set Back Mounted: .125" to .25"
- Size of Screws: #8 x 5/8"
- # of Screws: 4 pieces
- 32MM Compatible

Part #	Color	Price
SPX-C50	Black	\$2.41 ea.

See Mounting Accessories On Page S-114





Striplox

STRIPLO

Striplox Mini 60 & 120

- Type of Application: Commercial, domestic and architectural furniture, wardrobe closets, cabinetry, framing of artwork and mirrors, RV and marine fit outs and locker room.
- Connection: Male and female mortised into position.
- · Replaces the need to use biscuit joints, fasteners or cam dowels. This saves time on labor with a quick and easy install. Completely hidden joint.
- The connectors produce a tight and strong joint either in permanent or reversible applications.
- · Will not interfere with substrate finishes, such as veneers and paint.
- · Mounting Options: Horizontal, Vertical and Lock Up Mount
- Board or Panel Materials To Use: Solid Wood, MDF and Other Composite Materials

Part #	Description	Color	Price
SPX-M60	Striplox Mini 60	Black	\$1.15 ea.
SPX-M120	Striplox Mini 120	Black	\$1.85 ea.

See Mounting Accessories On Page S-114



- Lock Tab: Lock position is a click, no tab to remove.
- Board Depth: .394"

- Striplox Mini 60
 - Lift Clearance (Direction of Travel): 5/16" (8mm)
 - Projection- Recessed Mounted: Fully Concealed Joints



- Lock Tab: Lock tab for permanent mounting or must be sanded off or sliced off with a utility knife.
- Board Depth: .394'
- Lift Clearance (Direction of Travel): 7/16" (11mm)
- Projection- Recessed Mounted: Fully Concealed Joints



Striplox 90D 98


- Type of Application: Bulk head and kickboard, furniture, shop fitting displays and signage, exhibition and tradeshow events.
- Connection: Male and female, ideal male is mounted to the wall ceiling or other surface. Surface mounted ideal for any right angle.
- This patented design pulls the substrate firmly together to form a strong and tight joint in one simple action by distributing the loads evenly over the entire connector and joint.
- The joint is not visible once the cover is snapped into place.
- · Can create a perfect 90 degree angle.
- Mounting Options: Horizontal, Vertical and Side Mount
- Board or Panel Materials To Use: Solid Wood, MDF and Other Composite Materials
- Lock Tab: Cannot be removed, but can be overridden when you start the connection from the beginning of the clip.

	Part #	Color	Price
Δ	SPX-90DBK	Black	\$3.45 ea.
Α	SPX-90DWH	White	\$3.45 ea.
В	SPX-90DBK-51	Black	\$.95 ea.

See Mounting Accessories On Page S-114

- Lift Clearance (Direction of Travel): 11/16" (17mm)
- Projection- Surface Mounted: 1"
- Size of Screws: #8 x 5/8 • # of Screws: 6 pieces
- · 32MM Compatible






4.53

Striplox Griplox

- Type of Application: Anywhere traditional wood biscuits are used.
- Connection: Knock in (no glue required) std NO.20 biscuit slot.
- Easy to install, use standard biscuit cutter and simply knock in with a hammer.
- Unique gripping spikes on the front and back secure your project in place without glue.
- · Mounting Options: Horizontal & Vertical
- Board or Panel Materials To Use: Solid Wood, MDF and Other Composite Materials

lor Price
ick \$.30 ea.

- Board Depth: .394"
- Projection- Recessed Mounted: Fully concealed joints





Striplox



Striplox 180D

- Type of Application: Conference room tables, kitchen and benchtop tables, workstations, retail displays, signage and large exhibition displays.
- Connection: Male and female, ideally male is mounted to the wall, ceiling or other surfaces.
- Primarily used when you need to join items at 180 degrees.
- · Can be used even when board is already laminated.
- Very secure connection. The round disc locks closed by hand. Some force is required to unlock.
- Mounting Options: Horizontal, Vertical and Under Mount
- Board or Panel Materials To Use: Solid Wood, MDF and Other Composite Materials
- Lock Tab: Must add a screw in designated hole to make permanent.

Part #	Color	Price
SPX-180D	Black	\$7.83 ea.

- Projection- Surface Mounted: 1/2"
- Size of Screws: #8 x 5/8"
- # of Screws: 6 pieces
- 32MM Compatible





Striplox Megalox


See Mounting Accessories Below

- Type of Application: Bathroom, office, toilet or locker room partitions and bench top waterfalls.
- Connection: Male and female mortised into position.
- When creating a waterfall, saves time and because there is no glue to dry.
- · Will allow you to create a perfect alignment.
- Can support heavy panels, 650 lbs. when used vertically.
- Mounting Options: Horizontal, Vertical and Lock Up Mount
- Board or Panel Materials To Use: Solid Wood, MDF and Other Composite Materials
- · Lock Tab: Lock tab for permanent mounting or must be sanded off or sliced off with a utility knife.
 - Board Depth: 3/4"
 - Projection- Recessed Mounted: Fully concealed joints
 - Size of Screws: #8 x 5/8'
- # of Screws: 6 pieces
- · Screw Adjustment: Yes
- · 32MM Compatible

Part #	Color	Price
SPX-MEG	Black	\$4.75 ea.

See Mounting Accessories Below





Accessories

Liquidlox Adhesive 20G

General purpose, middle viscosity, fast cure adhesive

Part #	Price
SPX-ADH	\$12.39 ea.

Router Bits

Part #	Size	Price
SPX-7RB	7mm	\$12.39 ea.
SPX-10RB	10mm	\$12.39 ea.

Grivoly Jig Set


Adds speed to install & helps determine install of hardware

Part #	Size	Price
SPX-P23-JIG	Pro 23	\$7.23 ea.
SPX-C50-JIG	Clip 50	\$7.08 ea.
SPX-P55-JIG	Pro 55	\$7.67 ea.


Striplox Template

Adds speed to install & helps determine install of hardware

Part #	Price		
SPX-TEMP	\$18.65 ea.		







ILLUMINATED SURFACES

Auragami is ideally suited for onyx, quartz and many manufactured materials into lit counter and bar tops, curved surfaces and low clearance applications.

This light sheet provides extremely uniform illumination with as little as 3/8" installation depth for countertops.

Specs

- •24V • IP65
- UL Listed
- E II D:
- Fully Dimmable
- Natural White (5300K)
- 9.25" x 19.8" Sheet Which Is Cuttable As Small As 5/8" x 5/8" Square



CUTTABLE

A low voltage UL Listing allows for on-site customization which can eliminate custom order lead times. Cut LEDs from any part of the sheet to avoid obstacles without interrupting power to the rest of the sheet, while maintaining UL Listing. When discrepancies occur between drawing specs and field measurements or when changes need to be made, on-site customization avoids delays!



Connect

Auragami sheets interconnect quickly and easily with included sheet-to-sheet connection wires. Connect up to eight sheets in any arrangement while operating within Class 2 guidelines. Integrated 2-pin connection blocks eliminate the need to solder and speed installation.













LED Lighting


Auragami Flexible LED Sheet


Panel Size: 9.25" x 19.8"

Material: Polyimide with a Conformable Coating Layer (Silicon Based)









Duico

		# Of LED	Total	Max # Can	Price	
Part #	Dimension	Chips	Wattage	Connect	Each	10+ Pcs.
BLS-AU-NW	9.25" x 19.8" (1.27 sq. ft.)	420	12	12 Sq. Ft.	\$100.37 (\$79.00 sq. ft.)	\$93.98 ea. (\$74.00 sq. ft.)

Included with Each Sheet: A: 4-.71" Sheet-To-Sheet Connection Wires B: 4-3.74" Sheet-To-Sheet Connection Wires C: 1-24" Power Connection Lead Wire D: 2-Wago Connectors For Wires With Same Polarity E: 4- Cable Management Clips with Silicone Adhesive Backing F: 8- Domed Spacing Bumpers with Silicone Adhesive Backing


IP65 Auragami

Provides Protection From Dust & Splashing Water, Not Submersible

Lighting Specifications


Color Temperature	5300K
Beam Spread	120°
Lumens	860 sq. ft.
Color Rendering Index	95+
Rated Average Life	50,000 hrs.
Power Input	Constant Voltage
Chip Size	2835

AURAGAMI SAMPLE KIT AVAILABLE, PLEASE INQUIRE (BLS-AU-KIT)



Required

Power Supplies (IP20)



							F	Price
Part #	Type	Finish	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	Black	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	Black	4A	24V	96W	6.77"L x 2.83"W x 1.48"H	\$44.05	\$39.90 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable

Required for power supplies, dimmers & multi output cables.



		Overali			rice
Part#	Description	Length	Finish	Each	10+ Pcs.
BLS-PWL	Connects from power supplies, dimmers & multi output cables to light panel	12"	White	\$1.50	\$1.25 ea.

Optional

Dimmers



			Range of			Price	
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.	
LED-INLINE-DIM-WH	Inline Rotary	White	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
For Product Details & More Dimmer Options. See Pages L-134~136 & L-142~144							

Other Options: Rotary | Touch Dimmer | Radio Frequency


Duica





Customized lighting solutions are just a "SNAP" away with the Quadmod Panels.
Sold in 12" x 12" squares, the razor-thin (1.65mm thick) panels can be snapped down to 3" x 3" squares.

Backlighting your signs or surfaces requires just 1"-2" separation between panel and surface being illuminated (depending on the substrate density) for even illumination.





24V & Fully Dimmable

Offered In 6500K


Easy to use connectors & accessories make installation fast & simple


Limited 3 Year Warranty






End-to-end connection using our simple DIY connectors and connecting cables. (no soldering necessary)
Can connect up to 12 panels on one power supply.











Achieve versatile sizes & shapes





(No Soldering)

900 Lumens Per Sq. Ft.

Material: Aluminum With White Powder Coating

IP 20

Black Rubber Feet On Back Aid In Mounting Stability & Heat Dissipation











Quadmod LED Lighting Panel


Panel Size: 12" x 12"- Can "Snap" To 3" x 3" Material: Aluminum with White Powder Coating






IP20 Quadmod
Provides Low Protection of Dust & Water

Back Black rubber feet aid in mounting stability & heat dissipation







2 Mounting Options "Snap" In 3" Increments

Mounting Clips



		# Of LED	Total	Max # Can _	P	rice
Part #	Dimension	Chips	Wattage	Connect	Each	10+ Pcs.
QM-1212-CW	12" x 12"	96	8	12 Sq. Ft.	\$52.00	\$48.00 ea.

QUADMOD SAMPLE KIT AVAILABLE, PLEASE INQUIRE (QM-KIT)
OTHER COLOR TEMPERATURES AVAILABLE, PLEASE INQUIRE MINIMUMS APPLY

Lighting.	pecifications
Color Temperature	6500K
Beam Spread	120°
Lumens	900 sq. ft.
Color Rendering Index	80
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	4014











LED Lighting

Accessories for Quadmod LED Lighting Panel



Required

Power Supplies (IP20)



							F	rice
Part #	Type	Finish	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	Black	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	Black	4A	24V	96W	6.77"L x 2.83"W x 1.48"H	\$44.05	\$39.90 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable Required for power supplies, dimmers & multi output cables.



		Overall		F	Price
Part #	Description	Length	Finish	Each	10+ Pcs.
QM-PWL12	Connects from power supplies, dimmers &	12"	White	\$5.00	\$4.50 ea.
QM-PWL39	multi output cables to light panel	39"	White	\$6.00	\$5.50 ea.

Optional

<u>Dimmers</u>



Range of				F	Price		
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.	
LED-INLINE-DIM-WH	Inline Rotary	White	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144							

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144

Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables



			Arms	# of	Overall	Max # of Power	I	Price
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-5OUT-CBL-WH	5-Way Sweep	White	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.

For More Extension Cable Options, See Page L-147

Power Extension Cables



Part #	Description	Finish	Length	Each	10+ Pcs.
QM-EXT39	Allance the adesign on the material and it waste and	White	39"	\$6.00	\$5.50 ea.
QM-EXT79	Allows the designer to get around unlit areas without multiple power supplies	White	79"	\$8.00	\$7.50 ea.
QM-EXT118	without multiple power supplies	White	118"	\$11.00	\$10.25 ea.

Connecting Cables



Pa	rt#	Description	Finish	Length	Each	10+ Pcs.
QM-	CC03		White	3″	\$2.00	\$1.50 ea.
QM-	CC10	Allows the designer to get around unlit areas	White	10"	\$4.00	\$3.25 ea.
QM-	CC24	without multiple power supplies	White	24"	\$6.00	\$5.25 ea.
QM-	CC48		White	48"	\$8.00	\$7.25 ea.

Direct ConnectorSold 10 pieces per bag



			Price For	Bag of 10
Part #	Description	Dimensions	Each Bag	10+ Bags
QM-DCC	Female to Female connect end-to-end	1/2" L x 3/8"W x 1/4"H	\$4.75	\$4.00 ea.

Price

Price



Nova Backlighting System

The Original Edge Lite Panel



The Nova Backlight System can be customized per order for a wide variety of applications



- Material: Optical Grade PMMA Acrylic
- Super bright and long lasting up to 70,000 hours
- Integrated thermal management will ensure maximum life span and even illumination throughout
- Limited 3 Year Warranty



The Nova sheet can be custom manufactured in most sizes, shapes & light color options

Ceiling

Durable... Strong



Illuminate Any Translucent Material



Wallscapes
Less Build Up... Save Time & Money
No Frame or Housing

Even Illumination... No Dark Spots
Substrate can lay directly on the Nova sheet panel



Nova Backlighting System


Material: Optical Grade PMMA Acrylic

THE TECHNOLOGY

Nova sheet utilizes a patented 3-D v-groove etched grid pattern to create a bright and uniform illumination across the entire surface of the panel.


The Nova sheet utilizes superior quality 12V constant voltage LED's. The LED's are integrated into the perimeter of the panel without the use of framing materials.


The built in heat sink will ensure that the panel will last the life span, 70,000 hours!



LED LIGHT COLOR OPTIONS









Maximum Panel Size Length Max: 118" (2997mm) (mum44+721), 66 Was was well as required, subject to the configuration of the LED's or the back of the panel






ILLUMINATING OPTIONS











Nova Backlighting System

Material: Optical Grade PMMA Acrylic

FACE OPTIONS






Application Options

- A wide variety of accessory options are available, See Page L-11.
- Environment: Dry environments are standard but if needed for a wet location, then please inquire further
- Quoting Requirements: DXF (CAD) and/or PDF drawings with dimensions and wire locations labeled must be provided

BRIGHTNESS

2,000 to 10,000 Lux- Readings will vary with panel size & design


24" x 48" Sheet with 5300K LED's Lit Along 2 Edges (30W)



12" x 12" Sheet with 5300K LED's Lit Along 2 Edges (8W)




48" x 96" Sheet with 5300K LED's Lit Along 2 Edges (60W)



MOUNTING OPTIONS


Screw Mounting with Pre-Drilled Holes Mounting with Mirror Clips



Detailed Dimensions From Customer Required

Mounting with Z-Clips

Fabric Frame Option Available: Please Inquire




POWER CORD EXIT


Power Cord Exits From Short Side Edge Corner



Power Cord Exits From Middle of Each Long Side



Power Cord Exits From The Back Side



Recessed Notched **Power Cord Exit**





Accessories for Nova Backlighting System

Material: Optical Grade PMMA Acrylic

POWER SUPPLIES









DIMMERS

RF Dimmer with Remote (Plug In: Up To 60W)







Magnetic Dimming Power Supply Hardwire: 60W & 150W

Lutron Diva Sliding Dimmer



CONTROLLERS







Color Changing Temperature




For Turnable (CCT) White Only

SPIDER CABLES











SAMPLE KITS



1 pc. of Cool, Warm White & Pure White 10" x 8 " Sample with 1A Power Supply Part#: NOVA-5AMP-KIT Price: \$169.00 ea.



10" x 8" Sample with 1A Power Supply Part#: NOVA-SAMP108-*-P Price: \$59.00 ea.



10" x 8" Sample with 1A Power Supply & Dimmer Part#: NOVA-SAMP108-*-D



10" x 8" RGB Sample with 1A Power Supply & RGB Controller Part#:

Part#: NOVA-SAMP108-RGB-K Price: \$89.00 ea.



10" x 8" CCT Sample with 1A Power Supply & CCT Controller

Part#: NOVA-SAMP108-CCT-K Price: \$245.00 ea.

Price: \$69.00 ea. Price: \$8
Cool White (*CW), Pure White (*PW) & Warm White (*WW)



This light guide sheet was designed for edge lit illumination formulated with evenly dispersed illuminating (Pixie Dust) particles.



Framing Options (Required)

Thickness	U Channel	Angled	LED Ribbon	Aluminum Tape
of Acrylic	Recommended	Recommended	Recommended	Recommended
.157"		A1114 40 *	SPT12-*-30*-*-CW	LED-ALUTAPNC-375
.157"		ALU149-*	SP112-*-30*-*-CW	LED-ALUTAPNC-3/3
.236"	ALU257-*	A	SPT12-*-30*-*-CW or	LED-ALUTAPNC-375
.236"	1991-*	ALU149-*	SPT12-*-3560-*-RGB	LED-ALUTAPNC-3/5







Available Lengths: 2' x 2' & 2' x 4' Sheets *Material: Clear Acrylic*

SINGLE OR DOUBLE SIDED

- Crystal clear when illumination is off
- Can run any temperature of white or RGB
- Made with embedded diffuser particles to deflect and evenly emitted the light across the surface
- Can be machined, drilled, threaded and routed with standard equipment such as circular saws, drills and band saws
- Can easily be cut using a 3/32" carbide tipped blade with 5-6 teeth per inch, no polish req'd
- Edges can be flame polished or sanded with wet/dry 600 grit sandpaper for desired edge
- 4mm: Ideal for small applications, signage
 & shelving
- 6mm: Ideal for larger applications, signage, wall art & countertops
- Other sheet sizes available, please inquire

		Illumination		
Part #	Thickness	Distance	Size	Price
MLS-2424-157	4mm	up to 12"	2' x 2'	\$44.00 ea.
MLS-2448-157	(.157")	single side	2' x 4'	\$88.00 ea.
MLS-2424-236	6mm	up to 18"	2' x 2'	\$63.67 ea.
MLS-2448-236	(.236")	single side	2' x 4'	\$127.33 ea.





FREE Sample Kit

MLS-FSK (4mm)
MLS-FSK-236 (6mm)

Includes the following:

- Small piece of Magic Backlight Sheet
- Small piece of 3014 LED Ribbon
- Small piece of L-TASK-149 Aluminum Channel



Self Adhesive White Backer (Optional)

- 5' wide rolls
- 5' square ft. minimum

MLS-BACKER
Per Sq. Ft.: \$1.25

3M™ Wetordry™ Sandpaper (Optional)



- Used to polish edges
- 600 Grit
- 9" x 11" Sheet
- Can be used wet or dry

LED-ALUTAPNC-375

MLS-SAND-600 5 Pack: \$8.23

У

Foil Tape (Optional)

- Function: To Prevent light from escaping, thus providing maximum brightness
- Non conductive tape
- 3/8" x 10' per roll **Per Poll• \$**3

Eav. 1 900 999 2215

Per Roll: \$22.00



DIY: Brite Light Sheet

An inexpensive way to create Light Guide Panels



For Just

Part#: BLPS-1248

\$2.95 per sq. ft.


Brite Light Sheet is an optical PVC film with dot matrix designed to disperse light evenly across your acrylic panel


- The most affordable way to create DIY backlighting
- Sold in nominal 4 ft. x 25 ft. rolls... Can be shipped via UPS
- Easy to install... The Brite Light Sheet adheres to any acrylic or glass surface
- Zero gap clearance allows for heavy loads
- Low tack resistance enables the Brite Light Sheet to be easily removed and repositioned as desired without damage to the Light Guide Sheet
- Ideal for one sided small signs and shelving.
 When lit with 2 edges of LED's will illuminate evenly up to 14" in width

Framing Options (Required)

Thickness of Acrylic	U Channel Recommended	Angled Recommended	LED Ribbon Recommended	Aluminum Tape Recommended
1/8" 1/8"	ALU757-* 132-*	ALU149-*	SPT12-*-30*-*-CW	LED-ALUTAPNC-375
3/16" 3/16"	R104-582* 2325-*	ALU149-*	SPT12-*-30*-*-CW	LED-ALUTAPNC-375
1/4" 1/4"	ALU257-* 1991-*	ALU149-*	SPT12-*-30*-*-CW or SPT12-*-3560-*-RGB	LED-ALUTAPNC-375
3/8" 3/8" 3/8"	ALU57-* 383-* 2317-*	ALU269-* or ALU249-*	SPT12-*-30*-*-CW, SPT12-*-3560-*-RGB or ECO12-*35-*	LED-ALUTAPNC-375









FREE Sample Kit

BLPS-FSK

Includes the following:

- Small piece of acrylic
- 6" square of Brite Light Sheet
- 5" piece of 3014 LED Ribbon (works with any 12 volt transformer)

18.11.18

Foil Tape (Optional)

- Function: To Prevent light from escaping, thus providing maximum brightness
- Non conductive tape
- 3/8" x 10' per roll

LED-ALUTAPNC-375

Per Roll: \$22.00

BLPS-KIT

Includes the following:

- 2 ft. of 12V *Ultra* Brite LED Ribbon (Cool White, 3014 Chip)
- 2 ft. of 12V **Standard** Brite LED Ribbon (Cool White, 3014 Chip)
- 1 ft. x 2 ft. of Brite Light Sheet
- 1 piece of 2 ft. Aluminum Channel (*L-Task-149*)
- 1 Power Supply

Deluxe Kits

\$29.00 | BLPS-KIT-DIM

Includes the following:

- 2 ft. of 12V *Ultra* Brite LED Ribbon (*Cool White, 3014 Chip*)
- 2 ft. of 12V Standard Brite LED Ribbon (Cool White, 3014 Chip)
- 1 ft. x 2 ft. of Brite Light Sheet
- 1 piece of 2 ft. Aluminum Channel (L-Task-149)
- 1 Power Supply
- 1 Inline Dimmer










Triflex Flexible LED Sheet



Material: Flexible PCB with Copper Base

• Economical way to light up signs or translucent material

• Trimmable down to 2" x 4" pieces

· Connect up to 4 panels together • Requires 1-1/2" depth for NO HOT SPOTS

· Limited 3 Year Warranty








Per Sq. Ft.





IP54 Triflex Protection Against Dust

& a Fair Amount of Protection **Against Splashing Water**

Lighting Specifications

Color Temperature	6500K
Beam Spread	120°
Lumens	1710 sq. ft.
Color Rendering Index	85+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	2835

		-		TL		1 0 0 0 0 0 0 0 0 0 0 0
		# Of LED	Total	Max # Can	1	Price
Part #	Dimension	Chips	Wattage	Connect	Each	10+ Pcs.
BLS-TFX-CW	12" x 24" (2 sq. ft.)	108	26	8 Sq. Ft.	\$118.00 (\$59.00 sq. ft.)	\$110.00 ea. (\$55.00 sq. f




Required



Required

Power Supplies (IP20)



Part # Type Finish Amps Volts Watts Dimensions	Each 6+ Pcs.
LED-24V-3A Desktop Black 3A 24V 72W 4.68"L x 2.34"W x 1.48"	H \$28.75 \$26.05 ea.
LED-24V-4A Desktop Black 4A 24V 96W 6.77"L x 2.83"W x 1.48"	H \$44.05 \$39.90 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable Required for power supplies, dimmers & multi output cables.



		Overall			Price
Part #	Description	Length	Finish	Each	10+ Pcs.
BLS-PWL	Connects from power supplies, dimmers & multi output cables to light panel	12"	White	\$1.50	\$1.25 ea.

Optional

Connecting Cables



Part #	Function	Finish	Length	Each	10+ Pcs.
BLS-CC01	Is to allow the designer to get around unlit	White	1″	\$0.75	\$0.50 ea.
BLS-CC24	areas without multiple power supplies	White	24"	\$1.50	\$1.00 ea.

Price





Plug & Play ★ Waterproof ★ Dimmable

No Amplifiers or Power Supply Needed * Up To 165' Can Be Run From One Power Cord



Ideal For... Deck • Path Lighting • Building Outlines







Standard 120V



EASY TO USE



Hardwire To Wall Switch







Lighting Specifications

120°

Color Rendering Index

Constant

Chip Size

Rated Average Life

CW: 6500K WW: 3000K

30,000 hrs.

Voltage

2835

Our MAXX LED Light products are ETL certified and warranted as non-cuttable. If a customers does cut the product, they do so at their own risk.

MXL60-28-*: 152 per ft. MXL140-28-*: 320 per ft.



MAXX LED Light (Indoor/Outdoor): No Power Supply Needed!

Can Run Up To 164 Ft. On One Power Cord Available Lengths: 33', 82' & 164'

Material: Flexible PVC


- Ideal for applications in which longer lengths are desired
- Includes a factory sealed 2' power cord & end cap
- Consistent binning/color
- Field cuttable every 20" nominal and connectable
- Dimmable
- · Limited 2 Year Warranty



• 1/4"

Standard (Up To 152 Lumens Per Foot / 2835 Chip 60 Pcs/Meter)

D12 R5 D13



Ultra Bright (Up To 320 Lumens Per Foot / 2835 Chip 140 Pcs/Meter)



Part #	Length	# Of LED Chips	Total Wattage	Max # Can Connect	Price	10+ Pcs.
		Co	ol White * CW &	Warm White *WW		
MXL140-28-*3	33'	1400	103	164′	\$61.00 ea. (\$1.85')	\$55.00 ea. (\$1.67')
MXL140-28-*5	82'	3500	256	164'	\$139.00 ea.(\$1.69')	\$126.00 ea. (\$1.54')
MXL140-28-*6	164′	7000	512	164′	\$259.00 ea.(\$1.58')	\$235.00 ea.(\$1.43')

Required **Optional** (Any Combination) Required Optional Power Cord Connecting Splicer **Mounting Clips** 120V Single **End Cap** Cable Ribbon -e::TTb 0:0 | 0 :: 0 | 0:0

Power Cord (Additional Quantities Optional)



Connecting Cables (Optional)

Optional

Dimmer

Function: Allows the designer to get around unlit areas without multiple power supplies



Universal LED Ribbon Mounting Channels Aluminum channels that work with our ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62

legrand Dimmer Switches (Optional)

Input & Output Cords: 5.875" • Range of Dimming: 0-100% • Mounting: Wall

sofTap Touch Switch With Touch Slide Dimmer

LGD120-DIMST-MG LGD120-DIMST-WH Each: \$63.28 (Magnesium) Each: \$54.98 (White)

For More Options, Product Details & Wall Plates,

See Page L-143

Splicer (Optional)



Mounting Clips (Optional)



MXL28-MNT Each: \$0.21 100+ Pcs.: \$0.15 ea.

(ŲL)

2-Way L Connector (Optional)

MXL28-END

Each: \$0.25

100+ Pcs.: \$0.18 ea.

End Cap (Optional)

MXL28-2L Each: \$1.75 / 10+ Pcs.:

3-Way T Connector (Optional)

MXL28-3T Each: \$2.25 / 10+ Pcs.: \$1.95 ea.











LED Lighting

Brite Light Flex Color Changing (RGB: Indoor/Outdoor): No Power Supply / Amplifiers Needed!

Can Run Up To 164 Ft. On One Power Cord Available Lengths: 33', 82' & 164'

Material: Flexible PVC

Recognized as the most versatile and brightest RGB LED Ribbon Lighting on the market today, Outwater has expanded its offering with the introduction of the new super bright 120V RGB LED variant.

With no fixtures to hide, Outwater's 120V RGB LED Ribbon Flex Lighting can be easily mounted in all of those "hard to light" areas or virtually anyplace that could not be previously lit, and is perfectly suited for illuminating any type of indoor or outdoor application.

- Ideal for applications in which longer lengths are desired
- · Consistent binning/color
- Includes factory installed end cap
- · Power and controller included



IP65 Brite Lite Flex: Color Changing RGB Provides Protection From Dust & Splashing Water, Not Submersible

7 Colors From One Lighting Source















Standard Color Changing RGB (Up To 190 Lumens Per Foot / 5050 Chip 60 Pcs/Meter)



-	5/	8"	1
			3/8"

Beam Spread	120°
Lumens	Red: 190 per ft. Green: 144 per ft. Blue: 160 per ft.
Rated Average Life	35,000 hrs.
Constant	Voltage
Chip Size	SMD5050

Lighting Specifications

			# Of LED	Total	Max # Can		Price
Part#	Color Temp	Length	Chips	Wattage	Connect	Each	5+ Pcs.
DRL33-5060-RGB	RGB	33'	600	80	33′	\$89.00 (\$2.70')	\$75.00 ea. (\$2.27')
DRL82-5060-RGB	RGB	82'	1500	200	82'	\$180.00 (\$2.20')	\$162.00 ea. (\$1.98')
DRI 164-5060-RGB	RGR	164'	3000	400	164′	\$287.00 (\$1.75")	\$262.40 ea (\$1.60)

Our Brite Light Flex Color Changing products are ETL certified and warranted as non-cuttable. If a customers does cut the product, they do so at their own risk.

Power & Controller Included








Works with DRL164-5060-RGB

Required

120V Single

Ribbon



Mounting Clips (Optional)

DRL-50MNT Each: \$0.21 100+ Pcs.: \$0.12 ea.



End Cap (Optional)

Optional

Mounting Clips

DRL-50END Each: \$0.21 100+ Pcs.: \$0.12 ea.



Optional

End Cap

Universal LED Ribbon Mounting Channels Aluminum Channels That Work With Our Ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62





Non-Neon Lighting



PRODUCT FEATURES:

For Interior & Exterior!

• More economical option for signage and interior design.

Energy Efficient!

- This unique LED product will save you up to 70% or more on your energy costs!
- · Very low consumption
- · Low heat cool to the touch!

Long Life Rating and Durability!

- The LED's are rated to last up to 50,000 hours.
- · Virtually unbreakable
- Unique, flexible, and soft PVC jacket, is durable and impervious to the elements.
- 100% waterproof, when properly sealed.


Commercial Quality & Superior Brightness!

- NO HOT SPOTS!

This product provides a neon and fiber optic light brightness.

Flexible and Easy to Use!

- Standard 120V no drivers or transformers are necessary, just plug into the wall!
- Field cuttable- 120V every 39" & 24V every 4"
- Field bendable. This product can be bent to a minimum radius of 2" 3-1/8".
- · Various connector options are available for diverse applications.



When Off This Light Has A Milky White Cover







Non-Neon Lighting

Replaces Glass Neon Tubes

Material: PVC







MADE TO ORDE	R: SOLD BY THE I	NCH - MUST PURC	HASE POWER CORI	D & END CAPS
Part #	Cut Increments	Watts Per Foot	LED Color	Price
NZL120-CUT-RD	20"	3	Red	\$0.36 in.
NZL120-CUT-YE	20"	3	Yellow	\$0.36 in.
NZL120-CUT-BL	20"	3	Blue	\$0.36 in.
NZL120-CUT-GR	20"	3	Green	\$0.36 in.
NZL120-CUT-CW	20"	3	Cool White	\$0.36 in.
NZL120-CUT-WW	20"	3	Warm White	\$0.36 in.

33	FT. ROLL: INCL	UDES FACTORY	SEALED POW	ER CORD & END C	AP
Part#	Cut Increments	Watts Per Foot	LED Color	Price	2+ Pcs.
NZL120-33B-RD	20"	3	Red	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')
NZL120-33B-YE	20"	3	Yellow	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')
NZL120-33B-BL	20"	3	Blue	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')
NZL120-33B-GR	20"	3	Green	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')
NZL120-33B-CW	20"	3	Cool White	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')
NZL120-33B-WW	20"	3	Warm White	\$124.83 ea. (\$3.78')	\$112.41 ea. (\$3.41')



164	FT. ROLL: INCL	LUDES FACTORY	Y SEALED POV	VER CORD & END (CAP
Part #	Cut Increments	Watts Per Foot	LED Color	Price	2+ Pcs.
NZL120-164B-RD	20"	3	Red	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')
NZL120-164B-YE	20"	3	Yellow	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')
NZL120-164B-BL	20"	3	Blue	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')
NZL120-164B-GR	20"	3	Green	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')
NZL120-164B-CW	20"	3	Cool White	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')
NZL120-164B-WW	20"	3	Warm White	\$582.90 ea. (\$3.55')	\$524.89 ea. (\$3.20')




Our Non-Neon Lighting products are ETL certified and warranted as non-cuttable. If a customers does cut the product, they do so at their own risk.






Accessories for Non-Neon Lighting



	ACCESSORIES FOR							
	NON-NEON FLEXIBLE LED LIGHTING							
	Part #	Description	Price					
Α	NZL-1426-PWR	1.65 Ft. Long Powercord (Required)	\$4.35 ea.					
В	NZL-1426-2JN	2 Ft. Long Connecting Cable (Optional)	\$2.15 ea.					
C	NZL-1426-6JN	6 Ft. Long Connecting Cable (Optional)	\$4.55 ea.					
D	NZL-1426-2L	L Connector: 2 Way - Pins Included (Optional)	\$1.50 ea.					
E	NZL-1426-3T	T Connector: 3 Way - Pins Included (Optional)	\$1.60 ea.					
F	NZL-1426-SPL	2 in. Long Heat Shrink With Splicing Pin To Fit PVC Tubing (<i>Optional</i>)	\$1.00 ea.					
G	NZL-1426-END	End Cap (Required If Cutting)	\$0.35 ea.					
Н	NZL-1426-MNT	2" Long Plastic Mounting Clip (Optional)	\$0.20 ea.					
- 1	NZL-1426-CH2	2" Long Aluminum Mounting Clip (Optional)	\$0.50 ea.					
J	CT-2000	Multi Purpose Cutter w/5 Interchangeable Anvils & Storage Case (<i>Optional</i>)	\$29.95 kit					



* Seal w/GE Silicone or Equivalent














Mini Non-Neon Lighting

Replaces Glass Neon Tubes: Sold By The Foot or 33' Coils Material: PVC

- Field Cuttable Every 4"
- Rated 50,000 Hours
- For interior signage & interior design
- Extremely Flexible- Bend into letters and shapes. Can be bent to a minimum radius of 1.9" - 3.15".
- · Energy Saving
- Virtually Unbreakable- Extremely durable. Crush resistant up to 450 psi.









3/8" (10mm)












33' ROLL: IN	CLUDES FACTO	DRY SEALED PO	WER CORD &	END CAP (MUST BE	HARDWIRED)
Part #	Cut Increments	Watts Per Foot	LED Color	Price	10+ Pcs.
NZL24-1016-33RD	4"	3	Red	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')
NZL24-1016-33YE	4"	3	Yellow	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')
NZL24-1016-33BL	4"	3	Blue	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')
NZL24-1016-33GR	4"	3	Green	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')
NZL24-1016-33CW	4"	3	Cool White	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')
NZL24-1016-33WW	4"	3	Warm White	\$101.22 ea. (\$3.07')	\$91.14 ea. (\$3.20')

Our Mini Non-Neon Lighting products warranted as non-cuttable. If a customers does cut the product, they do so at their own risk.

24V

Accessories for Mini Non-Neon Lighting



	HARDWIRE POWER SUPPLIES (Required)								
						Input	Output		
	Part #	Dimensions	Voltage	Watts	Amps	Cord	Cord	Constant	Price
Α	LED-24V-2.5A-HW	7.5" x 1.88" x 1.33"	24	60	2.5	10.5"	10.5"	Voltage	\$25.00 ea.
В	LED-24V-4.17A-HW	8.74" x 2.71" x 1.69"	24	100	4.17	10.5"	10.5"	Voltage	\$42.00 ea.
C	LED-24V-8.3A-HW	9.84" x 3.11" x 2"	24	199	8.3	10.5"	10.5"	Voltage	\$74.70 ea.







	ACCESSOF	RIES FOR NON-NEON FLEXIBLE LED LIGH	ITING
	Part #	Description	Price
C	NZL-1016-PWR	1.65 Ft. Long Powercord (Required)	\$4.35 ea.
D	NZL-1016-2JN	2 Ft. Long Connecting Cable (Optional)	\$2.15 ea.
E	NZL-1016-6JN	6 Ft. Long Connecting Cable (Optional)	\$4.55 ea.
F	NZL-1016-2L	L Connector: 2 Way - Pins Included (Optional)	\$1.50 ea.
G	NZL-1016-3T	T Connector: 3 Way - Pins Included (Optional)	\$1.60 ea.
Н	NZL-1016-SPL	2 in. Long Heat Shrink With Splicing Pin To Fit PVC Tubing (Optional)	\$1.00 ea.
- 1	NZL-1016-END	End Cap (Required If Cutting)	\$0.35 ea.
J	NZL-1016-MNT	2" Long Plastic Mounting Clip (Optional)	\$0.20 ea.
K	NZL-1016-CH2	2" Long Aluminum Mounting Clip (Optional)	\$0.50 ea.
L	CT-2000	Multi Purpose Cutter w/5 Interchangeable Anvils & Storage Case (<i>Optional</i>)	\$29.95 kit

* Seal w/GE Silicone or Equivalent





























Our Mini Non-Neon Lighting products warranted as non-cuttable. If a customers does cut the product, they do so at their own risk.

DP24 SERIES THIS NEW LED 2835 CHIP, PROVIDES GREATER ENERGY EFFICIENCY, HIGH LUMENS & BUDGET FRIENDLY PRICING. DP246 28140 (Up To 406 Lumens Per Fo

7" Cable With DC5.5

- •This comprehensive array of LED 2835 ribbons includes width ranging from 1/4" to 1-3/16"
- •Special Feature: Ribbon has 2 female ends (DC 5.5) so it can be cut to size and then the remaining piece can be used for another project
- Available Lengths: 8.25' & 16.5" (Nominal)
- Available In: IP65 & IP20

7" Cable

With DC5.5

- Most design options can be accommodated with use of our FPC* connector series.
- Limited 2 Year Warranty







LED Lighting







DP24 Ribbon Flex Series

Available Lengths: 8.25' & 16.5' (Nominal)

Material: Flexible White PCB with Adhesive

- 2 Options Available

IP65 24V DP24 Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible

IP20 24V DP24 Ribbon

Provides Low Protection of Dust & Water



Ultra Thin DP246 28140 (Up To 406 Lumens Per Foot)

SI UN DI 240 20140 (Up 10 400 Lumens Per Foot)



3M™- Adhesive tape on bottom

		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
	IP20 (Cool	White *CW,	Warm White	e *WW & Pure	: White *PW)	
DP246-I28140-8*	8.25'	350	26	8.25'	\$31.92 (\$3.87')	\$27.36 ea. (\$3.32')

Lighting Specifications

Lighting.	pecifications
Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 406 per ft. WW: 400 per ft. PW: 403 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

DP248 2860 (Up To 209 Lumens Per Foot)

2" Cut Increments -

\[\text{\tinc{\text{\ti}\text{\texi{\text{\texi\tinte\text{\tin}}\\ \tittt{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\texi}}\tint{\text{\text{\text{\texi}\tint{\text{\text{\text{\text{\texi}}\tint{\tin}\tint{\text{\ti}}}\tintet{\text{\text{\text{\text{\text{\texi}\tint{\text{\tin}





-41/16"Thick

-----\1/16"Thick

			5/16"Wide	3M	™- Adhesive tape on bo	ottom
		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
	IP65 (Cool V	White *CW, I	Narm White	e *WW & Pure	White *PW)	
DP248-N2860-8*	8.25'	150	14	16.5′	\$20.52 (\$2.49')	\$17.10 ea. (\$2.07')
DP248-N2860-16*	16.5'	300	29	16.5'	\$37.44 (\$2.27')	\$31.20 ea. (\$1.89')
	IP20 (Cool V	White *CW, I	Narm White	e *WW & Pure	: White *PW)	
DP248-I2860-8*	8.25'	150	14	16.5′	\$15.12 (\$1.83')	\$12.60 ea. (\$1.53')
DP248-I2860-16*	16.5'	300	29	16.5'	\$26.64 (\$1.61')	\$22.20 ea. (\$1.89')
DP248-I2860-33WW	33′	600	58	16.5′	\$37.50 (\$1.14')	\$31.25 ea. (\$0.95')

Lighting Specifications

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 209 per ft. WW: 200 per ft. PW: 206 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

DP2410 2860 (Up To 339 Lumens Per Foot)



			3/8" Wide	` 3M	™- Adhesive tape on bo	ttom
		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
IP65 (Co	ol White *CW	, Warm Whit	te *WW, Pu	re White *PW	& Natural White	*NW)
DP2410-N2860-8*	8.25'	150	29	16.5′	\$22.85 (\$2.77')	\$19.99 ea. (\$2.42')
DP2410-N2860-16*	16.5'	300	58	16.5'	\$41.86 (\$2.54')	\$36.62 ea. (\$2.22')
IP20 (Cool White *CW, Warm White *WW, Pure White *PW & Natural White *NW)						
DP2410-l2860-8*	8.25'	150	29	16.5′	\$17.09 (\$2.07')	\$14.95 ea. (\$1.81')
DP2410-I2860-16*	16.5'	300	58	16.5'	\$30.34 (\$1.84')	\$26.54 ea. (\$1.61')

Lighting	pecifications
Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K NW: 5000K-5500K
Beam Spread	120°
Lumens	CW: 339 per ft. WW: 330 per ft. PW: 333 per ft. NW: 335 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835







LED Lighting

DP24 Ribbon Flex Series

Available Lengths: 8.25' & 16.5' (Nominal)
Material: Flexible White PCB with Adhesive

Special Feature
Ribbon has 2 female ends (DC 5.5) so it

Ribbon has 2 female ends (DC 5.5) so it can be cut to size and then the remaining piece can be used for another project

2 Options Available

IP65 24V DP24 Ribbon

IP20 24V DP24 Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible | Provides Low Protection of Dust & Water

DP2410 28120 (Up To 408 Lumens Per Foot)





		# Of LED	Total	Max # Can	Pi	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
IP65 (Cool	White *CW,	Warm White	*WW, Pu	re White *PV	V & Natural White	*NW)
DP2410-N28120-8*	8.25'	300	32	16.5′	\$29.57 (\$3.58')	\$25.87 ea. (\$3.14')
DP2410-N28120-16*	16.5'	600	64	16.5'	\$55.30 (\$3.35')	\$48.38 ea. (\$2.93')
IP20 (Cool	White *CW,	Warm White	*WW, Pu	re White * <mark>PV</mark>	V & Natural White	*NW)
DP2410-I28120-8*	8.25'	300	32	16.5'	\$23.81 (\$2.89')	\$20.83 ea. (\$2.53')
DP2410-I28120-16*	16.5'	600	64	16.5′	\$43.78 (\$2.65')	\$38.30 ea. (\$2.32')

DP2410 28182 (Up To 555 Lumens Per Foot)



1.5" Cut Increments	\ <u> </u>
\\[\begin{aligned} \D \dot \D \D \D \D \D \D \D \D \D \D \D \D \D	3M™- Adhesive tape on bottom

		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
	IP65 (Cool	White *CW,	Warm White	*WW & Pure	: White * PW)	
DP2410-N28182-8*	8.25'	455	39	16.5'	\$42.62 (\$5.17')	\$37.30 ea. (\$4.52')
DP2410-N28182-16*	16.5'	910	75	16.5'	\$81.41 (\$4.93')	\$71.23 ea. (\$4.32')
IP20 (Cool White *CW, Warm White *WW & Pure White *PW)						
DP2410-I28182-8*	8.25'	455	39	16.5′	\$36.86 (\$4.47')	\$32.26 ea. (\$3.91')
DP2410-I28182-16*	16.5'	910	75	16.5′	\$69.89 (\$4.24')	\$61.15 ea. (\$3.71')

DP2415 28196 (Up To 740 Lumens Per Foot)





	⊢ 2-13/16" Cut Increments ⊢	3/8"	
١		(>,	3M™- Adhesive tape on bottom

		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
IP65 (Coo	l White *CW	, Warm Whi	te *WW, Pu	re White *PW	& Natural White	*NW)
DP2415-N28196-8*	8.25'	490	53	16.5'	\$47.81 (\$5.79')	\$41.83 ea. (\$5.07')
DP2415-N28196-16*	16.5'	980	105	16.5'	\$91.78 (\$5.56')	\$80.30 ea. (\$4.87')
IP20 (Coo	l White *CW	, Warm Whi	te *WW, Pu	re White *PW	& Natural White	*NW)
DP2415-I28196-8*	8.25'	490	53	16.5'	\$42.05 (\$5.10')	\$36.79 ea. (\$4.46')
DP2415-I28196-16*	16.5'	980	105	16.5′	\$80.26 (\$4.86')	\$70.22 ea. (\$4.26')

7" Cable With DC5.5

7" Cable With DC5.5

Lighting Specifications

99	peemeations
Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K NW: 5000K-5500K
Beam Spread	120°
Lumens	CW: 408 per ft. WW: 400 per ft. PW: 403 per ft. NW: 335 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

Lighting Specifications

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 555 per ft. WW: 552 per ft. PW: 554 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K NW: 5000K-5500K
Beam Spread	120°
Lumens	CW: 740 per ft. WW: 738 per ft. PW: 739 per ft. NW: 335 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

LED Lighting







DP24 Ribbon Flex Series

Available Lengths: 8.25' & 16.5' (Nominal)
Material: Flexible White PCB with Adhesive

DP2420 28252 (Up To 947 Lumens Per Foot)

Special Feature

Ribbon has 2 female ends (DC 5.5) so it can be cut to size and then the remaining piece can be used for another project

> 7" Cable With DC5.5



7" Cable With DC5.5

21 2-120 20232 (op 10 3-17 Lumens Per Pool)

|--|

Shown IP20

- 2-13/16"Cut Increments - 1/2"	3M**-Adhesive tape on bottom
---------------------------------	------------------------------

		# Of LED	Total	Max # Can	P	rice				
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.				
IP20 (Cool White *CW, Warm White *WW & Pure White *PW)										
DP2420-I28252-8*	8.25'	630	75	8.25'	\$48.58 (\$5.89')	\$41.95 ea. (\$5.09')				

Lighting Specifications

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 947 per ft. WW: 941 per ft. PW: 944 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

DP2430 28384 (Up To 1253 Lumens Per Foot)



Shown IP20

Shown IP20

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 1253 per ft. WW: 1245 per ft. PW: 1249 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

Lighting Specifications

├─ 2-1/2" Cut Increments ─	
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	3M™- Adhesive tape on bottom

		# Of LED	Total	Max # Can	P	rice			
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.			
IP20 (Cool White *CW, Warm White *WW & Pure White *PW)									
DP2430-I28384-8*	8.25'	960 Per Ft.	104	8.25'	\$72.34 (\$8.77')	\$62.47 ea. (\$7.57')			

DP2440 28480 (Up To 1515 Lumens Per Foot)



	— 2-1/2" Cut Increments — 7/16"		
O		\Box	
O		1 1/1/2// (CDL	
∖⊠		9/16"	3M™- Adhesive tape on bottom
		1	
la	Paaaaa ^a aaaaaa ^a al		

		# Of LED	Total	Max # Can	Price	
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
DP2440-I28480-8*	8.25'	1200	130	8.25'	\$89.50 (\$10.85')	\$77.29 ea. (\$9.37')

Color Temperature	CW: 6000K-6500K WW: 2800K-3000K PW: 4000K-4500K
Beam Spread	120°
Lumens	CW: 1514 per ft. WW: 1512 per ft. PW: 1509 per ft.
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835









LED Lighting

Accessories for DP24 Ribbon Flex Series



Required

Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages R-119~120b Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable

Required for power supplies, dimmers & multi output cables.



			Overall		F	Price				
Part #	Works With	Description	Length	Finish	Each	6+ Pcs.				
For Cut Pieces of Ribbon										
LED-FPC-8-PWL	24V D248*	D 1:1611	24"	Black	\$2.40	\$2.20 ea.				
LED-FPC-10-PWL	24V D2410*	Power Link Cable	24"	Black	\$2.50	\$2.30 ea.				
LED-FPC-15-PWL	24V D2415*	with 100% Usable Connection	24"	Black	\$2.60	\$2.40 ea.				
LED-FPC-20-PWL	24V D2420*	Connection	24"	Black	\$2.95	\$2.75 ea.				

For Hardwire Power Linking Cables, See Page L-141

Optional

Dimmers A power linking cable required.

Range of				Price			
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.	
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
For Product Datails & Mara Dimmor Ontions Son Pages I 124-126 & I 142-144							

Other Options: Rotary | Touch Dimmer | Radio Frequency

Connecting Cables



Part #	Works With	Description	Finish	Length	Each	6+ Pcs.
		n				
LED-FPC-8-CON24	24V DP248*		White	24"	\$2.15	\$2.00 ea.
LED-FPC-8-CON36	24V DP248*	Directly connect 2 cut pieces of ribbon while providing ability to get around unlit areas	White	36"	\$2.50	\$2.30 ea.
LED-FPC-10-CON24	24V DP2410*		White	24"	\$2.40	\$2.20 ea.
LED-FPC-10-CON36	24V DP2410*		White	36"	\$2.70	\$2.50 ea.
LED-FPC-15-CON24	24V DP2415*		White	24"	\$2.60	\$2.40 ea.
LED-FPC-15-CON36	24V DP2415*		White	36"	\$2.95	\$2.75 ea.
LED-FPC-20-CON24	24V DP2420*		White	24"	\$2.80	\$2.60 ea.
LED-FPC-20-CON36	24V DP2420*		White	36"	\$3.15	\$2.95 ea.

For More Extension Cable Options, See Page L-145

End-To-End For 100% Usable Connections



Part #	Works With	Description	Each	6+ Pcs.
LED-FPC-8-EE-C	24V DP248*		\$1.10	\$1.00 ea.
LED-FPC-10-EE-C	24V DP2410*	Usable connection directly	\$1.30	\$1.20 ea.
LED-FPC-15-EE-C	24V DP2415*	connects 2 cut pieces	\$1.60	\$1.45 ea.
LED-FPC-20-EE-C	24V DP2420*		\$1.85	\$1.70 ea.

Universal LED Ribbon Mounting Channels Aluminum channels that work with our ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62



Phone: 1-800-631-8375

Price

Price









Cut Per LED Ribbon

Now you can create any desired length! Cut increment is LESS THEN 1"!

Nominal Lengths: 8.25' & 16.5' Material: Flexible White PCB with Adhesive


- This NEW LED 2835, provides greater energy efficiency, high lumens & budget friendly pricing.
- This comprehensive array of LED 2835 ribbons has a width of 3/8", 36 chips per ft. & 8.7 watts per ft.
- Special Feature: Ribbon Has 2 female ends (DC 5.5) so it can be cut to size and then the remaining piece can be used for another project.
- 3M Adhesive Back
- · Limited 3 Year Warranty

IP20 Cut Per LED Ribbon
Provides Low Protection of Dust & Water









CTL2410-I28120 (Up To 667 Lumens Per Foot)



3M™- Adhesive tape on bottom

		# Of LED	Total	Max # Can	Price		
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.	
Cool White *CW, Warm White *WW & Pure White *PW							
CTL2410-I28120-8*	8.25'	300	72	16.5′	\$38.22 (\$4.63')	\$34.12 ea. (\$4.14')	
Cool White *C, Warm White *W & Pure White *P							
CTL2410-I28120-16*	16.5'	600	144	16.5′	\$72.80 (\$4.41')	\$65.00 ea. (\$3.94')	

Color Temperature	CW/C: 6500K WW/W: 3000K PW/P: 4500K			
Beam Spread	120°			
Lumens	667 per ft.			
Color Rendering Index	80			
Rated Average Life	35,000 hrs.			
Constant	Voltage			
Chip Size	2835			











LED Lighting

Accessories for Cut Per LED












Required

Power Supplies



				Price	
Part # Type Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A Desktop 3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-6A Desktop 6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages R-119~120b Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable Required for power supplies, dimmers & multi output cables.



		Overall		Price		
Part #	Description	Length	Finish	Each	6+ Pcs.	
	For Cut Pieces of Ribbo	n				
LED-FPC-10-PWL	Power Link Cable with 100% Usable Connection	24"	Black	\$2.50	\$2.30 ea.	

For Hardwire Power Linking Cables, See Page L-141

Optional

Dimmers





	Price							
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.		
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.		
For Product Datails & More Dimmer Ontions See Pages L-134-136 & L-142-144								

Other Options: Rotary **Touch Dimmer** Radio Frequency

Multi Output Cables



			Arms # of		Overall	Max # of Power	Price				
Part #	Description	Finish	Size	Arms Length		Linking Cables	Each	6+ Pcs.			
For Cut Pieces of Ribbon & Pin Connection (Power Linking Cable Required For Each Outlet)											
LED-2WAY-BK	2-Way Sweep	Black	3"	2	7"	2	\$2.95	\$2.50 ea.			
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.			
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.			
For More Extension Cable Options, See Page L-147											





Connecting Cables



Part #	Description	Finish	Length	Each	6+ Pcs.
	For Cut Pieces of Ribbo	n			
LED-FPC-10-CON24	Directly connect 2 cut pieces of ribbon while	White	24"	\$2.40	\$2.20 ea.
LED-FPC-10-CON36	providing ability to get around unlit areas	White	36"	\$2.70	\$2.50 ea.

For More Extension Cable Options, See Page L-145

End-To-End For 100% Usable Connections



		Price			
Part #	Description	Each	6+ Pcs.		
LED-FPC-10-EE-C	Usable connection directly connects 2 cut pieces	\$1.30	\$1.20 ea.		

Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62



Price









High Density Ribbon

LED's are so close together that when installed inside our Vision Task Extrusions there is virtually NO HOT SPOTS! (See Pages L-55~62)

Nominal Lengths: 8.25' & 16.5' Material: Flexible White PCB with Adhesive

- This high density 2216, provides greater energy efficiency, high lumens & budget friendly pricing.
- This comprehensive array of LED 2216 ribbons has a width of 3/8", 127 chips per ft. & 7.3 watts per ft.
- Special Feature: Ribbon Has 2 female ends (DC 5.5) so it can be cut-to-size and then the remaining piece can be used for another project.
- 3M Adhesive Back
- Limited 3 Year Warranty





With DC5.5

HDL2410-I22420 (Up To 545 Lumens Per Foot)



-	-	 	-	 	 -	-1-	 	=	 -	-	1111	


21/32"Cut Increments 3/	/32" 30000 \ 3/8"Wide	3M"- Adhesive tape on bottom

		# Of LED	Total	Max # Can	Price						
Part #	Length	Chips	Wattage	Connect	Each 5+ Pcs.						
Cool White *CW, Warm White *WW & Pure White *PW											
HDL2410-I22420-8*	8.25'	1050	60	16.5'	\$65.52 (\$7.94')	\$58.50 ea. (\$7.09')					
Cool White *C, Warm White *W & Pure White *P											
HDI 2410-I22420-16*	16.5'	2100	120	16.5′	\$127.40 (\$7.72)	\$113.75 ea (\$6.89')					

Lighting Specifications

Color Temperature	CW/C: 6500K WW/W: 2800K-3000K PW/P: 4000K-4500K
Beam Spread	120°
Lumens	545 per ft.
Color Rendering Index	80
Rated Average Life	35,000 hrs.
Constant	Voltage
Chip Size	2216









7" Cable

With DC5.5

Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers A power linking cable required. Trini.

	Price								
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.			
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.			
For Dradust Datails 9 Mary Dimmer Ontions Soc Dancel 124, 126 9 L 142, 144									

roduct Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Universal LED Ribbon Mounting Channels Aluminum channels that work with our ribbons

For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62











Color Changing Temperature (CCT) Cut Per LED Ribbon

Versatile & field trimmable LED ribbon can be adapted to meet many design needs. Can program color temperature ranges between 3000K-6000K. Cut increment is less then 1"!

Nominal Lengths: 16.5'

Material: Flexible White PCB with Adhesive

- Now you can create any desired length! Cut increments is less then 1"!
- This NEW color changing temperature (CCT) LED 2835, provides greater energy efficiency, high lumens & budget friendly pricing.
- This comprehensive array of LED 2835 ribbons has a width of 3/8", 36 chips per ft. & 8.7 watts per ft.
- 3M Adhesive Back
- · Limited 3 Year Warranty

IP20 CCT Cut Per LED Ribbon

Provides Low Protection of Dust & Water





CCT TECHNOLOGY

Cool White





CTL2410-I28120-CCT (Up To 667 Lumens Per Foot)



11/32" Cut Increments

______1/32"Thick 3M[™]- Adhesive tape on bottom

		# Of LED	Total	Max # Can	Price		
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.	
CTL2410-I28120-CCT	16.5′	600	72	16.5′	\$70.98 (\$4.30')	\$63.38 ea. (\$3.84')	

Lighting Specifications

Temperature	3000K-6500K
Beam Spread	120°
Lumens	667 per ft.
Color Rendering Index	80
Rated Average Life	35,000 hrs.
Constant	Voltage
Chip Size	2835

LED Lighting










Accessories for Color Changing Temperature (CCT) Cut Per LED Ribbon



Required

Power Supplies



						h	Price
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Option 1: RF Controller With Remote For CCT



Features:

- 3A / 24V / 72W
- Input Wire: Female DC 5.5 / Hardwire
- Output Wire: Hardwire
- Controller Size: 4-1/2"L x 2-3/16"W x 3/4"H
- Receiver Size: 3-5/8"L x 1-3/4"W x 7/8"H
- · Color: White

Controller Functions:

- Mounting: Surface
- Remote Control Function: RF
- Gradient Change: 11 Grades
- Brightness Adjusting: 20 Grades
- · Sound: No


Option 2: RF CCT Controller With Desktop or Wall Option




Included With Every Dimmer

7" L x 1.75" W x .75" H Female DC 5.5 Input Cord: 18"

- Each dimmer is paired to the included receiver. However, multiple dimmers can be paired to one receiver. (Instructions included in package)
- Range of Dimming: 10%-100%
- Push Button On/Off Function
- All dimmers work up to 50' away from receiver
- All dimmer controllers run on battery
- · Limited 3 Year Warranty
- · Radio frequency goes through walls







Fits Over A Standard Receptacle Box

3.5" L x 1.37" W x .75" H

RF-CCT-CTRL-WT Each: \$114.75 6+ Pcs.: \$100.98 ea.



Desk Top Dimmer

4"L x 1.5"W x 1.8"H

RF-CCT-CTRL-DT

Each: \$120.40 6+ Pcs.: \$105.95 ea.

For More On Radio Frequency Dimmers, See Pages L-134~136

Universal LED Ribbon Mounting Channels
Aluminum channels that work with our ribbons
For Pricing & To See A Full Line Of Our
Mounting Channels, See Pages L-55~62













Premium Ribbon Flex

Available Lengths: 23.5", 8.25' & 16.5' Material: Flexible Silicone Cover with Adhesive

- Commercial Grade
- Field Trimmable
- Consumes Only a Few Watts Per Field Cuttable Strip
- 30,000 Hour Average Bulb Life
- Dimmable
- IP20 & IP65 Options
- No UV Radiation- Safe For Artwork
- · Limited 2 Year Warranty



2 Options Available

IP65 Premium Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible | Provides Low Protection of Dust & Water

IP20 Premium Ribbon





Single Ribbon Flex (Up To 280 Lumens Per Foot)

2 Pins Included





p 0		
4"Cut Increments	11/16"	
	3/8″Wide 3/8″Wide	3M™- Adhesive tape on bottom

			# Of LED	Total	Max # Can	F	Price	
Part #	Color Temp	Length	Chips	Wattage	Connect	Each	10+ Pcs.	
IP65								
RIB24-N5060-23-*	*CW/*PW/*WW	23.5"	36	7	16.5′	\$6.74 (3.37')	\$6.06 ea. (\$3.03')	
RIB24-N5060-8-*	*CW/*PW/*WW	8.25'	150	29	16.5'	\$20.02 (\$2.42')	\$16.45 ea. (\$1.99')	
RIB24-N5060-16-*	*CW/*PW/*WW	16.5'	300	58	16.5'	\$39.90 (\$2.41')	\$32.78 ea. (\$1.98')	
RIB24-N5060-16-AM	Amber	16.5'	300	58	16.5'	\$63.98 (\$3.87')	\$52.56 ea. (\$3.18')	
RIB24-N5060-16-RD	Red	16.5'	300	58	16.5'	\$46.62 (\$2.82')	\$38.30 ea. (\$2.32')	
RIB24-N5060-16-BL	Blue	16.5'	300	58	16.5'	\$46.62 (\$2.82')	\$38.30 ea. (\$2.32')	
RIB24-N5060-16-GN	Green	16.5'	300	58	16.5'	\$46.62 (\$2.82')	\$38.30 ea. (\$2.32')	
			IP20)				
RIB24-I5060-8-*	*CW/*PW/*WW	8.25'	150	29	16.5'	\$15.82 (\$1.91')	\$13.00 ea. (\$1.57')	
RIB24-I5060-16-*	*CW/*PW/*WW	16.5'	300	58	16.5'	\$31.50 (\$1.90')	\$25.88 ea. (\$1.56')	

Lighting Specifications

Color Temperature	PW: 4000K-4500K WW: 2800K-3200K AM: 1800K-2000K
Beam Spread	120°
Lumens	280 per ft.
Color Rendering Index	>80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	5050

Phone: 1-800-631-8375 Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.

LED Lighting











Accessories for Premium Ribbon Flex












Required

Power Supplies




							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.
				_		_	

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable

Required for power supplies, dimmers & multi output cables.



		Overall			rice
Part #	Description	Length	Finish	Each	6+ Pcs.
	Pin Connection (Pins Included)				
LED-RIBBON-PWL	Power Link Cable with Pin Connection	18"	Black	\$3.00	\$2.60 ea.
	For Cut Pieces of Ribbon				
LED-RIBBON-100U-PL	Power Link Cable with 100% Usable Connection	18"	Black	\$4.00	\$3.50 ea.
For Hardwire Power Linking Cables, See Page L-141					

Optional

Dimmers

A power linking cable required.



			Range of			rice
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
For Product Details & More Dimmer Options. See Pages L-134~136 & L-142~144						


Overall Max # of Power

Other Options: Rotary | Touch Dimmer | Radio Frequency

Arms

Multi Output Cables





For More Extension Cable Options, See Page L-147







of

End-To-End For 100% Usable Connections



			P	rice
Part #	Description	# of Pins	Each	6+ Pcs.
LED-RIBBON-100U-EE	Usable connection directly connects 2 cut pieces	4	\$0.85	\$0.75 ea.

Duisa

Price











LED Lighting

Accessories for Premium Ribbon Flex



Optional



Connectors


2-Way

Connects ribbon at a 90° angle.

3-Way

<u>Pin</u>

4-Way



		_	P	rice			
Part #	Description	# of Pins	Each	6+ Pcs.			
Pin Connection (Pins Included)							
LED-RIBBON-2W-C	2-Way L	4	\$1.75	\$1.50 ea.			
LED-RIBBON-3W-C	3-Way T	4	\$1.75	\$1.50 ea.			
LED-RIBBON-4W-C	4-Way Cross	4	\$1.75	\$1.50 ea.			
	For Cut Pied	es of Ribbon					
LED-RIBBON-2W-EE-C	2-Way L	4	\$1.75	\$1.50 ea.			
LED-RIBBON-3W-EE-C	3-Way T	4	\$1.75	\$1.50 ea.			
LED-RIBBON-4W-EE-C	4-Way Cross	4	\$1.75	\$1.50 ea.			

Length

18"

24"

36"

36"

24"

Each

\$2.75

\$3.25

\$3.50

\$3.50

\$3.25

\$3.50

\$4.50

Price

6+ Pcs.

\$2.40 ea.

\$2.85 ea.

\$3.05 ea.

\$3.05 ea.

\$2.85 ea.

\$3.05 ea.

\$3.95 ea.

Mounting Clips



		_	Price				
Part #	Description	Length	Each	100+ Pcs.			
LED-5050-MC	1 mounting clips & 2 screws	10mm	\$0.10	\$0.085 ea.			
	For More Mounting Clip Options, See Page L-149						

End-To-End For Pin Connections


Replacement parts-included with each ribbon & accessory



Part #	Description	# of Pins	Each	100+ Pcs.
LED-4P-CON	Male to male connect end-to-end	4	\$0.15	\$0.10 ea.

Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons













For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62







Premium RGB Ribbon Flex

Nominal Lengths: 40", 6.5' & 16.5' Material: Flexible Silicon Cover with Adhesive

- Commercial Grade
- Field Trimmable
- Nominal 40", 8.5' & 16.5' rolls
- Consumes Only a Few Watts Per Field Cuttable Strip
- 30,000 Hour Average Bulb Life
- 3M Adhesive Back
- No UV Radiation- Safe For Artwork
- · Limited 2 Year Warranty







IP65 Premium 24V RGB Ribbon
Provides Protection From Dust & Splashing Water, Not Submersible

RED

BLUE

PLIRPI F


WHITE

GREEN

YELLOW

CVAN

Single Ribbon Flex Strips (Up To 48 Lumens Per Foot)




			# Of LED	Total	Max # Can	Price	
	Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
Ī	RIB24-N5060-40RGB	40"	60	12	16.5′	\$8.37 (\$2.53')	\$6.88 ea. (\$2.08')
	RIB24-N5060-8RGB	8.5'	120	29	16.5'	\$20.72 (\$2.44')	\$17.02 ea. (\$2.00')

Lighting Specifications

Beam Spread	140°
Lumens	Red: 22 per ft. Green: 48 per ft. Blue: 7 per ft.
Rated Average Life	30,000 hrs.
Constant	Current
Chip Size	SMD5050

Single Ribbon Flex Coils (Up To 48 Lumens Per Foot)



Lighting Specifications

Beam Spread	140°
Lumens	Red: 22 per ft. Green: 48 per ft. Blue: 7 per ft.
Rated Average Life	30,000 hrs.
Constant	Current
Chip Size	SMD5050











LED Lighting

Accessories for Premium RGB Ribbon Flex



Required


Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Controllers



					F	Price
Part #	Description	Input Wire	Output Wire	Dimensions	Each	6+ Pcs.
LED-RGB36-CRP	Deluxe RGB controller with up to 25 color changing functions	Female DC 5.5: 18"	4 Pin Connection: 18"	4-3/8″L x 2-1/8″W x 1″H	\$35.95	\$31.00 ea.
LED-RGB36-INLINE	Super small RGB controller with up to 20 color changing functions	Female DC 5.5: 3-1/2"	4 Pin Connection	1-1/2″L x 1/2″W x 1/8″H	\$9.95	\$9.00 ea.

For Product Details & More Controller Options, See Pages L-134~136 & L-150
Other Options: Radio Frequency | Sound Activated

Optional


Connectors

2-Way

Connects ribbon at a 90° angle.

3-Wav

4-Way



			_	F	rice						
Part #	Works With	Description #		Each	6+ Pcs.						
Pin Connection (Pins Included)											
LED-RIBBON-2W-C	RGB Ribbon	2-Way L	4	\$1.75	\$1.50 ea.						
LED-RIBBON-3W-C	RGB Ribbon	3-Way T	4	\$1.75	\$1.50 ea.						
LED-RIBBON-4W-C	RGB Ribbon	4-Way Cross	4	\$1.75	\$1.50 ea.						
	For C	ut Pieces of Ribbon									
LED-RIBBON-2W-EE-C	RGB Ribbon	2-Way L	4	\$1.75	\$1.50 ea.						
LED-RIBBON-3W-EE-C	RGB Ribbon	3-Way T	4	\$1.75	\$1.50 ea.						
LED-RIBBON-4W-EE-C	RGB Ribbon	4-Way Cross	4	\$1.75	\$1.50 ea.						

End-To-End For 100% Usable Connections



			_	P	rice
Part #	Works With	Description	# of Pins	Each	6+ Pcs.
LED-RIBBON-100U-EE	RGB Ribbon	Usable connection directly connects 2 cut pieces	4	\$0.85	\$0.75 ea.








Price


Price

Accessories for Premium RGB Ribbon Flex



Optional

Connecting Cables



Part #	Works With	Description	Finish	Length	Each	6+ Pcs.				
Pin Connection (Pins Included)										
LED-RIBBON-RGB-CON	RGB Ribbon	Allows the designer to get	Black	18"	\$2.75	\$2.40 ea.				
LED-RIBBON-RGB-C24	RGB Ribbon	around unlit areas without	Black	24"	\$3.25	\$2.85 ea.				
LED-RIBBON-RGB-C36	RGB Ribbon	multiple power supplies	Black	36"	\$3.50	\$3.05 ea.				
For Cut Pieces of Ribbon										
LED-RIBBON-100U-R1	RGB Ribbon	Directly connect 2 cut pieces of ribbon while	Multi	24"	\$4.25	\$3.70 ea.				
LED-RIBBON-100U-R2	RGB Ribbon	providing ability to get around unlit areas	Multi	36"	\$4.50	\$3.95 ea.				
Pin Connection (Pin Included) To Cut Pieces of Ribbon										
LED-RIBBON-100U-4P	RGB Ribbon	Directly connect pin to cut piece of ribbon to get	Multi	18"	\$1.85	\$1.70 ea.				

around unlit areas For More Extension Cable Options, See Page L-146

Amplifiers



Part #	Description	Input Wire	Output Wire	Dimensions	Each	6+ Pcs.
LED-RIBBON-RGB-AMP	Is to extend the signal of an RGB controller when the power supply	4 Pin Connection: 18"	4 Pin Connection: 18"	3-1/2"L x 2-1/2"W x 7/8"H	\$17.50	\$15.65 ea.
LED-RGBMIN-AMP	is exceeded. (Must purchase another power supply when using this product)	4 Pin Connection	4 Pin Connection	1-5/8″L x 1/2″W x 1/8″H	\$8.00	\$7.20 ea.

Mounting Clips



					rice			
Part #	Works With	Description	Length	Each	100+ Pcs.			
LED-5050-MC	RGB Ribbon	1 mounting clips & 2 screws	10mm	\$0.10	\$0.085 ea.			
For More Mounting Clip Ontions See Page 1 140								

End-To-End For Pin Connections


Replacement parts-included with each ribbon & accessory



				P	rice
Part #	Works With	Description	# of Pins	Each	100+ Pcs.
LED-4P-CON	RGB Ribbon	Male to male connect end-to-end	4	\$0.15	\$0.10 ea.

Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons













For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62







LED Lighting

10MM 4 In 1 Chip Technology: Including Dedicated Warm or Cool White Option

Available Lengths: 16.5'

Material: Rolled Copper PCB with White Coating

- Field Cuttable
- Flexible
- · Limited 2 Year Warranty

RED	BLUE
PURPLE	GREEN
YELLOW	CYAN

2 Options Available

IP65 10MM 4 in 1 Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible

IP20 10MM 4 in 1 Ribbon

Provides Low Protection of Dust & Water



4 In 1 Ribbon Flex: Including Dedicated Warm or Cool White Options



Lumens	CW: 90 per ft. WW: 83 per ft. Red: 21 per ft. Green: 34 per ft. Blue: 9 per ft.		
Color Rendering Index	80		
Rated Average Life	30,000 hrs.		
Constant	Voltage		
Chip Size	SMD5050		

Lighting Specifications

120°

Color Temp

Beam Spread

CW: 5500K-6500K WW: 2800K-3000K

To See A Full Line Of Our Mounting Channels, See Pages L-55~62

IP20




300

16.5



57.5

16.5'



\$79.07 (\$4.79')

Required 4 In 1 Ribbon With Dedicated CW/WW

......

For Mounting Clips (LED-5050-MC), See Page L-149


Price

Price

Required

Power Supply

FNR24-IRGB*



Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.

\$68.76 ea. (\$4.17')

RF Controller

Features:

- 3A / 24V / 72W
- Controller Size: 4-1/4"L x 2"W x 3/4"H
- Receiver Size: 3-5/8"L x 1-3/4"W x 7/8"H
- · Mounting: Surface
- Remote Control Function: RF

Controller Functions:

- Static: 3 Options
- Flashing Strobe: 4 Options
- Gradient Change: 2 Options
- · Brightness Adjusting: 8 Grades
- · Color Jumping: 5 Options
- Sound: No

LED-RGBW-CR Each: \$29.95 / 6+ Pcs.: \$25.00 ea.





Optional

End-To-End For 100% Usable Connections



		_	r	rice
Part #	Description	# of Pins	Each	6+ Pcs.
LED-RGBW-100U-EE	Usable connection directly connects 2 cut pieces	5	\$0.85	\$0.75 ea.

Connecting Cables



Part #	Description	Finish	Length	Each	6+ Pcs.
	For Cut Pieces of Ribbo	n			
LED-RGBW-C1	Directly connect 2 cut pieces of ribbon while	White	24"	\$3.25	\$2.85 ea.
LED-RGBW-C2	providing ability to get around unlit areas	White	36"	\$3.50	\$3.05 ea.









12MM 4 In 1 Chip Technology: Including Dedicated Warm or Cool White Option

Available Lengths: 16.5'

Material: Rolled Copper PCB with White Coating

- Field Cuttable
- Flexible
- · Limited 2 Year Warranty

2 Options Available

IP65 12MM 4 in 1 Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible


IP20 12MM 4 in 1 Ribbon

Provides Low Protection of Dust & Water





12MM 4 In 1 Ribbon Flex: Including Dedicated Warm or Cool White Options



			# Of LED	Total	Max # Can	Price	
Part #	IP Rating	Length	Chips	Wattage	Connect	Each	5+ Pcs.
RGB/Cool White *C5060-16 & RGB/Warm White *W5016-16							
FNC24-NRGB*	IP65	16.5'	300	88	16.5′	\$97.52 (\$5.91')	\$85.82 ea. (\$5.20')
FNC24-IRGB*	IP20	16.5'	300	88	16.5'	\$84.30 (\$5.11')	\$74.20 ea. (\$4.50')

Lighting Specifications

Color Temp	RGB/CW RGB/WW
Beam Spread	120°
Color Rendering Index	80
Rated Average Life	30,000 hrs.
Constant	Current
Chip Size	5050

Required



Optional (Any Combination)



Required

Ribbon Flex 0:0 | 0 | 0 | 0:0 For Pricing See Page L-42

Required

Power Supply



							TICE
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.
						_	

For Product Details & More Power Options, See Pages L-137~140

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

RF Controller

Features:

- 3A / 24V / 72W
- Controller Size: 4-1/4"L x 2"W x 3/4"H
- Receiver Size: 3-5/8"L x 1-3/4"W x 7/8"H
- · Mounting: Surface
- Remote Control Function: RF

Controller Functions:

- Static: 3 Options
- Flashing Strobe: 4 Options
- Gradient Change: 2 Options · Brightness Adjusting: 8 Grades
- · Color Jumping: 5 Options
- · Sound: No

RGB With Power Dedicated Supply

LED-RGBW-CR

Each: \$29.95 / 6+ Pcs.: \$25.00 ea.












LED Lighting


Accessories for 12MM 4 In 1 Chip Technology



Optional

Connectors

Connects ribbon at a 90° angle.




		_	Price	
Part #	Description	# of Pins	Each	6+ Pcs.
	For Cut Pieces o	of Ribbon		
LED-RGBW12-2W-EE-C	2-Way L	5	\$2.05	\$1.75 ea.
LED-RGBW12-3W-EE-C	3-Way T	5	\$2.05	\$1.75 ea.
LED-RGBW12-4W-EE-C	4-Way Cross	5	\$2.05	\$1.75 ea.

End To End For 100% Usable Connections



			ŀ	rice
Part #	Description	# of Pins	Each	6+ Pcs.
LED-RGBW12-100U-EE	Usable connection directly connects 2 cut pieces	5	\$0.85	\$0.75 ea.

Connecting Cables



				P	rice			
Part #	Description	Finish	Length	Each	6+ Pcs.			
	Pin Connection (Pins Included)							
LED-RGBW12-CON18	All acceptable and a single of the control of the c	Black	18"	\$2.75	\$2.40 ea.			
LED-RGBW12-CON24	Allows the designer to get around unlit areas without multiple power supplies	Black	24"	\$3.25	\$2.85 ea.			
LED-RGBW12-CON36	without multiple power supplies		36"	\$3.50	\$3.05 ea.			
For Cut Pieces of Ribbon								
LED-RGBW12-100U-C1	Directly connect 2 cut pieces of ribbon while	Multi	24"	\$4.25	\$3.70 ea.			
LED-RGBW12-100U-C2	providing ability to get around unlit areas	Multi	36"	\$4.50	\$3.95 ea.			
Hardwire To 100% Usable								
LED-RGBW12-100U-ST	Hardwire power supply or dimmer to cut pieces	Multi	79"	\$4.50	\$3.95 ea.			
Hardwire To Pin								
LED-RGBW12-MCC	Hardwire power supply or dimmer to cut pieces	Black	6"	\$1.95	\$1.50 ea.			

Mounting Clips



			Price		
Part #	Description	Length	Each	100+ Pcs.	
LED-12MM-MC-IP20	1 mounting clips & 2 screws	12mm	\$0.10	\$0.085 ea.	

End-To-End For Pin Connections

Replacement parts- included with each ribbon & accessory



			P	rice
Part #	Description	# of Pins	Each	100+ Pcs.
LED-5P-CON	LED-5P-CON Male to male connect end-to-end		\$0.20	\$0.15 ea.

Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons
For Pricing & To See A Full Line Of Our
Mounting Channels, See Pages L-55~62











5 In 1 Warm White, Cool White & RGB Ribbon

Now you can mix colors and/or create white ranging from warm to cool

Nominal Lengths: 16.5'


Material: Flexible White PCB with Adhesive

- 5 colors on the same chip
- · Over 1 trillion color combinations
- Seemless blending of RGB with Tunable White (2400K to 6500K)
- Field Trimmable
- Flexible
- 3M Adhesive Back
- Limited 3 Year Warranty





5 In 1 Warm White, Cool White & RGB Ribbon



Required


Power Supply

Lighting Specifications

Temperature	2400K + RGB + 6500K
Beam Spread	120°
Color Rendering Index	80
Rated Average Life	35,000 hrs.
Constant	Voltage
Chip Size	5050
Citip Size	5050

Required

Power Supplies



					Price								
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.						
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.						
	For Product Details & More Power Options, See Pages L-137~140												

Required

Ribbon Flex

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

RF Controller

Features:

- 6A / 24V / 144W
- 4 Zones
- Input Wire: Female DC 5.5 / Hardwire
- Output Wire: Hardwire
- Controller Size: 5-7/16"L x 2-1/4"W x 3/4"H
- Receiver Size: 3-11/32"L x 1-3/4"W x 7/8"H
- · Color: White

Controller Functions:

- Mounting: Surface
- Remote Control Function: RF
- Gradient Change: 11 Grades
- Brightness Adjusting: 20 Grades
- Fire Simulator
- Sound: No Power St



LED-WRGBW-CR

Each: \$41.60 / 6+ Pcs.: \$39.00 ea.





Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62



Required

Controller







Standard 12V Ribbon Flex: Most Economical LED Ribbon

Available Lengths: 8.25' & 16.5' Material: Flexible Silicon Cover with Adhesive





piece can be used for another project


2 Options Available

IP65 Standard 12V Ribbon

IP20 Standard 12V Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible | Provides Low Protection of Dust & Water

ECO12-*3560-* (Up To 136 Lumens Per Foot)





Shown IP65

⊐1/8"Thick

				Cuttin	ng Incre	ement Chip	S						_	_	_		_	_		_
_				(Appro	ximately	/: 1-7/8	"	11/1	6"						3M	™- Adł	nesive	tape o	n bottom	_
7	O	O	O	· · · □	Ø	O		鹵	Ō	Ø	5/16"Wide									

		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
IP65 (C	ool White *	CW, Warm	White *WV	V, Pure Whit	e *PW & Amber *A	AM)
ECO12-N3560-8-*	8.25'	150	12	33′	\$14.76 (\$1.79')	\$12.30 ea. (\$1.49')
ECO12-N3560-16-*	16.5'	300	24	33'	\$25.20 (\$1.53')	\$21.00 ea. (\$1.27')
IP20 (C	ool White *	CW, Warm	White *WV	<mark>V</mark> , Pure Whit	e *PW & Amber *	AM)
ECO12-I3560-8-*	8.25'	150	12	33′	\$9.36 (\$1.13')	\$7.80 ea. (\$0.95')
ECO12-I3560-16-*	16.5'	300	24	33'	\$16.20 (\$0.98')	\$13.50 ea. (\$0.82')

Lighting Specifications

Cable

With DC5.5

" Cable

With DC5.5

99 -	centeations
Color Temperature	CW: 5500K WW: 2800K-3200K PW: 4200K AM: 2300K
Beam Spread	120°
Lumens	110-136 per ft.
Color Rendering Index	CW: 75 WW: 80 PW: 75 AM: 75
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD3528

ECO12-*35120-* (Up To 273 Lumens Per Foot)



		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
IP65 (Co	ool White *	CW, Warm	White *WV	V , Pure Whit	e * PW & Amber *	4M)
ECO12-N35120-8-*	8.25'	300	24	33'	\$23.52 (\$2.85')	\$19.32 ea. (\$2.34')
ECO12-N35120-16-*	16.5'	600	48	33'	\$42.00 (\$2.55')	\$34.50 ea. (\$2.09')
IP20 (Co	ool White *	CW, Warm	White *WV	<mark>V</mark> , Pure Whit	e *PW & Amber */	4 <i>M)</i>
ECO12-I35120-8-*	8.25'	300	24	33′	\$18.48 (\$2.24')	\$15.18 ea. (\$1.84')
ECO12-I35120-16-*	16.5′	600	48	33'	\$33.60 (\$2.04')	\$27.60 ea. (\$1.67')

Lighting Specifications

Color Temperature	CW: 5500K WW: 2800K-3200K PW: 4200K AM: 2300K
Beam Spread	120°
Lumens	252-273 per ft.
Color Rendering Index	CW: 75 WW: 80 PW: 75 AM: 75
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD3528

Phone: 1-800-631-8375 - Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.

LED Lighting

0







Standard 12V Ribbon Flex: Most Economical LED Ribbon

ECO12-*5060-* (Up To 382 Lumens Per Foot)




rery 3rd Chip roximately: 1-7/8") 11/16"	3M™- Adhesive tape on bottom
☐ ☐ ☐ ☐ ☐ ☐ 3/8"Wide	Transite tape on socioni

		# Of LED	Total	Max # Can	Price	
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
IP65 (Co	ool White *	CW, Warm	White * W V	V , Pure Whit	e * PW & Amber *	AM)
ECO12-N5060-8-*	8.25'	150	36	23′	\$23.52 (\$2.85')	\$19.32 ea. (\$2.34')
ECO12-N5060-16-*	16.5'	300	72	23'	\$43.68 (\$2.65')	\$35.88 ea. (\$2.17')
IP20 (Cd	ool White *	CW, Warm	White *WV	V, Pure Whit	e *PW & Amber *	AM)
ECO12-I5060-8-*	8.25'	150	36	23′	\$18.48 (\$2.24')	\$15.18 ea. (\$1.84')
ECO12-I5060-16-*	16.5'	300	72	23′	\$35.28 (\$2.14')	\$28.98 ea. (\$1.76')

Lighting Specifications

Color Temperature	CW: 5500K WW: 2800-3200K PW: 4200K AM: 2300K
Beam Spread	120°
Lumens	341-382 per ft.
Color Rendering Index	CW: 75 WW: 80 PW: 75 AM: 75
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD5050

Accessories For Standard 12V Ribbon Flex



Required


Power Supplies



							TICE
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional



			Range of		F	rice
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
	1 . 5 . 1 . 0		<u> </u>	C D 1404 404014		

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables



5	Way Sweep: DC 5.5

			AIIIIS	πUI	Overall	IVIAN # OI FOWEI		
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
For Cut Pieces	of Ribbon (Powe	r Linking C	able Red	uired F	or Each (Outlet) & DC 5.5	Conne	ction
LED-2WAY-BK	2-Way Sweep	Black	3"	2	7"	2	\$2.95	\$2.50 ea.
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.
			, _				7	70.00

For More Extension Cable Options, See Page L-147



Price

May # of Power








LED Lighting

Accessories For Standard 12V Ribbon Flex



Optional

End-To-End For 100% Usable Connections



					rice
Part #	Works With	Description	# of Pins	Each	6+ Pcs.
ECO12V-35-100U-EE	3528	Usable connection directly	2	\$0.85	\$0.75 ea.
LED-RIBBON-100U-EE	5050	connects 2 cut pieces	4	\$0.85	\$0.75 ea.

Power Linking Cable

Required for multi output cables or cut pieces of ribbon.




			Overall		F	Price
Part #	Works With	Description	Length	Finish	Each	6+ Pcs.
	Fo	r Cut Pieces of Ribb	on			
ECO12V-35-100U-PL	3528	Power Link Cable	18"	Black	\$4.00	\$3.50 ea.
LED-RIBBON-100U-PL	5050	with 100% Usable Connection	18"	Black	\$4.00	\$3.50 ea.

For Hardwire Power Linking Cables, See Page L-141

Connecting Cables






					г	rice
Part #	Works With	Description	Finish	Length	Each	6+ Pcs.
		For Cut Pieces of Ribbo	n			
ECO12V-35-100U-C1	3528	Directly connect 2	Red/Black	24"	\$3.25	\$2.85 ea.
LED-RIBBON-100U-C1	5050	cut pieces of ribbon while	White	24"	\$3.25	\$2.85 ea.
ECO12V-35-100U-C2	3528	providing ability to get	Red/Black	36"	\$3.50	\$3.05 ea.
LED-RIBBON-100U-C2	5050	around unlit areas	White	36"	\$3.50	\$3.05 ea.
		Hardwire				
ECO12V-35-100U-ST	3528	Hardwire power supply or	Red/Black	79"	\$4.50	\$3.95 ea.
LED-RIBBON-100U-ST	5050	dimmer to cut pieces	White	79"	\$4.50	\$3.95 ea.
	For More Ex	tension Cable Options, See P	ages L-145~	146		

Connectors

Connects ribbon at a 90° angle.



Part #	Works With	Description	# of Pins	Each	6+ Pcs.
	For	Cut Pieces of Ribbon			
ECO12V-35-2W-EE-C	3528	2 Way I	2	\$1.75	\$1.50 ea.
LED-RIBBON-2W-EE-C	5050	2-Way L	4	\$1.75	\$1.50 ea.
ECO12V-35-3W-EE-C	3528	2 Way T	2	\$1.75	\$1.50 ea.
LED-RIBBON-3W-EE-C	5050	3-Way T	4	\$1.75	\$1.50 ea.
ECO12V-35-4W-EE-C	3528	4-Way Cross	2	\$1.75	\$1.50 ea.
LED-RIBBON-4W-EE-C	5050	4-Way Cross	4	\$1.75	\$1.50 ea.

Mounting Clips



					rice
Part #	Works With	Description	Length	Each	100+ Pcs.
LED-3528-MC	3528	1 mounting clips & 2 screws	10mm	\$0.10	\$0.085 ea.
LED-5050-MC	5050	1 mounting clips & 2 screws	10mm	\$0.10	\$0.085 ea.

For More Mounting Clip Options, See Page L-149

Universal LED Ribbon Mounting Channels

Aluminum channels that work with our ribbons











For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62

Price

D..: --







Standard 12V LED RGB Ribbon Flex: Most Economical LED Ribbon

Available Lengths: 8.25' & 16.5' Material: Flexible White PCB with Adhesive

- Ideal for budget conscience applications
- Field trimmable

2 Options Available

IP65 Standard 12V RGB Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible

IP20 Standard 12V RGB Ribbon

Provides Low Protection of Dust & Water

Connect Ribbon Using Our 4 Pin Connecting System



Standard 12V LED RGB Ribbon Flex





			# Of LED	Total	Max # Can		Price
Part #	Color Temp	Length	Chips	Wattage	Connect	Each	10+ Pcs.
				IP65			
ECO12-N5060-8-RGB	RGB	8.25'	150	36	16.5′	\$23.48 (\$2.85')	\$19.27 ea. (\$2.34')
ECO12-N5060-16-RGB	RGB	16.5'	300	72	16.5′	\$43.89 (\$2.66')	\$35.85 ea. (\$2.17')
				IP20			
ECO12-I5060-8-RGB	RGB	8.25'	150	36	16.5′	\$20.16 (\$2.44')	\$16.56 ea. (\$2.01')
ECO12-I5060-16-RGB	RGB	16.5'	300	72	16.5′	\$36.96 (\$2.24')	\$30.36 ea. (\$1.84')

Lighting Specifications

4" Cable

With 4 Pin


Beam Spread	120°
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD5050

Accessories for Standard 12V LED RGB Ribbon Flex





	Optional	(Any (Combination)	
	Connector		Connecting Cable	
+	.	&/or		-
	See Page L-49		See Page L-49	



Optional		
Amp	lifier	
See Pa	ge L-49	

ゴ1/8"Thick

Required


Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
		_			·		

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Controllers



Part #	Description	Input Wire	Output Wire	Dimensions	Each	6+ Pcs.
	Deluxe RGB controller	Female	4 Pin	4-3/8"L x		
LED-RGB36-CRP	with up to 25 color	DC 5.5:	Connection:	2-1/8"W x	\$35.95	\$31.00 ea.
	changing functions	18"	18"	1″H		
	Super small RGB controller	Female	4 Pin	1-1/2"L x		
LED-RGB36-INLINE	with up to 20 color	DC 5.5:	Connection	1/2"W x	\$9.95	\$9.00 ea.
	changing functions	3-1/2"	Connection	1/8"H		

For Product Details & More Controller Options, See Pages L-134~136 & L-150 Other Options: Radio Frequency | Sound Activated

Price








LED Lighting

Optional

Connectors

Connects ribbon at a 90° angle.



	<u>100% Usabl</u>	<u>e</u>
2-Way	3-Way	4-Way


			_	Price			
Part #	Works With	Description	# of Pins	Each	6+ Pcs.		
LED-RIBBON-2W-C	RGB Ribbon	2-Way L	4	\$1.75	\$1.50 ea.		
LED-RIBBON-3W-C	RGB Ribbon	3-Way T	4	\$1.75	\$1.50 ea.		
LED-RIBBON-4W-C	IBBON-4W-C RGB Ribbon		4	\$1.75	\$1.50 ea.		
	For Co	ut Pieces of Ribbon					
LED-RIBBON-2W-EE-C	RGB Ribbon	2-Way L	4	\$1.75	\$1.50 ea.		
LED-RIBBON-3W-EE-C	RGB Ribbon	3-Way T	4	\$1.75	\$1.50 ea.		
LED-RIBBON-4W-EE-C	RGB Ribbon	4-Way Cross	4	\$1.75	\$1.50 ea.		


End-To-End For 100% Usable Connections



			_	P	rice
Part #	Works With	Description	# of Pins	Each	6+ Pcs.
LED-RIBBON-100U-EE	RGB Ribbon	Usable connection directly connects 2 cut pieces	4	\$0.85	\$0.75 ea.

Connecting Cables








					Price		
Part #	Works With	Description	Finish	Length	Each	6+ Pcs.	
LED-RIBBON-RGB-CON	RGB Ribbon	Allows the designer to get	Black	18"	\$2.75	\$2.40 ea.	
LED-RIBBON-RGB-C24	RGB Ribbon	around unlit areas without	Black	24"	\$3.25	\$2.85 ea.	
LED-RIBBON-RGB-C36	RGB Ribbon	multiple power supplies	Black	36"	\$3.50	\$3.05 ea.	
		For Cut Pieces of Ribbo	n				
LED-RIBBON-100U-R1	RGB Ribbon	Directly connect 2 cut pieces of ribbon while	Multi	24"	\$4.25	\$3.70 ea.	
LED-RIBBON-100U-R2	RGB Ribbon	providing ability to get around unlit areas	Multi	36"	\$4.50	\$3.95 ea.	
	Din Connec	tion (Districted A) To Cut Di	acce of Di	la la a sa			

Pin Connection (Pin Included) To Cut Pieces of Ribbon

Directly connect pin to LED-RIBBON-100U-4P **RGB Ribbon** cut piece of ribbon to get Multi 18" \$1.85 around unlit areas

For More Extension Cable Options, See Pages L-146

Amplifiers



Part #	Description	Input Wire	Output Wire	Dimensions	Each	6+ Pcs.
LED-RIBBON-RGB-AMP	Is to extend the signal of an RGB controller when the power supply	4 Pin Connection: 18"	4 Pin Connection: 18"	3-1/2"L x 2-1/2"W x 7/8"H	\$17.50	\$15.65 ea.
LED-RGBMIN-AMP	is exceeded. (Must purchase another power supply when using this product)	4 Pin Connection	4 Pin Connection	1-5/8"L x 1/2"W x 1/8"H	\$8.00	\$7.20 ea.

Mounting Clips



				Price					
Part #	Works With	Description	Length	Each	100+ Pcs.				
LED-5050-MC	1 mounting clips & 2 screws	10mm	\$0.10	\$0.085 ea.					
	LED-5050-MC RGB Ribbon 1 mounting clips & 2 screws 10mm For More Mounting Clip Options, See Page L-149								

End-To-End For Pin Connections

Replacement parts-included with each ribbon & acces \mathbf{n}

ППП

ssory	
3301 9	

Part #	Works With	Description	# of Pins	Each	100+ Pcs.	
LED-4P-CON	RGB Ribbon	Male to male connect end-to-end	4	\$0.15	\$0.10 ea.	

Universal LED Ribbon Mounting Channels Aluminum channels that work with our ribbons

For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62



\$1.70 ea.

Price

Price







Thin 12V Ribbon Flex

Available Lengths: 4', 8.25' & 16.5' Material: Flexible White PCB with Adhesive



Thinnest Ribbon On The Market... Only 4mm (.157")

Easy To Hide

IP65 Thin 12V Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible | Provides Low Protection of Dust & Water

DC12Y CO12V

IP20 Thin 12V Ribbon

In Fixtures

7" Cable With DC5.5

Special Feature Ribbon has 2 female ends (DC 5.5) so it can be cut to size and then the remaining piece can be used for another project

7" Cable With DC5.5

Basic Brightness (Up To 146 Lumens Per Foot)

	crements rd Chip nately: 2")	5/8"				-	-	 3M™-	- Adhe	esive t	ape or	n bott	om	 -	1/16"	Thic
0			Ø	0 ∫.157″ Wide												

		# Of LED	Total	Max # Can _	P	rice
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
	IP65 (Cool V	Vhite *CW,	Warm Whi	te *WW & Pu	ıre White * PW)	
SPT12-N3060-4-*	4′	75	6	23′	\$9.58 (\$2.39')	\$7.87 ea. (\$1.97')
SPT12-N3060-8-*	8.25'	150	12	23'	\$18.82 (\$2.28')	\$15.46 ea. (\$1.87')
SPT12-N3060-16-*	16.5'	300	24	23'	\$36.96 (\$2.24')	\$30.36 ea. (\$1.84')
	IP20 (Cool V	Vhite *CW,	Warm Whi	te *WW & Pu	ıre White * <mark>PW</mark>)	
SPT12-I3060-4-*	4′	75	6	23′	\$8.40 (\$2.10')	\$6.90 ea. (\$1.73')
SPT12-I3060-8-*	8.25'	150	12	23'	\$16.30 (\$1.98')	\$13.39 ea. (\$1.62')
SPT12-I3060-16-*	16.5'	300	24	23′	\$31.92 (\$1.93')	\$26.22 ea. (\$1.59')

Lighting Specifications

Color Temperature	CW: 6300K PW: 4400K WW: 3200K
Beam Spread	120°
Lumens	120-146 per ft.
Color Rendering Index	80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	SMD3014

Standard Brightness (Up To 292 Lumens Per Foot)



		# Of LED	Total	Max # Can	Price	
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
	IP65 (Cool V	Vhite *CW,	Warm Whi	te *WW & Pu	ıre White * PW)	
SPT12-N30120-4-*	4′	150	12	13′	\$15.12 (\$3.78')	\$12.42 ea. (\$3.11')
SPT12-N30120-8-*	8.25'	300	24	13′	\$30.24 (\$3.67')	\$24.84 ea. (\$3.01')
SPT12-N30120-16-*	16.5′	600	48	13′	\$49.68 (\$3.01')	\$43.20 ea. (\$2.62')
	IP20 (Cool V	Vhite *CW,	Warm Whi	te *WW & Pu	ıre White * <mark>PW</mark>)	
SPT12-I30120-4-*	4′	150	12	13′	\$13.83 (\$3.46')	\$11.36 ea. (\$2.84')
SPT12-I30120-8-*	8.25'	300	24	13′	\$27.72 (\$3.36')	\$22.77 ea. (\$2.76')
SPT12-I30120-16-*	16.5′	600	48	13′	\$45.54 (\$2.76')	\$39.60 ea. (\$2.40')

Lighting Specifications

Color Temperature	CW: 6300K PW: 4400K WW: 3200K
Beam Spread	120°
Lumens	272-292 per ft.
Color Rendering Index	80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	SMD3014








LED Lighting

Thin 12V Ribbon Flex

Ultra Brightness (Up To 482 Lumens Per Foot)






		# Of LED	Total	Max # Can	Price	
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
I	P65 (Cool V	/hite *CW,	Warm Whi	te *WW & Pu	re White * PW)	
SPT12-N30198-4-*	4′	248	20	11.5′	\$24.02 (\$6.01')	\$19.73 ea. (\$4.93')
SPT12-N30198-8-*	8.25'	495	40	11.5'	\$47.04 (\$5.70')	\$38.64 ea. (\$4.68')
SPT12-N30198-16-*	16.5'	990	79	11.5′	\$77.28 (\$4.68')	\$70.98 ea. (\$4.30')
ı	P20 (Cool V	/hite *CW,	Warm Whi	te *WW & Pu	re White *PW)	
SPT12-I30198-4-*	4′	248	20	11.5′	\$22.74 (\$5.68')	\$18.68 ea. (\$4.67')
SPT12-I30198-8-*	8.25'	495	40	11.5'	\$44.52 (\$5.40')	\$36.57 ea. (\$4.43')
SPT12-I30198-16-*	16.5'	990	79	11.5′	\$73.14 (\$4.43')	\$66.78 ea. (\$4.04')

Lighting Specifications

Color Temperature	CW: 6300K PW: 4400K WW: 3200K
Beam Spread	120°
Lumens	450-482 per ft.
Color Rendering Index	80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	SMD3014

Accessories For Thin 12V Ribbon Flex



Required

Power Supplies



						r	rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional Dimmers



Range of						Price
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables



			Arms	# of	Overall	Max # of Power		Price
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-2WAY-BK	2-Way Sweep	Black	3″	2	7″	2	\$2.95	\$2.50 ea.
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.

For More Extension Cable Options, See Page L-147





Universal LED Ribbon Mounting Channels Aluminum channels that work with our ribbons For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62

Duisa







Thin 12V RGB Ribbon Flex

Available Lengths: 8.25' & 16.5' Material: Flexible White PCB with Adhesive

- 60% Smaller Than Anything
- Works With Our Magic Backlighting Sheet & DIY: Brite Light Sheet (See Pages L-12~15)
- Easy To Hide





2 Options Available

IP65 Thin 12V RGB Ribbon

Provides Protection From Dust & Splashing Water, Not Submersible | Provides Low Protection of Dust & Water

Thin 12V LED RGB Ribbon Flex



			# Of LED	Total	Max # Can	Price Each 10+ Pcs.	
Part #	Color Temp	Length	Chips	Wattage	Connect		
				IP65			
SPT12-N3560-8-RGB	RGB	8.25'	150	36	23'	\$50.40 (\$6.11')	\$41.40 ea. (\$5.02')
SPT12-N3560-16-RGB	RGB	16.5'	300	72	23′	\$100.80 (\$6.11')	\$82.80 ea. (\$5.02')
				IP20			
SPT12-3560-8-RGB	RGB	8.25'	150	36	23′	\$47.88 (\$5.80')	\$39.33 ea. (\$4.77')
SPT12-3560-16-RGB	RGB	16.5'	300	72	23′	\$95.76 (\$5.80')	\$78.66 ea. (\$4.77')

Lighting Specifications Beam Spread 120° Rated 20,000 hrs. Average Life Constant Voltage SMD3535 Chip Size

4" Cable With 4 Pin

Accessories for Standard 12V LED RGB Ribbon Flex



Required


Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Controllers



Part #	Description	Input Wire	Output Wire	Dimensions	Each	6+ Pcs.
LED-RGB36-CRP	Deluxe RGB controller with up to 25 color changing functions	Female DC 5.5: 18"	4 Pin Connection: 18"	4-3/8"L x 2-1/8"W x 1"H	\$35.95	\$31.00 ea.
LED-RGB36-INLINE	Super small RGB controller with up to 20 color changing functions	Female DC 5.5: 3-1/2"	4 Pin Connection	1-1/2″L x 1/2″W x 1/8″H	\$9.95	\$9.00 ea.

For Product Details & More Controller Options, See Pages L-134~136 & L-150 Other Options: Radio Frequency | Sound Activated

Price









LED Lighting

Flex-S Ribbon

Flexible design allows you to create visible bends & 90° turns

Material: Flexible White PCB with Adhesive

• Flex-S LED Strip Lights Are Ideal For:
Halo Effect Signage, Back-lit 3D Letters,
Sign Letter Lighting, Archways,
Retail Display Lighting,
Architectural Lighting
& Accent Lighting.

Nominal Lengths: 16.5'

- Field Trimmable
- Flexible
- Twist & Turn On Sharp Corners
- Bend Sideways
- 3M Adhesive Back
- · Limited 3 Year Warranty





FLX126-I2860-16 (Up To 363 Lumens Per Foot)

0 + 0 0 + 0 0 + 0 0 1/4"Wide



		# Of LED	Total	Max # Can	P	rice
Part #	Length	Chips	Wattage	Connect	Each	5+ Pcs.
	Cool W	hite * CW , Wa	ırm White *	WW & Pure N	/hite *PW	
FI X126-I2860-16*	16.5'	300	36	16.5'	\$40.04 (\$2.43')	\$35.75 ea (\$2.17')

Lighting Specifications

Color Temperature	CW: 6000K WW: 3000K PW: 4000K
Beam Spread	120°
Lumens	363 per ft.
Color Rendering Index	80
Rated Average Life	35,000 hrs.
Constant	Voltage
Chip Size	2835

Powe



Required

Optional (Pick One Option)

3M[™]- Adhesive tape on bottom



Required

41/32"Thick



Required

Power Supplies



							TICE
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.
						_	

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers
A power linking cable required.

			Range of		P	rice
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144

Other Options: Rotary | Touch Dimmer | Radio Frequency

Universal LED Ribbon Mounting Channels
Aluminum channels that work with our ribbons

For Pricing & To See A Full Line Of Our Mounting Channels, See Pages L-55~62










Edge of Light: Light Is Directed To The Front or Back of Desired Lit Surface

Available Lengths: 22.5", 6' & 16.5' *Material: Flexible PVC Cover with Adhesive*

- Commercial Grade
- Field Trimmable
- Connectable male / female connector included
- Dimmable
- IP67 suitable in damp locations, not submersible





Edge of Light (Up To 125 Lumens Per Foot)



.596" distance betwee	n lights (Ap _l	orox. 5/8")	- wide	31	¶™- Adhesive tape or	n bottom
		# Of LED	Total	Max # Can		Price
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
		Cool W	hite *CW &	Warm White	*WW	
LED-EOL-12V-*	22.5"	40	3.12	32'	\$7.65 (\$4.08')	\$6.12 ea. (\$3.26')
LED-EOL-12V-*6	6′	120	9.36	32'	\$22.95 (\$3.83')	\$18.36 ea. (\$3.06')
LED-EOL-12V-*9	16.5'	330	26.4	32'	\$64.80 (\$3.93')	\$51.84 ea. (\$3.14')

Lignting	pecifications
Color Temperature	CW: 5500K WW: 3300K
Beam Spread	120°
Lumens	CW: 125 per ft. WW: 113 per ft.
Color Rendering Index	CW: 75 WW: 80
Rated Average Life	40,000 hrs.
Constant	Voltage
Chip Size	SMD3020

Required		Optional		Required
Power Supply		Dimmer		Edge of Light
	+		+	010=01010=0101

Required

Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.45	\$14.70 ea.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.
		1		_	0 11		

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers



			Range of		P	rice
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144

Other Options: Rotary | Touch Dimmer | Radio Frequency

Due to raw material cost fluctuations, prices are subject to change.

Drice



Outwater's Plastic Lens For LED Lighting: Lens Only

LENS CHARACTERISTICS									
Color	Transmission	Transmission Dispersion Surface Texture LED Diodes							
Frosted	High	High Low Pebbled							
Milk White	Medium	Medium Medium Smooth Slightly Visil							
Opaque White	Opaque White Low High Smooth Not Visible								

Frosted Lens: Allows the most light transmission. This is recommended for task lighting.

Milk White Lens: Allows moderate light transmission. The effect softens the light and reduces glare. A good choice for the largest variety of lighting situations

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases

These characteristics are general descriptions.
Customers must decide which color most suits their needs.

• Color: Opaque White

Under

120 Ft.

\$0.98 ft.

120 Ft. +

600 Ft. +

\$0.92 ft. \$0.82 ft.

· Length: 8 Ft.

Part #

L-VISION-F-WH



L-TASK-10LENS L-TASK-12LENS L-TASK-14LENS Material: Acrylic • Material: Styrene Material: Styrene Color: Frosted Or Color: Frosted Or Color: Frosted Or **Opaque White Opaque White Opaque White** · Length: 8 Ft. · Length: 8 Ft. · Length: 4 Ft. Under Under Under 600 Ft. + Part # Part # Part # 120 Ft. 120 Ft. + 120 Ft. 120 Ft. + 600 Ft. + 120 Ft. 120 Ft. + 600 Ft. + L-TASK-12LENS* \$0.76 ft. **L-TASK-14LENS*** \$1.21 ft. \$1.07 ft. \$0.98 ft. **L-TASK-10LENS*** \$1.03 ft. \$0.96 ft. \$0.90 ft. \$0.68 ft. \$0.62 ft. *For Opaque White Add -WH to the Part Number *For Opaque White Add -WH to the Part Number *For Opaque White Add -WH to the Part Number L-TASK-6LENS L-TASK-7DLENS L-TASK-8LENS · Material: Acrylic · Material: Acrylic Material: Acrylic Color: Frosted Or Color: Frosted Color: Frosted Or **Opaque White** · Length: 8 Ft. **Opaque White** · Length: 8 Ft. • Length: 8 Ft. Under Part # 120 Ft. 120 Ft. + 600 Ft. + Part # 120 Ft. + 600 Ft.+ Under 120 Ft. L-TASK-6LENS \$1.253 ft. \$1.12 ft. \$1.00 ft. Part # 120 Ft. + 600 Ft. + 120 Ft. L-TASK-8LENS* \$1.35 ft. \$1.22 ft. \$1.12 ft. **L-TASK-7DLENS*** \$1.21 ft. \$1.09 ft. \$0.99 ft. *For Opaque White Add -WH to the Part Number *For Opaque White Add -WH to the Part Number LED-OS-216-* L-VISION-D-WH L-TASK-15LENS · Material: Styrene .878" · Material: Acrylic Color: Frosted · Material: Acrylic · Color: Opaque White • Length: 4 Ft. & 8 Ft. Color: Frosted Or · Length: 8 Ft. Under **Opaque White** 1.36" Part # Length 120 Ft. 120 Ft. + 600 Ft. + • Length: 8 Ft. Under **LED-OS-216-4** 4 Ft. \$0.745 ft. \$0.69 ft. \$0.64 ft. Part # 120 Ft. 120 Ft. + 600 Ft. + LED-OS-216-8 8 Ft. \$0.745 ft. \$0.69 ft. \$0.64 ft. L-VISION-D-WH \$0.94 ft. \$0.84 ft. \$0.80 ft. Under Part # 120 Ft. 120 Ft. + 600 Ft.+ **L-TASK-15LENS*** \$1.22 ft. \$1.07 ft. \$0.99 ft. *For Opaque White Add -WH to the Part Number L-VISION-F-WH **LED-MTLENS L-TASK-1LENS** • Material: Acrylic · Material: Acrylic · Material: Acrylic Color: Frosted Or · Color: Milk White

• Length: 4 Ft.

Part #

LED-MTLENS

Under

120 Ft.

\$0.745 ft.

120 Ft. +

600 Ft. +

\$0.69 ft. \$0.65 ft.

600 Ft. +

\$0.96 ft. \$0.895 ft.

Opaque White

Under

120 Ft.

\$1.03 ft.

*For Opaque White Add -WH to the Part Number

120 Ft. +

· Length: 8 Ft.

Part #

L-TASK-1LENS*





Enhances Lighting Effect While Providing Even Illumination

LED task system allows for the look of a fixture • Tremendous design opportunities for custom sizes • Options available to work with all of our ribbons

LED Channels

PART #	4MM	6MM	8MM W/O CONN	8MM W/ CONN	10MM W/O CONN	W/	11MM x 6MM	12MM W/O CONN	12MM W/ CONN	15MM W/O CONN	15MM W/ CONN	15.9MM x 9.5MM	20MM W/O CONN	20MM W/ CONN	30MM	40MM
	.157" W	1/4" W	5/16" W	1/2" W	3/8" W	9/16" W	7/16" x 1/4"	1/2" W	5/8" W	9/16" W	13/16" W	5/8" x 3/8"	9/16" W	1" W	1-3/16" W	1-9/16" W
	SPT 12V	SPT 12V RGB DP 24V	ECO 12V DP 24V FLX 12V	DP 24V FLX 12V	RIB 24V ECO 12V FNR 24V	FNR 24V	MXL 120V	FVR 24V		DP 24V	DP 24V	DBL RGB	DP 24V	DP 24V	DP 24V	DP 24V
						Anodiz	ed Alu	minum	Chan	nels						
L-TASK-1F	Х	Х	Х		Х											
L-TASK-2F	Х	Х	Х		Х											
L-TASK-3F	Х	Х	Х		Х											
L-TASK-3LF	Х	Х	Х	Х	Х	Х		Х		Х			Х			
L-TASK-4D & 4S	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-TASK-45D & 45S	Х	X	X	X	Х	Х	X	Х	Х	Х			Х			
L-TASK-6F	Х	X	X	Х	Х	X		X	Х	Х			Х			
L-TASK-7D	X	Х	X	X	X	X	X	X	X	X	X	X	X			
L-TASK-8F	X	Х	X	X	X	X	X	X	Х	X	X	X	X	X	X	
L-TASK-9	X	Х	X	X	X	X	X	X	X	X	X	X	X			
L-TASK-10F	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-TASK-11	Х	X	Х		Х											
L-TASK-12 & 12F	Х	Х	Х		Х		12									
L-TASK-13	Х	X	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		
L-TASK-14F	Х	Х	Х	Х	Х	Х	Х	Х		Х			Х			
L-TASK-15D	Х	Х	Х	Х	Х	Х	Х	Х		Х			Х			
L-TASK-16	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			
L-TASK-17 & 17D	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	17D	Х			
L-TASK-18 & 18F	Х	Х	Х		Х		Х									
L-TASK-19D & 19S	Х	Х	Х		Х											
L-TASK-20PD-6	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			
L-TASK-21PD-6	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-TASK-22WP-6	Х	Х	Х	Х	Х		Х	Х								
L-TASK23W-6	Х	Х	Х		Х											
L-TASK-25-6	Х	Х	Х	Х	Х	Х		Х	Х	Х	Х		Х	Х		
L-TASK26-6	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			Х			
L-TASK-57	Х															
L-TASK-82	Х															
L-TASK-149	Х															
L-TASK-CLO	Х	Х	Х		Х											
						Plast	ic PVC (Channe	els							
L-TASK-133-BK & SIL	Х	Х	Х		Х											
L-TASK-35P-4 & 8	X	X	X		X											
L-TASK-50P-4 & 8	X	X	X	Х	X			Х								
L-TASK-50PS-4 & 8	X	X	X	X	X			X								

English measurements converted from metric. Metric is the most accurate.



LENS CHARACTERISTICS									
Color	Color Transmission Dispersion Surface Texture LED Diodes								
Frosted	High	Low	Pebbled	Visible					
Milk White	Medium Medium Smooth Slightly Vis								
Opaque White									

These characteristics are general descriptions. Customers must decide which color most suits their needs. Frosted Lens: Allows the most light transmission. This is recommended for task lighting.

Milk White Lens: Allows moderate light transmission. The effect softens the light and reduces glare. A good choice for the largest variety of lighting situations

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases

LED Aluminum Channels With Lens: Create Your Own Light Fixture

L-TASK-1F



L-TASK-2F



L-TASK-3F



Length: 4 Ft. **Soft White Acrylic Lens**

Part #	Price	120+
L-TASK-1F	\$2.57 ft.	\$2.24 ft.

Accessory Fuck			
Part #	Price	100+	
L-TASK-13-ACC	\$1.45 set	\$1.25 set	
Includes 2 End Caps, 2 Mounting Clips & Screws			

Length: 4 Ft. **Soft White Acrylic Lens**

Part #	Price	120+
L-TASK-2F	\$3.36 ft.	\$2.92 ft.
	Accessory Pack	

Part # Price 100+ L-TASK-2-ACC \$1.45 set \$1.25 set Includes 2 End Caps, 2 Mounting Clips & Screws

L-TASK-4

Length: 4 Ft. **Soft White Acrylic Lens**

Part #	Price	120+
L-TASK-3F	\$2.47 ft.	\$2.15 ft.

L-TASK-3LF











Length: 4 Ft. Frosted Styrene Lens

Part #	Price	120+
L-TASK-3LF	\$3.03 ft.	\$2.63 ft.

Length: 8 Ft. No Lens Price Part # 120+ L-TASK-4 \$1.42 ft. \$1.27 ft.

Length: 8 Ft. **Frosted Acrylic Lens**

Part #	120+	
L-TASK-4D	Price \$2.24 ft.	\$1.95 ft.
= 171511 15	72.2 III.	y 1.25 1t.

L-TASK-4S









\$1.05 set

L-TASK-45S


Length: 8 Ft. **Frosted Acrylic Lens**

Part # Price		120+
L-TASK-4S	\$2.45 ft.	\$2.13 ft.

Frosted Acrylic Lens

Length: 8 Ft. **Frosted Acrylic Lens**

Part #	Price	120+
L-TASK-45D	\$3.87 ft.	\$3.36 ft.






Length: 8 Ft. **Frosted Acrylic Lens**

Part #	Price	120+
L-TASK-45S	\$3.98 ft.	\$3.46 ft.

L-TASK-6F





Į.	.79" ,	
र्धी		
-	.92"	

Part # Price 120+ L-TASK-6F \$3.30 ft. \$2.87 ft. End Caps-Set of 2 Part # **Price** 100+

L-TASK-6-END \$1.25 set Mounting Cline Set of 3

wounting Clips- Set of 2		
Part #	Price	100+
L-TASK-6-CLIP	\$1.50 set	\$1.40 set

L-TASK-7D



Length: 8 Ft.

Frosted Styrene Lens Part # Price 120+ L-TASK-7D \$2.96 ft. \$2.57 ft.

Phone: 1-800-631-8375 Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.


LED Lighting




LED Aluminum Channels With Lens: Create Your Own Light Fixture




Part # L-TASK-11




Length: 8 Ft. Frosted Acrylic Lens			
Part # Price 120+			
L-TASK-8F	\$3.80 ft.	\$3.30 ft.	






Part #	Price	120+
L-TASK-9	\$1.45 ft.	\$1.26 ft.





Length: 8 Ft. **Frosted Acrylic Lens** Price 120+ Part # L-TASK-10F \$3.13 ft. \$2.72 ft.







Length: 8 Ft. No Lens	
Price	120+
\$1.32 ft.	\$1.17 ft.







100+

\$0.60 set

Length: 8 Ft. No Lens

Part #	Price	120+
L-TASK-12	\$1.43 ft.	\$1.25 ft.
E	nd Caps- Set of 2	2

Price

\$0.75 set

Mounting Clips- Set of 2		
Part #	Price	100+
L-TASK-12-CLIP	\$1.00 set	\$0.80 set

L-TASK-12F






110	steu Styrene Le	1113
Part #	Price	120+
L-TASK-12F	\$2.29 ft.	\$1.99 ft.
E	nd Caps- Set of 2	?

Part #	Price	100+
L-TASK-12-END	\$0.75 set	\$0.60 set
Mount	ing Clips- Set o	f 2

Part #	Price	100+
L-TASK-12-CLIP	\$1.00 set	\$0.80 set


L-TASK-13





	Length: 8 Ft. No Lens	
Part #	Price	120+
L-TASK-13	\$1.66 ft.	\$1.44 ft.

L-TASK-14F



Part #

L-TASK-12-END



Length: 4 Ft. Frosted Styrene Lens			
Part # Price 120+			
L-TASK-14F	\$3.54 ft.	\$3.07 ft.	


L-TASK-15D





Length: 8 Ft. **White Opaque Styrene Lens** Part # Price 120+ \$2.66 ft. L-TASK-15D \$2.31 ft.

L-TASK-16






	Length: 12 Ft. No Lens	
Part #	Price	120+
L-TASK-16	\$1.63 ft.	\$1.42 ft.

L-TASK-17

Length: 8 Ft. No Lens Price Part # 120+ L-TASK-17 \$1.66 ft. \$1.51 ft.







Length: 8 Ft. **White Opaque Styrene Lens** Price Part # 120+ L-TASK-17D \$2.87 ft. \$2.49 ft.



LED Aluminum Channels With Lens: Create Your Own Light Fixture





L-TASK-18-6

Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+ L-TASK-18-6 \$1.21 ft. \$1.05 ft. **End Caps-Set of 2** 100+ Part # Price

L-TASK-18-CAP \$0.35 set \$0.29 set **Mounting Clips-Set of 2**

Part #	Price	100+
L-TASK-18-CLIP	\$0.35 set	\$0.29 set







L-TASK-18F-6

Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+ L-TASK-18F-6 \$1.27 ft. \$1.10 ft. **End Caps-Set of 2** Price Part # 100+ L-TASK-18F-CAP \$0.35 set \$0.29 set

Mounting Clips- Set of 2

Part #	Price	100+
L-TASK-18F-CLIP	\$0.35 set	\$0.29 set



L-TASK-19D-*

Length: 3.3 Ft. & 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Price L-TASK-19D-3 \$1.46 ft. \$1.27 ft. L-TASK-19D-6 \$1.13 ft. \$1.30 ft.

End Caps- Set of 2

Part #	Price	100+
L-TASK-19D-CAP	\$0.45 set	\$0.35 set
Mounting Clips- Set of 2		
Part #	Price	100+
L-TASK-19D-CLIP	\$0.45 set	\$0.35 set



Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Price L-TASK-19S-3 \$1.56 ft. \$1.36 ft. L-TASK-19S-6 \$1.40 ft. \$1 22 ft

End Caps- Set of 2

Part #	Price	100+
L-TASK-19S-CAP	\$0.45 set	\$0.35 set
Mounting	2	
Davt #	Drico	100

L-TASK-19S-CLIP \$0.45 set \$0.35 set









Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+

L-TASK-20PD-6 \$2.38 ft. \$2.07 ft.

End Caps-Set of 2 Part # Price 100+ **L-TASK-20PD-CAP** \$0.45 set \$0.35 set

Mounting Clips-Set of 2

Part #	Price	100+
L-TASK-20PD-CLIP	\$0.45 set	\$0.35 set





End Caps- Set of 2

Part #		Price	100+
ĺ	L-TASK-21PD-CAP	\$0.60 set	\$0.55 set







Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+ L-TASK-22WP-6 \$2.11 ft. \$1.83 ft.

End Caps- Set of 2

Price 100+ Part # L-TASK-22WP-CAP \$0.45 set \$0.35 set

Mounting Clips- Set of 2

Part # Price 100+ \$0.45 set L-TASK-22WP-CLIP \$0.35 set



1.06"





L-TASK-23W-6

Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+ L-TASK-23W-6 \$1.41 ft. \$1.23 ft. End Caps- Set of 2 Price 100+ Part # L-TASK-23W-CAP \$0.45 set \$0.35 set



100+ L-TASK-23W-CLIP \$0.45 set \$0.35 set







Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+

L-TASK-25-6 \$2.51 ft. \$2.18 ft. End Caps- Set of 2

Part # Price 100+ L-TASK-25-CAP \$0.45 set \$0.35 set

Mounting Clips-Set of 2

Part # Price 100+ L-TASK-25-CLIP \$0.45 set \$0.35 set





L-TASK-26-6

Length: 6.6 Ft. • Milky White Lens Accessories (2- End Caps & 2- Mounting Clips) Part # Price 120+ L-TASK-26-6 \$1.99 ft. \$1.66 ft.

End Caps- Set of 2

Part # Price 100+ L-TASK-26-CAP \$0.45 set \$0.35 set

Mounting Clips- Set of 2

Part # Price 100+ L-TASK-26-CLIP \$0.45 set \$0.35 set



LED Aluminum Channels With Lens: Create Your Own Light Fixture







For LED Closet Rod Kit, See page L-100



Plastic PVC Channels: Create Your Own Light Fixture

- Designed for glass or acrylic edge lighting
- Holds our 3/8" LED Ribbon
- Perfect for etched or engraved substrate light guide panels
- · No adhesive needed friction fit



Part #

L-TASK-133-BK

L-TASK-133-SIL





No Lens Finish Price 120+ \$0.70 ft. Silver \$0.64 ft. \$0.67 ft. \$0.61 ft. Black











No Lens Part # Finish Length Price 120+ 4 ft. (*4) or \$0.40 ft. L-TASK-35P-* \$0.36 ft. Clear 8 ft. (*8)

Length: 4 Ft. or 8 Ft.





Length: 4 Ft. or 8 Ft. No Lens

Part #	Finish	Length	Price	120+
L-TASK-50P-*	Clear	4 ft. (*4) or	\$0.44 ft.	\$0.40 ft.
L-TASK-50PS-*	Silver	8 ft. (*8)	\$0.45 ft.	\$0.41 ft.



Introducing Outwater's Vision Series

Our Special Opaque White Lens will soften & virtually eliminate hot spots



Outwater's Vision Series enables designers to readily create colorful RGB wallscapes or high luminescence task lights.

LED Lens

LENS CHARACTERISTICS								
Color Transmission Dispersion Surface Texture LED Diodes								
Opaque White	Low	High	Smooth	Not Visible				

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases

These characteristics are general descriptions.

Customers must decide which color most suits their needs.

- LED vision system allows for the look of a fixture
- Tremendous design opportunities for custom sizes
- Options available to work with all of our ribbons



LED Channels

PART #	4MM	6MM	8MM W/O CONN	8MM W/ CONN	10MM W/O CONN	10MM W/ CONN	11MM x 6MM	12MM W/O CONN	12MM W/ CONN	15MM W/O CONN	15MM W/ CONN	15.9MM x 9.5MM	20MM W/O CONN	20MM W/ CONN	30MM	40MM
TAKI #	.157" W		5/16" W			9/16" W	7/16" x 1/4"	1/2" W			13/16" W		9/16" W		1-3/16" W	
	SPT 12V		ECO 12V DP 24V FLX 12V	DP 24V	RIB 24V ECO 12V	CTL 24V RIB 24V ECO 12V FNR 24V	IVIXL 120V	FNC 24V FVR 24V	FNC 24V FVR 24V	DP 24V	DP 24V	DBL RGB	DP 24V	DP 24V	DP 24V	DP 24V
					Clear	Anodiz	ed Aluı	minum	Chani	nels		,				
L-VISION-12BF	Х	Х	Х		Х	Х		Х		Х			Х			
L-VISION-3F	Х	Х	Х		Х		Х									
L-VISION-3LF	Х	Х	Х	Х	Х	Х	Х	Х		Х			Х			
L-VISION-4D	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-VISION-45	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-VISION-7D	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х			
L-VISION-8F	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	
L-VISION-10F	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х		Х	Х			
L-VISION-15D	Х	Х	Х	Х	Х	Х	X	Х		X			Х			
L-VISION-17D	Х	Х	Х	Х	Х	Х	Х	Х	Х	X		X	Х			

English measurements converted from metric. Metric is the most accurate.

LED Lighting

Outwater's Vision Series: Aluminum Channel with Opaque White Lens







Length: 8 Ft. • Lens Material: Acrylic Part # Price 120+ L-VISION-12BF \$2.29 ft. \$1.99 ft.

End Caps- Set of 2

Part #	Price	100+
L-VISION-12BF-END	\$0.75 set	\$0.60 set

Mounting Clips- Set of 2

Part #	Price	100+
L-VISION-12BF-CLIP	\$1.00 set	\$0.80 set

L-VISION-3F





Length: 4 Ft.	 Lens Mate 	rial: Styrene
Part #	Price	120+
L-VISION-3F	\$2.52 ft.	\$2.19 ft.

L-VISION-3LF



Length: 4 Ft. **Frosted Styrene Lens**

Part #	Price	120+
L-VISION-3LF	\$2.97 ft.	\$2.58 ft.

L-VISION-4D





Length: 8 Ft. Lens Material: Acrylic Part # Price 120+ L-VISION-4D \$2.15 ft. \$1.87 ft.

L-VISION-4S






L-VISION-7D






Lens Material: Styrene Length: 8 Ft. Part # **Price** 120+ L-VISION-7D \$3.18 ft. \$2.76 ft.

L-VISION-8F





Length: 8 Ft.	 Lens Mate 	Lens Material: Acrylic					
Part #	Price	120+					
L-VISION-8F	\$4.08 ft.	\$3.55 ft.					

L-VISION-10F





Length: 8 Ft.	•	Lens Material: Acrylic						
Part #		Price	12	20+				
L-VISION-10F	\$	3.36 ft.	\$2.	92 ft.				

L-VISION-15D





Length: 8 Ft.	•	Lens Ma	terial: Styrene
Part #		Price	120+
L-VISION-15D		\$2.66 ft.	\$2.31 ft.



Length: 8 Ft.	• Lens Mate	eriai: Styrene
Part #	Price	120+
L-VISION-17D	\$2.87 ft.	\$2.49 ft.



Modular Vision Rail

Perfect For Task Lighting

- NO GLARE!.. NO HOT SPOTS!
- Clean Continuous Lighting
- Modular Connections Allows User To Create Seamless Design
- Low Profile, Under 1"
- Super Bright! Approximately 330 Lumens Per Foot!
- Dimmable! When Dimmed Provides Soft & Ambient Light
- Limited 2 Year Warranty
















Modular Vision Rail

Available Lengths: 8", 1', & 2' Nominal

Material: Aluminum with Opaque White Polycarbonate Lens



Guide Rail Power Track

Material: ABS Plastic with Metal Rods


- Trimmable in the field
- Simply add lamp fixtures & connectors in any position onto the track

softens the light, reduces glare and e	liminates the "scalloping"	caused by the LED's in most cases.	

Λ	
N	
Λ	
N	

Part #	Length	Each	6+ Pcs.
MVR-RAIL9	8.6"	\$2.25	\$1.95 ea.
MVR-RAIL13	12.9"	\$2.45	\$2.15 ea.
MVR-RAIL25	24.8"	\$2.75	\$2.45 ea.
MVR-RAIL49	48.8"	\$4.25	\$3.95 ea.
MVR-RAIL73	72.4"	\$5.35	\$4.95 ea.

Overall



Modular Vision Light (Up To 680 Lumens Per Fixture)

Material: Aluminum with Opaque White Polycarbonate Lens

• Unique magnetic connection will "CLICK" onto the track for easy assembly



Lig	ht	ing	Sp	oeci	ifi	icat	ior	15

Price

PW: 4000K
WW: 3000K
MVR-8-*: 220 MVR-12-*: 380 MVR-24-*: 680
80+
50,000 hrs.
Current
SMD2835

.74"	
	Overall Length —

	velali #	OILLD	iotai	IVIAN # Call		
art# L	ength (Chips	Wattage	Connect	Each	6+ Pcs.
	Pure V	Vhite *P	W & Warı	n White *W	/W	
/R-8-*	7.8"	24	3	16′	\$7.45	\$6.93 ea.
R-12-*	11.8"	36	5	16′	\$8.95	\$8.40 ea.
R-24-*	23.6"	60	9	16′	\$14.10	\$13.25 ea.
/R-8-* R-12-*	Pure V 7.8" 11.8"	Vhite *P 24 36	W & War ı 3 5	n White *W 16' 16'	/W \$7.45 \$8.95	\$6.93 ea \$8.40 ea

Power Linking Cable



	Pri		Price
Part #	Description	Each	6+ Pcs.
MVR-PWL	Without Switch	\$2.95	\$2.25 ea.

Illuminated Connectors

(Material: Aluminum with Opaque White Polycarbonate Lens)



1.18"L x 1.18"W x .74"H **MVR-ANGLE-*** Each: \$1.95 6+ Pcs.: \$1.83 ea.



1.57" L x 1.57" W x .74" H **MVR-CROSS-*** Each: \$2.95 6+ Pcs.: \$2.77 ea.

Pure White *PW & Warm White *WW

Lighting	Specifications
Color	PW: 4000K
Tomporaturo	1/V//V/• 3UUUK

Temperature	WW: 3000K
Lumens	MVR-ANGLE: 40 MVR-CROSS: 90
Color Rendering Index	80+
Rated Average Life	50,000 hrs.
Constant	Current
Chin Size	SMD2835








LED Lighting

Accessories for Modular Vision Rail



Required

Power Supplies




						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-1A	Wall Mount	1A	24V	24W	3.13"L x 2.07"W x 1.52"H	\$11.65	\$10.60 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers



	Range of				Price		
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.	
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.	

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables



			Arms # of Overall Max # of Power		Max # of Power	Price		
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-2WAY-BK	2-Way Sweep	Black	3"	2	6-3/4"	2	\$2.95	\$2.50 ea.
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.

For More Extension Cable Options, See Page L-147



Connecting Cables



				P	rice
Part #	Description	Finish	Length	Each	6+ Pcs.
MVR-CC24	Is to allow the designer to get around unlit	White	23.6"	\$3.25	\$3.06 ea.
MVR-CC40	areas without multiple power supplies	White	39.3"	\$3.65	\$3.43 ea.







Thin Strip- Fastest & Easiest Connection In The Industry Today

Available Length: 12"

Material: White Aluminum PCB Board


- 100% Usable Lighting System
- 100% Connectable- No Soldering Necessary
- Dimmable
- Field Trimmable
- · Limited 2 Year Warranty







Thin Strip (Up To 485 Lumens Per Foot)



			# Of LED	Total	Max # Can	Price	
	Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
Cool White *CW & Warm White *WW							
	LED-PCB2-12-*	12"	18	5.4	6	\$9.95	\$8.50 ea.

Lighting Specifications

Color Temperature	CW: 6200K-6800K WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 485 per ft. WW: 380 per ft.
Color Rendering Index	CW/WW: 80
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD2835

Aluminum LED Mounting Channels (Optional)

Create Your Own CUSTOMIZED FIXTURE IN MINUTES



See Pages L-55~62



Lay In Tape

Measure & Cut Thin Strip

Where Marked





Lay Light In Channel

Apply Lens & Enjoy










LED Lighting

Accessories for Thin Strip









Power Connector See Page L-67

Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable

Designed to provide power to rigid ribbon strips. Comes with female DC 5.5 and one solderless clip.



		Overall			Price		
Part #	Description	Length	Finish	Each	10+ Pcs.		
LED-OS-662P	Power Link Cable with Thin Strip Connection	60"	Black	\$2.30	\$1.99 ea.		

Power Connector

Required to join thin strip fixtures.




		Price			
Part #	Description	Each	10+ Pcs.		
LED-PCB-CLIP	Allows seamless connection of 2 thin strips without soldering	\$1.50	\$1.25 ea.		

Optional

Dimmers

A starter fixture required.




Range of				Price		
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables

A starter fixture required for each outlet.

5-Way Sweep: DC 5.5



			Arms	# of	Overall	Max # of Power	Price	
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.
LED-2WAY-BK	2-Way Sweep	Black	3″	2	6-3/4"	2	\$2.95	\$2.50 ea.

For More Extension Cable Options, See Page L-147



Adhesive Tape



				Price		
Part #	Thickness	Width	Roll Size	Each	6+ Pcs.	
OUT-3/8X216	1/32"	3/8"	216′	\$15.00	\$13.50 ea.	

Omni Wand: One System With Multiple Solutions



The Problem:

This Display required 16 different custom sized light fixtures, which would have been very costly and time consuming to order with an extensive lead time.



The Solution:

Omni Wand made this project simple and cost effective utilizing just one system. Up to 8 ft. long, the Omni Wand fixture can be easily trimmed to any size required. With Omni Wand, now you are finally in control to create lights as per your specs... not the other way around.



Many Mounting & Connecting Options

Frosted Polycarbonate Lens Power Track for Adjustable Spot Lights

High Intensity 3630 IED Right Ribbon Strip

Trimmable Housing

LENS CHARACTERISTICS Color Transmission Dispersion Surface Texture **LED Diodes Pebbled**

Frosted Lens: Allows the most light transmission. This is recommended for task lighting.

Omni Wand: One System With Multiple Solutions


- 20-0 (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 10-0) | (- 1













See Page L-72

See Omni Wand Brochure

See Omni Wand Brochure







Ask For Brochure DS-19Omni

See Page L-77







Omni Wand T2: Pre-Assembled 12" Fixture With Lens


Omni Wand: One System With Multiple Solutions

Available Lengths: 12"


Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

- Clear Anodized
- Fixture can be rotated even when installed
- 12" (nominal) length

"Packs A Bright Punch In A Small Profile"



Accessories For Omni Wand T2



Required

Power Supplies



						riice	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional



Range of				Price				
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.		
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.		
For Product Details & More Dimmer Ontions See Pages I - 134~136 & I - 142~144								

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~14

Other Options: Rotary | Touch Dimmer | Radio Frequency

<u>Switches</u>



					FIICE			
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.		
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.		
For Product Details & More Switch Options, See Page L-149								

Drice







Create Your Own Custom LED Omni Wand Lighting Up To 8 Ft.

Omni Wand: One System With Multiple Solutions

Available Lengths: Up To 8'

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

it's as **Easy** as



Cut omni housina to size

Measure and fill housing with ribbon strip and solderless clip HENCE E FERENCE



Add proper end to fixture and snap lens into place



Rigid Ribbon: In Cool White Or Warm White



12V / 5.4W Color Temperature: CW: 6200-6800K / WW: 2800-3200K Lumens: CW: 485 / WW: 450 Beam Spread: 120° Length: 12" Trimmable every 2" LED-PCB2-12-*: \$9.95 ea.

Cool White (*CW) & Warm White (*WW)

Circuit Bridging Kit

Housing Extrusion 4 ft. (*4) & 8 ft. (*8)

Diameter: 1/2" Material: Aluminum Finish: Clear Anodized Designed to receive our 5630

SMD Rigid Ribbon & Power Track LED-OS-400-*: \$2.07 per ft.

Female/Male Connecting Cable



Length- 24": LED-OS-24: \$3.25 ea. Length- 30": LED-OS-30: \$3.50 ea. Length- 48": LED-OS-48: \$3.75 ea.

Solderless Clips

Effortlessly joins multiple Ribbons and Track

LED-PCB-CLIP: \$1.50 ea.

Kit includes 2"Trimmable Power Track & 1 Solderless Clip Kit allows adjustments to 1/16

For More Info, Please Inquire

LED-OS-EXT: \$1.99 ea.

Frosted Polycarbonate Lens

4 ft. (*4) & 8 ft. (*8)

LED-OS-216-*: \$0.69 per ft.

Female End Used for power input Left (*L) & Right (*R) LED-OS-665-*: \$1.55 ea.





Male End Used for power input Left (*L) & Right (*R) LED-OS-657-*: \$1.55 ea.

Male End Cap





Mounting Clips



Standoff Mount

Material: Aluminum

LED-OS-660: \$3.45 ea.

For Power Supplies & Accessories, See Page L-77








Omni Wand: Vertical

Omni Wand: One System With Multiple Solutions

Available Lengths: In Pre-Fabricated 10" & 16" Lengths or Create Your Own Length

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

As previously noted, the LED Omni Wand System's Spot Vertical LED Lighting System enables one to utilize corresponding snap on Modern Swivel or Bell Swivel Spot Lights for a targeted 15° beam spread, which can be added, removed or even repositioned to accommodate one's ever changing lighting needs along the length of the System's kitted 10-in. and 16-in. long, ½-in. diameter silver anodized aluminum fixtures.



Pricing For 10" & 16" Pre-Fabricated Fixtures

Part #	Color Temp	Kit Includes	Size	# Of LED Chips	Total Wattage	Price
		OMNI WAND FIXTURI	E			
LED-OS-V10-3*180		(1) Wand Light & (1) 180° Base / Foot	10" Height	15	7.5W	\$14.20 ea.
LED-OS-V16-3*180	Cool White (*CW)	(1) Wand Light & (1) 180° Base / Foot	16" Height	24	12W	\$19.25 ea.
LED-OS-V10-3*90	Warm White (*WW)	(1) Wand Light & (1) 90° Base / Foot	10" Height	15	7.5W	\$14.20 ea.
LED-OS-V16-3*90		(1) Wand Light & (1) 90° Base / Foot	16" Height	24	12W	\$19.25 ea.
		MODERN STYLE FIXTU	RE			
LED-OS-V10-1*180		(1) Modern Spot Light & (1) 180° Base / Foot	10" Height	1	1W	\$25.60 ea.
LED-OS-V16-1*180	Cool White (*CW)	(1) Modern Spot Light & (1) 180° Base / Foot	16" Height	1	1W	\$26.55 ea.
LED-OS-V10-1*90	Warm White (*WW)	(1) Modern Spot Light & (1) 90° Base / Foot	10" Height	1	1W	\$25.60 ea.
LED-OS-V16-1*90		(1) Modern Spot Light & (1) 90° Base / Foot	16" Height	1	1W	\$26.55 ea.
		BELL STYLE FIXTURE				
LED-OS-V10-2*180		(1) Bell Spot Light & (1) 180° Base / Foot	10" Height	1	1W	\$26.95 ea.
LED-OS-V16-2*180	Cool White (*CW)	(1) Bell Spot Light & (1) 180° Base / Foot	16" Height	1	1W	\$27.90 ea.
LED-OS-V10-2*90	Warm White (*WW)	(1) Bell Spot Light & (1) 90° Base / Foot	10" Height	1	1W	\$26.95 ea.
LED-OS-V16-2*90		(1) Bell Spot Light & (1) 90° Base / Foot	16" Height	1	1W	\$27.90 ea.
		ADD A SPOT				
LED-OS-401-*	Cool White (*CW)	(1) Modern Spot Light	2-3/8"L x 11/16" Dia.	1	1W	\$17.30 ea.
LED-OS-402-*	Warm White (*WW)	(1) Bell Spot Light	2-1/2"L x 1-1/4" Dia.	1	1W	\$18.70 ea.







Create Your Own Custom LED Omni Wand Lighting Up To 8 Ft.

Omni Wand: One System With Multiple Solutions

Available Lengths: Up To 8'

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

Housing Extrusion



LED-OS-400-*: \$2.07 per ft.

4ft. (*4) & 8ft. (*8)

Diameter: 1/2"

Material: Aluminum

Finish: Clear Anodized

Material: Aluminum
Finish: Clear Anodized
Designed to receive our 5630 SMD
Rigid Ribbon & Power Track

Rigid Ribbon



LED-PCB2-12-*: \$9.95 ea.

Cool White (*CW) & Warm White (*WW)

Length: 12"

Trimmable every 2"

Modern Swivel Spot Light



LED-OS-401-*: \$17.30 ea.

Cool White (*CW) & Warm White (*WW)

Bell Swivel Spot Light



LED-OS-402-*: \$18.70 ea.
Cool White (*CW) & Warm White (*WW)

Power Track



Length: 39" Works With Any Spot

Frosted Polycarbonate Lens



LED-OS-216-*: \$0.69 per ft. 4ft. (*4) & 8 ft. (*8) Solderless Clip



LED-PCB-CLIP: \$1.50 ea.Effortlessly joins multiple
Ribbons and Track

Male End



LED-OS-657-*: \$1.55 ea. Used for power output



LED-OS-665-*: \$1.55 ea.
Used for power output
Left (*L) & Right (*R)

Female End Cap



LED-OS-664: \$0.30 ea.

Finishing End



LED-OS-667: \$0.50 ea.Designed to connect directly to housing

90° Power Foot (Plastic)



LED-OS-654P: \$3.30 ea.

180° Power Foot (Plastic)



LED-OS-655P: \$3.30 ea.

With 60" power cord
For heights over 2 ft. with multiple
spots we recommend metal O-Flange
Cover & Screw Included

Offers robust screw mounted support and is ideal for use in highly trafficked vertical or horizontal applications. Can be used on top & bottom.

Economy O-Flange (Metal)



LED-OS-678: \$2.65 ea.

2 Screws Included

Deluxe O-Flange (Metal)



Power Cord With Solderless Clip

Designed to provide power to Rigid Ribbon Strips housed in the O-Flange. Comes with Female DC 5.5 and one Solderless Clip. O-Flange sold separately.



LED-OS-662P: \$2.30 ea. Length: 60"

For Power Supplies & Accessories, See Page L-77








Omni Wand: 2-Way, 3-Way & 4-Way Perimeter Lighting

Omni Wand: One System With Multiple Solutions

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

The LED Omni Wand System's Housing can be easily rotated even after installation to direct a generous 120° linear beam spread wherever it may be desired. In addition, the System can accommodate snap on Modern Swivel or Bell Swivel Spot Lights for a targeted 15° beam spread, which can be added, removed or even repositioned to accommodate one's ever changing lighting needs.









Omni Wand: 2-Way, 3-Way & 4-Way Perimeter Lighting

Omni Wand: One System With Multiple Solutions

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens

Housing Extrusion



4 ft. (*4) & 8 ft. (*8)

Diameter: 1/2" Material: Aluminum Finish: Clear Anodized Designed to receive our 5630 SMD Rigid Ribbon & Power Track LED-OS-400-*: \$2.07 per ft.

Rigid Ribbon



Modern Swivel Spot Light



LED-OS-401-*: \$17.30 ea. Cool White (*CW) & Warm White (*WW)

Bell Swivel Spot Light





LED-OS-402-*: \$18.70 ea. Cool White (*CW) & Warm White (*WW)

Power Track



LED-OS-214: \$4.15 ea.

Frosted Polycarbonate Lens

4 ft. (*4) & 8 ft. (*8)

LED-OS-216-* \$0.69 per ft.

Solderless Clip

Effortlessly joins multiple Ribbons and Track

LED-PCB-CLIP: \$1.50 ea





LED-OS-EXT: \$1.99 ea. For More Info, Please Inquire

90° Foot (Plastic)



LED-OS-654: \$2.35 ea. For heights over 2 ft. with multiple spots we recommend metal O-Flange

90° Power Foot (Plastic)



LED-OS-654P: \$3.30 ea.

With 60" power cord For heights over 2 ft. with multiple spots we recommend metal O-Flange

Offers robust screw mounted support and is ideal for use in highly trafficked vertical or horizontal applications. Can be used on top & bottom.

Economy O-Flange (Metal)



LED-OS-678: \$2.65 ea. 2 Screws Included

Deluxe O-Flange (Metal)



With Solderless Clip Designed to provide power to Rigid Ribbon Strips housed in the O-Flange. Comes with Female DC 5.5 and one

Power Cord



LED-OS-662P: \$2.30 ea. Length: 60"

Male End



Left (*L) & Right (*R)

L-Connector



Y-Connector



T-Connector



LED-OS-651: \$3.45 ea.

For Power Supplies & Accessories, See Page L-77







Omni Wand: Top Mount

Omni Wand: One System With Multiple Solutions

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens **Connects To Power Supply Top Mount** The LED Omni Wand System can also be used as Top Mounted LED **Center Bracket Extrusion** Top Mount "L" LED-OS-672 Lighting. Utilizing high intensity 5630 SMD chips, the System radiates LED-OS-400-* **Bracket Set** beautiful unimpeded illumination without shadows or scalloping, **LED-OS-671S Power Track** lending itself for use as a perfect wall washing light. The System's LED-OS-214 brackets are extremely durable and comprise all aluminum museum quality construction. The lighting can be mounted either horizontally or vertically and can be **Extrusion** pivoted within its housing to direct the lighting LED-OS-400-Lens where it is required. LED-OS-216-* Modern **Spot Light** Rigid Ribbon LED-OS-401-* LED-PCB2-12-Male End LED-OS-657-*



Trimmable: Every 2" LED-PCB2-12-*: \$9.95 ea. Cool White (*CW) & Warm White (*WW)

Housing Extrusion

Diameter: 1/2" Material: Aluminum Finish: Clear Anodized Designed to receive our 5630 SMD Rigid Ribbon & Power Track

Top Mount "L" **Bracket Set** LFD-0S-671S

LED-OS-400-*: \$2.07 per ft. 4 ft. (*4) & 8 ft. (*8)

Solderless Clips

Effortlessly joins multiple Ribbons and Track

LED-PCB-CLIP: \$1.50 ea.

Power Track



LED-OS-214: \$4.15 ea.

Modern Swivel Spot Light



Bell Swivel Spot Light





Circuit Bridging Kit

Kit includes 2"Trimmable Power Track & 1 Solderless Clip Kit allows adjustments to 1/16"

LED-OS-EXT: \$1.99 ea. For More Info, Please Inquire

Frosted Polycarbonate Lens



Male End



Left (*L) & Right (*R)

Top Mount "L" Bracket Set



LED-OS-671S: \$10.35 set

Top Mount "L" Bracket Set



LED-OS-672: \$4.40 ea.








LED Lighting

Accessories For Omni Wand System

Omni Wand: One System With Multiple Solutions

Material: Clear Anodized Aluminum Channel with Frosted Polycarbonate Lens



Required

Power Supplies




						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers



Range of					Price		
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.	
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
LED-DIM-648D	Standard Touch	Silver/Black	0-100%	22mm: Dia. x 16mm: W	\$9.00	\$8.25 ea.	

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142-144
Other Options: Rotary | Touch Dimmer | Radio Frequency

Switches



				_	r	rice
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.
LED-OS-648A	Touch On/Off	Sliver/Black	Recessed	22mm: Dia. x 16mm: W	\$9.00	\$8.50 ea.

For Product Details & More Switch Options, See Page L-149

Motion Sensors



					P	Price
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-DSEN	Door Sensor	Silver	Surface/ Recessed	Surface: 2-1/2"L x 1-1/8"W x 11/16"H Recessed: 2-1/2"L x 5/8": Dia	\$11.75	\$10.90 ea.

For Product Details & More Motion Sensor Options, See Page L-142

Connecting Cable



Part #	Description	Finish	Length	Price
LED-OS-24	Allance the placements are averaged unlit	Silver/Black	24"	\$3.25 ea.
LED-OS-30	Allows the designer to get around unlit areas without multiple power supplies	Silver/Black	30"	\$3.50 ea.
LED-OS-48	areas without multiple power supplies	Silver/Black	48"	\$3.75 ea.

Phone: 1-800-631-8375 - Fax: 1-800-888-3315

Due to raw material cost fluctuations, prices are subject to change.







Omni Wand: Sample Kit



KIT INCLUDES



18" Omni Wand **Housing Extrusion**



6" Cool White Rigid Ribbon Strip (5630 SMD Chip)








Cool White (1) & Warm White (1)





6" Warm White **Rigid Ribbon Strip** (5630 SMD Chip)











Fluorescent Lighting

"D" Light T5 Compact Light

Available Lengths: 22-1/2", 23-13/16", 25-1/8", 35-1/2" & 47"

Material: White PVC with Clear Polycarbonate Lens

- Each fixture comes with a cool or white bulb, protective lens cover, 6-foot power cord, screws, plastic mounting clips and one direct connector.
- Sturdy all white PVC construction
- · Standard On/Off switch
- Built in electronic end of life ballast with rapid start
- Approximate bulb life is 10,000 hours
- Ultra Low Profile- Only 7/8"
- Easy to find replacement bulbs: T5 lamps readily available!











"D" Light T5 Compact Light (Up To 1820 Lumens Per Fixture)





"D"-LIGHT FIXTURES WITH BULBS							6	REPLACEMEN	T BULBS
	Dimensions							<u> </u>	
			Max #				1	Replacement	
Part #	Watts	Lumens	Can Join	Length	Width	Depth	Price	Lamps	Price
Cool White *CW & Warm White *WW									
DLS-13W-*	13	715	10	22-1/2"	1-11/16"	7/8"	\$10.45 ea.	DLSB-13W-*	\$2.05 ea.
DLS-14W-*	14	750	10	23-13/16"	1-11/16"	7/8"	\$10.55 ea.	DLSB-14W-*	\$2.05 ea.
DLS-18W-*	18	900	10	25-1/8"	1-11/16"	7/8"	\$11.35 ea.	DLSB-18W-*	\$2.45 ea.
DLS-21W-*	21	1260	10	35-1/2"	1-11/16"	7/8"	\$12.55 ea.	DLSB-21W-*	\$2.85 ea.
DLS-28W-CW	28	1820	10	47"	1-11/16"	7/8"	\$14.35 ea.	DLSB-28W-CW	\$3.95 ea.



Connecting Cables (Optional)

Function: Allows the designer to get around unlit areas without multiple power supplies.



Part #	Length	Price
DLS-6CC	6"	\$1.00 ea.
DLS-12CC	12"	\$1.00 ea.

Hardwire Box (Optional)



PVC Mounting Clips (Optional)

Set of (2) Plastic White Mounting Clips & Screws





Look Of Fluorescent With Functionality & Energy Savings Of LED

STARLINK

Even Illumination

No Hotspots

No Power Supply

Simply Plug & Play

Can Link Up To 75 pcs. Off One Power Cord

Limited 3 Year Warranty

Sizes Available: 1', 2', 3' & 4'

Several Mounting Options

Shelf

45° Clip

Magnetic Tape

Virtually Seamless Connection

With Very Little Loss Of Light When Connected

Only .40" gap, while others can be up to 2"

90° Angled Power Cord
Power Cord With Rocker Switch
Right Angle Space Saving Connection

Glass



LED Lens

(0-

LENS CHARACTERISTICS						
Color	Transmission	Dispersion	Surface Texture	LED Diodes		
Opaque White	Low	High	Smooth	Not Visible		

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases







Starlink T5 Light Fixture

Available Nominal Lengths: 1', 2', 3' & 4'

Material: Polycarbonate with Opaque White Polycarbonate Lens






Starlink T5 Lighting Fixture (Up To 1550 Lumens Per Fixture) **Includes: Fixture & Plastic Mounting Clips**

Overall Length

Lighting Specifications

Color Temperature	CW: 6500K
Beam Spread	180°
Lumens	LED-120T5-12-CW: 300 LED-120T5-24-CW: 550 LED-120T5-36-CW: 1050 LED-120T5-48-CW: 1550
Color Rendering Index	CW: 80
Rated Average Life	25,000 hrs.
Constant	Current
Chip Size	SMD2835

			Overall	Length With	Length With	Total	Max # Can	P	rice
Part #	Color Temp	Finish	Length	Straight Power Cord	Angled Power Cord	Wattage	Connect	Each	6+ Pcs.
LED-120T5-12-CW	Cool White	White	10-7/8"	13"	12-3/16"	4	75	\$17.50	\$16.50 ea.
LED-120T5-24-CW	Cool White	White	19-13/16"	22"	21-1/8"	7	42	\$22.00	\$20.75 ea.
LED-120T5-36-CW	Cool White	White	32-7/8"	35"	34-1/4"	13	23	\$27.00	\$25.50 ea.
LED-120T5-48-CW	Cool White	White	44-3/4"	46-7/8"	46-1/16"	18	16	\$31.00	\$29.00 ea.



Straight Power Cords (Required)



LED-120T5-PC-2M Each: \$3.25 / 6+ Pcs.: \$2.80 ea.

90° Angled Power Cords (Required)



6'6" Power Cord LED-120T5-PC-2MR

10' Power Cord LED-120T5-PC-3MR Each: \$5.25 / 6+ Pcs.: \$4.50 ea. | Each: \$6.25 / 6+ Pcs.: \$5.50 ea.

Connecting Cable (Optional)

Function: Allows the designer to aet around unlit areas without multiple power supplies



LED-120T5-CC-12 12" \$2.50 ea. \$2.17 ea. LED-120T5-CC-48 48" \$4.00 ea. \$3.50 ea.

Mounting Options (Optional)

Metal 45° Mounting Clip



LED-120T5-45C Each: \$2.00 set 6+ Pcs.: \$1.80 set

Material: Stamped Steel

LED-120T5-MC Each: \$2.00 set 6+ Pcs.: \$1.80 set

Material: Stamped Steel









Professional LED Undercabinet Light

Available Lengths: 14" & 22"

Material: Aluminum Housing with Opaque White Polycarbonate Lens

- Replace older design with never version
- Dimmable
- Built in On/Off switch, along with a high/low light output option
- · Join together with connector or linking cable
- Other Colors Available: Stainless Steel & Oil Rubbed Bronze Please Inquire

LENS CHARACTERISTICS						
Color	Transmission	Dispersion	Surface Texture	LED Diodes		
Opaque White	Low	High	Smooth	Not Visible		



Professional LED Undercabinet Light (Up To 520 Lumens Per Fixture)

Includes: Connector & Twin-Screw Clamp Connector




Included In Every Fixture










			Overall	Total	Max # Can	P	rice
Part #	Color Temp	Finish	Length	Wattage	Connect	Each	6+ Pcs.
UC-14WH	Warm White	White	14"	7	115	\$30.00	\$26.25 ea.
UC-22WH	Warm White	White	22"	11	50	\$41.00	\$37.00 ea.



Lighting Specifications

Color Temperature	UC-14WH: 3000K UC-15WH: 3000K
Beam Spread	120°
Lumens	UC-14WH: 330 UC-15WH: 520
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Constant	Voltage



Power Cord (Optional)



Each: \$5.95

6+: \$5.25 ea.

□ legrand Dimmer Switches (Optional)

Input & Output Cords: 5.875"
Range of Dimming: 0-100% • Mounting: Wall

sofTap

Touch Switch With Touch Slide Dimmer LGD120-DIMST-MG

Each: \$63.28 (Magnesium)

LGD120-DIMST-WH Each: \$54.98 (White)

For More Options, Product Details & Wall Plates, See Page L-143

Connecting Cable (Optional)

Function: Allows the designer to get around unlit areas without multiple power supplies



- Length: 12"
- Finish: White

('nľ)

UC-LINK-CBL Each: \$2.55 6+: \$2.25 ea.











LED Lighting

Duo LED Under Cabinet Light Bar

Available Lengths: 8", 12", 18", 24" & 30" Material: Aluminum Body with Frosted Polycarbonate Lens

- Bringing out the best in bold, eye-catching residential, retail and commercial displays, Duo LED Under cabinet light bars are ideal for counters and cabinets. Thermally efficient, these fixtures are crated for illuminating heat sensitive perishables and color sensitive apparel, artwork and collectibles.
- · Does not require any driver or transformers
- · Backlighting with parabolic reflector allows a high uniformity of light
- Free of projected heat, UV and IR radiation
- On/Off Switch- Switch to either 2700K or 300K color temperature
- · Easily mounts to surface with included matching screws
- 5 Year WAC Lighting product warranty

LENS CHARACTERISTICS							
Color Transmission Dispersion Surface Texture LED Diodes							
Frosted	High	Low	Pebbled	Visible			

Each Light Bar Includes One Direct Connector For Virtually Seemless Connection








Duo LED Under Cabinet Light Bar (Up To 1095 Lumens Per Fixture)





Brushed Aluminum White

		# Of LED	Total	Max # Can	
Part #	Length	Chips	Wattage	Connect	Price
Brushed A	Numinum	*ALU, Bro	nze *BRZ 8	& White *WH	
BA-ACLED827/30*	8"	12	6	6	\$85.50 ea.
BA-ACLED1227/30*	12"	18	8	6	\$104.31 ea.
BA-ACLED1827/30*	18"	24	10	6	\$123.30 ea.
BA-ACLED2427/30*	24"	36	15	6	\$142.11 ea.
BA-ACLED3027/30*	30"	42	17.5	6	\$161.10 ea.

Connecting

Lighting Specifications Temperature 2700K or 3000K

Color Temperature	2700K or 3000K
Beam Spread	30°
Lumens	BA-ACLED827/30*: 330 BA-ACLED1227/30*: 475 BA-ACLED1827/30*: 545 BA-ACLED2427/30*: 930 BA-ACLED3027/30*: 1095
Color Rendering Index	90+
Rated Average Life	54,000 hrs.
Constant	Voltage

Power Cord (Optional)



Length: 6'Finish: White

Optional

Dimmer

BA-PC6-WH Each: \$10.71

Lutron Dimmer Switches (Optional)

Optional (Any Combination)

Input & Output Cords: 5.875" • Range of Dimming: 5-100% • Mounting: Wall



Optional

Power Cord

Skylark
On/Off Switch
With Slide Dimmer
S-600P-WH

S-600P-WH Each: \$18.00



Required

Duo

<u>Diva</u> Rocker Switch With Slide Dimmer

DVLV-600P-WH Each: \$43.50

For Product Details & Wall Plates, See Page L-142

Connecting Cables (Optional)

Function: Allows the designer to get around unlit areas without multiple power supplies



Part #	Length	Finish	Price
BA-IC12-WH	12"	White	\$9.90 ea.
BA-IC24-WH	24"	White	\$10.71 ea.
BA-IC36-WH	36"	White	\$11.70 ea.

Direct Connector (Optional)

Function: Connects two light bars



BA-I-WH Each: \$3.51







Integrated Magnets Snap to the Mounting Plate






LED Cabinet and Niche Light

Available Lengths: 6-15/16", 12-3/4", 18-5/8", 24-3/8" & 30-1/4" *Material: Extruded Aluminum Body with a Polycarbonate Lens*

- The low profile LED Cabinet and Niche Light luminaire is the ultimate high output, low power consumption task light. Seamless connections provide the perfect glare free solution for all surfaces while offering luxurious color rendering for full color spectrum illumination. Perfect for highly reflective surfaces such as stainless steel and polished stone, LED Cabinet and Niche Light produces an evenly diffused light with asymmetrical lighting distribution. Unique installation detail provides versatility and security.
- Energy Star® rated
- 30° asymmetrical forward throw illumination for full coverage of the task plane
- Free of projected heat, UV and IR radiation
- Connections made at the center of each fixture
- Includes screws for easy mount or simply mounts with magnetic plates
- 5 Year WAC Lighting product warranty



LED Cabinet and Niche Light (Up To 1210 Lumens Per Fixture)



Part#	Length	# Of LED Chips	Total Wattage	Max # Can Connect	Price
Abrasion Resista	nt Brushed Alu	minum *AL	& Anti-Micro	obial White P	aint *WH
LN-LED06P-27-*	6-15/16"	18	6.5	11	\$123.30 ea.
LN-LED12P-27-*	12-3/4"	35	10.5	6	\$161.10 ea.
LN-LED18P-27-*	18-5/8"	56	16	4	\$207.90 ea.
LN-LED24P-27-*	24-3/8"	70	20	3	\$245.70 ea.
LN-LED30P-27-*	30-1/4"	84	23.5	2	\$282.51 ea.



Color Temperature	2700K
Beam Spread	30°
Lumens	LN-LED06P-27*: 250 LN-LED12P-27*: 470 LN-LED18P-27*: 825 LN-LED24P-27*: 985 LN-LED30P-27*: 1210
Color Rendering Index	90
Rated Average Life	100,000 hrs.
Constant	Voltage










LED Lighting

Accessories for LED Cabinet and Niche Light











Power Supplies (Required)

Wall Mount & Desktop



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-1A	Wall Mount	1A	24V	24W	3.13"L x 2.07"W x 1.52"H	\$11.65	\$10.60 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.

For Product Details & More Power Options, See Pages L-137~140

(2.5A / 24V / 60W)

- 6-1/2" L x 1-5/8" W x 1-1/4" H
- 10AWG Output Cord: 72"
- Class 2

EN-2460-RB2-S Each: \$71.91



Dimmable Hardwire (الم

- (4A / 24V / 96W) • 6-1/2" L x 1-5/8" W x 1-1/4" H
- 10AWG Output Cord: 72"
- · Class 2

EN-24100-RB2-S Each: \$75.51



(4A / 24V / 96W)

- 12-5/8" L x 3-1/4" W x 2" H
- 10AWG Output Cord: 72"
- Class 2

EN-24100-277-RB2-T Each: \$170.10

Lutron Dimmer Switches (Optional)

Input & Output Cords: 5.875" • Range of Dimming: 5-100% • Mounting: Wall



Skylark On/Off Switch With Slide Dimmer S-600P-WH Each: \$18.00



Diva Rocker Switch With Slide Dimmer **DVLV-600P-WH** Each: \$43.50

For Product Details & Wall Plates, See Page L-142

Connecting Cables (Optional)

FUNCTION: ALLOWS THE DESIGNER TO GET AROUND UNLIT AREAS WITHOUT MULTIPLE POWER SUPPLIES



Part #	Length	Price
SL-IC-06	6"	\$7.11 ea.
SL-IC-12	12"	\$7.11 ea.
SL-IC-24	24"	\$8.10 ea.
SL-IC-36	36"	\$8.91 ea.

Multi Output Cables (Optional)

Function: Is to join multiple fixtures to one power supply

Cable Extender

- Length: 3-5/8"
- · Finish: White SL-IF

Each: \$7.11

3-Way "Y" Connector SL-Y Each: \$11.70 • Wire Length: 4" · Connector: 1-1/8" • Finish: White

4-Wav "X" Connector SL-X Each: \$12.51

- Wire Length: 4"
- Connector: 1-1/8"
- Finish: White

Multiple Terminal Block



- · Outputs: 8
- 4-7/8" L x 1-5/8" W x 3/4" H
- · Finish: White

MTB-08 Each: \$31.50

Power Supply Accessories (Optional)

Wiring Box With Switch

Function: Conceal wire connections

- 6-1/4" L x 1-5/8" W x 1-1/4" H
- Finish: White

TB-S Each: \$18.90



12" Extension Cable

Function: Used to extend distance between power supply and light

- Wire: 144"
- · Connector: 1-1/8"
- · Finish: White



Each: \$15.30

Mounting Clips (Optional)

Function: Holds cables neatly

- Sold 10 pieces per bag
- 1/2"
- · Finish: White

SL-WC-1

Each Bag: \$8.91









DP Conx

Available Lengths: 12", 24", 36", 48" & 60" Material: Aluminum Housing with Clear Polycarbonate Lens

- Used For: Cove Lighting, Cabinet Lighting & Shelf Lighting
- Uses smaller DC 3.5 connector
- Light Source: SMD2835 strip
- Low profile can be easily hidden
- Excellent heat sink
- · Mounting clips & screw included
- · Joinable by middle and right angle connector
- Easy Installation
- Limited 2 Year Warranty

LENS CHARACTERISTICS							
Color Transmission Dispersion Surface Texture LED Dic							
Clear	High	High	Smooth	Visible			











DP Conx (Up To 243 Lumens Per Foot)





		# Of LED	Total	Max # Can	Pı	rice
Part #	Length	Chips	Wattage	Connect	Each	6+ Pcs.
Cool Wi	hite * CW , No	atural Whi	ite *NW, Ρι	ıre White * P l	W & Warm White *	'WW)
DPCONX12-12-*	12"	30	4	16′	\$14.41	\$12.62 ea.
DPCONX12-24-*	24"	66	8	16′	\$18.56	\$16.57 ea.
DPCONX12-36-*	36"	102	12	16′	\$22.20	\$19.82 ea.
DPCONX12-48-*	48"	138	16	16′	\$26.63	\$23.77 ea.
DPCONX12-60-*	60"	174	20	16′	\$32.06	\$28.62 ea.

Lighting Specifications

Color Temperature	CW:6000K-6500K NW: 5000-5500K PW: 4000K-4500K WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 225 per ft. NW: 243 per ft. PW: 243 per ft. WW: 243 per ft.
Color Rendering Index	80+
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	2835











LED Lighting

Accessories for DP Conx











Required

Power Supplies (IP20)



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable


Required for power supplies, dimmers & multi output cables.



					Price
Part #	Description	Length	Finish	Each	6+ Pcs.
	DC 3.5 Connection				
DPCONX12-PWL	Power Link Cable DC 5.5 female to DC 3.5 male	6"	Black	\$1.75	\$1.45 ea.
	Hardwire				
DPCONX12-PWL-MCC	Power Link Cable with DC 3.5	39"	Black	\$2.25	\$1.95 ea.

Optional


Dimmers



			Range of		P	rice
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
For Product Details & More Dimmer Ontions See Pages I -134~136 & I -142-144						

Other Options: Rotary | Touch Dimmer Radio Frequency

Switches



						Price
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.
For Product Details & More Switch Options, See Page L-149						

Multi Output Cables



			Arms	# of	Overall	Max # of Power		Price
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-2WAY-BK	2-Way Sweep	Black	3″	2	7″	2	\$2.95	\$2.50 ea.

For More Extension Cable Options, See Page L-147

Connecting Cables



				P	rice
Part #	Function	Finish	Length	Each	6+ Pcs.
LED-35MM-39CC-BK	Is to allow the designer to get around unlit areas without multiple power supplies	Black	39"	\$2.50	\$2.05 ea.

Connectors Straight



			F	Price
Part #	Function	Dimensions	Each	6+ Pcs.
DPCONX12-SCONN	Straight	1″L	\$1.45	\$1.30 ea.
DPCONX12-LCONN	Angle	7/8"Lx7/8"W	\$1.45	\$1.30 ea.


ADJUSTTOANYHEIGHTNEEDEDWITHOUTRE-WIRING



BillyColorChanging Temperature (CCT) AdjustableShelfSystem

GoFrom2700K-6500K







- Now you can reposition your shelves multiple times without the need to re-wire the unit.
- · Standard lengths can ship from stock but customized options are available. Please Inquire.
- 2 choices of power supplies, both utilize "CCT" technology and allow for variable temperatures between warm white and cool white.
- Dimmable
- · Low Profile, High Efficiency Fixtures with Angled Beam
- White, opaque lens offers no visible LED diodes
- · Will work with wood or glass shelves

CustomizableLengthAvailable,PleaseInquire!(AllweneedisdimensAt)



Peel&Stick Adhesive& **WoodSarews** Included









Billy Color Changing Temperature (CCT) Adjustable Shelf System

Nominal Lengths: 24", 36" & 48"


Material: Anodized Aluminum with Opaque White Lens

IP20 Billy CCT Adjustable Shelf System

Provides Low Protection of Dust & Water

LENS CHARACTERISTICS				
Color Transmission Dispersion Surface Texture LED Diodes				
Opaque White	Low	High	Smooth	Not Visible













Fixtures Available In: 24", 36" or 48" Screws & Adhesive Included with Every Fixture Customizable Lengths Available, Please Inquire

Part #	Description	Total Wattage	Price
BLYK-136-CCT	36"- 1 Shelf Kit with 13' Copper Power Track	13.8	\$99.00 ea.
BLYK-148-CCT	48"- 1 Shelf Kit with 13' Copper Power Track	18.5	\$109.00 ea.
BLYK-224-CCT	24"- 2 Shelf Kit with 13' Copper Power Track	18.5	\$109.00 ea.
BLYK-236-CCT	36"- 2 Shelf Kit with 13' Copper Power Track	27.6	\$149.00 ea.
BLYK-248-CCT	48"- 2 Shelf Kit with 13' Copper Power Track	37	\$139.00 ea.
BLYK-324-CCT	24"- 3 Shelf Kit with 13' Copper Power Track	27.6	\$149.00 ea.
BLYK-336-CCT	36"- 3 Shelf Kit with 13' Copper Power Track	41.4	\$169.00 ea.
BLYK-348-CCT	48"- 3 Shelf Kit with 13' Copper Power Track	55	\$199.00 ea.
BLYK-424-CCT	24"- 4 Shelf Kit with 13' Copper Power Track	37	\$179.00 ea.
BLYK-436-CCT	36"- 4 Shelf Kit with 13' Copper Power Track	55	\$199.00 ea.
BLYK-524-CCT	24"- 5 Shelf Kit with 13' Copper Power Track	46	\$209.00 ea.

Lighting Specifications

Color Temperature	3000K-6000K
Beam Spread	120°
Lumens	BLYK-136-CCT: 214 per kit BLYK-148-CCT: 287 per kit BLYK-224-CCT: 287 per kit BLYK-224-CCT: 287 per kit BLYK-236-CCT: 428 per kit BLYK-324-CCT: 574 per kit BLYK-336-CCT: 642 per kit BLYK-336-CCT: 642 per kit BLYK-342-CCT: 850 per kit BLYK-424-CCT: 574 per kit BLYK-424-CCT: 571 per kit
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	2835

Required (Choose One)

Bluetooth/IR Power Supply with IR Remote (5A / 12V / 60W)

Includes: Driver, EZ Plug with Connector, Module & Remote Control

Allow user to dim & change temperature from 2700K to 600K. • Blueto

Includes: Driver, EZ Plug with Connector & Module
Bluetooth module allows control of light through your phone or tablet







Bluetooth Power Supply (5A / 12V / 60W)








Zip Strip

Available Lengths: 12" & 24"

Material: White Aluminum with Frosted Polycarbonate Lens

Mounting Options (Included)







LENS CHARACTERISTICS				
Color	Transmission	Dispersion	Surface Texture	LED Diodes
Frosted	High	Low	Pebbled	Visible

Starter with Touch Dimmer Function (Up To 650 Lumens Per Fixture)


The touch function lights come equipped with built in On/Off switch that doubles as a low, medium and high 3-stage touch dimmer. When leading with the dimmer fixture all following connection lamps will be controlled by the dimmer function.





Single without Touch Dimmer (Up To 650 Lumens Per Fixture)

The single lights can be connected to the touch function strip or used individually.



Lighting Specifications

Color Temperature	PW: 4500K WW: 3000K
Beam Spread	120°
Lumens	PW (12"): 330 WW (12"): 315 PW (24"): 650 WW (24"): 620
Color Rendering Index	PW/WW: 85
Rated Average Life	PW/WW: 30,000 hrs.
Constant	Voltage
Chip Size	SMD3528



oction (Paguired)

Required


Required Zip Strip

Power Supplies With Connection (Required)

PLUG & PLAY

Optional

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage • Comes With DC 3.5 Male Power Linking Cable • Limited 2 Year Warranty



LED-ZIP-TR-36W Each: 16.50 6+ Pcs.: \$14.85 ea.

- 5-3/16" L x 2-3/16" W x 1-1/4" H
- Input Cord: 36"

Desk Top (1.5A / 24V / 36W)

- Output Cord: 36"
- · Green On/Off LED Indicator Light
- Polarized 2 Prong Plug

Connecting Cable (Optional)

Function: Is to allow the designer to get around unlit areas without multiple power supplies



Part #	Length		6+ Pcs.	
LED-ZIP-CC-06	6"	\$1.50 ea.	\$1.35 ea.	
LED-ZIP-CC-24	24"	\$3.50 ea.	\$3.15 ea.	
LED-ZIP-CC-36	36"	\$3.75 ea.	\$3.38 ea.	







Tri-Glow Strip

Available Lengths: 12", 20" & 40"

Material: Aluminum with Clear Polycarbonate Lens

- Finish: High quality satin nickel finish
- · Can be used vertical & horizontal
- Ideal for application where corner mounting is required
- · Easy to connect
- · Excellent for freezer application





Tri-Glow Strip (Up To 980 Lumens Per Fixture)

Each Fixture Includes: 39" Connecting Cable, 2 Mounting Clips & 1 End to End Connector



× 1.	
\	
← 1-1/4"→	

		# Of LED	Total	Max # Can	ı	Price
Part #	Length	Chips	Wattage	Connect	Each	10+ Pcs.
	P	ure White	*PW & Wa	rm White *W	w	
LED-AGL-12-*	12"	42	3	12	\$16.00	\$12.95 ea.
LED-AGL-20-*	20"	72	5	8	\$24.00	\$18.95 ea.
LED-AGL-40-*	40"	144	11	3	\$44.00	\$36.95 ea.

Lighting Specifications

Color Temperature	PW: 4100K WW: 3200K
Beam Spread	90°
Lumens	LED-AGL-12-PW: 290 LED-AGL-20-PW: 490 LED-AGL-40-PW: 980 LED-AGL-12-WW: 275 LED-AGL-20-WW: 465 LED-AGL-20-WW: 931
Color Rendering Index	PW/WW: 75
Rated Average Life	PW/WW: 50,000 hrs.
Constant	Voltage
Chip Size	SMD3528

Required





Optional (Any Combination)

Angled Design Sits In Any 90° Corner





Power Supplies With Connection (Required)

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage Comes With DC 3.5 Male Power Linking Cable • Limited 2 Year Warranty

Desk Top (1.5A / 24V / 36W)

- 4.56" L x 1.92" W x 1.3" H
- 18AWG Input Cord: 60"
- 20AWG Output Cord: 60"
- Green On/Off LED Indicator Light
- Polarized 2 Prong Plug

LED-24V-1.5A

Each: \$23.50 / 6+ Pcs.: \$21.15 ea.

Desk Top (2A / 24V / 45W)

- 4.375" L x 1.75" W x 1.25" H
- 18AWG Input Cord: 60"
- 20AWG Output Cord: 60"
- Green On/Off LED Indicator Light
- Polarized 2 Prong Plug

LED-24V-2A

Each: \$24.50 / 6+ Pcs.: \$22.25 ea.

Dimmer (Optional)



LED-CLE-DIM Each: \$5.95 6+ Pcs.: \$5.25 ea.

- On/Off Switch
- 3-3/4" L x 1-1/8" W x 3/8" H
- Male DC 3.5 Output Cord: 36"
- Range of Dimming: 0-100%
- · Mounting: Screw

Junction Box (Optional)

Function: Is to join multiple fixtures to one power supply

- 1-5/8" L x 1-1/4" W x 5/8" H
- Power In: 1 Port · Power Out: 4 Ports

LED-CLE-JB Each: \$2.95 / 6+ Pcs.: \$2.45 ea.




DC 3.5

Connecting Cable (Optional)

Function: To connect junction box or other lights





Phone: 1-800-631-8375 Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.







Gen Next Thin Light Fixture

Available Lengths: 8", 12" & 16"

Material: Clear Polycarbonate

- Improved design & connection
- Easy to hide ultra compact
- High lumen output packed into a very small fixture

LENS CHARACTERISTICS								
Color	Transmission	Dispersion	Surface Texture	LED Diodes				
Clear	Full	None	Smooth	Visible				














Gen Next Thin Light Fixture (Up To 260 Lumens Per Fixture)



		# OI LED	iotai	Max # Can	F	iice			
Part #	Length	Chips	Wattage	Connect	Each	20+ Pcs.			
Pure White *PW & Warm White *WW									
LED-SLSHX-8-*	8"	9	1.6	23′	\$8.95	\$7.75 ea.			
LED-SLSHX-12-*	12"	12	2.3	23'	\$9.95	\$8.65 ea.			
LED-SLSHX-16-*	16"	18	3.0	23′	\$11.25	\$9.75 ea.			

Lighting Specifications

Lighting	Specifications
Color Temperature	PW: 4200K WW: 2800K-3200K
Beam Spread	120°
Lumens	LED-SLSHX-8-*: 155 LED-SLSHX-12-*: 190 LED-SLSHX-16-*: 260
Color Rendering Index	PW/WW: 80
Rated Average Life	PW/WW: 30,000 hrs.
Constant	Voltage
Chip Size	SMD2835
Chip Size	SMD2835







LED Lighting

Accessories for Gen Next Thin Light Fixture











.

Optional



Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable

Required for power supplies, dimmers & multi output cables.



		Overall		Price		
Part #	Description	Length	Finish	Each	6+ Pcs.	
LED-SLSHX-PWL	Power Link Cable with Gen Next Connection	18"	White	\$3.50	\$2.95 ea.	

For Product Details & More Power Linking Cables, See Page L-141

Optional

Dimmers

A power linking cable required.



	Range of				Price		
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.	
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.	

For Product Details & More Dimmer Options, See Pages L-134-136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables

A power linking cable required for each outlet.

5-Way Sweep: DC 5.5



			Arms	# of	Overall	Max # of Power	Price	
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.

For More Extension Cable Options, See Page L-147



Connecting Cables



Part #	Function	Finish	Length	Each	6+ Pcs.
LED-SLSHX-12C-WH	la ta allaccitha dasimaanta matanaccad codit	White	12"	\$1.75	\$1.58 ea.
LED-SLSHX-24C-WH	Is to allow the designer to get around unlit areas without multiple power supplies	White	24"	\$3.25	\$2.93 ea.
LED-SLSHX-36C-WH	areas without multiple power supplies	White	36"	\$4.25	\$3.83 ea.

Phone: 1-800-631-8375 Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.

Price











LED Lighting

SunRay T5 Fixture

Available Lengths: 1', 2', 3', 4' & 5' Nominal

Material: Aluminum with Opaque White Polycarbonate Lens







	LENS C	HARACTERI	STICS	
Color	Transmission	Dispersion	Surface Texture	LED Diodes
Opaque White	Low	High	Smooth	Not Visible

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases

SunRay (Up To 1140 Lumens Per Fixture)

Resembles a High Powered T5 Fluorescent bulb with the benefits of LED



			Length	4				
. \ \ \ \ \ \		Overall	w/Power	# Of LED	Total	Max # Can	P	rice
MVVV	Part #	Length	Adaptor	Chips	Wattage	Connect	Each	12+ Pcs.
Call For		(Cool White	*CW & W	arm White	*WW		
✓ Volume ✓	LED-T512-*	13-3/16"	14-1/2"	60	4.5	15′	\$22.95	\$19.20 ea.
Pricing	LED-T524-*	23-3/8"	24-5/8"	120	8.5	15′	\$30.25	\$26.15 ea.
MANNE	LED-T536-*	35-1/8"	36-3/8"	192	13	15′	\$40.75	\$35.15 ea.
	LED-T548-*-S	45"	46-1/4"	240	16	15′	\$48.60	\$41.95 ea.
	LED-T560-*	58-3/4"	60"	336	20	15′	\$60.25	\$52.05 ea.

Lighting Specifications

Color Temperature	CW: 3700K-4300K WW: 2800K-3200K
Lumens	LED-T512-CW: 289 LED-T512-WW: 273 LED-T524-CW: 597 LED-T524-CW: 553 LED-T536-CW: 932 LED-T536-CW: 926 LED-T548-CW-S: 1287 LED-T548-WW-S: 1227 LED-T560-CW: 1603 LED-T560-WW: 1525
Color Rendering Index	80+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD3014

Mounting Hardware

INCLUDED WITH EACH FIXTURE!

A VARIETY OF MOUNTING HARDWARE OPTIONS W/SCREWS







Magnetic Clip Connects To Metal (Optional)



- Material: Stamped Steel
- 1/2" Diameter Base
- 22 lbs. Pull Magnet

LED-T5-MAGCON \$3.00 (pair)

Note: SunRay can pivot in clips


LED Lighting







Accessories for SunRay T5 Fixture



Required

Power Supplies




						F	Price
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-1A	Wall Mount	1A	24V	24W	3.13"L x 2.07"W x 1.52"H	\$11.65	\$10.60 ea.
LED-24V-3A	Desktop	3A	24V	72W	3.41"L x 2.31"W x 1.26"H	\$28.75	\$26.05 ea.

For Product Details & More Power Options, See Pages L-137~140
Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers



			Range of		P	Price
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144

Other Options: Rotary | Touch Dimmer | Radio Frequency

Multi Output Cables




			Arms	# OT	Overali	Max # of Power		TICE
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.
LED-SPIDER-CBL	3-Way Spider	Black	4-1/2"	3	96"	4	\$6.25	\$5.55 ea.

For More Extension Cable Options, See Page L-147



Connecting Cables



				_	г	rice
Part #	Description	Function	Finish	Length	Each	6+ Pcs.
LED-A55MF-12CC-BK	Angled	Is to allow the designer to get around unlit	Black	12"	\$1.80	\$1.55 ea.
LED-A55MF-24CC-BK	Angled	areas without multiple power supplies	Black	24"	\$2.00	\$1.70 ea.

For More Extension Cable Options, See Page L-148

End Caps





• 1-1/2" L x 11/16" Dia.

LED-T5-END Each: \$1.95



Drice





The Best In Store Adjustable Shelf Lighting Solution On The Market



- Clean appearance with magnetic power cords- hide away cords from merchandise
- Posi-Lock Connection assures merchandise will not pull wiring like other brands
- Money Saving: Easy to adjust shelves without an electrician
- Low profile, easily hidden for clean neat appearance
- Lit shelves increase sales
- Limited 2 Year Warranty On Lighting












Power Track System

Power Track



- Length: 71-1/8"
- Material: PVC
- Finish: Black (*BK) & White (*WH)
- Magnetic Track: Requires no hardware to install
- Trimmable
- Once installed, no professional needed when reconfiguring for seasonal products
 new store plans
- Accommodates 12V or 24V lighting up to 10 amps
- Low profile & easily hidden



Posi-Lock Connection



- Overall Length: 26-1/4"
- Cable Length: 22-3/4"
- Finish: Black (*BK) & White (*WH)
- Locking link cable can be
- repositioned for easy shelf adjustment
- All cables have a posi-lock connection when connected to the track. It will not easily dislodge by merchandise
- Built in rare earth magnet on cables will allow you to easily hide wires

Power Linking Cable

Connects from power supply to power track LED-PWT-PL-*

> Each: \$4.00 12+ Pcs.: \$3.75 ea.


Locking Linking Cable

Connects from power track to the light LED-PWT-LL2-*

Each: \$4.00 12+ Pcs.: \$3.75 ea.

Power Track Lighting (Up To 905 Lumens Per Fixture)

Material: Aluminum with Opaque White Polycarbonate Lens (Pre-Installed Locking Linking Cable)




	Overall	Locking Linking	# Of LED	lotai	Max # Can		
Part #	Length	Cable Length	Chips	Wattage		Each	12+ Pcs.
LED-PWT-12V-CW3	35-1/8"	25"	63	9.8	-	\$36.40	\$31.15 ea.
LED-PWT-12V-CW4	46-7/16"	25"	84	13.7	-	\$42.58	\$36.20 ea.

Lighting Specifications

Color Temperature	CW: 6000K
Beam Spread	120°
Lumens	LED-PWT-12V-CW3: 785 LED-PWT-12V-CW4: 905
Color Rendering Index	CW: 80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	3014

SunRay (Up To 1018 Lumens Per Fixture)

Material: Aluminum with Opaque White Polycarbonate Lens (Locking Linking Cable Sold Separately)



	Overall	Length w	# Of LED	Total	Max # Can	P	rice
Part #	Length	Power Adaptor	Chips	Wattage	Connect	Each	12+ Pcs.
		Cool White *C	W & Warm	White *W	W		
LED-T536-*	35-1/8"	36-3/8"	192	13	15′	\$40.75	\$35.15 ea.
LED-T548-*-S	45"	46-1/4"	240	16	15′	\$48.60	\$41.95 ea.





Color Temperature	CW: 3700K-4300K WW: 2800K-3200K
Lumens	LED-T536-CW: 932 LED-T536-WW: 926 LED-T548-CW-S: 1287 LED-T548-WW-S: 1227
Color Rendering Index	80+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD3014







Power Track System

Shelf Edge Ticket With Integrated LED Lighting (Up To 1700 Lumens Per Fixture)

Material: Aluminum with Opaque White Polycarbonate Lens (Locking Linking Cable Sold Separately)











	Overall	Cord	# Of LED	Total	Max # Can	Р	rice
Part #	Length	Length	Chips	Wattage	Connect	Each	12+ Pcs.
LSL24-45-PW	45"	5"	161	22	-	\$60.48	\$51.66 ea.

Overall Length

Color Temperature	PW: 4200K
Beam Spread	120°
Lumens	LSL24-45-PW: 1870
Color Rendering Index	CW: 80
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	2835













Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers A power linking cable required.

|--|

Range of				Price			
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.	
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.	
For Product Details & More Dimmer Ontions, See Pages 1-134~136 & 1-142~144							

Other Options: Rotary | Touch Dimmer | Radio Frequency

Switches

A power linking cable required.



						Price
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.
For Product Details & More Switch Ontions, See Page I. 140						








LED Closet Rod Kit: Customized To Any Length

Kit Includes (Available In 3 Sizes): Closest Rod, Ribbon Flex Light & 2 Mounting Brackets









	-2" Cut Increm	nents-		
	F5/8	3″⊣		
		a : a		
,				
\ 				 5-1/8″Thick
TESA double-	sided adhesiv	ve tape on bo	ttom	



Lighting Specii	ications
Color Temperature	CW: 6500K
Beam Spread	120°
Lumens	3 Ft.: 480 4 Ft.: 800 5 Ft.: 1120
Color Rendering Index	CW: 75
Rated Average Life	40,000 hrs.
Constant	Voltage
Chip Size	SMD3528

				# Of LED	Total	Price	Per Kit
Part #	Color Temp	Finish	Length	Chips	Wattage	Each	10+
LED-CLOSET-3	Cool White	Clear	3′	54	7.4	\$39.00	\$36.00 ea.
LED-CLOSET-4	Cool White	Anodized	4′	72	9.9	\$52.00	\$47.50 ea.
LED-CLOSET-5	Cool White	Aluminum	5′	90	12.4	\$65.00	\$57.00 ea.

For 8 ft. Lens (L-TASK-CLO), See page L-60



Required

Power Supply	

Optional (Pick One Option)
Switch	Motion Sensor

Switch		Motion Sensor	
	or		+

Required **Closet Rod**

Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional



					11100		
	Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
	LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.
For Product Details & More Switch Ontions See Page L-149							

Motion Sensors



					ı	Price
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-DSEN	Door Sensor	Silver	Surface/	Surface: 2-1/2"L x 1-1/8"W x 11/16"H	\$11.75	\$10.90 ea.
LED-DSEN	Door Sensor	Silver	Recessed	Recessed: 2-1/2"L x 5/8": Dia.	\$11./5	\$10.90 ea.
					_	









LED Lighting

Infinity Light

Material: Aluminum Construction with Polycarbonate Lens

- Connectable
- Supplied with 18" connecting cable
- Connect up to 20 fixtures
- · Limited 3 Year Warranty







LENS CHARACTERISTICS						
Color Transmission Dispersion Surface Texture LED Diodes						
Opaque White	Low	High	Smooth	Not Visible		
Clear	Full	None	Smooth	Visible		



Optional

Dimmer





		# Of		Max#		Price			
		Lens	LED	Total	Can	Each	ı	10+ Pcs.	
Part #	Color Temp	Type	Chips	Wattage	Connect	OB, WH or BK	MC	OB, WH or BK	MC
Matte Chrome *MC, Oil Rubbed Bronze *OB, White *WH & Black *BK									
LED-L1TW-*-CW	Cool White		12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.
LED-L1TW-*-PW	Pure White	Clear	12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.
LED-L1TW-*-WW	Warm White		12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.
LED-L1TW-*-CW-FR	Cool White	0	12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.
LED-L1TW-*-PW-FR	Pure White	Opaque	12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.
LED-L1TW-*-WW-FR	Warm White	White	12	3.8	20	\$18.00	\$24.00	\$16.00 ea.	\$21.00 ea.

Reauired

Power Cord

99	
Color Temperature	CW: 5700K PW: 4000K WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 166 PW: 180 WW: 166
Color Rendering Index	CW/PW: 85 WW: 80
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	SMD2835

(ŲL)

Lighting Specifications

1.75

Power Cord (Required)



- · Function: On/Off • Cord Length: 10'

		FIICE		
Part #	Finishes	Each	6+ Pcs.	
LED-L1TW-PC-BK	Black	\$3.95	\$3.56 ea.	
LED-L1TW-PC-WH	White	\$3.95	\$3.56 ea.	

legrand Dimmer Switches (Optional)

Optional

Connecting

Cable



Required

Infinity Light

<u>sofTap</u> Touch Switch With Touch Slide Dimmer

LGD120-DIMST-MG LGD120-DIMST-WH Each: \$54.98 (White) Each: \$63.28 (Magnesium)

For More Options, Product Details & Wall Plates, See Page L-143



Connecting Cable (Optional)

Drice

Function: Is to allow the designer to get around unlit areas without multiple power supplies



Part #	Length	Color	Price	6+ Pcs.
LED-L1TW-CC24-WH	24"	White	\$2.50 ea.	\$2.25 ea.
LED-L1TW-CC36-BK	36"	Black	\$3.00 ea.	\$2.70 ea.
LED-L1TW-CC36-WH	36"	White	\$3.00 ea.	\$2.70 ea.







Utopia Ultra Bright Puck Light- Only Pivot Option On The Market!

Does It All! Even Light Distribution Without Any Hot Spots! *Material: Aluminum with Opaque White Polycarbonate Lens*


- Pivoting head allows light to be directed to desired locations
- Connectable
- Supplied with 18" connecting cable
- Connect up to 20 fixtures off one power supply




LENS CHARACTERISTICS						
Color	Transmission	Dispersion	Surface Texture	LED Diodes		
Opaque White	Low	High	Smooth	Not Visible		

Opaque White Lens: Allows the least light transmission. The effect softens the light, reduces glare and eliminates the "scalloping" caused by the LED's in most cases













		# Of LED	Total	Max # Can	Price	
Part #	Finish	Chips	Wattage	Connect	Each	10+ Pcs.
	Pure Wh	ite *PW &	Warm Whi	te *WW		
LED-UTO-CHR-*	Stainless	7	2.5	20	\$11.50	\$10.25 ea.
LED-UTO-BK-*	Black	7	2.5	20	\$11.50	\$10.25 ea.
LED-UTO-WH-*	White	7	2.5	20	\$11.50	\$10.25 ea.
LED-UTO-SC-*	Satin Chrome	7	2.5	20	\$11.50	\$10.25 ea.



Drill Hole Size



Lighting Specifications

Color Temperature	PW: 5700K WW: 2800K-3200K
Beam Spread	120°
Lumens	PW: 240 WW: 148
Color Rendering Index	PW/WW: 85
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD5730












LED Lighting

Accessories for Utopia Ultra Bright Puck Light







Required **Gen Next** or Pricing, See Page L-102

Required

Power Supplies



						Price	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-1A	Wall Mount	1A	24V	24W	3.13"L x 2.07"W x 1.52"H	\$11.65	\$10.60 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable Required for power supplies, dimmers & switches.



Part # Description		Overall		Price		
		Length	Finish	Each	6+ Pcs.	
LED-WF-PWL	Power Link Cable with Utopia Connection	18"	White	\$3.00	\$2.60 ea.	

For Product Details & More Power Linking Cables, See Page L-141

Optional

Dimmers

A power linking cable required.



Range of				Price		
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Switches

A power linking cable required.



				F	Price			
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.		
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.		
For Product Details & More Switch Options, See Page L-149								

Connecting Cables



			_	P	rice
Part #	Function	Finish	Length	Each	6+ Pcs.
LED-WF-CC24	Is to allow the designer to get around unlit	White	24"	\$2.00	\$1.60 ea.
LED-WF-CC36	.ED-WF-CC36 areas without multiple power supplies		36"	\$2.50	\$2.25 ea.









LED Lens

LENS CHARACTERISTICS							
Color	Transmission	Dispersion	LED Diodes				
Milk White	Medium	Medium	Smooth	Slightly Visible			

Milk White Lens: Allows moderate light transmission. The effect softens the light and reduces glare. A good choice for the largest variety of lighting situations.







Marquee Puck Light Series

Surface Square Marquee Puck (Up To 300 Lumens Per Fixture)



			# Of LED	Total	Max # Can	P	rice		
	Part #	Finish	Chips	Wattage	Connect	Each	6+ Pcs.		
	Cool White *CW, Warm White *WW & Pure White *PW								
	LFD-MOSS-S-*	Satin Aluminum	1	3.5	10	\$15.75	\$13.75 ea		



Lighting Specifications

Color Temperature	CW: 6000K-6500K WW: 2900K-3100K PW: 4000K
Beam Spread	120°
Lumens	CW/WW: 260-300
Color Rendering Index	CW/WW: 80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	СОВ





Lighting Specifications

Color Temperature	CW: 6000K-6500K WW: 2900K-3100K PW: 4000K
Beam Spread	120°
Lumens	CW/WW: 260-300
Color Rendering Index	CW/WW: 80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	COB

Surface Round Marquee Puck (Up To 300 Lumens Per Fixture)



Part #	Finish	Chips	Wattage	Connect	Each	6+ Pcs.
	Cool White *CW,	Warm Whi	ite *WW &	Pure White	*PW	
LED-MRQRD-S-*	Satin Aluminum	1	3.5	10	\$14.25	\$12.25 ea.

Surface Mount |←2-1/2"→| \$3/16"

Lighting Specifications

CW: 6000K-6500K WW: 2900K-3100K PW: 4000K
120°
CW/WW: 260-300
CW/WW: 80
20,000 hrs.
Voltage
COB

Surface Square Marquee Plus (Up To 450 Lumens Per Fixture)



			# Of LED	Total	Max # Can	P	rice	
	Part #	Finish	Chips	Wattage	Connect	Each	10+ Pcs.	
Cool White *CW, Warm White *WW & Pure White *PW								
	LED-MQKS-B-*	Brushed Satin	12	5	7	\$23.25	\$19.50 ea.	



Lighting Specifications


	WW: 2900K-3100K PW: 4000K
Beam Spread	120°
Lumens	CW/WW: 400-450
Color Rendering Index	CW/WW: 80
Rated Average Life	20,000 hrs.
Constant	Voltage
Chip Size	SMD5630

LED Lighting





Accessories for Marquee Puck Light Series



Required

Power Supplies



						Price		
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.	
LED-12V-1A	Wall Mount	1A	12V	12W	2.91"L x 1.61"W x 1.14"H	\$8.95	\$8.20 ea.	
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.	

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Junction Box

Required for power supplies, dimmers, switches, motion sensors & multi output cables.



			Price			
Part #	Function	Input Cord	Outputs	Dimensions	Each	6+ Pcs.
LED-MQ-J3	Joins multiple	39" Female DC 5.5	3	1-1/2"L x 1-1/4"W x 3/8"H	\$2.75	\$2.30 ea.
LED-MQ-J4	fixtures to one	39" Female DC 5.5	4	1-1/2"L x 1-5/8"W x 3/8"H	\$3.25	\$2.70 ea.
LED-MQ-J5	powers supply	39" Female DC 5.5	5	1-1/2"L x 2-1/4"W x 3/8"H	\$3.45	\$2.85 ea.

Optional

Dimmers



	Price					
Part # Description		Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.
LED-DIM-648D	Standard Touch	Silver/Black	0-100%	22mm: Dia. x 16mm: W	\$9.00	\$8.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144 Other Options: Rotary | Touch Dimmer | Radio Frequency

Switches



					Price		
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.	
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.	
LED-OS-648A	Touch On/Off	Sliver/Black	Recessed	22mm: Dia. x 16mm: W	\$9.00	\$8.50 ea.	

For Product Details & More Switch Options, See Page L-149

Motion Sensors



				_		1166
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-DSEN	Door Sensor	Silver	Surface/ Recessed	Surface: 2-1/2"L x 1-1/8"W x 11/16"H Recessed: 2-1/2"L x 5/8": Dia.	\$11.75	\$10.90 ea.
LED-MSEN	Door Sensor	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$14.50	\$13.05 ea.

For Product Details & More Motion Sensor Options, See Page L-142

Multi Output Cables



			Arms	# of	Overall	Max # of Power	Price		
Part #	Description	Description Finish Size		Arms	Length	Linking Cables	Each	6+ Pcs.	
LED-2WAY-BK	2-Way Sweep	Black	3″	2	6-3/4"	2	\$2.95	\$2.50 ea.	

For More Extension Cable Options, See Page L-147

Price

For Multiple Design Options...
Outwater Introduces:

The "Way Far" Better Light



LED Wafer Puck Light Series

Wafer Puck Light

- No Holes To Bore
- Surface Mount
- Connectable
- Lightweight
- Super Thin
- Easy To Install: Available In Magnetic, Adhesive or Surface Mount

See Page L-108




Moveable Wafer Track System

- Add A Light Anywhere Needed
- Adjustable
- Lightweight
- Super Thin 1/4"
- Easy To Install

See Page L-109





Wafer Puck Light Battery Kit

- No Power Supply
- Install Anywhere
- All Inclusive Kit
- Lightweight
- Super Thin 1/4"
- Easy To Install

See Page L-112











Wafer Puck Light

The "Way Far" Better Light Thinnest Surface Mounted Puck- Recessed Look Without The Work!

Material: PVC Body with Prismatic Clear Polycarbonate Lens

- Super thin & super bright
- Greater light output then a 20W halogen bulb
- Dimmable
- Supplied with 18" connecting cable












IP20 Wafer Puck Light
Provides Low Protection of Dust & Water

Wafer Puck Light (Up To 250 Lumens Per Fixture)





Color Temperature	CW: 6500K WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 250 WW: 230
Color Rendering Index	CW: 80 WW: 85
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD3014

Lighting Specifications

			Total				Pı	rice
Part #	Color Temp	Finish	Mount Options	# Of LED Chips	Wattage	Max # Can Connect	Each Kit	10+ Kits
LED-WF-MC-CW-A	Cool White	Matte Chrome	Adhesive or	21 Per Fixture	2.2	5 fixtures for 1 amp power supply	\$9.00	\$7.80 ea.
LED-WF-MC-WW-A	Warm White	Matte Chrome	Screw Mount	21 Per Fixture	2.2	15 fixtures for 3 amp power supply 25 fixtures for 5 amp power supply	\$9.00	\$7.80 ea.







Moveable Wafer Track System

Material: PVC Body with Prismatic Clear Polycarbonate Lens

- Easily move the puck light anywhere along the track
- Freedom to add puck lights anywhere you need them
- Offered with 3', 4', 6' & 12' track
- Connect up to 25 puck lights off 1 power supply
- Available jumper cable allow for shelf to shelf lighting connection





Moveable Wafer Track System (Up To 250 Lumens Per Fixture)







Choose a Track (comes with adhesive):



Part #	Length	Price						
Black *BK & White *WH								
LED-WF-TRK-2-*	2′	\$4.00 ea.						
LED-WF-TRK-3-*	3′	\$6.00 ea.						
LED-WF-TRK-4-*	4′	\$8.00 ea.						
LED-WF-TRK-6-*	6′	\$12.00 ea.						
LED-WF-TRK-12-*	12′	\$24.00 ea.						

Lighting Specifications

Color Temperature	CW: 6500K WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 250 WW: 230
Color Rendering Index	CW: 80 WW: 85
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD3014

2 Choose Number of Wafer Lights:


			Total					
Part #	Color Temp	Finish	# Of LED Chips	Wattage	Max # Can Connect	Each	10+	
LED-WF-MC-CW-MT	Cool White	Matte Chrome	21 Per Fixture	2.2	5 fixtures for 1 amp power supply 15 fixtures for 3 amp power supply	\$9.00	\$7.80 ea.	
LED-WF-MC-WW-MT	Warm White	Matte Chrome	21 Per Fixture	2.2	25 fixtures for 5 amp power supply	\$9.00	\$7.80 ea.	







Accessories for Wafer Puck Light & Moveable Wafer Track System




Required

Power Supplies

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage • Comes With Appropriate Power Linking Cable • Limited 2 Year Warranty









		Overall		F	Price
Part #	Description	Length	Finish	Each	6+ Pcs.
LED-WF-PWL	Power Link Cable with Wafer Connection	18"	White	\$3.00	\$2.60 ea.
	E D 1 (D ()) 0 M D 1 () 1			-	

For Product Details & More Power Linking Cables, See Page L-141

Optional

<u>Dimmers</u>

A power linking cable required.



			Range of		P	rice
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
LED-INLINE-TCHDIM	Inline Touch	Black	0-100%	1-1/4"L x 3/4"W x 7/16"H	\$7.95	\$7.25 ea.

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144

Other Options: Rotary | Touch Dimmer | Radio Frequency

Switches

A power linking cable required.



						rice
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-SWITCH-3A/6A	On/Off	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$4.50	\$4.05 ea.
LED-PLUNT-36-WH	On Door Opens/ Off Door Closed	Black	Surface	2-3/4"L x 2"W x 1"H	\$13.50	\$12.15 ea.

For Product Details & More Switch Options, See Page L-149








LED Lighting

Price

Price

Accessories for Wafer Puck Light & Moveable Wafer Track System



Optional

Motion Sensors

A power linking cable required.



				-		1100
Part #	Description	Finish	Mounting	Dimensions	Each	6+ Pcs.
LED-MSEN	Door Sensor	Black	Surface	2-1/4"L x 1"W x 3/4"H	\$14.50	\$13.05 ea.
		1 10			•	


For Product Details & More Motion Sensor Options, See Page L-142

Multi Output Cables

Works with wafer puck light only A power linking cable required for each outlet.

			Arms	# 01	Overali	Max # OI Power		TICE		
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.		
LED-5OUT-CBL-BK	5-Way Sweep	Black	8-3/4"	5	19"	5	\$5.50	\$4.85 ea.		
LED-SPIDER-CBL 3-Way Spider Black 4-1/2" 3 96" 4 \$6.25 \$5.55 ea.										
	For More E	xtension (Cable Op	tions,	See Page	L-147				





Connecting Cables

Works with wafer puck light only



			_			_
Part #	Function	Finish	Length	Each	6+ Pcs.	
LED-WF-CC24	Is to allow the designer to get around unlit	White	24"	\$2.00	\$1.60 ea.	
LED-WF-CC36	areas without multiple power supplies	White	36"	\$2.50	\$2.25 ea.	

Jumper Cable

Works with wafer puck light only



					TICC
Part #	Function	Finish	Length	Each	6+ Pcs.
JC24	Designed to connect one track to another / Useful when going level to level or make a 90º turn	Black	24"	\$2.50	\$2.25 ea.





Wafer Puck Light- Battery Operated Kit

Outwater is proud to introduce the first of its kind, low cost LED Closet & Cabinetry battery operated Wafer Puck Light!

Material: PVC Body with Prismatic Clear Polycarbonate Lens

- Super thin, low profile... great for tight applications
- The included door plunger allows the light to turn on when the door is open & off when closed without depleting battery life
- When activated, the built-in timer on the door plunger allows light to turn off automatically in 90 seconds, thus saving battery power
- Cheaper than installing an electrical outlet
- Suited for existing closets, cabinets or drawers
- Surface mounts with supplied peel & stick tape or screws
- Low voltage no risk of shock



Wafer Puck Light- Battery Operated Kit (Up To 250 Lumens Per Fixture)



ALL INCLUSIVE KIT WITH RECHARGEABLE BATTERY



- (A) 3 lights w/peel & stick adhesive, screws & (3) 18" extension leads.
- (B) Rechargeable 4800MAH Battery pack: 4-1/4"L x 2-1/4"W x 3/4"H comes supplied with power supply Battery Life Expectancy: 8.7 Hours Continuous See Page L-140 For More Info.
- (C) Door plunger: 2-3/4"L x 2"W x 1"H w/3' input/output wires




Direct In	terconnectio	n

					# Of LED	Total	P	rice
Part #	Color Temp	Description	Finish	Mount Options	Chips	Wattage	Each Kit	10+ Kits
LED-WF-RB-MC-CW	Cool White	Rechargeable	Matte	Adhesive or	21 Per	2.2	\$59.95	\$54.95 ea.
LED-WF-RB-MC-WW	Warm White	Battery Kit	Chrome	Screw Mount	Fixture	2.2	\$59.95	\$54.95 ea.

See Page L-108 for our LED Wafer "Way Far" Better Light & Page L-109 for our LED Wafer Track System

For other Closet Lighting, See Page L-100





Lighting Specifications

Temperature	WW: 2800K-3200K
Beam Spread	120°
Lumens	CW: 250 WW: 230
Color Rendering Index	CW: 80 WW: 85
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD3014







Venus Ultra Bright Puck Light

Material: Aluminum with Clear Polycarbonate Lens

- Extremely bright 3-1/2" produces a "Shower of Light"
- Supplied with 39" connecting cable
- · Connect up to 12 fixtures off one power supply





NEW & IMPROVED Higher Lumens! Lower Cost!



Provides Protection From Dust & Splashing Water, Not Submersible

Venus Ultra Bright Puck Light (Up To 325 Lumens Per Fixture)



		# Of LED	Total	Max # Can	P	rice
Part #	Finish	Chips	Wattage	Connect	Each	10+ Pcs.
	Pure Whit	е * PW & И	arm White	e *WW		
LED-VEN-CHR-*	Polished Chrome	42	3	12	\$17.25	\$14.95 ea.
I FD-VFN-RCH-*	Brushed Chrome	42	3	12	\$17.25	\$14.95.62





Lighting Specifications

PW: 3800K-4200K WW: 2800K-3200K
90°
PW: 325 WW: 300
PW/WW: 75
50,000 hrs.
Voltage
SMD3528

Required



Optional Dimmer





Power Supplies With Connection (Required)

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage Comes With DC 3.5 Male Power Linking Cable • Limited 2 Year Warranty

Desk Top (1.5A / 24V / 36W)

- 4.56" L x 1.92" W x 1.3" H
- 18AWG Input Cord: 60"
- 20AWG Output Cord: 60"
- Green On/Off LED Indicator Light
- Polarized 2 Prong Plug

LED-24V-1.5A

Each: \$23.50 / 6+ Pcs.: \$21.15 ea.

Desk Top (2A / 24V / 45W)

- 4.375" L x 1.75" W x 1.25" H
- 18AWG Input Cord: 60"
- 20AWG Output Cord: 60"
- Green On/Off LED Indicator Light
- Polarized 2 Prong Plug

LED-24V-2A

Each: \$24.50 / 6+ Pcs.: \$22.25 ea.

Dimmer (Optional)



LED-CLE-DIM Each: \$5.95 6+ Pcs.: \$5.25 ea.

- · On/Off Switch
- 3-3/4" L x 1-1/8" W x 3/8" H
- Male DC 3.5 Output Cord: 36"
- Range of Dimming: 0-100%
- · Mounting: Screw

Junction Box (Optional)

Function: Is to join multiple fixtures to one power supply

- 1-5/8" L x 1-1/4" W x 5/8" H • Power In: 1 Port
- Power Out: 4 Ports

LED-CLE-JB Each: \$2.95 / 6+ Pcs.: \$2.45 ea.




Connecting Cable (Optional)

Function: To connect junction box or other lights



Each: \$2.50











LED Top Hat Spotlight

Material: Satin Aluminum with Clear Polycarbonate Lens


- Sleek & Attractive Design
- Connectable
- Surface Mount











Top Hat Spotlight (Up To 85 Lumens Per Fixture)



cations
CW: 6500K
60°
CW: 85
CW: 80
30,000 hrs.
Voltage
5MM DIA

Lighting Specifications

Required

Power Supply



Power Supplies (Required)

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage Comes With Appropriate Power Linking Cable • Limited 2 Year Warranty



Plug Type (1A / 12V / 12W)

- 2.91" L x 1.61" W x 1.14" H
 - **LED-12V-1A** Each: \$8.95
- 22AWG Output Cord: 60" • Polarized 2 Prong Plug

6+: \$8.20 ea.

Optional Rechargeable **Battery Available** See page L-140

How Long Will My Battery Last?

Battery Longevity: (AMPS x VOLTS) WATTS



LED & Halogen Lighting

Connectable Canister Light- LED & Halogen

Material: Steel

- · All metal construction
- · Spring clip mounting
- 3-3/4" drill hole size
- FB-*: Includes 50W PAR-20 Halogen Bulb
- LED-FB-*: Includes 8W LED PAR-20 Bulb















Plug-In Swivel Recessed- LED & Halogen

Material: Steel

- · All metal construction
- Spring clip mounting
- 2-7/8" drill hole size
- 24" cord with polarized plug

Available Finishes for RLF & HSP Series:



Brushed Chrome








Lighting Specifications

NW: 5000K WW: 2700K-3200K Halogen: 2700K

HSP Series





	_	Price			
Part #	Bulb Type	Each	20+ Pcs.		
Black (*BK), White (*1	WH), Brushed Chrom	e (* BC), & C	hrome (*CHR)		
HSP-35-*	Halogen	\$20.27	\$17.06 ea.		
LED-35-*-4W-NW	LED Natural Wh.	\$28.00	\$24.40 ea.		
LED-35-*-5W-WW	LED Warm White	\$28.00	\$24.40 ea.		
REP	LACEMENT HALOGI	EN BULB 🍳			
HSP-35-BULB	Halogen	\$6.83	-		
F	REPLACEMENT LED	BULB 옥			
LG10-40-NW	Natural White	\$7.75	-		
LG10-30-WW	Warm White	\$7.75	-		

See Page L-151 For LED Bulb Specs

- HSP-35-* includes halogen 35W/120V GU-10 base lamp
- LED-35-*-5W-* includes LED 5W/120V GU-10 base lamp
- Dimmable

PLEASE NOTE: BULBS ARE COMPLIMENTARY. WE ARE NOT RESPONSIBLE FOR BREAKAGE DURING SHIPPING OR DEFECTS.







Twinkle Fiber Optics

Recommended Panel Material: Gloss Finish Acrylic Material: PMMA

- Endless End of Light for ceiling & Curtain Effect possibilities for creating one of a kind effects
- Covers area approximately 6.5' x 6.5' (42.25 sq. ft.)
- Light engine can be set for single color, gradual change, jumping change or twinkle effects
- Fiber optic kits with black polyethylene coating are suitable for moist environments
- Star point refers to the points where the fibers come through the panel
- In End of Light applications, alternating the use of included end pieces and optional starburst end caps create a realistic night sky effect
- In Light Curtain applications, fibers can be trimmed at any point to create your desired effect

Lighting Specifications

Beam Spread	120°
Lumens	Red/Green/Blue: 180
Rated Average Life	50,000 hrs.




End of Light Kit With Black Polyethylene Coating

ALL INCLUSIVE KIT

- **(A)** Light engine w/remote Installation instructions included
- (B) 40 strands of fiber, 2.2mm thick
- (C) 40 end pieces





Part #	Length	# of Fibers	Star Points Per Sq. Ft.	Total Wattage	Price
LED-FO-40	6'6"	40	2	16	\$184.00 ea.




Curtain Effect Kit Without Black Polyethylene Coating

ALL INCLUSIVE KIT

- (A) Light engine w/remote Installation instructions included
- (B) 120 strands of fiber, (60) .75mm thick, (60) 1.0mm thick
- (C) 120 end pieces





Part #	Length	# of Fibers	Star Points Per Sq. Ft.	Total Wattage	Price
LED-FO-60	6'6"	120	6	16	\$189.00 ea.



Starburst End Cap (Optional)




LED-FO-STAR Each: \$0.50

Optic Comb For Use With Curtain Effect Kit (Optional)



LED-FO-COMB Each: \$2.00

- 30"L x 3/16"W x 5/8"H
- Material: Linear PE Plastic
- Color: Ivory











LED Lighting

Grip It - No Drill Clamp: Illuminated

Material: Clear Anodized Aluminum











Color		Panel	anel 🔺 Maximum		# Of LED	Total	Price		
Part #	Temp	Finish	Thickness	Sign Size	Length	Chips	Wattage	Each	20+
LED-SC80-MC	Cool White	Matte Chrome	3/16" - 5/16"	6-5/16" x 6-5/16"	3-1/8"	6	.4	\$12.16	\$11.01 ea.
LED-SC120-MC	Cool White	Matte Chrome	3/16" - 5/16"	9-1/2" x 9-1/2"	4-3/4"	9	.6	\$15.07	\$13.67 ea.
LED-SC180-MC	Cool White	Matte Chrome	3/16"- 5/16"	14-3/16" x 14-3/16"	7-1/16"	12	.8	\$17.82	\$16.12 ea.

Lighting Specifications

Color Temperature	CW: 6000K-6500K
Beam Spread	120°
Lumens	CW: 40-80
Color Rendering Index	CW: 70
Rated Average Life	50,000 hrs.
Chip Size	SMD3528

▲ Maximum sign size per piece

Required









Power Supplies (Required)

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 Constant Voltage • Limited 2 Year Warranty **Comes With Appropriate Power Linking Cable**

Plug Type (1A / 12V / 12W)



Junction Box (Required)

Function: Is to join multiple fixtures to one power supply

LED-STD-JB10 Each: \$3.00

- 2" L x 1-1/4" W x 1/2" H
- # of Outputs: 10
- Input Cord: 19-11/16"











LED Standoffs: Perfect for Lobbies & Reception Areas

Material: Aluminum

- The standoff wire is 38" long
- Up to 10 pieces can be connected to one power supply
- #6 screws & drywall anchors included










Provides Low Protection of Dust & Water



Cap: 15/64

Finishes: Polished Matte Black Chrome Chrome

cifications
CW: 6000K-6500K
120°
CW: 30-40
CW: 70
10,000 hrs.
SMD2908


Maximum Recommended Spacing: 20" x 20" for 4 Standoffs

			Panel Thickness	Barrel	Thread		# Of LED	Total	F	Price
Part #	Color Temp	Finish	(When Graphic is Routed)	Length	Length	Diameter	Chips	Wattage	Each	60+
STD-LED-2525-PC	Cool White	Polished Chrome	Up to 1/2"	1″	3/4"	1″	6	.4	\$7.83	\$6.83 ea.
STD-LED-2525-MC	Cool White	Matte Chrome	Up to 1/2"	1″	3/4"	1"	6	.4	\$7.83	\$6.83 ea.
STD-LED-2525-BK	Cool White	Black	Up to 1/2"	1″	3/4"	1″	6	.4	\$7.83	\$6.83 ea.
STD-LED-2525-M-*	Red (*RD), Blue (*BL) & Green (*GR)	Matte Chrome	Up to 1/2"	1″	3/4"	1"	6	.4	\$7.83	\$6.83 ea.
STD-LED-2525-B-*	Red (*RD), Blue (*BL) & Green (*GR)	Black	Up to 1/2"	1″	3/4"	1"	6	.4	\$7.83	\$6.83 ea.









Junction Box (Required)

Function: Is to join multiple fixtures to one power supply

LED-STD-JB10 Each: \$3.00

- 2"L x 1-1/4"W x 1/2"H
- # of Outputs: 10
- Input Cord: 19-11/16"

How Long Will My Battery Last? **Battery Longevity:** $\frac{(AMPS \times VOLTS)}{WATTS} = HRS$

Optional Rechargeable

Battery Available See page L-140

Power Supplies (Required) **PLUG & PLAY**

Short Circuit Protection • Overload Circuit Protection • IP20 Constant Voltage • Limited 2 Year Warranty **Comes With Appropriate Power Linking Cable**

Plug Type (1A / 12V / 12W) • 2.91" L x 1.61" W x 1.14" H

- Output Cord: 60"
- · Polarized 2 Prong Plug
- LED-STD-TR-1A Each: \$8.95 6+ Pcs.: \$8.20 ea.



Forstner Drill Bit (Optional)

- · Extra sharp cutting edges for smooth, flat bottomed holes
- Hole Size: 3/4"



• Shank: 3/8" Each: \$10.50









LED Lighting

LED Ladder Backlight System

Available Lengths: Nominal 20" & 40"


Material: Aluminum with White Coating


- Ultra Bright: Latest 2835 chip technology produces up to 1440 lumens per length.
- Works with FSB41TX-CL, FSB81TX-CL & FSB150TX-CL. Please Inquire
- Backlight as little as 1-1/2" depth without hotspots
- Easily connect ladders together for versatile sizing
- · No heat sink required





Limited Protection From Touch, Tools & Splashing Water





Ask About Our Sample	
SEG Framing Kit	
1	Part #: FOGA-DES-KIT

			# Of LED	Total	Max # Can		Price
Part #	Color Temp	Description	Chips	Wattage	Connect	Each	10+ Pcs.
LED-LDR194-CW	Cool White	4- Row 19.69" Length	24	29	5	\$15.90	\$12.75 ea.
LED-LDR196-CW	Cool White	6- Row 19.69" Length	36	43	3	\$23.75	\$18.90 ea.
LED-LDR394-CW	Cool White	4- Row 39.37" Length	48	58	2.5	\$26.00	\$20.75 ea.
LED-LDR396-CW	Cool White	6- Row 39.37" Length	72	86	1.5	\$39.00	\$31.25 ea.

Li	g١	ht	in	g	S	p	e	ci	fi	ca	ti	0	ns	,

CW: 6500K
168°
436 per ft.
85+
50,000 hrs.
Voltage
2835

Required




Optional (Pick One Option)



	Kequirea
	Ladder
_	· • \$ • · •//• · • \$ • ·
	For Pricing
	See Page L-119

Required

Power Supplies (IP20)



						F	Price
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-6A	Desktop	6A	12V	72W	4.68"L x 2.34"W x 1.48"H	\$27.85	\$25.35 ea.
LED-12V-9A	Desktop	9A	12V	108W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$40.35 ea.

For Product Details & More Power Options, See Pages L-137~140

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery



The System with profile since 1965

FAB LED STRIP









2 Powerful LED Options Illuminates SEG Graphics Evenly Without Hot Spots

- Designed to fit inside the frame of FSB81TX and FSB150TX-CL.
- Comes complete with finger lift hi-tack acrylic permanent tape.






STANDARD



DELUXE



Lighting Specifications

140

Color Temperature	CW: 6000K-7000K
Beam Spread	40°
Initial Lumens	LED-FBF83-CW: 550-650 per ft. LED-FBF14-CW: 1000-1100 per ft. LED-FBF7-DLX-CW: 550-650 per ft. LED-FBF84-DLX-CW: 700-800 per ft. LED-FBF18-DLX-CW: 2000-2100 per ft.
Color Rendering Index	75+
Rated Average Life	30,000 hrs.
Constant	Voltage
Chip Size	SMD3535
Warranty	3 Years Limited

•	o ensure even manimation, the rao LED strip
	should be spaced no more then 2" apart.
	Strip Distance: 2"
- 55	

- The overall width of your frame should not exceed 96", but the brightness level is greatest at 50" or less.
- Do not exceed running more lights than suggested because of voltage drop. However, if you "split" the load using a 2-way connector then you can have more lights on each side. The 2-way connector requires 2 power linking cables (LED-FBF-PWL*) that work with these lights. For Accessories, See Page L-121.

		Color	# Of LED	Total	Max # Can		
Part #	Length	Temp	Modules	Wattage	Connect	Price	20+ Pcs.
		STANDA	ARD BRIG	HTNESS			
LED-FBF83-CW	8"	Cool White	3	7	10	\$13.50 ea.	\$12.50 ea.
LED-FBF14-CW	14"	Cool White	5	10	7	\$23.00 ea.	\$21.50 ea.
		DELU)	KE BRIGH	TNESS			
LED-FBF7-DLX-CW	6-1/8"	Cool White	3	7	8	\$16.00 ea.	\$15.00 ea.
LED-FBF84-DLX-CW	8"	Cool White	4	8	10	\$21.00 ea.	\$20.00 ea.
LED-FBF18-DLX-CW	18-1/2"	Cool White	9	20	4	\$47.00 ea.	\$45.10 ea.





Accessories for FAB LED Strips



LED Lighting The System

with profile

since 1965













Required

Power Supplies



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-2.5A-HWS	L Hardwire	2.5A	24V	60W	11.8"L x 1.25"W x 0.78"H	\$45.36	\$40.50 ea.
LED-24V-3A	Desktop	3A	24V	72W	4.68"L x 2.34"W x 1.48"H	\$28.75	\$26.05 ea.
LED-24V-4A	Desktop	4A	24V	96W	6.77"L x 2.83"W x 1.57"H	\$44.05	\$39.90 ea.
LED-24V-6A	Desktop	6A	24V	144W	6.77"L x 2.83"W x 1.57"H	\$52.15	\$47.40 ea.
	_	_					

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Power Linking Cable





			Overali			TICE
Part #	Works With	Description	Length	Finish	Each	6+ Pcs.
LED-FBF-PWL18	FAB LED Strip	Dannar Link Cabla	18"	Black	\$3.10	\$2.90 ea.
LED-FBF-PWL40	FAB LED Strip	Power Link Cable	40"	Black	\$4.55	\$4.30 ea.

Optional

Multi Output Cables



			Arms	# of	Overall	Max # of Power		Price
Part #	Description	Finish	Size	Arms	Length	Linking Cables	Each	6+ Pcs.
Power Linking Cable Required For Each Outlet								
LED-2WAY-BK	2-Way Sweep	Black	3"	2	6-3/4"	2	\$2.95	\$2.50 ea.

Connecting Cables



Part #	Works With	Description	Finish	Length	Each	6+ Pcs.
LED-FBF-CC-12	FAB LED Strip	Allows the designer to get	Black & Red	12"	\$1.65	\$1.49 ea.
LED-FBF-CC-18	FAB LED Strip	around unlit areas without	Black & Red	18"	\$2.75	\$2.48 ea.
LED-FBF-CC-40	FAB LED Strip	multiple power supplies	Black & Red	40"	\$4.50	\$3.95 ea.

Hanging Cable

Works With: FSB43TC-CL, FSB92TX-CL, FSB80TX-CL, FSB81TX-CL & FSB150TX-CL



FWH-8-PC 8 Ft. Cable Each: \$7.15 / 200 Pcs. \$5.20 ea.

FWH-15-PC 15 Ft. Cable Each: \$7.95 / 200 Pcs. \$6.10 ea.



Ask About Our Sample SEG Framing Kit

Price











Nova SEG Frame: Bring Your SEG Game To The Next Level

Available Lengths: 16" x 20", 24" x 36", 30" x 40" & 36" x 48"

Material: PMMA with Aluminum Frame

Only 10.6MM Overall Thick-Ultra Thin & LightSupplied with a 12V Power Supply at No Extra Cost

• Fast Activation- No Flickering

• Aluminum heat sink preserves the life span of your frame

 $\bullet \ \mathsf{Uses} \ \mathsf{High} \ \mathsf{Quality} \ \mathsf{PMMA} \ \mathsf{Material} \mathsf{-} \ \mathsf{90\%} \ \mathsf{Output}$

• Limited 5 Year Warranty





		# Of LED	Total	1	Price
Part #	Description	Chips	Wattage	Each	10+ Pcs.
NOVA-1620-CW	16" x 20" X 7/16" Frame With Power Supply	105	15	\$104.63	\$99.40 ea.
NOVA-2436-CW	24" x 36" X 7/16" Frame With Power Supply	189	28	\$252.00	\$239.40 ea.
NOVA-3040-CW	30" x 40" X 7/16" Frame With Power Supply	210	31	\$325.00	\$308.75 ea.
NOVA-3648-CW	36" x 48" X 7/16" Frame With Power Supply	252	37	\$444.00	\$421.80 ea.





Lighting Specifications

Color Temperature	CW: 6500K-7300K
Beam Spread	120°
Lumens	NOVA-1620-CW: 1400 NOVA-2436-CW: 2520 NOVA-1620-CW: 2802 NOVA-1620-CW: 3360
Color Rendering Index	85+
Rated Average Life	50,000 hrs.
Constant	Current
Chip Size	2835

Required



Optional (Pick One Option)



Required



Optional

Dimmers

A power linking cable required.



			Range of			Price
Part #	Description	Finish	Dimming	Size	Each	6+ Pcs.
LED-INLINE-DIM-WH	Inline Rotary	White	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
For Product Details & More Dimmer Ontions, See Pages 1-134~136 & 1-142~144						

For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~14

Other Options: Rotary | Touch Dimmer | Radio Frequency








Fully Assembled Front Loading Aluminum Frames

Material: Aluminum Frame with Acyclic Light Guide Panel

- Comes ready to use: Clear PVC cover, mounting hardware & power supply included
- Easy front load feature
- Can be used either landscape or portrait
- Low profile, should meet ADA requirements
- Plug & Play

FRONT VIEW






SUPER BRIGHT! EVEN ILLUMINATION!

BACK VIEW





BEVELED EDGE PROFILE



SHOWNIELDMINATEL



Lighting Specifications

Color Temperature	WW: 7500K-8500K
Lumens	FLF-LED-0811: 275 FLF-LED-1117: 475 FLF-LED-1620: 625 FLF-LED-2228: 1000 FLF-LED-2436: 1250
Color Rendering Index	CW: 75-80
Rated Average Life	50,000 hrs.
Chip Size	SMD2835

			Graphic	Reveal Dimensions	Overall Dimensions	Total		Price
Part #	Color Temp	Finish	Size	(Nominal)	(Nominal)	Wattage	Each	5+
FLF-LED-0811	Cool White	Anodized Aluminum	8.5" x 11"	8-1/8" x 10-11/16"	10-1/8" x 12-3/4"	3	\$88.20	\$70.56 ea.
FLF-LED-1117	Cool White	Anodized Aluminum	11" x 17"	10-5/8" x 14-3/8"	12-1/2" x 18-5/16"	4	\$116.55	\$92.40 ea.
FLF-LED-1620	Cool White	Anodized Aluminum	16" x 20"	15-19/32" x 19-5/8"	17-3/8" x 21-3/8"	6	\$141.75	\$113.40 ea.
FLF-LED-2228	Cool White	Anodized Aluminum	22" x 28"	21-1/2" x 27-1/2"	23-3/8" x 29-3/8"	10	\$199.50	\$162.23 ea.
FLF-LED-2436	Cool White	Anodized Aluminum	24" x 36"	23-5/8" x 35-1/2"	25-1/2" x 37-3/8"	13	\$333.90	\$267.12 ea.







Crystal Light Box

For Counter & Wall Mount Displays Material: Acrylic with Aluminum Post

- Super thin 3/8"
- Available in wall mount & counter top
- Power supply included
- Includes On / Off Switch



(ŶĹ)

Constant Voltage Power Supply Included

WALL MOUNT











21

			Graphic	Reveal Dimensions	Overall Dimensions	Total	P	rice
	Part #	Color Temp	Size	(Nominal)	(Nominal)	Wattage	Each	5+
Ī	CLB-LED-0811-W	Cool White	8.5" x 11"	8" x 10-5/8"	10-13/16" x 13-5/16"	1.8	\$60.48	\$50.40 ea.
	CLB-LED-1117-W	Cool White	11" x 17"	10-5/8" x 16-5/8"	13-3/4" x 19-3/4"	3.6	\$92.99	\$77.49 ea.
	CLB-LED-1620-W	Cool White	16" x 20"	15-1/2" x 19-3/4"	18-1/4" x 23-11/16"	6	\$130.41	\$108.68 ea.
	CLB-LED-2228-W	Cool White	22" x 28"	21-9/16" x 27-9/16"	24-3/4" x 30-3/4"	9	\$232.85	\$194.04 ea.
	CLB-LED-2436-W	Cool White	24" x 36"	23-1/2" x 35-5/8"	27-1/8" x 39-1/8"	11	\$340.20	\$282.50 ea.
	CLB-LED-0811-C	Cool White	8.5" x 11"	8" x 10-5/8"	10-13/16" x 13-5/16"	1.8	\$62.78	\$52.32 ea.
	CLB-LED-1117-C	Cool White	11" x 17"	10-5/8" x 16-5/8"	13-3/4" x 19-3/4"	3.6	\$95.29	\$79.41 ea.

Available for either wall mount (-w) or counter top (-c) applications.








"Tiny" Spot LED Lights

Material: Aluminum with Clear Polycarbonate Lens

- Ultra compact & extremely bright
- Fully Connectable
- Emits virtually no heat
- Heads swivels 360° and pivots 180° for easy direction of light
- On/Off Switch (Only Tiny Spot 15)
- 39" connecting cable (Only Tiny Spot 15)
- 39" connecting cable with 3.5 Male/Male Connector (Only Tiny Spot 11)
- Screws Included



Tiny Spot 15 (Up To 110 Lumens Per Fixture)



Tiny Spot 11 (Up To 110 Lumens Per Fixture)



Optional

Battery

Available

Rechargeable

See page L-140

Lighting Specifications For Tiny Spot 15 & Tiny Spot 11

Color reinperature	CVV. 0300K
Beam Spread	60°
Lumens	CW: 110
Color Rendering Index	CW: 75
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	CREE3535

			# Of LED	Total	Max # Can		Price
Part #	Color Temp	Finish	Chips	Wattage	Connect	Each	10+ Pcs.
LED-TS05S-CW	Cool White	Polished Chrome	1	2	15	\$13.00	\$11.85 ea.
LED-TS05-CW	Cool White	Polished Chrome	1	2	15	\$12.25	\$11.00 ea.

Required



Optional (Any Combination)



Required



Power Supplies (Required)

PLUG & PLAY

Short Circuit Protection • Overload Circuit Protection • IP20 • Constant Voltage Comes With DC 3.5 Reducer Power Linking Cable • Limited 2 Year Warranty

Plug Type (1A / 12V / 12W)

- 2.91"L x 1.61"W x 1.14"H
- 22AWG Output Cord: 5'
- Polarized 2 Prong Plug

LED-12V-1A Each: \$8.95 10+ Pcs.: \$8.20 ea.



Plug Type (3A / 12V / 36W)

- 3.41"L x 2.31"W x 1.26"H
- 18AWG Output Cord: 6'
- Polarized 2 Prong Plug

LED-12V-3A Each: \$16.15

6+ Pcs.: \$14.70 ea.

Junction Box (Optional)

Function: Is to join multiple fixtures to one power supply Only Works With LED-TS05-CW


- 1-5/8" L x 1-1/4" W x 5/8" H
- Power In: 1 Port
- Power Out: 4 Ports
 LED-CLE-JB

Each: \$2.95 / 6+ Pcs.: \$2.45 ea.

Connecting Cable (Optional)

Function: To connect junction box or other lights
DC 3.5
Length: 39"
DC 3.5

LED-35MM-39CC-BK Each: \$2.50 / 6+ Pcs.: \$2.25 ea.



How Long Will My Battery Last?

Battery Longevity: (AMPS x VOLTS)

Phone: 1-800-631-8375 - Fax: 1-800-888-3315

Due to raw material cost fluctuations, prices are subject to change.

= HRS









Slim Series: Wall Washer


Available Lengths: 19.7" & 39.4" *Material: Silver Aluminum Housing*

- Perfect for landscape lighting, buildings facades and both indoor and outdoor displays.
- No UV & RF Interference
- Maintenance Fee
- Low Voltage
- Easily connectable with waterproof connectors
- Two Sizes for numerous applications
- Limited 5 Year Warranty





			# Of LED	Iotai	Max # Can	Max. Lig.		rice
Part #	Color Temp	Size	Chips	Wattage	Connect	Dis.	Each	10+ Pcs.
LED-WALL24-CW	Cool White	1.4" D x 2.2" H x 19.7" L	24	10	10	10′	\$85.00	\$74.80 ea.
LED-WALL48-CW	Cool White	1.4" D x 2.2" H x 39.4" L	48	20	5	13′	\$138.07	\$121.51 ea.



Required

Power Supplies (IP67)



							rice
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-24V-2.5A-HW	Hardwire	2.5A	24V	60W	7.5"L x 1.8"W x 1.3"H	\$25.00	\$22.50 ea.
LED-24V-4.17A-HW	Hardwire	4.17A	24V	100W	8.7"L x 2.7"W x 1.7"H	\$42.00	\$38.20 ea.

For Product Details & More Power Options, See Pages L-137~140

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

<u>Power Linking Cable</u> Required for power supplies



		Overali			1100
Part #	Description	Length	Finish	Each	6+ Pcs.
LED-WALL-PWL	Connects from power supplies to wall washer	12"	Black	\$7.95	\$7.25 ea.

Drice





Omni Display Arms For Wall & Cabinets


Material: Anodized Aluminum with Frosted Polycarbonate Lens

- 270° rotation on fixture
- · No assembly required
- · Mounting screws included















	# Of LED	iotai	FII	ce
Part #	Chips	Wattage	Each	10+ Pcs.
Coo	l White *	W & Warm	White *WW	
LED-OS-220A-*	18	5.4	\$21.90	\$18.90 ea.

Required **Power Supply** See Page L-127





	Required
	Omni Display Arm
F	For Pricing, See Page L-127

Required



						rice	
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-3A	Wall Mount	3A	12V	36W	3.41"L x 2.31"W x 1.26"H	\$16.15	\$14.70 ea.
For Product Details & More Power Ontions See Pages L-137-140							

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Dimmers



			Range of		r	rice
Part #	Description	Finish	Dimming	Dimensions	Each	6+ Pcs.
LED-INLINE-DIM	Inline Rotary	Black	0-100%	2-5/8"L x 1-3/8"W x 1"H	\$5.95	\$5.25 ea.
For Product Details & More Dimmer Options, See Pages L-134~136 & L-142~144						
Other Options: Rotary Touch Dimmer Radio Frequency						

Phone: 1-800-631-8375 Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.

Halogen / LED Lighting







Klem Light Fixture

Material: Metal

- Lightweight But Extremely Durable! All stainless steel construction with nickel plated components and highly polished shades of the light head.
- Safe For Museum Pieces! Halogen bulbs with dichroic reflector. 80% of potentially harmful heat is reflected to the rear of the light head while 100% of the light shines on the subject matter.
- Easy To Use! Each fixture is uniquely designed for ease of fixation
- No Transformer Required! 120V simply plug into any outlet. Black power cord is 10 feet long with 3 prong plug.
- Versatile and Portable! The light head clamp can be adjusted to various angles for the greatest potential of any exhibit.

Lighting Specifications

HALOGEN				
Beam Spread	50°			
Lumens	CW: 1260			
Rated Average Life	CW: 2 000 hrs			

Lighting Specifications


LED				
Color Temperature	CW: 6000K WW: 2700K-3000K			
Beam Spread	35°			
Lumens	CW: 340 WW: 290			
Color Rendering Index	CW/WW: 80			
Rated Average Life	CW/WW: 30,000 hrs.			
Constant	Voltage			
Chip Size	SMD2835			

Cielo® XL: Sturdy Clamp Mechanism Fits Up To 3" Thick Material (No Screw Mounting)




Part #	Description	Price
	Cool White (*CW) & Warm White (*WW)	
200X-CL	Cielo® Exhibit Light Fixture	\$99.75 ea.
200X-CL-HAL	Cielo® Exhibit Light Fixture With 75W Halogen Bulb	\$110.25 ea.
200X-CL-LED-*	Cielo® Exhibit Light Fixture With 5W LED Bulb	\$99.75 ea.

Paneo®: Top Panel Mounted (Two-Piece Bracket Assembly & Mounting)




Part #	Part # Description			
	Cool White (*CW) & Warm White (*WW)			
205-P	Paneo® Exhibit Light Fixture	\$89.25 ea.		
205-P-HAL	Paneo® Exhibit Light Fixture With 75W Halogen Bulb	\$99.75 ea.		
205-P-LED-*	Paneo® Exhibit Light Fixture With 5W LED Bulb	\$89.25 ea.		

Mount to panel by hooking the light fixture into a base unit affixed invisibly to the rear edge of the panel.





Imago®: Surface Mounted



Part #	Description	Price
	Cool White (*CW) & Warm White (*WW)	_
210-l	Imago® Exhibit Light Fixture	\$93.45 ea.
210-I-HAL	Imago® Exhibit Light Fixture With 75W Halogen Bulb	\$103.95 ea.
210-I-LED-*	Imago® Exhibit Light Fixture With 5W LED Bulb	\$93.45 ea.






Halogen / LED Lighting

"Arc It" Lights

Material: Metal

- Fully adjustable light head allows for great flexibility in a variety of applications
- Display arm can also be adjusted at a variety of angles by using the gear adjuster to lock into place





24" CURVED ARM

CLAMP ADJUSTS FOR /8"-3-3/8" **PANELS**





		Price				
Part #	Description	Each	10+ Pcs.			
	Cool White (*CW) & Warm White (*W	W)				
LED-ARC-SC*	24" Curved Arm, 5W High Powered LED Bulb	\$62.65	\$56.77 ea.			
LED-GNECK-SC*	19" Flexible Arm, 5W High Powered LED Bulb	\$62.65	\$56.77 ea.			
HAL-ARC-SC	24" Curved Arm, 50W Halogen Bulb	\$54.90	\$49.02 ea.			
HAL-GNECK-SC	19" Flexible Arm, 50W Halogen Bulb	\$54.90	\$49.02 ea.			
REPLACEMENT LED BULB						
LMR16-30-CW	Cool White	\$7.75	-			
LMR16-30-WW	Warm White	\$7.75	-			

See Page L-151 For LED Bulb Specs

Lighting Specifications

LED		
Color Temperature	CW: 6000K WW: 3000K	
Beam Spread	30°	
Lumens	CW: 340 WW: 290	
Color Rendering Index	CW/WW: 80	
Rated Average Life	CW/WW: 50,000 hrs.	
Constant	Voltage	
Chip Size	SMD2835	

Lighting Specifications

HALOGEN

Beam Spread	36°
Lumens	CW: 1700
Rated Average Life	CW: 2,000 hrs








"Center Stage" Exhibit & Display Lights

Super bright, energy efficient & cost effective LED option for showcasing your exhibit, display & products Material: Aluminum

- Super bright- comparable to an 150W halogen bulb
- · Energy efficient only 21W
- Includes On/Off switch at the base of the fixture
- Includes a 10' long power cords with a 3 prong plug
- · Nominal 18" overall length
- The light head will swivel approximately 360° and will rotate down or up 45°
- Sturdy, but light weight aluminum construction with a protective acrylic lens
- Light head measures 5-3/4" x 2-1/2"













				# Of LED	Total	P	rice
Part #	Color Temp	Finish	Length	Chips	Wattage	Each	10+
LED-EXL21-BK	Cool White	Black	18" (Nominal)	50	21	\$58.00	\$54.00 ea.
LED-EXL21-SL	Cool White	Silver	18" (Nominal)	50	21	\$58.00	\$54.00 ea.

Lighting Specifications				
Color Temperature	CW: 6000K-7000K			
Beam Spread	120°			
Lumens	CW/WW: 1600			
Color Rendering Index	70			
Rated Average Life	36,000 hrs.			
Constant	Voltage			
Chip Size	5630			

Mounting Clips (Optional)

Small Clamp

- Clamps up to 1-3/16"
- · Material: Aluminum

LED-EXL-SC-* Each: \$6.75 ea. Black (*BK) & Silver (*SIL)



Large Clamp

- Clamps up to 1-3/4"
- Material: Aluminum

LED-EXL-LC-* Each: \$6.75 Black (*BK) & Silver (*SIL)



Cabinet Mounting Plate

- Screw mount to the top of a cabinet
- Material: Aluminum
- 1/4" Screw Hole, Screws Included

LED-EXL-CP-* Each: \$2.95

Black (*BK) & Silver (*SIL)

Note: Other Mounting Options Available- Please Inquire









LED Lighting

Channel Letter Lighting System: The New Generation Of Channel Letters


Available Lengths: 30', 37' & 49' Material: Polycarbonate Housing

- NEW LED modules innovatively designed for indoor & outdoor lighting
- Widest, most even spread of light, to work in shallow and deep cans
- Offers the most even lighting technology available
- UV/IR protected and IP67 rating to handle extreme weather conditions
- Mounts with supplied 3M adhesive on the back or can be fastened with screws (Not Supplied)
- · Limited 3 Year Warranty

Channel Letter Lighting Suitable For Wet Locations

LED-YOCL-UCW (Up To 125 Lumens Per Foot)





Beam Spread 180° 125 per ft Lumens **Color Rendering Index** 70+ Rated Average Life 50,000 hrs. Constant Voltage Chip Size

Lighting Specifications


Color Temperature

UCW: 7500K

Of LED Price Description Length **Total Wattage** Each 10+ **Color Temp** Chips LED-YOCL-UCW Ultra Cool White 75 pc. module string 30' 38W (.50W per mod) \$56.00 (\$0.75 per mod) \$49.80 ea. (\$0.66 per mod)

LED-LGCL-CW (Up To 140 Lumens Per Foot)






75 Modules per 37' Coil (.72 watts per mod)

Lighting Specif	ications
Color Temperature	CW: 6500K
Beam Spread	180°
Lumens	140 per ft
Color Rendering Index	70+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	2835

				# Of LED		1	Price
Part #	Color Temp	Description	Length	Chips	Total Wattage	Each	10+
LED-LGCL-CW	Cool White	75 pc. module string	37′	3	54W (.72W per mod)	\$39.70 (\$0.52 per mod)	\$36.50 ea. (\$0.49 per mod)

LED-ANPCL-UCW (Up To 205 Lumens Per Foot)





Color Temperature	UCW: 7500K
Beam Spread	180°
Lumens	205 per ft
Color Rendering Index	70+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	3030

Lighting Specifications

				# Of LED			rice
Part #	Color Temp	Description	Length	Chips	Total Wattage	Each	10+
LED-ANPCL-UCW	Ultra Cool White	75 pc. module string	49′	2	90W (1.2W per mod)	\$105.33 (\$1.40 per mod)	\$96.55 ea. (\$1.28 per mod)

Recommended Depth/	Part #	Min. Depth		Rcmd. Spacing Between Rows								
Spacing Coverage Chart	LED-YOCL-UCW	1.5"	2"	3"	3"	7"	4"	10"	5"	15"	6"-8"	15"
To Avoid Hot Spots	LED-ANPCL-UCW	2"	2"	3″	3″	7″	4"	10"	5"	15"	6"-8"	15"
10 Avoid Hot Spots	LED-LGCL-CW	3″	N/A	N/A	3"	5″	4"	7.5"	5″	9″	6"-8"	12"

Required Required **Power Supply Channel Letter** Modules

Required

Power Supplies (IP67)



							TICE
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-5A-HW	Hardwire	5A	12V	60W	7.5"L x 1.88"W x 1.33"H	\$25.00	\$22.50 ea.
LED-12V-8.3A-HW	Hardwire	8.3A	12V	100W	8.74"L x 2.71"W x 1.69"H	\$44.00	\$39.50 ea.

For Product Details & More Power Options, See Pages L-137~140

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery









RGB Channel Letter Lighting: The New Generation Of Channel Letters

Available Lengths: 30'

Material: Polycarbonate Housing

- NEW LED modules innovatively designed for indoor & outdoor lighting
- Latest LED chip technology = maximum brightness output
- Smart RGB controller offers a multitude of programmable patterns
- High IP67 rating to handle damp weather conditions
- Mounts with supplied 3M adhesive on the back or can be fastened with screws (Not Supplied)
- · Limited 3 Year Warranty





Endless Possibilities of Colors



PURPLE WHITE **GREEN** YELLOW CYAN

LED-TRICL-RGB





Min. Can Depth: 4"

Module Dimensions: 2.83"L x .79"W x .55"D 60 Modules per 30' Coil (.72 watts per mod)

			# Of LED			Price		
Part #	Color Temp	Description	Length	Chips	Total Wattage	Each	10+	
LED-TRICL-RGB	RGB	60 pc. module string	30′	2	43W	\$197.80	\$179.40 ea.	
LED-I NICL-NOD	NGD	oo pc. module string	30	30 3	.72W per mod	(\$3.29 per mod)	(\$2.99 per mod)	

Lighting Specifications

Color lemperature	KGR
Beam Spread	160°
Color Rendering Index	70+
Rated Average Life	50,000 hrs.
Constant	Voltage
Chip Size	5050



Required

Power Supplies (IP67)



Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.
LED-12V-5A-HW	Hardwire	5A	12V	60W	7.5"L x 1.88"W x 1.33"H	\$25.00	\$22.50 ea.
LED-12V-8.3A-HW	Hardwire	8.3A	12V	100W	8.74"L x 2.71"W x 1.69"H	\$44.00	\$39.50 ea.
						_	

For Product Details & More Power Options, See Pages L-137~140 Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Smart Controller (SPI)

RGB Channel Letter WIFI-28 Preset Programs & 80+ SPI Programmable Functions

> **LED-TRICL-CTRL** Each: \$75.00



Features:

- 8A / 12V / 100W
- Receiver Size: 5"L x 3.34"W x 1.23"H
- Max Length: 50'
- · Output Signal: SPI
- Input: Female DC 5.5 Output: Ethernet CAT5E
- · Mounting: Screw
- · Remote Control Function: WIFI
- · Limited 3 Year Warranty

Controller Functions:

Create a strobing, chasing, flashing, meteor & curtain effect!

- Racing Patterns
- Wave Patterns
- Jumping Patterns
- Strobing Color Combination Patterns
- · Static/Color: 7 Options (Red, Green, Blue, Purple, Cyan (Aqua) & White







Diamond Brite LED Channel Letter Modules

Material: Polycarbonate Housing

- New Technology: Each LED is lensed separately, no silicone! This prevents yellowing from U.V. or salt water air.
- IP 68 rated modules and power supply
- Supplied with 3M adhesive
- Can be mounted with screw (not included)



Chip Size



Lighting Specifications Color Temperature CW: 6500K Beam Spread 120°, 140° or 160° LED-EC2: 43 per mod. LED-ECS2: 50 per mod. LED-EC3: 64 per mod. LED-ECS3: 65 per mod. LED-ECS3: 75 per mod. Lumens LED-EC4: 85 per mod. Color Rendering Index Rated Average Life 50.000 hrs. LED-EC*: Voltage LED-ECE*: Voltage LED-ECS*: Current Constant

2835

A. 2 LED Module





		Beam		Dimen	sions		# Of LED	Total	Min. Can	Max # Can	Price		
	Part #	Spread	Α	В	C	D	Chips	Wattage	Depth	Connect	50 Pcs.	100+ Pcs.	
	Cool White (Must be purchased in 50 pc. increments)												
Α	LED-EC2-CW	120°	1.50"	2.50"	1"	.29"	2	.72	3-1/8"	50	\$0.95 ea. (\$47.50/50 pcs.)	\$0.81 ea. (\$81.00/100 pcs.)	
Α	LED-ECS2-12-CW	160°	1.50"	2.25"	1″	.375"	2	.90	2"	50	\$1.00 ea. (\$50.00/50 pcs.)	\$0.88 ea. (\$44.00/100 pcs.)	
В	LED-EC3-CW	120°	2.60"	3.75"	1″	.29"	3	.72	3-1/8"	50	\$1.10 ea. (\$55.00/50 pcs.)	\$0.97 ea. (\$97.00/100 pcs.)	
В	LED-ECE3-12-CW	140°	2.50"	3.75"	1"	.375"	3	.72	2"	50	\$0.80 ea. (\$40.00/50 pcs.)	\$0.70 ea. (\$70.00/100 pcs.)	
В	LED-ECS3-12-CW	160°	2.50"	3.50"	1″	.375"	3	.72	2"	50	\$1.15 ea. (\$57.50/50 pcs.)	\$1.03 ea. (\$51.50/100 pcs.)	
C	LED-EC4-CW	120°	1.57"	4.25"	1″	.29"	4	1.44	3-1/8"	50	\$1.72 ea. (\$86.00/50 pcs.)	\$1.58 ea. (\$158.00/100 pcs.)	

Required

Power Supplies

				Price					
Part #	Type	Amps	Volts	Watts	Dimensions	Each	6+ Pcs.		
LED-12V-5A-HW	Hardwire	5A	12V	60W	7-1/2"L x 1-5/8"W x 1-1/4"H	\$25.00	\$22.50 ea.		
For Product Details & More Power Ontions See Pages 1-137-140									

Other Options: Plug In | Hardwire | Hardwire Dimmable | Rechargeable Battery

Optional

Channels For Diamond Brite: Will Hold 2 LED Module & 3 LED Module

Clear PVC Channel



L-TASK-58P-4 Per Ft.: \$0.46' 120 Ft.: \$0.44'



Sold In 4 Ft. Lengths Other Lengths Available, Please Inquire

White Channel Letter Track & Cover With Adhesive



LED-ECTKC-WH Per Ft.: \$0.75' 120 Ft.: \$0.69' **Sold In Nominal** 3.25 Ft. Lengths



Works With All 12V & 24V Standard & RGB Lighting

Outwater's Wireless Radio Frequency Dimmers

Now You Are In Control

Now You Have Greater Control Of Your Lighting Design With Our 10 Zone Dimmer By Pairing Multiple Controllers To One Receiver Or Several Receivers To One Controller

- No Wiring Needed
- Each dimmer is paired to the included receiver.
- Unlike infrared receivers which operate on line of site, Outwater's radio frequency sends signals thru any obstacles, such as: walls, cabinet doors, furniture, up to 50 ft. away from receiver.
- Dimmer controller runs on a battery (3V CR302 included) for all styles
- •Battery Life: 3 Years
- •Freedom to position controller anywhere
- Dimmer Range: 10-100%Dimmer Type: PWM
- Push button On/Off function for all styles
- •Limited 3 year warranty
- IP Rating: IP20







Available In 3 Styles









Wireless Radio Frequency For Standard Dimming Control

Standard Dimmer: 10 - 100%

Button Style



Dia: 1.25" x H: .45" Mounting: Screw Battery Operated Finish: Stainless Steel



L: 4" x W: 1.5" x H 1.8"

Battery Operated

Finish: Black Case With

Black Button

Non Skid Bumpons

Desktop Style



Wall Style

No Wiring Needed

L: 3.5" x W: 1.37" x H .75" Mounting: Wall Battery Operated Finish: White Case With Silver Button




Easily installs into standard receptacle box. Attaches with 2 screws.

Price

Standard Receiver



L: 3.5" x W: 1.375" x H: .75" 12V/8A/96W or 24V/8A/192W Input Cord: 18" DC 5.5 Female Output Cord: 18" DC 5.5 Male



Part #	Description	Each	6+ Pcs.
	Standard RF Dimmer Kit	ts	
RF-CTRL-BT	Button Style With Receiver	\$48.00	\$43.20 ea.
RF-CTRL-DT	Desktop Style With Receiver	\$67.50	\$60.75 ea.
RF-CTRL-WT	Wall Style With Receiver	\$65.00	\$58.50 ea.
Individual I	Price To Create Your Own K	it: For St	andard
RF-RECVR	Receiver	\$33.00	\$29.70 ea.
RF-BUTTON	Button Style	\$18.25	\$16.45 ea.
RF-DESK	Desktop Style	\$38.50	\$34.65 ea.
RF-WALL	Wall Style	\$36.55	\$32.90 ea.

Wireless Radio Frequency For RGB Control

RGB Dimmer: Allows to stop on one color and dim from 10 - 100% range

Desktop Style



L: 4" x W: 1.5" x H 1.8" Battery Operated Finish: Black Case With Black Button Non Skid Bumpons



Wall Style

No Wiring Needed

L: 3.5" x W: 1.37" x H .75" Mounting: Wall Battery Operated Finish: White Case With Silver Button



Easily installs into standard receptacle box. Attaches with 2 screws.

RGB Receiver

L: 7" x W: 1.75" x H: .75" 12V/8A/96W or 24V/8A/192W Input Cord: 18" DC 5.5 Female Output Cord: 18" Pin Connection Screw Mount



		Price			
Part #	Description	Each	6+ Pcs.		
	RGB RF Dimmer Kits				
RF-RGB-CTRL-DT	Desktop Style With Receiver	\$95.50	\$86.00 ea.		
RF-RGB-CTRL-WT	Wall Style With Receiver	\$91.15	\$82.05 ea.		
Individual F	Price To Create Your Own K	it: For I	RGB		
RF-RGB-RECVR	Receiver	\$58.00	\$52.20 ea.		
RF-RGB-DESK	Desktop Style	\$44.00	\$39.60 ea.		
RF-RGB-WALL	Wall Style	\$39.35	\$35.45 ea.		

LED Lighting

LED Dimmers



Wireless Radio Frequency For CCT Control

CCT Dimmer: Allows to stop on one color and dim from 10 - 100% range



Desktop Style

L: 4" x W: 1.5" x H 1.8" Battery Operated Finish: Black Case With Black Button Non Skid Bumpons



Wall Style

No Wiring Needed L: 3.5" x W: 1.37" x H .75" Mounting: Wall Battery Operated

Battery Operated
Finish: White Case With
Silver Button



Easily installs into standard receptacle box. Attaches with 2 screws.

Price

CCT Receiver


L: 7" x W: 1.75" x H: .75" 12V/8A/96W or 24V/8A/192W Input Cord: 18" DC 5.5 Female Screw Mount



			1100						
Part #	Description	Each	6+ Pcs.						
	CCT RF Dimmer Kits								
RF-CCT-CTRL-DT	Desktop Style With Receiver	\$120.40	\$105.95 ea.						
RF-CCT-CTRL-WT	\$114.75	\$100.98 ea.							
Individual	Individual Price To Create Your Own Kit: For CCT								
RF-CCT-RECVR	Receiver	\$60.75	\$58.05 ea.						
RF-CCT-DESK	Desktop Style	\$47.61	\$45.49 ea.						
RF-CCT-WALL	Wall Style	\$42.52	\$40.64 ea.						

Allows Flexibility To Control Your LED Lights

Up To 10 Zones



For Power Supply, See Pages L-137 \sim 140 (Required) • The switch much be within 50' of each receivers.

Scenario 1: Pairing One Controller (C) To One Receiver (R)

Works With Standard RF, RGB RF & CCT RF

Scenario 2:
Pairing Several Receivers (R)
To One Controller (C)

Works With Standard RF, RGB RF & CCT RF

Scenario 3:
Pairing Multiple Controllers (C)
To One Receiver (R)

Works With Standard RF

LED Power Supplies

Our high quality power supplies have many safety features. Reference individual series, the safety features are defined below.

CLASS 2: Refers to the NEC- National Electric Code. To avoid potential cable overheating due to excessive currents and electric shock, the output of the power supply is limited to 60VDC or 100VA. (100W when used with an AC-DC power supply)

CLASS II: Referring to a power supply with either a double or reinforced insulation barrier between the input and the output.

Class II power supplies will have a double square symbol.


LEVEL VI: Increase efficiency and reduced "no-load" power consumption.

SHORT CIRCUIT PROTECTION: A protection circuit that limits current and acts as an electronic circuit breaker, unit returns to full functionality when the short is removed. **OVERLOAD CIRCUIT PROTECTION:** A protection circuit that prevents the output current from exceeding maximum ratings.

Wall Mount

- Certification: UL, ROHS, FCC
- Input Voltage: 100V 220V
- Operating Temperature: 32° 104°
- Frequency: 50HZ 60HZ
- Constant: Voltage
- IP Rating: IP20

- Indoor Use
- Plug Type: Polarized 2 Prong
- Output Cord: DC 5.5
- Warranty: Limited 2 Year
- Housing Material: ABS Plastic





	Output	iviax	IVIAX	mput	Output	wire			FIICE	
Part #	Volts	Watts	Amps	Cord	Cord	Gauge	Class	Dimensions	Each	6+ Pcs.
						12V				
LED-12V-1A	12V	12W	1A	-	72"	22AWG	Class 2	A: 2.91" x B: 1.61" x C: 1.14"	\$8.95	\$8.20 ea.
LED-12V-3A	12V	36W	3A	-	72"	18AWG	Class 2	A: 3.41" x B: 2.31" x C: 1.26"	\$16.15	\$14.70 ea.
						24V				
LED-24V-1A	24V	24W	1A	-	72"	22AWG	Class 2	A: 3.13" x B: 2.07" x C: 1.52"	\$11.65	\$10.60 ea.
LED-24V-1.5A-DC5.5	24V	36W	1.5A	-	72"	22AWG	Class 2	A: 3.13" x B: 2.07" x C: 1.52"	\$12.22	\$11.59 ea.

Desktop

• Certification: UL, ROHS, FCC

• Input Voltage: 100V - 220V

• Operating Temperature: 32° - 10

• Frequency: 50HZ - 60HZ

Constant: Voltage

• IP Rating: IP20

• IP Kating: IP20
• Indoor Use

• Plug Type: Polarized 2 Prong

• Output Cord: DC 5.5

• Warranty: Limited 2 Year

• Housing Material: ABS Plastic

A A B	c UL us

	Output	Max	Max	Input	Output	Wire				Price
Part #	Volts	Watts	Amps	Cord	Cord	Gauge	Class	Dimensions	Each	6+ Pcs.
12V										
LED-12V-6A	12V	72W	6A	48'	72"	18AWG	Class 2 / Class II	A: 4.68" x B: 2.34" x C: 1.48"	\$27.85	\$25.35 ea.
LED-12V-9A	12V	108W	9A	48"	72"	18AWG	Class II	A: 6.77" x B: 2.83" x C: 1.57"	\$44.05	\$40.35 ea.
24V										
LED-24V-3A	24V	72W	3A	48"	72"	18AWG	Class 2 / Class II	A: 4.68" x B: 2.34" x C: 1.48"	\$28.75	\$26.05 ea.
LED-24V-4A	24V	96W	4A	48"	72"	18AWG	Class II	A: 6.77" x B: 2.83" x C: 1.57"	\$44.05	\$39.90 ea.
LED-24V-6A	24V	144W	6A	48"	72"	18AWG	Class II	A: 6.77" x B: 2.83" x C: 1.57"	\$52.15	\$47.40 ea.

Some LED fixtures may require a power link cable to connect to the power supply. Please refer to product listing.

LED Lighting

LED Power Supplies

Our high quality power supplies have many safety features. Reference individual series, the safety features are defined below.

CLASS 2: Refers to the NEC- National Electric Code. To avoid potential cable overheating due to excessive currents and electric shock, the output of the power supply is limited to 60VDC or 100VA. (100W when used with an AC-DC power supply)

CLASS II: Referring to a power supply with either a double or reinforced insulation barrier between the input and the output.

Class II power supplies will have a double square symbol.

SHORT CIRCUIT PROTECTION: A protection circuit that limits current and acts as an electronic circuit breaker, unit returns to full functionality when the short is removed. **OVERLOAD CIRCUIT PROTECTION:** A protection circuit that prevents the output current from exceeding maximum ratings.

Non-Dimmable Hardwire


- Certification: UL, ROHS
- Input Voltage: 100V 265V
- Operating Temperature: -22° 122°
- Frequency: 50HZ 60HZ
- Constant: Voltage
- IP Rating: IP67
- Indoor & Outdoor Use
- Warranty: Limited 2 Year
- Housing Material: Aluminum (Aluminum housing provided superior heat sink for maximum performance)



I												
		Output	Max	Max		Wire				Price		
	Part #	Volts	Watts	Amps	Input Cord	Output Cord	Gauge	Class	Dimensions	Each	6+ Pcs.	
			12V									
	LED-12V-5A-HW	7-5A-HW 12V 60W 5A 7.5" 7.5" 18AWG Class 2 A: 7.5" x B: 1.88" x C: 1.33"								\$25.00	\$22.50 ea.	
	LED-12V-8.3A-HW	12V	99.6W	8.3A	10.5"	10.5"	18AWG	-	A: 8.74" x B: 2.71" x C: 1.69"	\$44.00	\$39.50 ea.	
	LED-12V-16.6A-HW	12V	199W	16.6A	10.5"	10.5"	18AWG	Class 2	A: 9.84" x B: 3.11" x C: 2"	\$74.70	\$67.10 ea.	
	24V											
	LED-24V-1.25A-HW	24V	30W	1.25A	10.5"	10.5"	18AWG	Class 2	A: 7.16" x B: 1.14" x C: .78"	\$15.50	\$13.95 ea.	
lew)	LED-24V-2.5A-HWSL	24V	60W	2.5A	39" with US plug	39" with DC5.5	18AWG	Class 2	A: 11.8" x B: 1.25" x C: .78"	\$45.36	\$40.50 ea.	
	LED-24V-2.5A-HW	24V	60W	2.5A	10.5"	10.5"	18AWG	Class 2	A: 7.5" x B: 1.88" x C: 1.33"	\$25.00	\$22.50 ea.	
	LED-24V-4.17A-HW	24V	100W	4.17A	10.5"	10.5"	18AWG	Class 2	A: 8.74" x B: 2.71" x C: 1.69"	\$42.00	\$38.20 ea.	
	LED-24V-8.3A-HW	24V	199W	8.3A	10.5"	10.5"	18AWG	-	A: 9.84" x B: 3.11" x C: 2"	\$74.70	\$67.10 ea.	

MOX Lighting Universal Dimmable Hardwire

- Certification: ETL
- Input Voltage: 100 130VAC
- Operating Temperature: 4° 104°
- Frequency: 50HZ 60HZ
- Constant: Voltage
- Indoor & Outdoor Use
- Warranty: Limited 3 Year
- Housing Material: ABS Plastic or Aluminum (Fully insulated case)





	Output	Max	Max	Input	Output	Wire Gauge				F	Price
Part #	Volts	Watts	Amps	Cord	Cord	Primary	Secondary	Class	Dimensions	Each	6+ Pcs.
12V											
LED-12V-5A-HWUD	12V	60W	5A	-	-	-	-	Class 2	A: 7.09" x B: 2.36" x C: 1.38"	\$71.20	\$64.30 ea.
LED-12V-10A-HWUD	12V	120W	10A	-	-	-	-	Class 2	A: 10.12" x B: 3.07" x C: 1.89"	\$117.55	\$106.15 ea.
24V											
LED-24V-2.5A-HWUD	24V	60W	2.5A	-	-	-	-	Class 2	A: 7.09" x B: 2.36" x C: 1.38"	\$71.20	\$64.30 ea.
LED-24V-5A-HWUD	24V	120W	5A	-	-	-	-	Class 2	A: 10.12" x B: 3.07" x C: 1.89"	\$117.55	\$106.15 ea.

Some LED fixtures may require a power link cable to connect to the power supply. Please refer to product listing.

LED Power Supplies

Our high quality power supplies have many safety features. Reference individual series, the safety features are defined below.


CLASS 2: Refers to the NEC- National Electric Code. To avoid potential cable overheating due to excessive currents and electric shock, the output of the power supply is limited to 60VDC or 100VA. (100W when used with an AC-DC power supply)

CLASS II: Referring to a power supply with either a double or reinforced insulation barrier between the input and the output. Class II power supplies will have a double square symbol.

SHORT CIRCUIT PROTECTION: A protection circuit that limits current and acts as an electronic circuit breaker, unit returns to full functionality when the short is removed. **OVERLOAD CIRCUIT PROTECTION:** A protection circuit that prevents the output current from exceeding maximum ratings.

Magnitude Magnetic Dimmable Hardwire

- Certification: ETL
- Input Voltage: 120V
- Operating Temperature: -22° 122°
- Frequency: 50HZ 60HZ
- · Constant: Voltage
- IP Rating: NEMA 3R
- Indoor & Outdoor Use
- Warranty: Limited 5 Year
- Housing Material: Aluminum (Aluminum housing provided superior heat sink for maximum performance)






	Output	Max	Max	Input	Output	Wire Gauge					Price
Part #	Volts	Watts	Amps	Cord	Cord	Primary	Secondary	Class	Dimensions	Each	6+ Pcs.
	12V										
LED-12V-5A-HDM	12V	60W	5A	6"	6"	20AWG	14AWG	Class 2	A: 6.55" x B: 2.25" x C: 2.55"	\$80.85	\$78.16 ea.
LED-12V-13A-HDM	12V	156W	13A	6"	6"	18AWG	12AWG	Class 2	A: 9.80" x B: 3.00" x C: 3.00"	\$97.35	\$94.11 ea.
LED-12V-16.6A-HDM	12V	200W	16.6A	6"	6"	18AWG	12AWG	Class 2	A: 9.80" x B: 3.00" x C: 3.00"	\$103.95	\$100.49 ea.
						24	4V				
LED-24V-4A-HDM	24V	96W	4A	6"	6"	20AWG	14AWG	Class 2	A: 9.80" x B: 3.00" x C: 3.00"	\$89.93	\$86.93 ea.
LED-24V-6A-HDM	24V	144W	6A	6"	6"	18AWG	12AWG	Class 2	A: 9.80" x B: 3.00" x C: 3.00"	\$97.35	\$94.11 ea.
LED-24V-8.3A-HDM	24V	200W	8.3A	6"	6"	18AWG	12AWG	Class 2	A: 9.80" x B: 3.00" x C: 3.00"5	\$103.95	\$100.49 ea.

Magnitude MLV/TROAC Dimmable Hardwire

- Certification: UL, UL 8750, FCC
- Input Voltage: 120VAC
- Operating Temperature: -22° 122°
- Frequency: 50HZ 60HZ
- · Constant: Voltage
- IP Rating: NEMA 3R
- Indoor & Outdoor Use
- Warranty: Limited 5 Year
- Housing Material: Aluminum (Compact aluminum housing provided superior heat sink for maximum performance)





	Output	Max	Max	Input	Output	Wire	Gauge			F	Price
Part #	Volts	Watts	Amps	Cord	Cord	Primary	Secondary	Class	Dimensions	Each	6+ Pcs.
						12	2 V				
LED-12V-3.3A-HDMB	12V	40W	3.3A	6"	6"	18AWG	14AWG	Class 2	A: 6.77" x B: 2.67" x C: 1.26"	\$63.15	\$61.05 ea.
LED-12V-5A-HDMB	12V	60W	5A	6"	6"	18AWG	14 AWG	Class 2	A: 6.77" x B: 2.67" x C: 1.26"	\$76.40	\$73.86 ea.
						24	4V				
LED-24V-2.5A-HDMB	24V	60W	2.5A	6"	6"	18AWG	14AWG	Class 2	A: 6.77" x B: 2.67" x C: 1.26"	\$76.40	\$73.86 ea.
LED-24V-4A-HDMB	24V	96W	4A	6"	6"	18AWG	14AWG	Class 2	A: 6.77" x B: 2.67" x C: 1.26"	\$84.98	\$82.15 ea.

Some LED fixtures may require a power link cable to connect to the power supply. Please refer to product listing.

IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. **GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES**

LED Lighting

LED Power Supplies

Our high quality power supplies have many safety features. Reference individual series, the safety features are defined below.


CLASS 2: Refers to the NEC- National Electric Code. To avoid potential cable overheating due to excessive currents and electric shock, the output of the power supply is limited to 60VDC or 100VA. (100W when used with an AC-DC power supply)

CLASS II: Referring to a power supply with either a double or reinforced insulation barrier between the input and the output. Class II power supplies will have a double square symbol.

SHORT CIRCUIT PROTECTION: A protection circuit that limits current and acts as an electronic circuit breaker, unit returns to full functionality when the short is removed. **OVERLOAD CIRCUIT PROTECTION:** A protection circuit that prevents the output current from exceeding maximum ratings.

Magnitude MLV/TROAC Dimmable Hardwire

- Certification: UL Recognized, UI 8750 & FCC
- Input Voltage: 120V
- Operating Temperature: -22° 122°
- Frequency: 50HZ 60HZ
- · Constant: Voltage
- IP Rating: IP67
- Indoor & Outdoor Use
- Warranty: Limited 5 Year
- · Housing Material: Aluminum (Super compact aluminum housing provided superior heat sink for maximum performance and easy to hide)






	Output	Max	Max	Input	Output	Wire (Gauge			F	Price
Part #	Volts	Watts	Amps	Cord	Cord	Primary	Secondary	Class	Dimensions	Each	6+ Pcs.
						12	2V				
LED-12V-3.3A-HDMC	12V	40W	3.3A	6"	6"	18AWG	14AWG	Class 2	A: 4.92" x B: 1.97" x C: .77"	\$56.91	\$55.02 ea.
LED-12V-5A-HDMC	12V	60W	5A	6"	6"	18AWG	14AWG	Class 2	A: 4.92" x B: 1.97" x C: .77"	\$70.16	\$67.82 ea.
						24	IV				
LED-24V-2.5A-HDMC	24V	60W	2.5A	6"	6"	18AWG	14AWG	Class 2	A: 4.92" x B: 1.97" x C: .77"	\$70.58	\$68.23 ea.
LED-24V-4A-HDMC	24V	96W	4A	6"	6"	18AWG	14AWG	Class 2	A: 4.92" x B: 1.97" x C: .77"	\$76.40	\$73.86 ea.

Rechargeable Battery With Overcharge Protection

- Constant: Voltage
- Warranty: Limited 2 Year
- IP Rating: IP20
- · LED Indicator: Red when not fully charged & green when charged
- · Can use switch or sensor without depleting battery life
- · On/Off switch on battery
- · Power Supply: Included for charging
- Plug Type: Input- DC 5.5 Male & Output- DC 5.5 Female





								P	rice
Part #	Volts	Amps	Input Cord	Output Cord	Dimensions	Class	Longevity	Each	6+ Pcs.
					12V				
LED-RB12V-4.8A	12V	4.8	9-1/2" DC 5.5	5-/12" DC 5.5	A: 4.25" x B: 2.25" x C: .75"	Class II	2.5 hrs. (ECO12-*3560-16-*)	\$30.60	\$27.05 ea.
LED-RB12V-8A	12V	8	Male	Female	A: 4.313" x B: 2.688" x C: .875"	Class II	4 hrs. (ECO12-*3560-16-*)	\$44.30	\$39.05 ea.
					24V				
LED-RB24V-3A	24V	3	3" DC 5.5	6" DC 5.5	A: 4.375" x B: 2.25" x C: .688"	Class II	12 hrs. (RIB24-I5060-*)	\$72.55	\$63.90 ea.
LED-RB24V-5A	24V	5	Female	Male	A: 5" x B: 2.563" x C: 1.75"	Class II	20 hrs. (RIB24-I5060-*)	\$108.63	\$95.70 ea.
			How Long Wi	II My Battery L	.ast? Battery Longevity:		x VOLTS) = HRS		


Some LED fixtures may require a power link cable to connect to the power supply. Please refer to product listing.

WATTS

LED Power Supplies


Power Linking Cables

Some LED fixtures may require a power link cable to connect to the power supply. Please refer to product listing.



				Wire			P	rice
	Part #	Compatible	Function	Length	Gauge	Color	Each	6+ Pcs.
			Dedicated System Connection					
Α	LED-RIBBON-PWL	Single Ribbon	With Pin Connection (Pins Included)	18"	22AWG	Black	\$3.00	\$2.60 ea.
В	LED-SLSHX-PWL	Gen Next Thin Light	With Gen Next Connection	18"	18AWG	White	\$3.50	\$2.95 ea.
C	LED-WF-PWL	Utopia & Wafer	With Utopia & Wafer Connection	18"	24AWG	White	\$3.00	\$2.60 ea.
			For Cut Pieces of Ribbon					
D	LED-FPC-8-PWL	24V DP248* Ribbon	100% Usable Connection	24"	22AWG	White	\$2.40	\$2.20 ea.
D	LED-FPC-10-PWL	24V DP2410* Ribbon	100% Usable Connection	24"	22AWG	White	\$2.50	\$2.30 ea.
D	LED-FPC-15-PWL	24V DP2415* Ribbon	100% Usable Connection	24"	22AWG	White	\$2.60	\$2.40 ea.
D	LED-FPC-20-PWL	24V DP2420* Ribbon	100% Usable Connection	24"	22AWG	White	\$2.95	\$2.75 ea.
E	ECO12V-35-100U-PL	ECO12V 3528 (8MM)	100% Usable Connection	18"	22AWG	Black	\$4.00	\$3.50 ea.
E	LED-RIBBON-100U-PL	Single Ribbon	100% Usable Connection	18"	22AWG	White	\$4.00	\$3.50 ea.
			Hardwire					
F	LED-WIR9-BK	-	With Female DC 5.5	108"	22AWG	Black	\$2.55	\$2.25 ea.
F	LED-DCF-MCC	-	With Female DC 5.5	18"	22AWG	Black	\$1.95	\$1.65 ea.
G	LED-FPC-8-ST	24V DP248* Ribbon	With 100% Usable Connection	36"	22AWG	White	\$1.75	\$1.60 ea.
G	LED-FPC-10-ST	24V DP2410* Ribbon	With 100% Usable Connection	36"	22AWG	White	\$1.85	\$1.70 ea.
G	LED-FPC-15-ST	24V DP2415* Ribbon	With 100% Usable Connection	36"	22AWG	White	\$1.95	\$1.80 ea.
G	LED-FPC-20-ST	24V DP2420* Ribbon	With 100% Usable Connection	36"	22AWG	White	\$2.05	\$1.90 ea.
Н	LED-RIBBON-100U-RT	24V Single RGB Ribbon	With 100% Usable Connection	79"	22AWG	Multi	\$4.50	\$3.95 ea.
Н	LED-RIBBON-100U-ST	24V Single Ribbon	With 100% Usable Connection	79"	22AWG	White	\$4.50	\$3.95 ea.
- 1	LED-RIBBON-MCC	24V Single Ribbon	With Pin Connection (Pins Included)	18"	22AWG	White	\$1.95	\$1.65 ea.
- 1	LED-RIB-RGB-MCC	24V Single RGB Ribbon	With Pin Connection (Pins Included)	18"	22AWG	Multi	\$1.95	\$1.65 ea.
J	LED-T5-MCC	T-5 Sunray	With Right Angle Male DC 5.5	18"	22AWG	White	\$1.95	\$1.65 ea.
K	LED-SLSHX-MCC	Gen Next Thin Light	With Gen Next Connection	18"	18AWG	White	\$2.50	\$2.25 ea.
L	LED-WF-MCC	Utopia & Wafer	With Utopia & Wafer Connection	18"	24AWG	White	\$1.95	\$1.65 ea.
M	LED-813MINI-M	Marque Puck Light	With Marque Connection (Male)	6"	22AWG	Black	\$1.95	\$1.65 ea.
N	LED-813MINI-F	Marque Puck Light	With Marque Connection (Female)	6"	22AWG	Black	\$1.95	\$1.65 ea.

Luminous Ceiling Panels: LED & Fluorescent Applications



EGG CRATE LOUVER White, Black, Brass or Chrome

Material: Styrene • Available by sheet or case • Sheet size: 2' x 4'

Durable & Economical • Variety of patterns to choose from

Egg Crate Louver

Part #	Pattern	Color	Panel Thickness	Sheets Per Case	Price Per Sheet	Case Per Sheet
L2-BK	Egg Crate Louver 5/8" x 5/8" x 3/8"	Black	3/8"	15*	\$13.40	\$12.15
L2-WH	Egg Crate Louver 5/8" x 5/8" x 3/8"	White	3/8"	15 *	\$12.35	\$10.75
L2-CH	Parabolic Louver 1/2" x 1/2" x 5/16"	Chrome	7/16"	10*	\$32.00	\$30.00

* CRATING CHARGES ARE EXTRA

Additional \$5.00 carting charge under 15 sheets. Additional \$5.00 charge under 10 sheets.

LED Dimmers



\$LUTRON

- Lutron dimmers work with our magnetic low voltage & TRIAC hardwire dimmable power supplies
- Range of dimming depends on the led light (most LED's will not dim to 0)


• Wall plates sold separately

- Fits most standard wall plates
- Works with Nova Sheet
- IP Rating: IP20

Limited 2 Year Warranty

120V Dimmer Feature List

120V Dillillier Feature List										
Features	Skylark (S-600P-WH)	Diva (DVLV-600P-WH)								
Single Pole	Х	Х								
Night Time Locator	Х	Х								
Works With Our Hardwire Dimmable Driver	х	x								
RF Wireless	Х	Х								
Color: White	Х	Х								
Power Failure Memory	Х	Х								
UL	Х	Х								
ROHS										
cULus										
FCC										
Wall Mounting	Х	Х								








			Max.	Input	Output		
Part #	Description	Volts	Watts	Cord	Cord	Dimensions	Price
S-600P-WH	SKYLARK- On/Off switch with slide dimmer	120V	450W	5.875"	5.875"	A: 4.125" x B: 2.125" x C: 1.687"	\$18.00 ea.
DVLV-600P-WH	DIVA- Rocker switch with slider dimmer	120V	450W	5.875"	5.875"	A: 4.125" x B: 2.125" x C: 1.625"	\$43.50 ea.
CW-1-WH	White Wall Plate (screwless)	-	-	-	-	A: 4.69" x B: 2.94" x C: 0.30"	\$4.25 ea.

OPI Series

120V Dimmer Feature List

Features	OPI Series (OPDM-16-3)
3-Way	Х
Single Pole	X
Night Time Locator	Х
Works With Our Hardwire Dimmable Driver	Х
RF Wireless	
Color: White	Х
Magnesium Color	
UL	Х
FCC	
Wall Mounting	X
LED Light Indicator	Х

- OPI Series dimmer works with our magnetic low voltage & TRIAC hardwire dimmable power supplies
- Range of dimming depends on the led light (most LED's will not dim to 0)
- Wall plates sold separately
- Fits most standard wall plates
- Works with 120V Brite Light Flex & Infinity






Part #	Description	Volts	Watts	Cord	Cord	Dimensions	Price
OPDM-16-3	Rocker switch with slider dimmer	120V	600W	5.875"	5.875"	A: 4.125" x B: 2.25" x C: 1.50"	\$15.00 ea.
CW-1-WH	White Wall Plate (screwless)	-	-	-	-	A: 4.69" x B: 2.94" x C: 0.30"	\$4.25 ea.
RWP26W	White Wall Plate (screwless)	-	-	-	-	A: 4.94" x B: 3.15" x C: 0.25"	\$2.52 ea.

Max

Sensor

Works With All Wall Mount & Desktop Power Supplies

- IP Rating: IP20
- Warranty: Limited 1 Year
- Mounting: Surface or Recessed





Output

Input



			Max.	Max.				Pi	rice
Part #	Description	Volts	Amps	Watts	Input Cord	Output Cord	Dimensions	Each	6+
LED-DSEN	Daa# Camaa#	12V	2A	24W	18" DC 5.5	18" DC 5.5	Surface: A: 2.5" x B: 1.125" x C: .687"	\$11.75	¢10.00
LED-D2EN	Door Sensor	24V	2A	48W	Female	Male	Recessed: A: 2.5" x B: .625"	\$11./5	\$10.90 ea.



LED Dimmers

☐ legrand

120V Dimmer Feature List


Features	Radiant (RH703PTUTC)	Radiant Wireless Main (LC2101-WH)	Radiant Wireless Remote (LC2103-WH)	Softouch (LGD120-DIMST*)							
Tru-Universal	X	X		X							
3-Way	X			X							
Buttom End Cut-Off	X	X		X							
Single Pole	X	X		Х							
Night Time Locator	X			X							
Works With Our Hardwire Dimmable Driver	х	X	X	х							
RF Wireless		X	X	X							
Color: White		X	X	Х							
Magnesium Color				X							
3 Face Colors: White, Light Almond & Ivory	x			х							
UL	X	X	X	X							
ROHS	X	X	X	Х							
cULus	X			X							
FCC	X	X		X							
Wall Mounting	X	X	X	Х							


- Legrand dimmers work with our magnetic low voltage & TRIAC hardwire dimmable power supplies
- Ranging of dimming depends on the led light (most LED's will not dimm to 0)
- Wall plates sold separately
- Fits most standard wall plates

- True-Universal technology automatically adapts to light eliminating flickering
- Radiant wireless features voice activated control with Google Assistant or Amazon Alexa (Only LC2101-WH & LC2103-WH)

- Work with 120V Brite Light Flex & Infinity
- IP Rating: IP20







				Max.		
Part #	Description	Finish	Volts	Watts	Dimensions	Price
RH703PTUTC	Radiant- Rocker switch with slide dimmer	White	120V	450W	A: 4.25" x B: 1.75" x C: 1.25"	\$62.30 ea.
LC2101-WH	Radiant Wireless Main-Touch with touch slide dimmer	White	120V	450W	A: 4.19" x B: 1.75" x C: 1.73"	\$90.72 ea.
LC2103-WH	Radiant Wireless Remote-Touch with touch slide dimmer	White	120V	450W	A: 4.19" x B: 1.75" x C: 1.73"	\$71.06 ea.
LGD120-DIMST-MG	coffee Touch quitch with touch clide dimmer	Magnesium	120V	450W	A: 4.187" x B: 1.75" x C: 1.75"	\$63.28 ea.
LGD120-DIMST-WH	sofTap-Touch switch with touch slide dimmer	White	120V	450W	A: 4.187" x B: 1.75" x C: 1.75"	\$54.98 ea.
LGD120-WP-MG	Well Dietes For setTon (Cold Consertable)	Magnesium	-	-	A: 5" x B: 3.375" x C: .375"	\$7.98 ea.
LGD120-WP-WH	Wall Plates For sofTap (Sold Separately)	White	-	-	A: 5" x B: 3.375" x C: .375"	\$5.50 ea.
RWP26W	Wall Plates For Radiant & Radiant Wireless (Sold Separately)	White	-	-	A: 4.94" x B: 3.15" x C: .375"	\$2.52 ea.

LED Dimmers

Standard Dimmers

Works With All Wall Mount & Desktop Power Supplies


- Warranty: Limited 1 Year
- IP Rating: IP20

A. Inline Rotary (Short Cables)

Available In: Black or White













G. Radio Frequency







- 10 level brightness adjustment
- 10 level of speed adjustment
- Dimmer adjust shortcut-Switch to 100%, 50%, 25% brightness
- 8 dynamic effects
- Auto save function
- Ultra slim design

			Max.	Max.				Dimmer	Range of	_	P	rice
	Part #	Volts	Amps	Watts	Input Cord	Output Cord	Dimensions	Type	Dimming	Mounting	Each	6+ Pcs.
Α	LED-INLINE-DIM	_12V	6A	72W_	6" DC 5.5	6" DC 5.5	L: 2.6" x	Rotary	0-100%	_	\$5.95	\$5.25 ea.
^	(Finish: Black)	24V	6A	144W	Female	Male	W: 1.4" x H: 1"	notal y	0-100%	_	رو.وړ	33.23 Ca.
Α	LED-INLINE-DIM-WH	_12V	6A	72W	6" DC 5.5	6" DC 5.5	L: 2.6" x	Dotoni	0-100%		\$5.95	\$5.25 ea.
A (Finish: White)		24V	6A	144W	Female	Male	W: 1.4" x H: 1"	Rotary	0-100%	-	\$5.95	\$5.25 ea.
В	B LED-INLINE-TCHDIM		2A	24W_	6" DC 5.5	6" DC 5.5	L: 1.25" x	Touch	0-100%	_	\$7.95	\$7.25 ea.
Ь	LED-INCINE-I CHDIM	24V	2A	48W	Female	Male	W: .75" x H: .44"	Toucii	0-100%	-	37.93	37.23 ea.
C LED-DIM-BR		12V	6A	72W	3.75"	3.75"	L: 2.25" x	Push	0-100%		\$2.50	\$2.35 ea.
	LED-DIM-BK	24V	6A	144W	Bare	Bare	W: .5" x H: .18"	Pusii 0-100%	-	J2.JU	\$2.55 ea.	
D	LED-ROTY-DIM	12V	8A	96W	24" DC 5.5	24" DC 5.5	L: 2.25" x	Dotani	0-100%	Screw	\$9.95	\$9.00 ea.
U	LED-ROI 1-DIM	24V	8A	192W	Female	Male	W: 3.5" x H: 1.5"	Rotary	0-100%	sciew	\$9.95	\$9.00 ea.
Е	LED-DIM-648D	12V	2A	24W	18" DC 5.5	18" DC 5.5	Dia: 22mm x	Touch	0-100%	Recessed	\$9.00	\$8.25 ea.
_	LED-DIM-048D	24V	2A	48W	Female	Male	W: 16mm	Touch	0-100%	Recessed	\$9.00	30.25 ea.
F	LED-CLE-DIM	12V	2A	24W		36" DC 3.5	L: 3.75" x	Durah	0.1000/	C	ĊE OE	¢5 25
г	LED-CLE-DIM	24V	2A	48W	-	Male	W: 1.13" x H: .37"	Push	0-100%	Screw	\$5.95	\$5.25 ea.
G	LED INLINE BE	12V	6A	72W	3.5" DC 5.5	3.5" DC 5.5	L: 1.5" x	RF	0.1000/		¢0.0E	\$9.00 ea.
G	LED-INLINE-RF -	24V	6A	144W	Female	Male	W: .5" x H: .125"	KF	0-100%	-	\$9.95	39.00 ea.

.....

LED Cables & Connectors

Connecting Cables For 24V DP24, ECO12V 3528 & ECO 12V RGB



















						Wire		F	Price
	Part #	Descriptions	Works With	Function	Length	Gauge	Color	Each	6+ Pcs.
Α	LED-FPC-8-CON24	Connecting Cable	24V DP248*		24"	22AWG	White	\$2.15	\$2.00 ea.
Α	LED-FPC-8-CON36	Connecting Cable	24V DP248*		36"	22AWG	White	\$2.50	\$2.30 ea.
В	LED-FPC-10-CON24	Connecting Cable	24V DP2410*		24"	22AWG	White	\$2.40	\$2.20 ea.
В	LED-FPC-10-CON36	Connecting Cable	24V DP2410*		36"	22AWG	White	\$2.70	\$2.50 ea.
C	LED-FPC-15-CON24	Connecting Cable	24V DP2415*	Discreticular and 2 and a large of	24"	22AWG	White	\$2.60	\$2.40 ea.
C	LED-FPC-15-CON36	Connecting Cable	24V DP2415*	Directly connect 2 cut pieces of ribbon while providing ability to	36"	22AWG	White	\$2.95	\$2.75 ea.
D	LED-FPC-20-CON24	Connecting Cable	24V DP2420*	get around unlit areas	24"	22AWG	White	\$2.80	\$2.60 ea.
D	LED-FPC-20-CON36	Connecting Cable	24V DP2420*	get around unit areas	36"	22AWG	White	\$3.15	\$2.95 ea.
E	ECO12V-35-100U-C1	Connecting Cable	ECO12V 3528		24"	22AWG	Red/Black	\$3.25	\$2.85 ea.
Ε	ECO12V-35-100U-C2	Connecting Cable	ECO12V 3528		36"	22AWG	Red/Black	\$3.50	\$3.05 ea.
F	LED-RIBBON-100U-R1	Connecting Cable	ECO12V RGB		24"	22AWG	Multi	\$4.25	\$3.70 ea.
F	LED-RIBBON-100U-R2	Connecting Cable	ECO12V RGB		36"	22AWG	Multi	\$4.50	\$3.95 ea.
G	ECO12V-35-100U-ST	Connecting Cable	ECO12V 3528	Hardwire power supply or dimmer	79"	22AWG	Red/Black	\$4.50	\$3.95 ea.
Н	LED-RIBBON-100U-RT	Connecting Cable	ECO12V RGB	to cut pieces of ribbon	79"	22AWG	Multi	\$4.50	\$3.95 ea.
1	LED-RIBBON-100U-4P	Connecting Cable	ECO12V RGB	Directly connect pin to cut piece of ribbon to get around unlit areas	18"	22AWG	Multi	\$1.85	\$1.70 ea.

Connectors For 24V DP24, ECO12V 3528 & ECO 12V RGB


















					Price		
	Part #	Descriptions	Works With	Function	Each	6+ Pcs.	
Α	LED-FPC-8-EE-C	Connector	24V DP248*		\$1.10	\$1.00 ea.	
В	LED-FPC-10-EE-C	Connector	24V DP2410*	Haalala aannaatian	\$1.30	\$1.20 ea.	
C	LED-FPC-15-EE-C	Connector	24V DP2415*	Usable connection	\$1.60	\$1.45 ea.	
D	LED-FPC-20-EE-C	Connector	24V DP2420*	directly connect 2 cut pieces	\$1.85	\$1.70 ea.	
E	ECO12V-35-100U-EE	Connector	ECO12V 3528	2 cut pieces	\$0.85	\$0.75 ea.	
F	LED-RIBBON-100U-EE	Connector	ECO12V RGB		\$1.15	\$.95 ea.	
G	ECO12V-35-2W-EE-C	2-Way L-Shape Connector	ECO12V 3528		\$1.75	\$1.50 ea.	
Н	ECO12V-35-3W-EE-C	3-Way T-Shape Connector	ECO12V 3528	Usable connection	\$1.75	\$1.50 ea.	
1	ECO12V-35-4W-EE-C	4-Way +-Shape Connector	ECO12V 3528		\$1.75	\$1.50 ea.	

Phone: 1-800-631-8375 - Fax: 1-800-888-3315 Due to raw material cost fluctuations, prices are subject to change.

LED Cables & Connectors

•

Single

Connecting Cables & Connectors For Premium 24V Ribbon & RGB













Single & RGB Ribbon

Single & RGB Ribbon





























.....

P	rice
Each	6+ Pcs.
\$1.75	\$1.50 ea.
\$1.75	\$1.50 ea.


Price

	Part #	Descriptions	Works With	Function	Each	6+ Pcs.
Α	LED-RIBBON-2W-EE-C	2-Way L-Shape Connector	Single & RGB Ribbon	Usable connection to connect	\$1.75	\$1.50 ea.
Α	LED-RIBBON-3W-EE-C	3-Way T-Shape Connector	Single & RGB Ribbon		\$1.75	\$1.50 ea.
Α	LED-RIBBON-4W-EE-C	4-Way +-Shape Connector	Single & RGB Ribbon	ribbon at 90° angle		\$1.50 ea.
В	LED-RIBBON-2W-C	2-Way L-Shape Connector	Single & RGB Ribbon	Din sourcetion to connect	\$1.75	\$1.50 ea.
В	LED-RIBBON-3W-C	3-Way T-Shape Connector	Single & RGB Ribbon	Pin connection to connect	\$1.75	\$1.50 ea.
В	LED-RIBBON-4W-C	4-Way +-Shape Connector	Single & RGB Ribbon	ribbon at 90° angle		\$1.50 ea.
C	LED-RIBBON-100U-EE	Connector	Single & RGB Ribbon	Usable connection directly connect 2 cut pieces	\$0.85	\$0.75 ea.

							1100		
	Part #	Descriptions	Works With		Function	า		Each	100+ Pcs.
D	LED-4P-CON	Pin Connector	Single & RGB Rib	obon Pin connection	to conn	ect ribbon	strips	\$0.15	\$0.10 ea.
								_	
						Wire			Price
	Part #	Descriptions	Works With	Function	Length	Gauge	Color	Each	6+ Pcs.
Е	LED-RIBBON-100U-C1	Connecting Cable	Single Ribbon	Directly connect 2 cut	24"	22AWG	White	\$3.25	\$2.85 ea.
Е	LED-RIBBON-100U-C2	Connecting Cable	Single Ribbon	pieces of ribbon while	36"	22AWG	White	\$3.50	\$3.05 ea.
F	LED-RIBBON-100U-R1	Connecting Cable	RGB Ribbon	providing ability to	24"	22AWG	Multi	\$4.25	\$3.70 ea.
F	LED-RIBBON-100U-R2	Connecting Cable	RGB Ribbon	get around unlit areas	36"	22AWG	Multi	\$4.50	\$3.95 ea.
G	LED-RIBBON-100U-ST	Connecting Cable	Single Ribbon	Hardwire power supply or dimmer to cut	79"	22AWG	Red/Black	\$4.50	\$3.95 ea.
Н	LED-RIBBON-100U-RT	Connecting Cable	RGB Ribbon	pieces of ribbon	79"	22AWG	Multi	\$4.50	\$3.95 ea.
1	LED-RIB-CON-BK	Connecting Cable	Single Ribbon		18"	22AWG	Black	\$2.75	\$2.40 ea.
- 1	LED-RIB-CON-WH	Connecting Cable	Single Ribbon		18"	22AWG	White	\$2.75	\$2.40 ea.
1	LED-RIB-CON24-WH	Connecting Cable	Single Ribbon	All acceptable and a single out to met	24"	22AWG	White	\$3.25	\$2.85 ea.
- 1	LED-RIB-CON36-BK	Connecting Cable	Single Ribbon	Allows the designer to get around unlit areas without	36"	22AWG	Black	\$3.50	\$3.05 ea.
1	LED-RIB-CON36-WH	Connecting Cable	Single Ribbon	multiple power supplies	36	22AWG	White	\$3.50	\$3.05 ea.
J	LED-RIBBON-RGB-CON	Connecting Cable	RGB Ribbon	multiple power supplies	18"	22AWG	Black	\$2.75	\$2.40 ea.
J	LED-RIBBON-RGB-C24	Connecting Cable	RGB Ribbon		24"	22AWG	Black	\$3.25	\$2.85 ea.
J	LED-RIBBON-RGB-C36	Connecting Cable	RGB Ribbon		36"	22AWG	Black	\$3.50	\$3.05 ea.
K	LED-RIBBON-100U-4P	Connecting Cable	RGB Ribbon	Directly connect pin to cut piece of ribbon to get around unlit areas	18"	22AWG	Multi	\$1.85	\$1.70 ea.


LED Cables & Connectors

Multi Output Cables/Ports









			Length					Wire		Price		
	Part #	Descriptions	Α	В	C	D	E	# of Outputs	Gauge	Color	Each	6+ Pcs.
Α	LED-2WAY-4P-WH	2 Way Splitter with 4 Pin	12"	5.5"	-	-	-	2 Arms	22AWG	White	\$2.95	\$2.50 ea.
В	LED-2WAY-BK	2 Way Splitter with DC 5.5		3"	-	-	-	2 Arms	22AWG	Black	\$2.65	\$2.25 ea.
C	LED-3WAY-S-BK	3 Short Arm Sweep Cable w/ DC 5.5		3.75"				3 Arms	22AWG	Black	\$2.75	\$2.45 ea.
D	LED-4WAY-BK	4 Short Arm Sweep Cable w/ DC 5.5	9"	3.75"				4 Arms	22AWG	Black	\$3.05	\$2.75 ea.
E	LED-3WAY-BK	3 Arm Sweep Cable with DC 5.5		17"	-	-		3 Arms	22AWG	Black	\$4.25	\$3.85 ea.
E	LED-5OUT-CBL-BK	E Arm Swaan Cable with DC E E	19"	8.75"	-	-		5 Arms	22AWG	Black	\$5.50	\$4.85 ea.
E	LED-5OUT-CBL-WH	5 Arm Sweep Cable with DC 5.5	19"	8.75"	-	-		5 Arms	22AWG	White	\$5.50	\$4.85 ea.
F	LED-SPID2-CBL	2 Arm Spider Cable with DC 5.5	98"	54"	38"	6"	4"	2 Arms & 1 End	18AWG	Black	\$7.20	\$6.48 ea.
F	LED-SPID3-CBL	3 Arm Spider Cable with DC 5.5	96"	40"	26"	6"	4"	3 Arms & 1 End	18AWG	Black	\$8.40	\$7.56 ea.
F	LED-SPIDER-CBL	3 Arm Spider Cable with DC 5.5	96"	25"	23.5"	4.5"	25"	3 Arms & 1 End	22AWG	Black	\$6.25	\$5.55 ea.
F	LED-SPIDER-CBL-WH	5 Arrii Spider Cable With DC 5.5	96"	25"	23.5"	4.5"	25"	3 Arms & 1 End	22AWG	White	\$6.25	\$5.55 ea.

Bulk Wire

Part #	Description	Works With	Length	# of Wires	Wire Gauge	Price	100+ Ft.
LED-2WR18-PVC-BK	Bulk Roll	Single Ribbon	656.17' (200M)	2 Wire PVC Coated	18AWG	\$0.70	\$0.63 per ft.
LED-4WR18-PVC-BK	Bulk Roll	RGB Ribbon	656.17' (200M)	4 Wire PVC Coated	18AWG	\$0.85	\$0.77 per ft.
LED-5WR18-PVC-BK	Bulk Roll	Special Effects: Dedicated Cool or Warm White Options	656.17' (200M)	5 Wire PVC Coated	18AWG	\$0.95	\$0.85 per ft.

LED Cables & Connectors

Connectors

















For Use With Bare Wire Connections



1.625" 1.5" 1.5" 1.5" 1.5"	\$0.85 \$0.85 \$1.29 \$1.29	6+ Pcs. \$0.68 ea. \$0.68 ea. \$1.15 ea. \$1.15 ea.
1.5" 1.5" 1.5"	\$0.85 \$1.29 \$1.29	\$0.68 ea. \$1.15 ea.
1.5" 1.5"	\$1.29 \$1.29	\$1.15 ea.
1.5"	\$1.29	•
		\$1.15 ea.
1.5"	ĊΛ OΓ	
	\$0.85	\$0.68 ea.
1"	\$1.02	\$0.95 ea.
1"	\$1.25	\$1.18 ea.
1"	\$1.62	\$1.55 ea.
1.125"	\$1.72	\$1.64 ea.
.75"	\$0.46	\$0.42 ea.
.75"	\$0.53	\$0.49 ea.
.75"	\$0.69	\$0.64 ea.
1.5"	\$0.85	\$0.68 ea.
1"	\$0.85	\$0.68 ea.
1.5"	\$0.85	\$0.68 ea.
1.5"	\$0.85	\$0.68 ea.
	1" 1" 1.125"75"75"75" 1.5" 1"	1" \$1.02 1" \$1.25 1" \$1.62 1.25" \$1.72 .75" \$0.46 .75" \$0.53 .75" \$0.69 1.5" \$0.85 1" \$0.85 1.5" \$0.85

Connecting Cables





				Wire						
	Part #	Descriptions	Function	Length	Gauge	Color	Each	6+ Pcs.		
Α	LED-55MF-12-*	Connecting Cable	DC 5.5 male to DC 5.5	12"	22AWG	Black (*BK) & White (*WH)	\$1.80	\$1.55 ea.		
Α	LED-55MF-24-*	Connecting Cable	female	24"	22AWG	Black (*BK) & White (*WH)	\$2.00	\$1.70 ea.		
Α	LED-55MF-48-*	Connecting Cable	lemale	48"	22AWG	Black (*BK) & White (*WH)	\$3.50	\$3.05 ea.		
В	LED-A55MF-12CC-*	Angled Connecting Cable	Right angle DC 5.5	12"	22AWG	Black (*BK) & White (*WH)	\$1.80	\$1.55 ea.		
В	LED-A55MF-24CC-*	Angled Connecting Cable	male to right angle	24"	22AWG	Black (*BK) & White (*WH)	\$2.00	\$1.70 ea.		
В	LED-A55MF-48CC-*	Angled Connecting Cable	DC 5.5 female	48"	22AWG	Black (*BK) & White (*WH)	\$3.50	\$3.05 ea.		

LED Connectors, Mounting Clips & Switches

Switches





				Max.	Max.		Output		IP		_	Price	
	Part #	Function	Volts	Amps	Watts	Input Cord	Cord	Dimensions	Warranty	Rating	Mounting	Each	6+ Pcs.
					Е	Black *BK &	White *WH						
Λ	LED-SWITCH-3A/6A	On/Off	12V	6A	72W	12" DC 5.5	12" DC 5.5	L: 2.25" x	1 Year	IP20	Surface	\$4.50	\$4.05 ea.
^	LLD-SWITCH-SA/OA	Oll/Oll	24V	6A	144W	Female	Male	W: 1" x H: .75"	ı icai	11 20	Juliace	34.JU	34.03 Ca.
В	LED-PLUNT-36-W	Light turns on when door is opened and	12V	6A	72W	36" DC 5.5	36" DC 5.5	L: 1.063" x W: .375" x	_	_	Surface	\$5.02	\$4.75 ea.
_	LLD I LONI 30 W	off when closed	24V	6A	144W	Female	Male	H: .875"			Janace	75.02	уч./ <i>э</i> са.
_	LED-RSW-18-*	On/Off	12V	6A	72W	18" DC 5.5	18" DC 5.5	1/2" Nominal			Recessed	\$2.64	\$2.45 ea.
_	LED-U3W-10-	OII/OII	24V	6A	144W	Female	Male	Diameter			necesseu	32.04	32.43 ea.
_	LED-RSW-24-*	On/Off	12V	6A	72W	24" DC 5.5	24" DC 5.5	1/2" Nominal			Recessed	\$2.90	\$2.61 ea.
_	LED-N3W-24-	4-* On/OII	24V	6A	144W	Female	Male	Diameter			necesseu	\$2.90	32.01 ea.
_	LED-RSW-36-*	On/Off	12V	6A	72W	36" DC 5.5	36" DC 5.5	1/2" Nominal			Recessed	\$3.37	\$3.03 ea.
_	LED-K3W-30-"	On/On	24V	6A	144W	Female	Male	Diameter			Recessed	\$5.57	\$5.05 ea.
_	LED-LRSW-18-*	On/Off	12V	6A	72W	18" DC 5.5	18" DC 5.5	3/4" Nominal			Dossessed	\$2.97	\$2.67 ea.
C	LED-LK3W-10-"	On/On	24V	6A	144W	Female	Male	Diameter	-	-	Recessed	\$2.97	\$2.07 ea.
	LED-LRSW-24-*	On/Off	12V	6A	72W	24" DC 5.5	24" DC 5.5	3/4" Nominal			Dococcod	¢2.20	\$2.88 ea.
C	LED-LR3W-24-*	OH/OH	24V	6A	144W	Female	Male	Diameter	-	-	Recessed	\$3.20	\$2.00 ea.
	LED LDCW 26 *	0/0#	12V	6A	72W	36" DC 5.5	36" DC 5.5	3/4" Nominal			Daggard	ć2.cc	¢2.20
C	C LED-LRSW-36-*	On/Off	24V	6A	144W	Female	Male	Diameter	-	-	Recessed	\$3.66	\$3.29 ea.

Heat Shrink Tubing



- Material: Black Polyethylene (PE)
- Halogen-free retardant and environmentally friendly material- UL224
- 2:1 Shrink Ratio
- Operating Temperature Range:
 -65 F To +225 F (-55C to +125C)
- Other Colors Available, Please Inquire

Part #	Inside Diameter	Approximate Wire Gauge	Price Per Foot	Full Coil Length	Full Coil
HST-332-BK	3/32"	22-24AWG	\$0.06	1312'	\$62.00 ea.
HST-18-BK	1/8"	20-22AWG	\$0.08	1312'	\$84.00 ea.
HST-316-BK	3/16"	18-20AWG	\$0.11	1312'	\$114.00 ea.
HST-14-BK	1/4"	16-18AWG	\$0.16	656'	\$85.00 ea.
HST-932-BK	9/32"	14-16AWG	\$0.17	656'	\$88.00 ea.
HST-38-BK	3/8"	12-14AWG	\$0.21	656'	\$111.00 ea.
HST-12-BK	1/2"	10-12AWG	\$0.53	656'	\$139.00 ea.
HST-34-BK	3/4"	8-10AWG	\$0.60	656'	\$312.00 ea.

.

Mounting Clips with Screws







					riice
	Part #	Description	Material	Each	100+ Pcs.
Α	LED-3528-MC	5/16" IP20/IP65 Ribbon	Silicone	\$0.10	\$0.085 ea.
Α	LED-5050-MC	3/8" IP20/IP65 Ribbon	Silicone	\$0.10	\$0.085 ea.
В	LED-8MM-MC-IP20	5/16" IP20 Ribbon	Plastic	\$0.10	\$0.085 ea.
В	LED-10MM-MC-IP20	3/8" IP20 Ribbon	Plastic	\$0.10	\$0.085 ea.
В	LED-12MM-MC-IP20	1/2" IP20 Ribbon	Plastic	\$0.10	\$0.085 ea.
C	LED-8MM-MC-IP65	5/16" IP20 Ribbon	Plastic	\$0.10	\$0.085 ea.
C	LED-10MM-MC-IP65	3/8" IP20 Ribbon	Plastic	\$0.10	\$0.085 ea.

LED Controllers & Amplifiers

Standard RGB Controllers

Works With All Wall Mount & Desktop Power Supplies

A. 12V Small RGB Controller With Up To 20 Color Changing Functions

Controller Functions:

- Static: 16 Options
- Gradual Color Change: 2 Options
- · Color Jumping: 2 Options



Controller Functions:

- Flashing: 1 Options
- Gradual Color Change: 2 Options
- · Color Jumping: 2 Options





B. Super Small RGB Controller With Up To 20 Color Changing Functions

Controller Functions:

- Static: 20 Options
- Brightness Adjusting: 19 Options



D. Deluxe RGB Controller With Up To 25 Color Changing Functions

Controller Functions:

- Static: 7 Options
- Flashing: 10 Options
- Gradual Color Change: 2 Options
- Color Jumping: 2 Options



Remote Control



E. RGBW Controller For 4 in 1 Ribbon

Controller Functions:

- Static: 3 Options
- Flashing Strobe: 4 Options
- Gradient Change: 2 Options
- Brightness Adjusting: 8 Grades
- · Color Jumping: 5 Options



Controller Functions:

- Gradient Change: 11 Grades
- Brightness Adjusting: 20 Grades
- Fire Simulator
- 4 Zones



			iviax.	iviax.					nemote Contro			TICE
	Part #	Volts	Amps	Watts	Input Cord	Output Cord	Dimensions	Color	Function	Mounting	Each	6+ Pcs.
Α	LED-RGB12-CON	12V	6A	72W	DC 5.5 Female Port	5" Pin Connection	L: 1.87" x W: 1.37" x H: .87"	White	IR	Screw	\$7.95	\$7.00 ea.
В	LED-RGB36-INLINE	12V 24V	6A 6A	72W 144W	3.5" DC 5.5 Female	Pin Connection	L: 1.5" x W: .5" x H: .12"	White	RF	Inline	\$9.95	\$9.00 ea.
c	LED-RGB36-MIN	12V 24V	6A 6A	72W 144W	DC 5.5 Female Port	9.5" Pin Connection	L: 1.87" x W: 1.37" x H: .87"	White	RF	Screw	\$12.95	\$12.00 ea.
D	LED-RGB36-CRP	12V 24V	12A 12A	144W 288W	18" DC 5.5 Female	18" Pin Connection	L: 4.75" x W: 2" x H: 1"	Black	RF	Screw	\$29.95	\$25.00 ea.
E	LED-RGBW-CR	12V 24V	6A 6A	72W 144W	DC 5.5 Female Port	Screw Terminal	L: 3.62" x W: 1.75" x H: .87"	White	RF	Adhesive	\$29.95	\$25.00 ea.
F	LED-WRGBW-CR	12V 24V	6A 6A	72W 144W	DC 5.5 Female Port	Screw Terminal	L: 3.62" x W: 1.75" x H: .87"	White	RF	Adhesive	\$41.60	\$39.00 ea.

Amplifiers

Used to extend the signal of an RGB controller-power supply required





			Max.	Max.							Price
	Part #	Volts	Amps	Watts	Input Cord	Output Cord	Dimensions	Color	Mounting	Each	6+ Pcs.
^	LED-RIBBON-RGB-AMP	12V	12A	144W	18" Pin	18" Pin	L: 3.5" x	Cilven	C	¢14.60	\$12.78 ea.
A	LED-KIBBON-KGB-AMP	24V	12A	288W	Connection	Connection	W: 2.5" x H: .87"	Silver	Screw	\$14.60	\$12.78 ea.
	LED DCDMIN AMD	12V	12A	144W	Pin	Pin	L: 1.62" x	VA/I- :+ -	La Dia	¢0.00	ć7.20
В	LED-RGBMIN-AMP	24V	12A	288W	Connection	Connection	W: .5" x H: .12"	White	Inline	\$8.00	\$7.20 ea.

LED Bulbs

Center Stage LED Bulbs

Narrow Spot & Flood Options • Low Wattage & High Lumens





MR16 Bulbs (12V)



lighting facts

			# Of LED	Total		Price			inting :	spec	Incatio	ns	
Part #	Color Temp	Finish	Chips	Wattage	Each	25+ Pcs.	Color Temp	Beam Spread	Lumens	CRI	Average Life (Hrs)	Constant	Chip Size
LMR16-30-CW	Cool White		4 x 1.25W	5	\$7.75	\$7.35 ea.	6000K	30°	340	80	30,000	Voltage	SMD2835
LMR16-30-WW	Warm White	Satin	4 x 1.25W	5	\$7.75	\$7.35 ea.	2700K-3000K	30°	290	80	30,000	Voltage	SMD2835
LMR16-120-CW	Cool White	Aluminum	4 x 1.25W	5	\$7.75	\$7.35 ea.	6000K	120°	340	80	30,000	Voltage	SMD2835
LMR16-120-WW	Warm White		4 x 1.25W	5	\$7.75	\$7.35 ea.	2700K-3000K	120°	290	80	30,000	Voltage	SMD2835
LMR16-30WH-CW	Cool White		4 x 1.25W	5	\$7.75	\$7.35 ea.	6000K	120°	315	80	30,000	Voltage	SMD2835
LMR16-30WH-WW	Warm White	White	4 x 1.25W	5	\$7.75	\$7.35 ea.	2700K-3000K	120°	290	80	30,000	Voltage	SMD2835
LMR16-120WH-CW	Cool White	wille	4 x 1.25W	5	\$7.75	\$7.35 ea.	6000K	120°	315	80	30,000	Voltage	SMD2835
LMR16-120WH-WW	Warm White		4 x 1.25W	5	\$7.75	\$7.35 ea.	2700K-3000K	120°	290	80	30,000	Voltage	SMD2835







			# Of LED	Total	1	Price		Beam	jnung :	phed	Average	15	
Part #	Color Temp	Finish	Chips	Wattage	Each	25+ Pcs.	Color Temp	Spread	Lumens	CRI	Life (Hrs)	Constant	Chip Size
LMR16-80CB-CW	Cool White	Satin	1	5	\$9.95	\$9.00 ea.	5700K-6300K	80°	500	80	30,000	Voltage	18 x 33mm
LMR16-80CB-WW	Warm White	Aluminum	1	5	\$9.95	\$9.00 ea.	2700K-3500K	80°	450	80	30,000	Voltage	18 x 33mm





Dimmable GU10 Bulbs (120V)





			# Of LED	Total		Price			ghting :	Spec	cificatio	ns	
5								Beam			Average	_	
Part #	Color Temp	Finish	Chips	Wattage	Each	25+ Pcs.	Color Temp	Spread	Lumens	CRI	Life (Hrs)	Constant	Chip Size
LG10-40-NW	Natural White	White	5 x .9W	4.5	\$7.95	\$7.35 ea.	5000K	40°	370	80	25,000	Voltage	SMD2835
LG10-40-WW	Warm White	White	5 x .9W	4.5	\$7.95	\$7.35 ea.	2700K-3000K	40°	290	80	25,000	Voltage	SMD2835
LG10-120-CW	Cool White	Satin	4 x 1.25W	5	\$7.75	\$7.35 ea.	6000K	120°	340	80	30,000	Voltage	SMD2835
LG10-120-CW	Warm White	Aluminum	4 x 1.25W	5	\$7.75	\$7.35 ea.	2700K-3000K	120°	290	80	30,000	Voltage	SMD2835



Dimmable GU10 COB Bulbs (120V)



Capping 17			# Of LED	Total		Price			giitiiig .	she	illicatio	113	
								Beam			Average		
Part #	Color Temp	Finish	Chips	Wattage	Each	25+ Pcs.	Color Temp	Spread	Lumens	CRI	Life (Hrs)	Constant	Chip Size
LG10-35CB-CW	Cool White		1	5	\$9.95	\$9.00 ea.	5700K-6300K	35°	500	80	30,000	Voltage	18 x 33mm
LG10-35CB-WW	Warm White	Satin	1	5	\$9.95	\$9.00 ea.	2700K-3500K	35°	450	80	30,000	Voltage	18 x 33mm
LG10-80CB-CW	Cool White	Aluminum	1	5	\$9.95	\$9.00 ea.	5700K-6300K	80°	500	80	30,000	Voltage	18 x 33mm
LG10-80CB-WW	Warm White		1	5	\$9.95	\$9.00 ea.	2700K-3500K	80°	450	80	30,000	Voltage	18 x 33mm

LED Bulbs

Center Stage LED Bulbs

Narrow Spot & Flood Options • Low Wattage & High Lumens

PAR 38

LP38-120

Dimmable LED Par Bulb (120V): E26 Base



lighting facts







				# Of LED	Total	1	Price		Li C Beam	ghting S	Spec	ificatio	ns	
Part #	Color Temp	Finish	Type	Chips	Wattage	Each	12+ Pcs.	Color Temp	Spread	Lumens	CRI	Life (Hrs)	Constant	Chip Size
LP20-30-CW	Cool White			7	8	\$9.95	\$9.40 ea.	6000K-6800K	30°	550	80	30,000	Voltage	SMD2835
LP20-30-WW	Warm White		PAR 20	7	8	\$9.95	\$9.40 ea.	2700K-3200K	30°	475	80	30,000	Voltage	SMD2835
LP20-120-CW	Cool White		FAN 20	7	8	\$9.95	\$9.40 ea.	6000K-6800K	120°	520	80	30,000	Voltage	SMD2835
LP20-120-WW	Warm White			7	8	\$9.95	\$9.40 ea.	2700K-3200K	120°	430	80	30,000	Voltage	SMD2835
LP30-30-CW	Cool White			9	11	\$15.95	\$15.10 ea.	6000K-6800K	30°	807	80	30,000	Voltage	SMD2835
LP30-30-WW	Warm White	Satin	PAR 30	9	11	\$15.95	\$15.10 ea.	2700K-3200K	30°	786	80	30,000	Voltage	SMD2835
LP30-120-CW	Cool White	Aluminum	FAN 30	9	11	\$15.95	\$15.10 ea.	6000K-6800K	120°	700	80	30,000	Voltage	SMD2835
LP30-120-WW	Warm White			9	11	\$15.95	\$15.10 ea.	2700K-3200K	120°	690	80	30,000	Voltage	SMD2835
LP38-30-CW	Cool White			15	20	\$23.95	\$22.70 ea.	6000K-6800K	30°	1330	80	30,000	Voltage	SMD2835
LP38-30-WW	Warm White		PAR 38	15	20	\$23.95	\$22.70 ea.	2700K-3200K	30°	1120	80	30,000	Voltage	SMD2835
LP38-120-CW	Cool White		PAR 30	15	20	\$23.95	\$22.70 ea.	6000K-6800K	120°	1300	80	30,000	Voltage	SMD2835
LP38-120-WW	Warm White			15	20	\$23.95	\$22.70 ea.	2700K-3200K	120°	1200	80	30,000	Voltage	SMD2835







									—Liz	ahtina 9	Sna	ificatio	nc	
			Neck	# Of LED	Total		Price		Beam	jiiting .	ppe	Average	113	
Part #	Color Temp	Finish	Type	Chips	Wattage	Each	12+ Pcs.	Color Temp	Spread	Lumens	CRI	Life (Hrs)	Constant	Chip Size
LP20-38CB-CW	Cool White		PAR 20	1	6	\$16.95	\$16.00 ea.	5700K-6300K	38°	550	80	30,000	Voltage	18 x 33mm
LP20-38CB-WW	Warm White		PAR 20	1	6	\$16.95	\$16.00 ea.	2700K-3200K	38°	450	80	30,000	Voltage	18 x 33mm
LP30-38CB-CW	Cool White	Satin	PAR 30	1	10	\$31.35	\$29.75 ea.	5700K-6300K	38°	950	80	30,000	Voltage	18 x 33mm
LP30-38CB-WW	Warm White	Aluminum	PAR 30	1	10	\$31.35	\$29.75 ea.	2700K-3200K	38°	850	80	30,000	Voltage	18 x 33mm
LP38-80CB-CW	Cool White		PAR 38	1	16	\$39.95	\$37.95 ea.	5700K-6300K	80°	1600	80	30,000	Voltage	18 x 33mm
LP38-80CB-WW	Warm White		PAR 38	1	16	\$39.95	\$37.95 ea.	2700K-3200K	80°	1500	80	30,000	Voltage	18 x 33mm

IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES











LED Lighting

Horizon LED Ceiling Panels: Edge To Edge Uniform Lighting

Material: White Powder Coated Aluminum Frame with PMMA LGP & PS Diffuser

- The PMMA provides a 5-8 year life span without turning yellow. The PS diffuser offers a 90% light transmission.
- Save money on energy costs, due to low wattage consumption
- Save money on maintenance costs, as average rated life is 50,000 hours
- Easy to install- drop in, suspended install options or surface mount with included clips
- Instant on, no delay, no flickering of light or buzzing noise, as with fluorescent lamps, 90% power factor
- Ideal for commercial applications because no RF interference, no UV or IR radiation & mercury free!
- Includes dimmable power supply, 0-10V dimming
- 5 Year Manufacturer Warranty







DLC Standard 2' x 2' Ceiling Panel

(Up To **4600** Lumens Per Fixture: **115** Lumens Per Watt)



- Color Temp: PW- 4000K
- Total Wattage: 40W
- · Weight: Under 9 lbs.

LED-PAN-2X2

Each: \$40.00 6+ Pcs.: \$38.00 ea. 12+ Pcs.: \$34.00 ea.

Lighting Specifications

Color Temperature	PW: 4000K
Beam Spread	120°
Lumens	4600 115 Lumens Per Watt
Color Rendering Index	PW: >80
Rated Average Life	50,000 hrs.
Power Factor	≥ .90
THD	< 15%
Input Voltage	AC 100-277V

DLC Standard 2' x 4' Ceiling Panel

(Up To **5750** Lumens Per Fixture: **115** Lumens Per Watt)



- Color Temp: PW- 4000K
- Total Wattage: 50W
- · Weight: Under 18 lbs.

LED-PAN-2X4

Each: \$64.00 6+ Pcs.: \$61.00 ea. 12+ Pcs.: \$56.00 ea.

Lighting Specifications

Color Temperature	PW: 4000K
Beam Spread	120°
Lumens	5750 115 Lumens Per Watt
Color Rendering Index	PW: >80
Rated Average Life	50,000 hrs.
Power Factor	≥ .90
THD	< 15%
Input Voltage	AC 100-277V

PACKED 2 PER CARTON - \$10.00 BROKEN BOX FEE (#BB10)









WAC 120V LED Track Heads



OCULUX

The Oculux 7001 combines high output COB LED with easy-to-install films for three separate beam-spread, along with an adjustable base to accommodate a variety of user preferences. Ideal for residential spaces and lower-mounted commercial applications.

Material: Die-cast aluminum with baffled front cover for glare control

Lig	hting	Speci	ficat	ions
_				

Color Temperature	3000K
3 Beam Spread Options	50°, 30° & 17°
Lumens	890
Color Rendering Index	90+
Rated Average Life	50,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years



Part #	Finish	Total Wattage	Price
H-7011-930-BK	Black (BK)	11	\$56.70 ea.
H-7011-930-BN	Brushed Nickel (BN)	11	\$66.51 ea.
H-7011-930-WH	White (WH)	11	\$56.70 ea.
H-7011-930-DB	Dark Bronze (DB)	11	\$56.70 ea.



RADIANT

The Radiant low voltage track luminiare is designed in four finishes including an elegant Antique Bronze. The Radiant features a transitional look with a rich elegance that compliments many architectural styles, ideal for various spot lighting applications.

Material: Die-cast aluminum fixture with polycarbonate track adapter. Ceramic bi-pin socket.

Lighting Specifications

Color Temperature	3000K
Beam Spread Options	N/A
Lumens	490
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Chip Size	MR16 LED
Limited Warranty	5 Years



Part #	Finish	Total Wattage	Price
HHT-856LED-BK	Black (BK)	9	\$113.31 ea.
HHT-856LED-BN	Brushed Nickel (BN)	9	\$123.30 ea.
HHT-856LED-WH	White (WH)	9	\$113.31 ea.
HHT-856LED-AB	Antique Bronze (AB)	9	\$123.30 ea.



SILO X10

Silo offers superior light output in a small, sleek design. Engineered synthesis of driver, single point source LED, optical and thermal management in a slender die-cast housing. Ideal for residential, retail and lower mounting height commercial applications.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Ligh	iting 9	Specif	ications

Color Temperature	3000K
2 Beam Spread Options	35° & 25°
Lumens	790
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years

Lighting Specifications

3000K

90

50° & 15° 785

50.000 hrs.

COBLED

Color Temperature

Lumens

Chip Size

2 Beam Spread Options

Color Rendering Index

Rated Average Life

Limited Warranty



Part #	Finish	Total Wattage	Price	
H-2010-930-BK	Black (BK)	10	\$92.70 ea.	
H-2010-930-BN	Brushed Nickel (BN)	10	\$102.51 ea.	
H-2010-930-WH	White (WH)	10	\$92.70 ea.	
H-2010-930-DB	Dark Bronze (DB)	10	\$92.70 ea.	
H-2010-930-BR	Brushed Brass (BR)	10	\$102.51 ea.	



SILO X20

Silo offers superior light output in a small, sleek design. Engineered synthesis of driver, single point source LED, optical and thermal management in a slender die-cast housing. Ideal for residential, retail and lower mounting height commercial applications.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

3	P	4	
BN	WH	DB	BR

Part #	Finish	Total Wattage	Price
H-2020-930-BK	Black (BK)	20	\$149.31 ea.
H-2020-930-BN	Brushed Nickel (BN)	20	\$159.30 ea.
H-2020-930-WH	White (WH)	20	\$159.30 ea.
H-2020-930-DB	Dark Bronze (DB)	20	\$149.31 ea.
H-2020-930-BR	Brushed Brass (BR)	20	\$97.20 ea.







WAC 120V LED Track Heads



SUMMIT 201

Summit track luminaires offer driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LED's outperform halogen 50W MR16. Developed for upscale residential and commerical environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Lıg	htin	ıg S	p	eci	tıca	tio	ns
Color Te	mpe	ratu	re		300	0K	


Color Temperature	3000K
2 Beam Spread Options	40° & 15°
Lumens	750
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years

Lighting Specifications

2 Beam Spread Options 40° & 15°

3000K





Part #	Finish	Total Wattage	Price
H-LED201-30-BK	Black (BK)	15	\$94.50 ea.
H-LED201-30-WH	White (WH)	15	\$94.50 ea.



SUMMIT 202


Summit track luminaires offer driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LED's outperform halogen 50W MR16. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.



Color Temperature





Part #	Finish	Total Wattage	Price
H-LED202-30-BK	Black (BK)	15	\$94.50 ea.
H-LED202-30-WH	White (WH)	15	\$94.50 ea.



SUMMIT 207

Summit track luminaires offer driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LED's outperform halogen 50W MR16. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Color Temperature	3000K
2 Beam Spread Options	40° & 15°
Lumens	750
Color Rendering Index	90
Rated Average Life	50,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years

Lighting Specifications

2 Beam Spread Options 40° & 15°

3000K

750

50.000 hrs

COB LED

5 Years

90

Color Temperature

Color Rendering Index

Rated Average Life


Limited Warranty

Lumens

Chip Size

Lighting Specifications





Part #	Finish	Total Wattage	Price
H-LED207-30-BK	Black (BK)	15	\$94.50 ea.
H-LED207-30-WH	White (WH)	15	\$94.50 ea.



SUMMIT 208

Summit track luminaires offer driverless AC LED technology and easy change of beam angles in field. Superior light output in a small, unobtrusive design. The high output LED's outperform halogen 50W MR16. Developed for upscale residential and commerical environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

7" 2-5/8"
3-1/4" 4"

Part #	Finish	Total Wattage	Price
H-LED208-30-AB	Antique Bronze (AB)	15	\$113.31 ea.









WAC 120V LED Track Heads



EXTERMINATOR

Exterminator offers superior light output in a small, unobtrusive design. The high output LED's out perform a 20W metal halide fixture at the size of a typical MR16 luminaire. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Ligl	hting S	pecifications
_		

Color Temperature	3000K
Beam Spread	40°
Lumens	920
Color Rendering Index	90
Rated Average Life	60,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years





Part #	Finish	Total Wattage	Price
H-LED20F-930-BK	Black (BK)	23	\$197.91 ea.
H-LED20F-930-BN	Brushed Nickel (BN)	23	\$206.91 ea.
H-LED20F-930-WH	White (WH)	23	\$197.91 ea.



EXTERMINATOR II (14W)

Exterminator offers superior light output in a small, unobtrusive design. The high output LED's out perform a 20W metal halide fixture at the size of a typical MR16 luminaire. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Lighting Specifications

Color Temperature	3000K
Beam Spread	40°
Lumens	663
Color Rendering Index	90
Rated Average Life	100,000 hrs.
Chip Size	COB LED
Limited Warranty	5 Years





Part #	Finish	Total Wattage	Price
H-1014F-930-BK	Black (BK)	14	\$160.11 ea.
H-1014F-930-BN	Brushed Nickel (BN)	14	\$169.11 ea.
H-1014F-930-WH	White (WH)	14	\$160.11 ea.

5-5/16 3-7/8" -4-11/16"→ **-2-3/4"**+

EXTERMINATOR II (22W)

Exterminator offers superior light output in a small, unobtrusive design. The high output LED's out perform a 20W metal halide fixture at the size of a typical MR16 luminaire. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

Lig	hting	Spec	ificat	ions

3000K
40°
1535
90
50,000 hrs.
COB LED
5 Years

Lighting Specifications

3000K

55° 2185

90

60,000 hrs

COBLED

Color Temperature

Color Rendering Index

Rated Average Life

Limited Warranty

Beam Spread

Lumens

Chip Size





Part #	Finish	Total Wattage	Price
H-1023F-930-BK	Black (BK)	22	\$218.70 ea.
H-1023F-930-BN	Brushed Nickel (BN)	22	\$227.70 ea.
H-1023F-930-WH	White (WH)	22	\$218.70 ea.

BK -5-1/4"

EXTERMINATOR II (35W)

Exterminator offers superior light output in a small, unobtrusive design. The high output LED's out perform a 20W metal halide fixture at the size of a typical MR16 luminaire. Developed for upscale residential and commercial environments.

Material: Die-cast aluminum fixture with removable front cap for lenses or accessories.

	CI
BN	WH

Part #	Finish	Total Wattage	Price
H-1035F-930-BK	Black (BK)	35	\$292.50 ea.
H-1035F-930-BN	Brushed Nickel (BN)	35	\$301.50 ea.
H-1035F-930-WH	White (WH)	35	\$292.50 ea.







Accessories for WAC 120V LED Track Heads

This hardware is applicable to the line-volt track heads A power connector must be purchased separately from the track

Colors Available: Black (*BK), White (*WH), Dark Bronze (*DB) & Brushed Nickel (*BN)

1. Track & Power Connectors

Track

- 2 end caps supplied with each length.
- Can be installed on sheetrock, plaster, wood or suspended ceilings.
- Field cuttable

Part #	Finish	Length	Price
WL-HT6-*	*BK & *WH	6′	\$46.71 ea.
WL-HT6-*	*DB & *BN	6′	\$62.91 ea.
WL-HT8-*	*BK & *WH	8′	\$56.70 ea.
WL-HT8-*	*DB & *BN	8′	\$79.11 ea.

Floating Canopy

 Connects to outlet box allowing track to be powered anywhere along the length of the track.

ength of the track.		
Part #	Finish	Price
WL-HFC-*	*BK & *WH	\$17.91 ea.
WI-HFC-*	*DR & *RN	\$21.50 ea

Live End Connector

 Used for direct wiring from conduit through the ceiling.



Part #	Finish	Price
WL-HLE-*	*BK & *WH	\$11.70 ea.
WL-HLE-*	*DB & *BN	\$13.50 ea.

2. Track Joiners with Power Connectors

Straight Line Power Connector

 Used to supply power from the source at the junction of two tracks.



Part #	Finish	Price
WL-HI-PWR-*	*BK & *WH	\$17.10 ea.
WL-HI-PWR-*	*DB & *BN	\$18.90 ea.

Flexible Track Connector

 Connects two track sections at variable angles from 60° to 180°.

Part #	Finish	Price
WL-HFLX-*	*BK & *WH	\$25.11 ea.
WL-HFLX-*	*DB & *BN	\$28.71 ea.

"T" 3-Way Connector

 Used to join three track sections to make a "T" configuration.



Part #	Finish	Price
WL-HT-*	*BK & *WH	\$20.70 ea.
WL-HT-*	*DB & *BN	\$25.11 ea.

"L" Left/Right Angle Connector

 Used to join two track section to make a 90° angle.



Part #	Finish	Price
WL-HL-*	*BK & *WH	\$17.10 ea.
WL-HL-*	*DB & *BN	\$20.70 ea.

"X" 4-Way Connector

 Used to join four track sections to make a "X" configuration.



Part #	Finish	Price
WL-HX-*	*BK & *WH	\$25.11 ea.
WL-HX-*	*DB & *BN	\$29.70 ea.

15' Plug-In Power Cord

 Used with any power connector to wire a section of track as a portable unit.



Part #	Finish	Price
WL-HCORD-BK	Black	\$15.30 ea.
WL-HCORD-WH	White	\$15.30 ea.

3. Track Joiners w/o Power Connectors

Straight Line Connector

• Used to join two sections of track.

Part #	Finish	Price
WL-HI-*	*BK & *WH	\$11.70 ea.
WL-HI-*	*DB & *BN	\$13.50 ea.

1111111111

Dead End Straight Line Connector

• Used as connector where power is not to go through.

Part #	Finish	Price
WL-HI-DEC-*	*BK & *WH	\$9.90 ea.
WL-HI-DEC-*	*DB & *BN	\$11.70 ea.

4. Extended Track Heads & Suspension Kit

Extended Track Heads

• Extend drop of track heads.

Part #	Finish	Price	
WL-H18-*	*BK & *WH	\$30.51 ea.	
WL-H18-*	*DB & *BN	\$34.11 ea.	
WL-H36-*	*BK & *WH	\$35.91 ea.	
WL-H36-*	*DB & *BN	\$39.51 ea.	

Suspension Kit

 Supports the weight of the track. Parts & instructions included.




Part #	Finish	Lengtn	Price
WL-SK18-*	*BK & *WH	18"	\$28.71 ea.
WL-SK18-*	*DB & *BN	18"	\$32.31 ea.
WL-SK24-*	*BK & *WH	24"	\$30.51 ea.
WL-SK24-*	*DB & *BN	24"	\$34.11 ea.
WL-SK36-*	*BK & *WH	36"	\$34.11 ea.
WL-SK36-*	*DB & *BN	36"	\$37.71 ea.
WL-SK48-*	*BK & *WH	48"	\$37.71 ea.
WL-SK48-*	*DB & *BN	48"	\$41.31 ea.


Power Station

PDS-NL-300









we've got the POWER!!!



Housing & Receptacles:

- Material: ABS
- · Color/Finish: Black
- Recommended material thickness: 3/4" to 3"
- · Each outlet faces a different direction minimizing issues caused by oversized plugs
- · Unit locks in its upper most position
- 12" clearance under mounting surface required
- 3 year warranty





Waterpr	oof Ring

	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDS-LE-220-BK	2	AC 125V/12A Max	2	2.1A Shared	\$39.00	\$36.00 ea.
PDS-NL-300-BK	3	AC 125V/12A Max	0	n/a	\$38.00	\$35.00 ea.

Vertical Mount Power Dock • 120V

PDS-MO-300-BK





	l I	Plug	P	rice
Part #	Receptacles Rating		Each	10 +
PDS-MO-300-BK	3	15A/125V/AC	\$102.22	\$92.93 ea.
			•	

Housing:

• Material: Aluminum

- Receptacles: • Material: ABS & Polycarbonate
- · Color/Finish: Black
- Recommended material thickness: 5/16" to 1-3/4"
- · Reset Switch, Rated A 15A

· Color/Finish: Anodized

- LED Power Switch
- · For use in kitchen, plug into a GFCI outlet
- · Surge protection & Reset button
- · Locking ring holds unit firmly in place from underneath
- Unit locks in its upper most position
- Standard splash proof, water resistant seal when in recessed position
- · 12" Clearance under mounting surface required
- · 100% guarantee on normal wear and tear



PDS-CA-420-BK

we've got the **POWER!!!**






Housing & Receptacles:

- Material: Flame Retardant ABS
- Color/Finish: Black
- Recommended material thickness: up to 1-1/2"
- Surge protection
- 1 year warranty



	Flip-Up Pull Ring
0 =-	Outlet Folds Over
	Grommet Lowers Into Hole
THE RESERVE	Surge Protection Light
	Reset Button



2.86"

	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	12+
PDS-CA-420-BK	4	12A, 125V, 50/60HZ	2	5V/2.1A Max Total	\$82.35	\$71.60 ea.

PDD-HC-240-BK






Housing & Receptacles:

- Material: ABS
- · Color/Finish: Black
- Recommended material thickness: 5/8" to 1"
- Two high speed ethernet jacks & two RJ11 phone jacks
- · Supports Windows 98, 2000, ME, XP & Mac OSX
- Can support up to 4 high speed downstream devices up to 480 bps
- · Circuit breaker & surge protection
- Two 2.0A USB smart phone charging ports 1 primary, 1 secondary
- 1 year warranty

	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	12+
PDD-HC-240-BK	2	10A, 1250V Max	4	2.0A Each	\$59.95	\$56.95 ea.

Power Dome



Housing & Receptacles:





- Material: Polycarbonate
- · Color/Finish: Black
- Recommended material thickness: 1/2" to 1-3/4"
- Available in White, Green & Orange, please inquire.
- 1 year warranty



	Plug		Plug USB		l	Price
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDG-BEH-220-BK	2	15A	2	2A Shared	\$136.20	\$129.64 ea.

Includes 3

Power Hubs

Power Pyramid

we've got the POWER!!!






- Material: Polycarbonate
- Color/Finish: Black
- Recommended material thickness: 1/4" to 1-1/4"
- · Available in Gloss White, please inquire.

• Material: Polycarbonate

• Color/Finish: Gloss Black

- Optional surge protection available, please inquire.
- 1 year warranty

Housing:



	Plug	J		USB	Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDD-BEM-240-BK	2	15A	4	2A Shared per Module	\$207.92	\$197.90 ea.

Power Bar



Housing:


• Material: Polycarbonate

- Color/Finish: Gloss Black
- Color/Finish: Black

Receptacles:

• Material: Polycarbonate

- Recommended material thickness: 1/4" to 1-1/2"
- · Available in Gloss White, please inquire.
- Optional surge protection available, please inquire.
- 1 year warranty



	Plug	J		USB	Price		
Part #	Receptacles	Rating	Ports Rating		Each	10 +	
PDD-BEB-240-BK	2	15A	4	2A Shared per Module	\$231.65	\$228.75 ea.	

New

Power Center Grommets • 120V

we've got the **POWER!!!**

Power Hubs









Housing & Receptacles:


- Material: ABS
- Color/Finish: Black
- Recess Mounts in an 80mm (3-1/8") Dia. Hole
- Recommended material thickness: 3/4" to 3"
- 1 year warranty

PDG-FE-200










	Plug		USB		Price	
Part #	Receptacles	Receptacles Rating		Rating	Each	10+
PDG-FE-200-BK	2	AC120V/10A	0	-	\$12.26	\$11.23 ea.


PDG-FE-120






PDG-FE-040







Bore Hole Dia. 31/8"
Two 3 ft. USB Cables with Detachable Charging USB Adaptors

 Part #
 Plug
 USB
 Price

 Receptacles
 Rating
 Ports
 Rating
 Each
 10 +

 PDG-FE-040-BK
 0
 4
 0.5A each
 \$27.41
 \$25.16 ea.

Power Cable

with 3 Prong Grounded

120V Plug

PDG-NL-120-BK







	Plu	Plug USB			Price		
Part #	Receptacles	Rating	Ports	Rating	Each	10+	
PDG-NL-200-BK	2	125V, 15A	-	-	\$67.64	\$60.88 ea.	
PDG-NL-120-BK	1	125V. 15A	2	4.2A Shared	\$102.84	\$92.56 ea.	


we've got the **POWER!!!**

Housing & Receptacles:

• Recommended material thickness: 3/4" to 2"




- Material: ABS
 - · Waterial. ADS
- Color/Finish: Black
- Flip top lid/ABS plastic
- Surge protection
- 3 year warranty




Power Rotate






Housing & Receptacles:







- Rotates to hide away
- Available in White, Green & Orange, please inquire.
- 1 year warranty



	Plug			n2R	Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDG-BEE-300-BK	3	15A	-	-	\$150.38	\$148.50 ea.
PDG-BEE-220-BK	2	15A	2	2A Shared	\$178.11	\$175.89 ea.

we've got the **POWER!!!**

Overall Size

2-1/16" 1-3/4

Power Distribution Center

PDC-BY-320-BK



Housing & Receptacles:

- Material: ABS
- Color/Finish: Black
- Recommended material thickness: 1-1/2"
- 1 year warranty






	Plug		USB	Price		
Part #	Receptacles Rating		Ports	Rating	Each	10 +
PDC-BY-320-BK	3	125V/60HZ/12A	2	2.1A Shared	\$26.04	\$23.44 ea.

Horizontal Power Docks







		P	lug	Price			
	Part #	Receptacles	Rating	Each	Each 10+		
PDC	C-MO-300-BK	3	15A/125VAC	\$126.88	\$117.39 ea.		


Housing:

• Material: Aluminum

- Color/Finish: Matte Black
- Material: ABS

Receptacles:

- Color/Finish: Black
- Recommended material thickness: 5/8" to 2-3/8"
- Can be locked into position at 45° or 60° to allow easy access
- Cover can be closed with cords in place, concealed by a flexible strip
- 2 Category 5E data modules (Note: Data modules are un-wired)
- · 100% guarantee on normal wear and tear
- · Clear Anodized housing available, please inquire




we've got the POWER!!!

PDC-NL-120 Housing: • Material: Aluminum

Receptacles:

- Material: ABS Plastic
- Color/Finish: Black, Satin Aluminum Color/Finish: Black
- Recommended material thickness: 3/4" to 3"
- Pop-up spring loaded
- Optional surge protection available, please inquire.
- 3 year warranty




	Housing	Plug		USB		Price	
Part #	Color	Receptacles	Rating	Ports	Rating	Each	10 +
PDC-NL-120-BK	Black	1	125V, 12A	2	4.2A Shared	\$140.72	\$126.64 ea.
PDC-NL-120-SA	Satin Aluminum	1	125V, 12A	2	4.2A Shared	\$140.72	\$126.64 ea.

PDC-NL-200



	Housing	Plug		USB		Price	
Part #	Color	Receptacles	Rating	Ports	Rating	Each	10 +
PDC-NL-200-BK	Black	2	125V, 12A	-	-	\$100.12	\$90.11 ea.
PDC-NL-200-SA	Satin Aluminum	2	125V, 12A	-	-	\$100.12	\$90.11 ea.

PDC-NL-220



	Housing	Plug			USB	Price	
Part #	Color	Receptacles	Rating	Ports	Rating	Each	10 +
PDC-NL-220-BK	Black	2	125V, 12A	2	4.2A Shared	\$156.96	\$141.26 ea.
PDC-NL-220-SA	Satin Aluminum	2	125V, 12A	2	4.2A Shared	\$156.96	\$141.26 ea.

we've got the **POWER!!!**

Power Hubs



PDC-BT-320-SA-M




Housing: Receptacles:

- Material: Anodized Aluminum
- Color/Finish: Silver/Aluminum
- Material: ABS Plastic
 Color/Finish: Black
- Recommended material thickness: 3/4" to 2-1/4"
- 1 year warranty




Buttons to Show/Hide Outlet

• Motorized rotation, Dual IC protection, Photoelectric detection



	Plug	9		USB	Price	
Part #	Receptacles	Rating	Ports Rating		Each	5+
PDC-BT-320-SA-M	3	110V	2	5V 2.5A Each	\$213.92	\$203.17 ea.

PDC-BT-320-SA



	Plug	Plug USB Prid		USB		Price
Part #	Receptacles	Rating	Ports	Rating	Each	5 +
PDC-BT-320-SA	3	110V	2	5V 2.5A Each	\$138.68	\$131.68 ea.

IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES

Power Hubs

PDG-BY-020-BK

we've got the **POWER!!!**


Housing:

• Color/Finish: Black





- Recommended material thickness: Up to 3"
- 1 year warranty



5 ft. Cord	2 Prong Plug In	2" Dia. 1-1/2"
		Poro Holo

	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDG-BY-020-BK	0	-	2	2@2.1A Each	\$16.22	\$14.59 ea.

PDC-BY-120-*

Housing:

Receptacles:




- Material: Flame Retardant ABS
- Color/Finish: Brushed Chrome Color/Finish: Black & Black

• Material: Aluminum / ABS

- Recommended material thickness: Up to 1-1/2"
- 1 year warranty







	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10 +
PDC-BY-120-BCHR	1	120V, 12A	2	2.1A Shared	\$19.53	\$17.58 ea.
PDC-BY-120-BK	1	120V, 12A	2	2.1A Shared	\$16.25	\$14.30 ea.


we've got the **POWER!!!**

PDC-BY-220-BK






Housing & Receptacles:



- · Color/Finish: Black
- Recommended material thickness: Up to 1-1/2"
- 1 year warranty




	Plug		USB		Price		
Part #	Receptacles	Rating	Ports	Rating	Each	10+	
PDC-BY-220-BK	2	120V, 12A	2	2.1A Shared	\$20.62	\$18.55 ea.	

PDC-BY-320-BKS







• Color/Finish: Black

• Recommended material thickness: Up to 1-1/2"

- · Reset On/Off Switch
- 1 year warranty



	Plug		USB		Price	
Part #	Receptacles	Rating	Ports	Rating	Each	10+
PDC-BY-320-BKS	3	120V, 12A	2	2.1A Shared	\$27.12	\$24.41 ea.

QI Chargers

we've got the **POWER!!!**

Works With All Glass Back Cell Phones • Overcharge Protection: Phone will not continue to charge once at 100%

WCD-NL-150-BK (Wireless Charging












- Material: Polycarbonate
- Color/Finish: Black
- Pop up with USB ports for charging
- Recommended material thickness: 2-1/8"
- 1 year warranty



	Pli	ug	USB		Price	
Part #	Output	Rating	Ports	Ports Rating		6+
WDC-NL-150-BK	5W	5V/5A	3	1@2.4A Each 2@1A Each	\$63.64	\$58.33 ea.

WCD-NL-950-BK & WCD-NL-951-BK (Wireless Charging)














- Material: Polycarbonate
- · Color/Finish: Black
- Recommended material thickness: 1-1/16"
- 1 year warranty







	Plug		USB		Price	
Part #	Output	Rating	Ports	Rating	Each	6+
WCD-NL-950-BK	5W	5V/2A	-	-	\$42.54	\$38.99 ea.
WCD-NL-951-BK	10W	9V/1.67A	-	-	\$48.33	\$44.30 ea.

QI Chargers

we've got the **POWER!!!**

USB

Rating

Each

\$54.57

6+

\$50.02 ea.

Ports

Works With All Glass Back Cell Phones • Overcharge Protection: Phone will not continue to charge once at 100%

WCD-NL-900-BK (Wireless Charging) Housing: Material: Polycarbonate Color/Finish: Black Can be installed on top or under desk Recommended material thickness: 1/8" 1 year warranty Decal Not Included Mounting Hardware Included

Output

5W

Rating

12V/1A

Part #

WCD-NL-900-BK



IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES

Angled Power Strips (120V)





By eliminating wall cutouts, show off your backsplash or showcase without the interruption of obtrusive outlets and extension cords!








available





It is recommended that all electrical products be installed by a licensed electrician.

36"

APT-36-*

\$203.36

\$193.19 ea.


be done in the field.


IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES



Angled Power Strips (120V)

By eliminating wall cutouts, show off your backsplash or showcase without the interruption of obtrusive outlets and extension cords!





It is recommended that all electrical products be installed by a licensed electrician.



$\underset{\text{by Outwater}}{\mathbf{O}} \mathbf{R} \mathbf{A} \mathbf{C}^*$







CX189 | CX189F (flexible)

H<u>₹</u>/F

Duropolymer®
H: 1" | 2,7cm
P: 1" | 2,7cm
F: 1-3/8" | 3,5cm
L: 6'6" | 200cm
Designed By
Orio Tonini

CX190 | CX190F (flexible)



Duropolymer® H: 3/4" | 2cm P: 1-1/8" | 3cm L: 6'6" | 200cm Designed By Orio Tonini

C361




Purotouch® H: 2" | 5cm

P: 2" | 5cm F: 2-3/4" | 7cm L: 6'6" | 200cm Designed By Pierre Daems

Indirect Lighting







CX188 | CX188F (flexible)



Duropolymer® H: 1-3/8" | 3,4cm P: 1-1/8" | 3cm F: 1-1/2" | 3,9cm L: 6'6" | 200cm Designed By Orio Tonini

CX190 | CX190F (flexible)



Duropolymer®
H: 3/4" | 2cm
P: 1-1/8" | 3cm
L: 6'6" | 200cm

Designed By
Orio Tonini

C362



Purotouch®
H: 2" | 5cm
P: 2" | 5cm
F: 2-3/4" | 7cm
L: 6'6" | 200cm

Designed By
Pierre Daems





CX190 | CX190F (flexible)



Duropolymer® H: 3/4" | 2cm P: 1-1/8" | 3cm L: 6'6" | 200cm Designed By Orio Tonini

C380



Purotouch®
H: 2" | 5cm
P: 2" | 5cm
F: 2-1/2" | 6,4cm
L: 6'6" | 200cm
Designed By
Orio Tonini

Purotouch® a proprietary polymer blend formulated to create deep reliefs and crisp details.




Duropolymer® high impact resin blend. Ideally suited for baseboards and chair rails.

Indirect Lighting











C394

Purotouch® H: 3-3/4" | 9,5cm P: 1-1/4" | 3,1cm F: 3-3/4" | 9,6cm L: 6'6" | 200cm Designed By Orio Tonini

SX179 | SX179F (flexible)




Duropolymer® H: 3-7/8" | 9,7cm P: 1-1/8" | 2,9cm F: 3-7/8" | 9,8cm L: 6'6" | 200cm Designed By Orio Tonini



Purotouch® H: 2-3/8" | 6cm P: 3-7/8" | 10cm F: 4-1/8" | 10,5cm L: 6'6" | 200cm Designed By Orio Tonini







C381



Purotouch® H: 3-3/4" | 9,5cm P: 2" | 5cm F: 3-3/4" | 9,5cm L: 6'6" | 200cm Designed By Orio Tonini

SX179 | SX179F (flexible)



Duropolymer® H: 3-7/8" | 9,7cm P: 1-1/8" | 2,9cm F: 3-7/8" | 9,8cm L: 6'6" | 200cm Designed By Orio Tonini

C357



Purotouch® H: 2-3/4" | 7,1cm P: 4-3/8" | 11cm F: 5" | 12,6cm L: 6'6" | 200cm Designed By Jacques Vergracht





C373 | FC373 (flexible)



Purotouch® H: 3-1/8" | 8cm P: 2" 5cm F: 3-3/4" | 9,5cm L: 6'6" | 200cm Designed By Ulf Moritz

2x SX179 | SX179F (flexible)



Duropolymer® H: 3-7/8" | 9,7cm P: 1-1/8" | 2,9cm F: 3-7/8" | 9,8cm L: 6'6" | 200cm Designed By Orio Tonini

Purotouch® a proprietary polymer blend formulated to create deep reliefs and crisp details.



Duropolymer® high impact resin blend. Ideally suited for baseboards and chair rails.

ORAC* by Outwater

Indirect Lighting









C382



Purotouch® H: 5-1/2" | 14cm P: 2" | 5cm F: 5" | 12,7cm L: 6'6" | 200cm Designed By Orio Tonini

C902




Purotouch® H: 4" | 10,3cm P: 4" | 10,3cm F: 5-5/8" | 14,2cm L: 6'6" | 200cm



Purotouch® H: 6-1/8" | 15,5cm P: 1-1/4" | 3,1cm F: 6-1/8" | 15,6cm L: 6'6" | 200cm Designed By Orio Tonini







C383



Purotouch® H: 5-1/2" | 14cm P: 2" | 5cm F: 5" | 12,8cm L: 6'6" | 200cm Designed By Orio Tonini

C391




Purotouch® H: 2-3/8" | 6cm P: 6-1/4" | 16cm F: 5-7/8" | 14,8cm L: 6'6" | 200cm Designed By Orio Tonini



Purotouch® H: 4-3/8" | 11cm P: 5-1/2" | 14cm F: 7" | 17,8cm L: 6'6" | 200cm Designed By Ulf Moritz





C364



H: 5-1/2" | 14cm P: 3-1/8" | 8cm F: 5-5/8" | 14,2cm L: 6'6" | 200cm Designed By Pierre Daems Red Dot Design Award 2014

Purotouch®

C358



Purotouch®

H: 2-7/8" | 7,3cm P: 5-1/2" | 14cm F: 6" | 15,3cm L: 6'6" | 200cm Designed By Jacques Vergracht

Purotouch® a proprietary polymer blend formulated to create deep reliefs and crisp details.




Duropolymer® high impact resin blend. Ideally suited for baseboards and chair rails.

Indirect Lighting











Purotouch® H: 3" | 7,6cm P: 6-3/4" | 17,1cm F: 7-1/8" | 18,1cm L: 6'6" | 200cm Designed By Jacques Vergracht



Purotouch® H: 2-7/8" | 7,4cm P: 6-3/4" | 17,3cm F: 7-1/2" | 19cm L: 6'6" | 200cm Designed By Jacques Vergracht



Purotouch® H: 6-3/4" | 17,1cm

P: 5-3/4" | 14,6cm F: 8-5/8" 21,8cm L: 6'6" | 200cm







C374 | FC374 (flexible)



Purotouch® H: 7-1/8" | 18cm P: 2" | 5cm F: 7-3/8" | 18,6cm L: 6'6" | 200cm Designed By Ulf Moritz

C371





Purotouch® H: 7-1/4" | 18,5cm P: 2-1/4" | 5,8cm F: 7-1/2" | 19cm L: 6'6" | 200cm



Purotouch® H: 11" | 28cm P: 2-3/4" | 7cm F: 11-1/8" | 28,4cm L: 6'6" | 200cm Designed By Ulf Moritz







C396



Purotouch® H: 7-1/4" | 18,5cm P: 2-3/8" | 6,1cm F: 7-1/2" | 19,1cm L: 6'6" | 200cm Designed By Orio Tonini

C901



Purotouch® H: 5-7/8" | 14,8cm P: 4-7/8" | 12,4cm F: 7-1/2" | 19,2cm L: 6'6" | 200cm

TFM-49-A (Trim-Fast)



(2) 1/2" permanent adhesive strips on the bottom back of the moulding.

Purotouch® a proprietary polymer blend formulated to create deep reliefs and crisp details.



Duropolymer® high impact resin blend. Ideally suited for baseboards and chair rails.

IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES

TERMS AND CONDITIONS

"Vendor":

Outwater Plastics Industries, Inc. & Architectural Products by Outwater, LLC

PRICES:

All prices are subject to change without notice. No deduction will be allowed at settlement. Minimum order is \$25.00 (Merchandise only). Orders less than this minimum will be billed as \$25.00 plus shipping charges and tax, if applicable.

NOTE:

Orders are accepted with the understanding that they will be billed at the price in effect on the day of shipment.

PAYMENT TERMS:

N30

To establish N30 terms, we must be supplied with your company's Dun & Bradstreet number (DUNS Number). Concerns not rated favorably with Dun & Bradstreet, not rated at all with Dun & Bradstreet or inactive accounts, are required to furnish, on company letterhead, four (4) trade references, the name of their bank and account number, their Federal LD. number or CRA-issued business number, and the date and state/province their business was incorporated.

Please note: If supplying trade references, please allow 2-3 weeks for processing.

Credit Card

We accept major credit cards (Visa, MasterCard, American Express and Discover.) Please note: When authorizing us to charge your card in an amount over \$500.00, we require a signed credit card authorization form, which we will fax or email to you for your signature. Order processing will not begin until this authorization is returned to us.

COD.

C.O.D. orders are no longer accepted.

Prepayment

Customers not wishing to use a credit card or set up N30 terms, may prepay orders. Please speak with your sales representative when placing your order. We accept company checks and certified / bank checks. Order processing will not begin until we receive payment. Non-certified checks (company or personal) may take an additional five business days after receipt before order processing will begin.

Other Terms

Large orders, Custom or Special Order items may require certified funds and/or a deposit, regardless of existing credit terms. If applicable, this will be discussed at time of order. If a deposit is required, order processing will not begin until deposit is received by us. Should deposit be sent in the form of a non-certified check, it may take an additional five business days after receipt before order processing will begin.

WARRANTY:

All merchandise is produced to standard and commercial tolerances. Vendor warrants product to be free from defects in workmanship and material. When Vendor has determined that a product is defective, it will be replaced. At Vendor's discretion, a credit may be offered instead of replacement. Vendor liability is limited to the cost of the defective product. No other warranty is expressed or implied.

LIABILITY:

The customer shall test and verify the suitability of the product for intended use. No warranty for intended use is made. The customer assumes all risk and liability. Vendor's only obligation is replacement or credit for product proven defective. Vendor shall not be liable for any loss or damage from the use or inability to use the product.

TECHNICAL ADVICE:

Any technical advice furnished or recommended by Vendor or any representative of Vendor concerning any use or application of any product is believed to be reliable but the company makes no warranty of results obtained. The customer shall test for and verify suitability for intended use.

FREE SAMPLE POLICY:

Reasonable sample quantities are available at no charge for many of the products within this catalog; to test their suitability for your intended use or application. Most samples are shipped free of charge via standard U.S. mail or UPS ground. Other shipping options are available, at customer's expense. Please discuss with our sales representatives.

MERCHANDISE RETURN POLICY:

Merchandise may not be returned for credit without prior authorization from our Customer Service department. Please have your order number available when contacting us.

- You may return most items purchased for a partial refund within 30 days of purchase.
 A restocking fee will apply and shipping charges will not be refunded. Restocking fees as follows:
 - 20% restocking fee applies to most stock items. Some dropship items will be subject to a higher restocking fee. Where applicable, fees are stated within our catalog.
 - 40% restocking fee applies on items that have been cut for shipping purposes.
 Custom or Special order items may not be returned.
- · Refund will only be issued in the original form of payment.
- Customer is responsible for the shipping cost of items returned. Be mindful of packaging as any damage during return shipment is the responsibility of the customer.
- Returned material must be received in original condition.
- Any products cut, altered, modified or installed by the customer may not be returned.
- We reserve the right to refuse unauthorized returns. Unauthorized returns will be returned to the customer at their expense.

DAMAGE/LOSS:

- Upon receiving your shipment, please inspect the packages carefully for signs of damage. Check contents for damaged or missing items.
- Damage and/or loss claims <u>must</u> be reported within 48 hours from time of receipt!
- We utilize small parcel carriers [UPS and Federal Express] and many LTL freight carriers [such as YRC, New Penn and UPS Freight] when shipping our products. Specific instructions will vary depending on the carrier.
- If Damage/Loss is suspected, please do the following:
 - Inspect your shipment as soon as it arrives.
 - If your merchandise has arrived via LTL freight carrier, all damages/loss must be notated on the delivery receipt at time of delivery. Please take digital photographs and email to: customerservice@outwaterplastics.com.
 - Please keep all merchandise and packing material for possible inspection by the
 - Contact our Customer Service Department immediately! It is best to get in touch with us right away. Be advised that claims made after 48 hours of receipt will not be honored.

DEFECTIVE MERCHANDISE POLICY:

Every item that we sell meets our highest standards for quality and performance. If a defect in merchandise is suspected, please proceed as follows:

- Inspect merchandise for quality before altered or installed.
- Upon the finding of parts which may be defective, contact our Customer Service
 Department immediately! We will request digital images, a sample of the material,
 or a combination of both material and images to be sent to our Customer Service
 Department for evaluation.
- Upon review of the samples/images we will determine if replacement or refund is appropriate. Return of the defective merchandise will also be determined at this time and if deemed necessary an RMA (Return Merchandise Authorization) will be issued.
- The responsibility of Outwater Plastics and Architectural Products ends here.
 Any loss incurred for labor, transportation or any other expenses are not covered.

PICK UP ORDERS:

Orders placed for pick up must be picked up within 2 weeks from the date placed, or the date material becomes available. Orders not picked up within 2 weeks will be cancelled. To secure material for a longer time period; arrangements may be made for non-refundable prepayment and pick up by a specified date.

SHIPPING TERMS:

Shipments are F.O.B. shipping point.

SHIPPING TERMS IN CANADA:

- All transport (shipping) fees are F.O.B. shipping point.
- Brokerage Fees (Entry, Duties and GST):
- Will be paid by shipper for shipments that meet all of the following conditions:
- (1) shipment departs from our Bogota, NJ warehouse,
- (2) shipment is transported via UPS Ground Service and (3) shipping fees are pre-paid and added to the order total.
- Are the responsibility of the purchaser for all shipments that have any one of the following conditions:
- (1) shipment departs from a warehouse location other than Bogota, NJ,
- (2) shipment is being transported by a carrier other than UPS,
- (3) shipment is being transported through a UPS service level other than Ground or

*** WE RESERVE THE RIGHT TO SUBSTITUTE OR "EQUAL" ***

(4) shipping fees are not being pre-paid and added to the order total.

 EAST COAST
 2 LOCATIONS

 24 River Road

 • Bogota, NJ 07603
 (800) 631-8375
 4720 West Van Buren
 • Phoenix, AZ 85043

IMPORTANT: Due to Raw Material Fluctuation, Catalog Prices Below May Not Be Accurate. GO TO WWW.OUTWATER.COM FOR THE MOST UP-TO-DATE PRICES

Outwater Plastics Industries, Inc. 24 River Road P.O. Box 500 Bogota, NJ 07603-0500

Catalog Code 030

We encourage you to explore our new website, which makes shopping at Outwater easier than ever before. Online you can access videos, product details and installation guides, download specialty catalogs, and create an account.

When you become a registered user take advantage of these benefits:

- · Track orders
- · View purchase history
- · Manage payment methods
- · Save items and create wish lists
- · Get quotes
- · Set up multiple users under one company account





Join our mailing list to receive exclusive offers, free passes to trade shows, and information about exciting new products!



Outwater stocks all products in our east and west coast warehouse facilities to provide customers with fast, cost-effective shipping. Please call our sales department to request free samples.

1-800-631-8375