

AP[®] Physics C: Electricity and Magnetism 2004 Free-Response Questions

The materials included in these files are intended for noncommercial use by AP teachers for course and exam preparation; permission for any other use must be sought from the Advanced Placement Program[®]. Teachers may reproduce them, in whole or in part, in limited quantities, for face-to-face teaching purposes but may not mass distribute the materials, electronically or otherwise. This permission does not apply to any third-party copyrights contained herein. These materials and any copies made of them may not be resold, and the copyright notices must be retained as they appear here.

The College Board is a not-for-profit membership association whose mission is to connect students to college success and opportunity. Founded in 1900, the association is composed of more than 4,500 schools, colleges, universities, and other educational organizations. Each year, the College Board serves over three million students and their parents, 23,000 high schools, and 3,500 colleges through major programs and services in college admissions, guidance, assessment, financial aid, enrollment, and teaching and learning. Among its best-known programs are the SAT[®], the PSAT/NMSOT[®], and the Advanced Placement Program[®] (AP[®]). The College Board is committed to the principles of excellence and equity, and that commitment is embodied in all of its programs, services, activities, and concerns.

For further information, visit www.collegeboard.com

Copyright © 2004 College Entrance Examination Board. All rights reserved. College Board, Advanced Placement Program, AP, AP Central, AP Vertical Teams, APCD, Pacesetter, Pre-AP, SAT, Student Search Service, and the acom logo are registered trademarks of the College Entrance Examination Board. PSAT/NMSOT is a registered trademark jointly owned by the College Entrance Examination Board and the National Merit Scholarship Corporation. Educational Testing Service and ETS are registered trademarks of Educational Testing Service. Other products and services may be trademarks of their respective owners.

For the College Board's online home for AP professionals, visit AP Central at apcentral.collegeboard.com.

CONSTANTS AND CONVERSION FACTORS		UNITS		PREFIXES			
1 unified etemic mass unit	$1 \mu = 1.66 \times 10^{-27} \text{ kg}$	<u>Name</u>	<u>Symbol</u>	Factor	Prefi	<u>x Sym</u>	lbol
I unified atomic mass unit,	$10^{-1.00} \times 10^{-10}$ kg	meter	m	10 ⁹	giga	G	
	= 931 MeV/c	kilogram	kg	10 ⁶	mega	u M	
Proton mass,	$m_p = 1.67 \times 10^{-27}$ kg	second	s	10^{3}	kilo	k	
Neutron mass,	$m_n = 1.67 \times 10^{-5} \text{ kg}$			10-2	inite 	K	
Electron mass,	$m_e = 9.11 \times 10^{-31} \text{ kg}$	ampere	А	10 -2	centi	с	
Magnitude of the electron charge,	$e = 1.60 \times 10^{-19} \mathrm{C}$	kelvin	Κ	10^{-3}	milli	m	
Avogadro's number,	$N_0 = 6.02 \times 10^{23} \mathrm{mol}^{-1}$	mole	mol	10^{-6}	micro	ο μ	
Universal gas constant,	$R = 8.31 \text{ J/(mol} \cdot \text{K})$	hertz	Нт	10^{-9}	nano	n	
Boltzmann's constant,	$k_B = 1.38 \times 10^{-23} \mathrm{J/K}$	nowton	N	10-12			
Speed of light,	$c = 3.00 \times 10^8 \text{ m/s}$	newton	IN D	10	pico	р	
Planck's constant,	$h = 6.63 \times 10^{-34} \mathrm{J} \cdot \mathrm{s}$	pascal	Ра	VALUES OF TRIGONOMETRIC		TRIC	
	$= 4.14 \times 10^{-15} \mathrm{eV} \cdot \mathrm{s}$	joule	J	FUNCTIONS FOR COMMON AND			ANGLES
	$hc = 1.99 \times 10^{-25} \mathrm{J} \cdot \mathrm{m}$	watt	W	θ	sin 0	cos θ	tan 0
	$= 1.24 \times 10^3 \mathrm{eV} \cdot \mathrm{nm}$	coulomb	С	0°	0	1	0
Vacuum permittivity,	$\epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2 / \text{ N} \cdot \text{m}^2$	volt	V		1/0	50	50
Coulomb's law constant,	$k = 1/4\pi\epsilon_0 = 9.0 \times 10^9 \mathrm{N} \cdot \mathrm{m}^2/\mathrm{C}^2$	ohm	Ω	30	1/2	√3/2	√3/3
Vacuum permeability,	$\mu_0 = 4\pi \times 10^{-7} (\mathrm{T} \cdot \mathrm{m}) / \mathrm{A}$	henry	Н	37°	3/5	4/5	3/4
Magnetic constant,	$k' = \mu_0 / 4\pi = 10^{-7} (\mathrm{T \cdot m}) / \mathrm{A}$	farad	F				
Universal gravitational constant,	$G = 6.67 \times 10^{-11} \text{ m}^3/\text{kg} \cdot \text{s}^2$	tesla	Т	45°	√ 2/2	√ 2/2	1
Acceleration due to gravity		degree Celsius	°c	53°	4/5	3/5	4/3
at the Earth's surface,	$g = 9.8 \text{ m/s}^2$		C		-115	515	
1 atmosphere pressure,	$1 \text{ atm} = 1.0 \times 10^5 \text{ N/m}^2$	volt	eV	60°	$\sqrt{3}/2$	1/2	$\sqrt{3}$
	$= 1.0 \times 10^5 \mathrm{Pa}$						
1 electron volt,	$1 \text{ eV} = 1.60 \times 10^{-19} \text{ J}$			90°	1	0	∞
		1			·		

TABLE OF INFORMATION FOR 2004 and 2005

The following conventions are used in this examination.

I. Unless otherwise stated, the frame of reference of any problem is assumed to be inertial.

II. The direction of any electric current is the direction of flow of positive charge (conventional current).

III. For any isolated electric charge, the electric potential is defined as zero at an infinite distance from the charge.

ADVANCED PLACEMENT PHYSICS C EQUATIONS FOR 2004 and 2005

MECHANICS

$v = v_0 + at$	a = E = E
$x = x_0 + v_0 t + \frac{1}{2}at^2$	f = f
$v^2 = v_0^2 + 2a(x - x_0)$	h = I =
$\sum \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$	J = K -
$\mathbf{F} = \frac{d\mathbf{p}}{dt}$	$k = \ell =$
$\mathbf{J} = \int \mathbf{F} dt = \Delta \mathbf{p}$	<i>L</i> =
$\mathbf{p} = m\mathbf{v}$	m = N =
$F_{fric} \leq \mu N$	P =
$W = \int \mathbf{F} \cdot d\mathbf{r}$	p = r =
$K = \frac{1}{2}mv^2$	$\mathbf{r} = T$
$P = \frac{dW}{dt}$	t = U =
$P = \mathbf{F} \cdot \mathbf{v}$	υ =
$\Delta U_g = mgh$	W = x =
$a_c = \frac{v^2}{r} = \omega^2 r$	$\mu = \theta =$
$\tau = \mathbf{r} \times \mathbf{F}$	$\tau = \omega =$
$\Sigma \mathbf{\tau} = \mathbf{\tau}_{net} = I \boldsymbol{\alpha}$	$\alpha = \alpha$
$I = \int r^2 dm = \sum mr^2$	
$\mathbf{r}_{cm} = \sum m\mathbf{r} / \sum m$	
$v = r\omega$	
$\mathbf{L} = \mathbf{r} \times \mathbf{p} = I\boldsymbol{\omega}$	
$K = \frac{1}{2}I\omega^2$	
$\omega = \omega_0 + \alpha t$	
$\theta = \theta_0 + \omega_0 t + \frac{1}{2}\alpha t^2$	
$\mathbf{F}_s = -k\mathbf{x}$	
$U_s = \frac{1}{2}kx^2$	
$T = \frac{2\pi}{\omega} = \frac{1}{f}$	
$T_s = 2\pi \sqrt{\frac{m}{k}}$	
$T_p = 2\pi \sqrt{\frac{\ell}{g}}$	
$\mathbf{F}_G = -\frac{Gm_1m_2}{r^2}\hat{\mathbf{r}}$	
$U_G = -\frac{Gm_1m_2}{r}$	

NI	65	ELECTRICI
=	acceleration	$F = \begin{pmatrix} 1 & q_1 q_2 \end{pmatrix}$
=	force	$r - \frac{1}{4\pi\epsilon_0} \frac{1}{r^2}$
=	frequency	F
=	height	$\mathbf{E} = -$
=	rotational inertia	q
=	impulse	$\mathbf{6}\mathbf{E} \cdot d\mathbf{A} = Q$
=	kinetic energy	$\Psi \mathbf{E} \cdot d\mathbf{A} = \frac{1}{\epsilon_0}$
=	spring constant	
=	length	$E = -\frac{av}{c}$
=	angular momentum	dr
=	mass	$V = \begin{pmatrix} 1 \\ \nabla \\ q_i \end{pmatrix}$
=	normal force	$V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{1}{r_i}$
_	momentum	1
_	radius or distance	$U_{F} = qV = \frac{1}{1} \frac{q_{1}q_{2}}{q_{1}q_{2}}$
_	nosition vector	$4\pi\epsilon_0 r$
_	period	c Q
=	time	$C = \frac{1}{V}$
=	potential energy	KE A
=	velocity or speed	$C = \frac{K C_0^{21}}{L}$
=	work done on a system	d
=	position	$C_p = \sum_i C_i$
=	coefficient of friction	i
=	angle	$\frac{1}{1} = \sum \frac{1}{1}$
=	torque	$C_s \xrightarrow{i} C_i$
=	angular speed	dO
=	angular acceleration	$I = \frac{dQ}{dt}$
		<i>ui</i>
		$U_{c} = \frac{1}{2}QV = \frac{1}{2}CV^{2}$
		2 2
		$R = \frac{\rho \ell}{\Lambda}$
		A V - IP
		V = IK
		$R_s = \sum_i R_i$
		1 51
		$\frac{1}{R} = \sum_{i} \frac{1}{R_{i}}$
		P = IV
		$\mathbf{F}_M = q\mathbf{v} \times \mathbf{D}$
		$\oint \mathbf{B} \cdot d\boldsymbol{\ell} = \mu_0 I$
		$\mathbf{F} = \int I d\boldsymbol{\ell} \times \mathbf{B}$
		$B_s = \mu_0 nI$
		$\phi_m = \int \mathbf{B} \cdot d\mathbf{A}$
		$\mathcal{E} = -\frac{d\phi_m}{d\phi_m}$
		dt
		$\mathcal{E} = -L \frac{dI}{dt}$
		<i>u</i> 1 2
		$U_L = \frac{1}{2}LI^2$

ELECTRICITY AND MAGNETISM A = areaB = magnetic field C = capacitanced = distanceE = electric field $\mathcal{E} = \text{emf}$ F = forceI = currentL = inductance $\ell = \text{length}$ n = number of loops of wire per unit length P = powerQ = chargeq = point chargeR = resistancer = distancet = timeU = potential or stored energy V = electric potential v = velocity or speed ρ = resistivity ϕ_m = magnetic flux κ = dielectric constant

GEOMETRY AND TRIGONOMETRY

Rectangle A = areaA = bhC = circumferenceTriangle V = volume S = surface area $A = \frac{1}{2}bh$ b = baseCircle h = height $A = \pi r^{2}$ $\ell = \text{length}$ $C = 2\pi r$ W = width r = radius $V = \ell w h$ Cylinder $V = \pi r^2 \ell$ $S = 2\pi r\ell + 2\pi r^2$ Sphere $V = \frac{4}{3} \pi r^3$ $S = 4\pi r^2$ **Right Triangle** $a^2 + b^2 = c^2$ $\sin\theta = \frac{a}{c}$ 2 $\cos \theta = \frac{b}{c}$ $\tan \theta = \frac{a}{b}$

$$\begin{array}{c} c \\ \theta \\ 90^{\circ} \\ b \end{array} a$$

CALCULUS

$$\frac{df}{dx} = \frac{df}{du} \frac{du}{dx}$$
$$\frac{d}{dx}(x^n) = nx^{n-1}$$
$$\frac{d}{dx}(e^x) = e^x$$
$$\frac{d}{dx}(\ln x) = \frac{1}{x}$$
$$\frac{d}{dx}(\sin x) = \cos x$$
$$\frac{d}{dx}(\cos x) = -\sin x$$
$$\int x^n dx = \frac{1}{n+1}x^{n+1}, n \neq -1$$
$$\int e^x dx = e^x$$
$$\int \frac{dx}{x} = \ln|x|$$
$$\int \cos x dx = \sin x$$
$$\int \sin x dx = -\cos x$$

PHYSICS C Section II, ELECTRICITY AND MAGNETISM Time—45 minutes 3 Questions

Directions: Answer all three questions. The suggested time is about 15 minutes for answering each of the questions, which are worth 15 points each. The parts within a question may not have equal weight. Show all your work in the booklet in the spaces provided after each part, NOT in this green insert.



E&M. 1.

The figure above left shows a hollow, infinite, cylindrical, uncharged conducting shell of inner radius r_1 and outer radius r_2 . An infinite line charge of linear charge density $+\lambda$ is parallel to its axis but off center. An enlarged cross section of the cylindrical shell is shown above right.

(a) On the cross section above right,

- i. sketch the electric field lines, if any, in each of regions I, II, and III and
- ii. use + and signs to indicate any charge induced on the conductor.
- (b) In the spaces below, rank the electric potentials at points a, b, c, d, and e from highest to lowest (1 = highest potential). If two points are at the same potential, give them the same number.

 $__V_a$ $__V_b$ $__V_c$ $__V_d$ $__V_e$

Copyright © 2004 by College Entrance Examination Board. All rights reserved. Visit apcentral.collegeboard.com (for AP professionals) and www.collegeboard.com/apstudents (for AP students and parents).



(c) The shell is replaced by another cylindrical shell that has the same dimensions but is nonconducting and carries a uniform volume charge density $+\rho$. The infinite line charge, still of charge density $+\lambda$, is located at the center of the shell as shown above. Using Gauss's law, calculate the magnitude of the electric field as a function of the distance *r* from the center of the shell for each of the following regions. Express your answers in terms of the given quantities and fundamental constants.

- ii. $r_1 \leq r \leq r_2$
- iii. $r > r_2$



E&M. 2.

In the circuit shown above left, the switch *S* is initially in the open position and the capacitor *C* is initially uncharged. A voltage probe and a computer (not shown) are used to measure the potential difference across the capacitor as a function of time after the switch is closed. The graph produced by the computer is shown above right. The battery has an emf of 20 V and negligible internal resistance. Resistor R_1 has a resistance of 15 k Ω and the capacitor *C* has a capacitance of 20 μ F.

- (a) Determine the voltage across resistor R_2 immediately after the switch is closed.
- (b) Determine the voltage across resistor R_2 a long time after the switch is closed.
- (c) Calculate the value of the resistor R_2 .
- (d) Calculate the energy stored in the capacitor a long time after the switch is closed.

(e) On the axes below, graph the current in R_2 as a function of time from 0 to 15 s. Label the vertical axis with appropriate values.



Resistor R_2 is removed and replaced with another resistor of lesser resistance. Switch S remains closed for a long time.

(f) Indicate below whether the energy stored in the capacitor is greater than, less than, or the same as it was with resistor R_2 in the circuit.

____Greater than _____Less than _____The same as

Explain your reasoning.



E&M. 3.

A rectangular loop of dimensions 3ℓ and 4ℓ lies in the plane of the page as shown above. A long straight wire also in the plane of the page carries a current *I*.

(a) Calculate the magnetic flux through the rectangular loop in terms of *I*, ℓ , and fundamental constants.

Starting at time t = 0, the current in the long straight wire is given as a function of time t by

 $I(t) = I_0 e^{-kt}$, where I_0 and k are constants.

(b) The current induced in the loop is in which direction?

____ Clockwise ____ Counterclockwise

Justify your answer.

The loop has a resistance *R*. Calculate each of the following in terms of *R*, I_0 , *k*, ℓ , and fundamental constants. (c) The current in the loop as a function of time *t*

(d) The total energy dissipated in the loop from t = 0 to $t = \infty$

END OF SECTION II, ELECTRICITY AND MAGNETISM