



## 35 Fine Patch

Roberts Fine Patch 35 provides a smooth and permanent finish to a variety of substrates prior to the installation of floor coverings such as vinyl sheet and tiles.

Roberts Fine Patch 35 contains no sand therefore giving the user a true featheredge. Roberts Fine Patch 35 allows the installation of most types of floor covering in as little as 20 minutes over concrete, ceramic and quarry tiles.

Roberts Fine Patch 35 is used to-

- ✓ smooth ridges
- ✓ fill in scratches gouges and joints to provide a true featheredge over concrete, wood, terrazzo, ceramic and quarry tiles.

### SUB FLOOR PREPARATION

Sub floor must be free of oil, grease, wax, curing compounds, dust, old adhesive and any other contaminations which may inhibit bond. Do not use curing compounds, solvents or acids and etching to prepare the substrate. Sub floors must be dried at a minimum of 10 degrees centigrade.

### Note:

Concrete floors must be dry in accordance with AS.1884 1985 Appendix A 70% Relative humidity maximum.

Where temperatures less than 5°C or greater than 35°C are encountered, contact our technical staff for specific advice.

### MIXING

Place a small amount of clean water in a clean pail and then add a small amount of powder while mixing to achieve the desired consistency. Over watering of Fine Patch 35 will reduce the tensile and bond strength.

### APPLICATION

Apply the mixed compound to the substrate using a trowel. Can be applied from featheredged to 3mm thickness. Imperfections or minor trowel marks can be removed after 1 hour by gentle sanding. Allow to dry before installing floor coverings and wipe any sanded areas with a damp cloth to remove dust prior to installing floor coverings.

### CLEAN UP

Clean all equipment with water immediately after use.

### PACKAGING

Roberts Fine Patch 35 10kg Paper Bags.

### STORAGE

Roberts Fine Patch 35 is a cement based product, which must be stored in a dry area off the ground and out of direct sunlight.

### COVERAGE

Approximately 8m<sup>2</sup> at 1mm thickness per 10kg bag.

Applied as a featheredge expect to gain up to 30m<sup>2</sup> depending on texture of the substrate.

### SHELF LIFE

12 months in dry conditions.

### POT LIFE

Approximately 20 minutes at 20 degrees centigrade. This will vary depending on fluctuations in temperatures.

### SAFETY DIRECTIONS

Hazardous according to the criteria of NOHSC. Contains cement silica. Wear gloves and mask when handling. Wash hands thoroughly after use. Material safety data sheets are available upon request.

### MANUAL HANDLING

Manual handling of this bag without due care and attention may result in personal injury.

### NOTE

Robert Fine Patch 35 is for internal use only. Don't use in wet areas or external areas.

Do not install Fine Patch 35 onto substrates of ambient temperature below 10 degrees.

Issued: September 2010

The application, use and processing of our products is the responsibility of the user. Any technical or other advice, information or data provided by us, whether verbally, in writing or by way of trials or tests, is given without guarantee or warranty. Refer to Material Safety Data Sheets for information on Storage & Handling, Health and Safety, and Transport.

## RLA POLYMERS PTY LTD

ACN 004 709 915

215 Colchester Road, Kilsyth, Victoria 3137 Australia

P.O. Box 147, Kilsyth, Victoria 3137 Australia

Telephone: (03) 9728 1644 • Facsimile: (03) 9728 6009

E-mail: info@rlapolymers.com.au • Web: www.rlapolymers.com.au



67 Dalgety Drive (P.O. Box 97-575)  
Manukau City, Auckland, New Zealand

Telephone: (9) 268 0301

Facsimile: (9) 268 0305

