

Thickness Gages 57B Bench Style



57B-12

Features

- Solid casting with ribbed frame provides strength and rigidity for accurate measurements.
- Gage is furnished with a lift lever so work can be easily placed between the contacts.
- Large 54 mm/ 2.125" diameter lower anvil provides convenient stage for small parts or flat materials.
- 4.75 mm/ .187" diameter radiused upper contact normally provided.
- 102 mm/ 4" throat depth for part clearance.
- Indicator mounts with adjustable back for quick positioning for each gaging requirement.
- Available with Dial Indicator or Digital Electronic Indicator.

Technical Data

Metric	Order no.	Inch	Capacity	Description
57B-11M	57B-11		0-25 mm/ 0-1"	Dial Indicator readout with 25 mm/ 1" sensitive range and .01mm/.001"grads.
	XLI-57B-11			μMaxμm® XL Digital Indicator with 25 mm/ 1" range and .001mm/ .00005" resolution (Model XLI-50002).
	EMD-57B-11		0-21.5 mm/ 0-.85"	Maxμm/// Digital Indicator with selectable range and resolution, 2033101.
	EDI-57B-11			μMaxμm Digital Indicator with 2 mm/ .08" sensitive range, .0005 mm/ .00002" resolution (Model EDI-20101).
57B-12M	57B-12		0-12.5mm/ 0-.5"	Dial Indicator readout with 12.50 mm/ .50" sensitive range and .01 mm/ .0005" grads.
	XLI-57B-12			μMaxμm® XL Digital Indicator with 12.50 mm/ .50" range and .001 mm/ .00005" resolution (Model XLI-10002).

*Alternate Indicators and contact points available upon request.
Contact Mahr Federal.*