## PROFILE SW 908

Product specification sheet



## Features

- A sophisticated design for maximum performances and esthetic integration capability.
- Bended multi-fold MDF cabinet for thoughness and optimal damping.
- 13" sandwich composite "W" cone.
- Built-in Digital Signal Processor (DSP).
- Subsonic filter for optimized sub bass in small room.
- Night mode (dynamic compression).
- Boost mode.
- High power, high efficiency **BASH**® amplifier.
- Proprietary port design with double deflector integral to the cabinet structure, minimizing air flow and ensuring optimal rigidity.
- Three finishes, natural wood veneering.

## **Technical specifications**

Туре	Active subwoofer with DSP
Drivers	13'' W cone woofer, 2-1/2'' voice coil
Cut-off frequency (-6dB)	23Hz
Frequency response (+/-3dB)	27 to 150Hz
Amplifier	500Wrms (700W max) BASH®
DSP section	24dB/octave active filter (50 to 150Hz), adjustable phase from 0° to 180° (by step of 1°), 24dB/octave subsonic filter (15 to 45Hz), Boost mode, Night mode, 3 users presets
Input	LFe/Stereo/Digital SPDIF coaxial
Power mode	On/Off/Autopower
Dimensions (HxWxD)	19.2x20x15'' (488x510x380mm)
Net weight	59,5lbs (27kg)





Focal® is a trademark of Focal-JMLab® - BP 374 - 108, rue de l'Avenir - 42353 La Talaudière cedex France - Tel. 00 33 4 77 43 57 00 - Fax 00 33 4 77 37 65 87 - www.focal-fr.com - SCSD050727/1