CD-DA/CD-R/RW ready

CZ201A

CD-DA/CD-R/RW ready

Front USB Slot

• iPod and iPhone direct control

Beat EQ for sound adjustment

2V / 2-channel audio pre-out

CD-DA/CD-R/RW readv

MP3 and WMA compatible with ID3-TAG display

Front-panel AUX input with level control

Beat EQ for sound adjustment

4 x 45 W MOS-FET power amplifier

2V / 2-channel audio pre-out

Front-panel AUX input with level control

4 x 45 W MOS-FET power amplifier

• Built-in Bluetooth® hands-free (HFP & PBAP)

 MP3 and WMA compatible with ID3-TAG display iPod[®] and iPhone[®] direct control Front USB Slot

 Beat EQ for sound adjustment · Built-in High Pass Filter & Low Pass Filter

4V / 6-channel audio pre-out

• Front-panel AUX input with level control

4 x 50 W MOS-FET power amplifier

MP3 and WMA compatible with ID3-TAG display

CD/USB/MP3/WMA receiver







MP3/WMA FM/AM 2V/2ch Subwoofer M-BRSSEX BeatEl LPF High Visibility | Integral | MOS-FET | 45W×4 ≈

CZ101AF

-Z709A / FZ409A

CD/USB/MP3/WMA/AAC receiver with CeNET control

MP3/WMA/AAC USB OEL MATOUCH SENSOR

BBE.MP M-BASSEX 24 bit BeatE0

LPEXAPE 4V/6ch 2V/6ch AUX.

• 4V/6 ch output: only for FZ709A • 2V/6 ch



only for FZ709A



 Built-in Bluetooth hands-free (HFP & OPP) and audio streaming (A2DP & AVRCP) (only for FZ709A) MP3, WMA and iTunes® AAC compatible

output: only for FZ409A • Bluetooth ready: with ID3-TAG display USB audio for iPod (Rear)

optional BLT370)

CD-R/RW ready

Rear USB connector

Sound Restorer

iPod direct control via USB

• 6V / 6-channel audio preout

Subwoofer volume control

3-way active crossover

Digital time alignment control

"SLIDETRAK" for dynamic operation

MP3, WMA and iTunes AAC compatible

The FZ709A and FZ409A simplify operation so that now it is just a matter of touching a few iconised illuminated capacitive sensor buttons. This is an example of the intuitive H.M.I. design that minimises the number of buttons while maximising functionality. Since only relevant button icons appear for the task at hand, button-hunting is eliminated and access is more direct and

MP3/WMA/AAC FM/AM IISB

PLEO LPF HPF Sound Restorer

Made for iPod

CX201A

2-DIN CD/USB/MP3/WMA receiver

MP3/WMA FM/AM USB

MP3/WMA FM/AM 2V/4ch

AUX MOS-FE

LPO 6 50 W×4 CeNET 6-CD

2-DIN 6-disc CD/MP3/WMA receiver with CeNET control

2V/4ch RUX Submoofer M-BRSSEX

 CD-R/RW ready MP3/WMA FM/AM USB Built-in Bluetooth hands-free (HFP & OPP) and audio streaming (A2DP & AVRCP) MP3 and WMA compatible with ID3-TAG display

• iPod and iPhone direct control Front USB Slot Beat EQ for sound adjustment 2V/4-channel audio pre-out

 BBE MP for compressed audio sound improvement

 Built-in High Pass Filter & Low Pass Filter Touch sensor operation • Full dot OEL (Organic Electro Luminescence)

Beat EQ for sound adjustment

• 4V / 6-channel audio pre-out (only for FZ709A) • 2V / 6-channel audio pre-out (only for FZ409A) Remote control included (only for FZ709A /

optional for FZ409A) • iPod video ready (optional for CCA748 and universal monitor required) Bluetooth Interface ready (only for FZ409A /

CD/USB/MP3/WMA/AAC receiver with CeNET control

2-DIN Bluetooth CD/USB/MP3/WMA receiver



• 4 x 50 W MOS-FET power amplifier

CD-R/RW readv

Front USB Slot

CD-R/RW ready

• 18 FM, 6 AM station presets

4-channel audio pre-out

(EA1251 is required)

VF display with Spectrum system

CeNET iPod interface compatible

· 2-channel AUX input with level control

iPod and iPhone direct control

· Beat EQ for sound adjustment

4 x 50 W MOS-FET power amplifier

2V/4-channel audio pre-out

MP3 and WMA compatible with ID3-TAG display

Built-in 6-disc CD changer

MP3 and WMA compatible with ID3-TAG display

Bluetooth

☐iPod ☐iPhone

Microphone —

HX LPEXHPE 24bit P.E.

8V/8ch AUX CeNE Conceptual diagram of frequency

0 10k 20k 40k 70k 96k 100k(Hz)

— Audio with 96kHz sampling

WQ3010D

dual 4-ohm voice

WG3010

4-ohm voice coil

subwoofer

900 W Max. 30 cm [12"]

coil subwoofer

1500 W Max. 30 cm [12"]

CD receiver with CeNET control

phase characteristics <Phase Characteristics> of high-range spectrum

• Dual 24-bit/96kHz sampling digital to analogue burr-brown converters and DSP Built-in 4-way crossovers

level output


 Digital time alignment for each line 8-channel/8-volt gold plate oxygen-free RCA output 0.5dB-step electronic volume

5-band parametric equaliser

adjustment circuit

Copper plated chassis • 2 × 2-channel AUX inputs CeNET iPod interface compatible (EA1251 is required)

APA2180





420 W mono power

amplifier

APA4360

XH7110

850W mono power amplifier



WQ2510D 1500 W Max. 25 cm [10"] dual 4-ohm voice coil



subwoofer













400 W 4/3/2 channel

power amplifier





SRU1720M 16.5 cm (6-3/4") / 15 cm × 20 cm (6" x 8") MultiFit speaker system

SRU1320M 250 W Max. 13 cm (5-1/4") / 13 cm × 18 cm (5" x 7") MultiFit speaker system

Highest grade materials for high power handling,

superior response, and stately looks







16.5 cm (6-1/2") 2-way component system SRP1321S

13 cm (5-1/4") 2-way component system



SRP4620M 10 cm (4") / 10 cm × 15 cm (4" × 6") MultiFit speaker system 10 cm × 15 cm (4" × 6") OEM replacement adaptor included

15 cm × 23 cm (6" × 9") MultiFi speaker system





Full range of multiaxial, coaxial and component speakers flexibly deliver high quality sound.

16.5 cm (6-1/2") 2-way component system

SRE2031R

SRE1731R

SRE1331R

20 cm (8") multiaxial 3-way


16.5 cm (6-1/2") multiaxial 3-way

13 cm (5-1/4") multiaxial 3-way


400 W Max.

200 W Max.

13 cm (5-1/4") 2-wa component system



Multiaxial 3-way



15 cm × 23 cm (6" × 9")

15 cm x 23 cm (6" x 9")


2.5 cm (1") balanced-drive tweeter

SRE211H

200 W Max.

140 W Max.

10 cm (4") coaxial 2-way





16 cm (6-1/2")

2-way component


SRQ6932R

Full range of coaxial speakers to easily upgrade



180 W Max. 16 cm (6-1/2") coaxial 2-way SRG1321F 160 W Max. 13 cm (5-1/4") coaxial 2-way 140 W max. 10 cm (4") coaxial 2-way







280 W Max.

16 cm (6-1/2") multiaxial 3-way

SRQ211H
















80 W Max. 9 cm (3-1/2")



SRQ6831C

Speaker SRQ series


Multiaxial and component speakers provide

the exact solution for your acoustic environment.

350 W Max. 15 cm × 20 cm (6" x 8") custom fit multiaxial 3-way SRQ57300

15 cm × 23 cm (6"x 9") multiaxial 3-way















custom fit coaxial 2-way SRG46210

150 W Max. 10 cm × 15 cm (4"x 6") custom fit coaxial 2-way custom fit coaxial 2-way

Car Audio & Multimedia

2011-2012

Turn vour drive into quality time

Your time driving can be made more comfortable, entertaining and even safer with Clarion. Our full lineup of high quality car entertainment products help turn your vehicle into "the place to be" for quality time. Everything from grea sound with thundering bass, to vivid images with cinematic presence, is yours for the asking. And with easy operation and hands-free communication, Clarion makes sure you'll be driving safely all the way.



Bluetooth makes driving safer by making hands-free mobile phone communication possible while driving. Clarion offers a full lineup of Bluetooth compatible models so you can communicate safely and enjoy audio streaming from phone to car audio system as well. Parrot Bluetooth, renowned for its expanded functionaland reliability, is offered on certain



Listening to iPod might be something you do every day. Now it can be part of your car entertainment as well. Just connect it to Clarion's head unit via USB terminal iPod music plays through the car audio

system! Control operations at the head unit or at the iPod that you're so familiar with. Compatible iPod/iPhone® models and Multimedia head units can work together for video playback as well.



NX501A

2-DIN DVD multimedia station with 6.2-inch

touch panel & built-in navigation





VIDEO EIGEN	DVD-Video/DVD±R/DVD±RW/CD/CD-R/RW/Video-CD ready Built-in navigation on 4GB flash memory microSD card slot for navigation map update Built-in Parrot Bluetooth interface® hands-free (HFP) and audio streaming (A2DP & AVRCP) MP3/WMA compatible with ID3-TAG display Rear USB connector iPod and iPhone direct control (optional CCA748) isoble required fire in the video playbook.
MP3/WMA FM/AM USB	
2200K AV 6Ch Rear Vision AUX. Ruill-in Ravigation Revelopment Phones EX. Rear EQ. (24 bit.) Rear EQ. (27 bit.) Rear EQ. (27 bit.) Rear EQ. (27 bit.) Rear EQ. (27 bit.)	
LPFWHPF SOW×4 PRNEL PRN	

Interactive GUI



D-Video/DVD±R/DVD±RW/ D/CD-R/RW/Video-CD ready ilt-in navigation on 4GB flash memory

- ar USB connector od and iPhone direct control (optional CCA748
- cable required for iPod video playback) 2 AV inputs
- Dedicated rear vision camera RCA input 4V/6-channel audio pre-out and 2-channel audio
- pre-out for 2-Zone

The NX501A's touch sensor GUI (Graphical User Interface) supports flick operation, so you can quickly scroll to another menu page. Feature icons are animated for an enhanced appearance, and they can be dragged and dropped into different positions to customise the screen



GUI & voice guidance

■ Navigation voice guidance :

direct control on touch-panel display Text to speech UK English, Chinese, Indonesian, T

- Text to speech voice : UK English, Chinese
- Text to speech voice : UK English, Indonesian, Malay, Thai

Sophisticated and efficient navigation graphics

bridges with elevations















Smart, simple and

Elevation modelling and

3D rendering for a realistic view



Roads, junctions and Signposts information Topographical view Modelling terrain in 3D

7-inch (1-DIN) touch panel control





2-DIN VX401A /1-DIN VZ401A

cable required for iPod video playback) 2 AV AUX input



In addition to providing 3 preset equalisation patterns, Beat EQ lets you customise the level and range of the bass, midrange and treble of each pattern. In addition, Magna Bass EX boosts the 50Hz range to deliver dynamic bass performance.

Beat EQ and Magna Bass EX Magna Bass's centre frequency is for precisely powerful sound

4 × 50 watt with MOS-FET power amp

NX501A features an MOS-FET (Metal Oxide Semiconductor Field Effect ransistor) power amplifier capable of delivering 4 × 50 watt of high quality sound with superior linearity and less distortion than conventional power amps even with the volume cranked up.



2-DIN VX709A /1-DIN VZ709A

DVD multimedia station with 6.2-inch (2-DIN).

DVD multimedia station with 7-inch (2-DIN). 7-inch (1-DIN) touch panel control



MP3/WMA/AAC FM/AM USB Rear Vision Rux Subwoofer Camera Input level control M-BRSSEX 24 bit P.EO 50 W × 4 PANEL CENET premium content.

USB memory (device)

nnector cable (CCA748)





200 Hz - 200 Hz Bass boost/M-Bass On

2-Zone entertainment Clarion's 2-Zone entertainment system divides the in-car

spatial environment into discrete front and rear zones. As a result, it is possible for the front and rear seat passengers to enjoy different entertainment sources without interfering with

mobile phone CAA185 CC2011E



/Z509A

DVD multimedia station with 7-inch touch panel control

Made for Pod




MP3/WMA/AAC Navigation ready with optional NP509A Rear USB connector



MP3/WMA/AAC compatible with ID3-TAG display DivX Certified® to play DivX® video, including

FM/AM USB • iPod direct control (optional CCA748 cable



■ Navigation system example

Map coverage:

Indonesia Brunei



ment (only for USB function)



Hide-away memory navigation system

Bluetooth interface ready (optional BLT370)

BBE MP for compressed audio sound improve-

2 AV AUX input 6-channel audio pre-out (Front/ Rear/ Subwoofer)

Direct connection with VZ509A

SD card slot for map updating

and audio mix

SA509 required)

VX709A/VZ709A requires CCB509 interface

System integration: Touch screen operation,

AV interruption, navigation voice guidance

Stand-alone mode available (optional

SiRF III GPS module with 20-channel

No speed pulse connection required

Built-in 2GB flash memory for navigation

DVD-Video/DVD±R/DVD±RW/Video CD/

DivX Certified to play DivX video, including

Navigation ready with optional NP509A

MP3/WMA/AAC compatible with ID3-TAG display

iPod direct control (optional CCA748 required for

and 2-channel audio pre-out for 2-Zone

CD-R/RW ready

premium content

iPod video playback)

Rear USB connector

A509

Stand-alone accessory kit for NP509A

VX409A

DVD-Video/DVD±R/DVD±RW readv

MP3/WMA compatible with ID3-TAG display

CD-DA/HDCD/CD-R/RW readv

18 FM, 6 AM station presets

iPod direct control (optional

CCUIPOD2 cable required)

4V/6-channel audio pre-out

Rear AV input

Rear AV output



DIN VX409A / 1-DIN VZ409A

DVD multimedia station with 6.5-inch (2-DIN).

7-inch (1-DIN) touch panel control

MP3/WMA

VZ409A


FM/AM USB 4V/6ch Rear AV

Submoofer Submoo

CCB509

CeNET converter for NP509A









remote eve



• IR remote control and

External speaker for



SA509 (Speaker)



15.6-inch widescreen LCD overhead colour monitor with DVD Player

10.2-inch widescreen LCD overhead colour monitor with DVD Player
















- (Mirror image)
- On Screen Display
- 2 x AV Inputs (Back side) / 1 x AV Output (Back side)
- Capability to read: DVD Format / DVD±R / DVD±RW / CD-DA

7-inch / 16:9 headrest / stand-alone





27.5 (D) mm



 Ultra compact housing for easy headrest installation (192.7 (W) × 133.5 (H) × 32.5 (D) mm) • Dimensions: 177.8 (W) × 118.5 (H) ×

5.6-inch / 16:9 headrest / stand-alone



 Ultra compact housing for easy headrest installation (160.8 (W) × 111.8 (H) × 32.5 (D) mm) • Dimensions: 150 (W) × 101 (H) × 27

System examples NX501A/VZ401A/VX401A/VZ400A/ or all other monitors with NTSC video input and reverse gear connection

or All other monitors

High-performance 1/4" colour CMOS sensor.

• High-resolution glass lens for high image quality.

Dimensions: 23.4 (W) x 23.4 (H) x 22 (D) mm

PQE033

for CC2011E

Finishing camera cover

REVERSE GEAR Sense




CC2011E

CC4001U

- Ultra compact colour CCD camera
- Built-in IR Transmitter for Wireless Headphones
- Headphone Quantity Included, 2 • IR Remote Control
- 3.5mm AUX Input Connection
- Slot-in DVD mechanism / USB / SD / MMC
- CD-R / CD-RW / MPEG / MP3 / WMA / VCD / SVCD

System examples



VX401A/VZ400A/ CCD camera CCA534 15 metres VX400A/VZ709A/ VX709A/VZ509A

Camera cables for CC2011E CAA185 Connecting cables for compact camera CCA532 (7m) / CCA533 (10m) / Camera CCA534 (15m)





VA700 WH143H / WH253H FM200







MCD360 3-way electronic

Bluetooth audio / mobile-phone transceiver for AUX input

crossover

External microphone For NX501A/VZ401A/ VX401A/VZ709A/VX709A/ MAX686BT/VRX786BT

CeNET - iPod interface Remote Controls Interfaces to enjoy iPod with full RCB-147-600

Infrared joystick remote control RCB-176-600 iPod connecting unit Infrared remote control

 Compatible with WXZ466MP and HX-D3 RCB-176-200 (CONNECT via CD CHANGER MODE) Infrared remote control

RCB-187 Direct iPod connection Remote control For VZ709A/VX709A/VZ509A iPod video connecting cable

 For NX501A/VX401A/VZ401A/CZ501A/ CZ201A/VZ709A/VX709A/VZ509A/ VZ400A/VX400A/FZ709A/FZ409A/ MAX686BT/VRX786BT

ACCESSORIES

DXZ786USB/DXZ586USB/

FZ409A/CZ309A/CZ200A/ CZ100A/DUZ386MP/

BLT370

DUB276MP/

operation

EA1251

DUB276MPW

- CCUIPOD2 iPod audio / video connecting cable
- For VX409A/VZ409A/VRX486VD/ MAX386VD

CCA-748

- Specification and design are subject to change without notice.
- LCD panels use the latest high-tech components and boast an effective pixel rate of 99.99%. However, be aware that 0.01% or less of the pixels may be defective.



www.clarion.com

Clarion (Malaysia) Sdn., Bhd.

Phase 1. Free Industrial Zone. 11900 Bayan Lepas, Penang, Malaysia Office Phone: +60-4-6148-400 Office Fax: +60-4-6438-713 http://www.clarion.com/my

Clarion (H.K.) Industries Co., Ltd. Unit 712, 7 F, Tower 1, Harbour Centre, 1 Hok Cheung Street, Hung Hom, Kowloon, Hong Kong

Distributor

Tel: (852) 2723-2088, Fax: (852) 2723-1991

WARNING: Driver is prohibited by law from viewing a video signal on any in-dash monitor while the vehicle is in motion.