Technical Specification - Rascal Powerchair P327 SL

Powerchair type Class	Class A, B or C	Class B
Department of Transport Class	Class 1 2 or 3	Class 2
Overall dimensions fully assembled	length x width x height mm (in)	1120 (44.09) x 690 (27) x 1210 (47.6)
flax height when fully elevated	mm (in)	1470 (57.9)
Ground to seat height - lowest position	mm (in)	620 (24)
Ground to seat height - highest position	mm (in)	870 (34)
Maximum carrying capacity - not to be exceeded kg (lb)		182 (400)
Aass (weight) including batteries	kg (lb)	123 (271)
Battery voltage and capacity	volts and ampere hours	12v x 55Ah x 2
ype of seat		Captain seat with scissor lift mechanism
Vheel size front/rear	mm (in)	152 (6) solid / 305 (12) pneumatic
yre pressure normal - drive wheels	p.s.i. (bar)	35 (2)
yre pressure maximum - not to be exceeded	d p.s.i. (bar)	50 (3.5)
Naximum speed	km/h (m.p.h.)	6.4 (4)
Minimum braking distance from maximum speed metres		1.6 (5.2)
Range on full charge and flat ground	km (miles)	Up to 32 (20)
he turn-around width	m (ft)	1.2 (4)
he maximum safe slope	degrees of slope	6° - Do not exceed the Powerchair may topple
he maximum climbing ability facing upwards	degrees of slope	6°
Ground clearance	mm (in)	50 (2.0)
Naximum obstacle climbing ability	mm (in)	50 (2.0)
Naximum safe descendable kerb height	mm (in)	50 (2.0)