

## NEC MultiSync® LCD1990SX



**High-end 19 inch professional LCD monitor for CAD/CAM, DTP, financial market and medical sectors with outstanding features and benefits for ergonomics and economy.**

- High performance PVA TFT display
- Innovative features such as AmbiBright, AutoBright, TileMatrix & TileComp or OverDrive On/Off
- ErgoDesign®: Height adjustable stand (150 mm) with 90° Pivot features
- Best economy, reduced Total Cost of Ownership and extended lifetime with multiple power saving features such as Ambient Light Sensor, EcoModes, Power Off timer and Scheduler
- Extraordinary features such as QuickRelease stand, CableComp, ColorComp, OSD KeyGuide or self diagnostics

**see more.**

NEC Display Solutions

# NEC MultiSync® LCD1990SX

## TECHNICAL SPECIFICATIONS

Panel Technology	PVA TFT
Screen Size [inch/cm]	19.0 / 48.2
Pixel Pitch [mm]	0.294
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	1500:1
Brightness (typ.) [cd/m <sup>2</sup> ]	250
Response Time (typ.) [ms]	8 (grey-to-grey), 20 (14 white / black; 6 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	50.0 - 85.0
Optimum Resolution	1280 x 1024 at 60 Hz
Supported Resolutions	1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: x DVI-D; Digital/ Analog: 1 x DVI-I; Analog: 1 x D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Advanced NTAA (Advanced Non-Touch-Auto-Adjustment); Advanced User Menu; Black Level; Brightness; Colour Temperature Control; Contrast; Expansion Mode; Fine Adjust (analog); Hotkeys; Intelligent Power Management; Language Select; Monitor Information; OmniColor™: sRGB and 6-axis-colour-control; On-Screen-Display (OSD) lock-out; Programmable 12-bit LUT; Sharpness; User Menu
Safety and Ergonomics	EPEAT Silver™; CE; ERP; TCO 03; TÜV Ergonomics; TÜV GS; C-tick; GEEA/Energy Label; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; PCBC/B-mark; PSB; RoHS
Power Consumption on Mode [W]	28 (Eco Mode 1); 39 (max.); 23 (Eco Mode 2)
Stand-by Mode [W]	1
Power Supply	100-120 V/220-240 V; 0.63 A/0.27 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height adjustable Stand [mm]	150
Screen Tilt / Swivel [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	402.3 x 410.7 - 560.7 x 247.3 (Landscape mode) Without stand: 402.30 x 330.30 x 80.00
Bezel Width [mm]	12 (left and right); 13.6 (top and bottom)
Weight [kg]	8.4; Without stand: 5.80
Cable Management	yes
Kensington security slot	yes
Benefits	Adjustable power LED (colour and brightness); Advanced NTAA (Advanced Non-Touch- Auto-Adjustment); AmbiBright; ambix <sup>3</sup> ™; Auto Black Level; Auto Brightness; Auto Contrast; AutoBright; CableComp; CableComp with Sync Continuity Detection; ColorComp; DDC/CI compatible; Direct Brightness and Contrast; EcoModes; NaViSet® and NaViSet® Administrator compatible; OmniColor™: sRGB and 6-Axis-Colour-Control; Overdrive; Quick release Stand and Handle; Rapid Response Technology; RapidMotion; Real Time Clock with Scheduler (Power-On and Power-Off Timer); Self Diagnostics; TileComp; TileMatrix; TORO™ Design; Windows XP Option: MultiSync® Soundbar 90
Audio Functions	Option: MultiSync® Soundbar 90
Colour Versions	Silver Front Bezel, Light Grey Back Cabinet Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable DVI-A - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight

